



Associates

Traffic, Transportation & Civil Engineering

Ali R. Khorasani, P.E.

P.O. Box 804, Spencer, MA 0156, Tel: (508) 560-4041

Traffic Impact Study


For

**Proposed
Restaurant**

Located at

79 Pullman Street

Worcester, Massachusetts



April 2024

TABLE OF CONTENTS

	<u>Page</u>
1) INTRODUCTION	3
Project Description	3
2) EXISTING CONDITIONS	5
Study Area Roadway Network	5
Traffic Volumes	6
Safety Concerns	9
Existing Conditions Summary	11
3) FUTURE CONDITIONS	13
Site-Generated Traffic Engineering	13
Trip Distribution and Assignment	14
Site Access and Circulation	15
4) TRAFFIC OPERATIONS	17
Traffic Operations Measures	17
Existing Conditions	18
Future Conditions	18
5) FINDINGS	22
Conclusion & Recommendations	23

1

INTRODUCTION


Lacy Topas, LLC, the developer of the site of the former Sylvan Learning Center, hereafter referred to as the applicant is proposing the redevelopment of a 0.68-acre parcel of land to construct a stand-alone restaurant consisting of a 2,328 square foot (sf) building with a total of 29 associated off-street parking spaces. The proposed redevelopment project consists of constructing a 2,328-sf building that will house a fast casual restaurant, replacing the former learning center. The site is located south of West Mountain Street and approximately 1,200 feet west of the intersection of West Boylston Street, East Mountain Street, and West Mountain Street (the Summit). The proposed redevelopment site is zoned ML 0.5 and MG 0.5. Land use along West Mountain Street is primarily commercial. Figure 1 depicts the proposed site plan. As shown in Figure 1, the proposed site will be accessed by one driveway from Pullman Street.

Project Description

The applicant proposes to redevelop an existing site and build a new 2,328-sf building that will house a fast casual restaurant replacing the former learning center at this location. The proposed site is zoned ML 0.5 and MG 0.5 and is shown on the site plan in Figure 1. The proposed redevelopment site is located approximately 1,200 feet west of the intersection of West Boylston Street, East Mountain Street, and West Mountain Street.

The building is designed and situated in such a way that it will have ample off-street parking. This will eliminate the potential for on-street parking activities, thus maintaining optimal safety for motorists along West Mountain Street and Pullman Street. The proposed redevelopment will have one driveway off Pullman Street on the east side of the building and 150 feet south of the intersection of West Mountain Street and Pullman Street. This driveway will also serve a digital pickup lane to a drive through window, as there will be no menu board for ordering. All orders will be electronic via the internet or mobile application. The driveways and all parking spaces are designed in such a way that they will provide safe access to both the drive through window and the parking spaces. The dimensions of the proposed driveway and parking spaces are designed and will be built to the standards of the City of Worcester.

FIGURE 1
Proposed Redevelopment Site Plan



2

EXISTING CONDITIONS

Evaluation of the transportation impacts associated with the proposed redevelopment project requires a thorough understanding of the existing transportation system in the immediate vicinity of the site. Evaluating existing roadway network operating conditions necessitates an examination of existing roadway traffic volumes, geometric features, and local community traffic-related issues. Each of these elements is described below.

Study Area Roadway Network

The study area for this traffic impact report has been defined by the City of Worcester's Department of Transportation and Mobility to include the following two signalized intersections and the proposed Pullman Street driveway for this fast casual restaurant.

- West Mountain Street at Pullman Street
- West Mountain Street at Brooks Street

West Mountain Street is a two-way roadway with two travel lanes in each direction in the immediate vicinity of the proposed restaurant. The roadway width is approximately 50' in dimension in the vicinity of the proposed redevelopment site and provides a 1-foot shoulder on each side of the road in front of the proposed site. It provides two, 12-foot lanes in each direction. It also has a paved sidewalk on each side of the street. It is fairly straight on either side of the proposed site for a distance of approximately 1,400 feet. It traverses in easterly and westerly general directions and provides access to other major roadways in the area, including I-90 to the west and I-290 to the east. This street intersects with West Boylston Street to the east forming a 4-legged intersection that is equipped with a fully actuated traffic signal system. It also intersects with Pullman Street and Brooks Street in front of the proposed site forming two 3-legged "T" intersections. Both of these two intersections are also controlled by fully actuated traffic signal systems. No speed limit signs are posted on this street except a Warning Thickly Settled sign with a 30 miles per hour (mph) plate for eastbound traffic approximately a quarter of a mile west of the proposed site.

Brooks Street is a two-way roadway with one lane in each direction that serves several commercial, industrial and some new residential land uses. It traverses in the northerly and southerly general directions, and it is 3,550 feet (two thirds of a mile) in length. It has a 30-foot paved surface, and a sidewalk is available on the east side of the street for a distance of 1,600 feet. The width of the sidewalk begins at eight feet and gradually tapers off. Although Brooks Street continues all the way to West Boylston Street at its intersection with Airlie Street, it is cut off to traffic at the site of the former Showcase Cinemas, effectively becoming a dead-end

street. Its northerly terminus intersects West Boylston Street and as stated earlier its traffic is controlled by a traffic signal system. There are no speed limit signs posted on this street. However, since this street is thickly settled, the prima facia speed limit of 30 mph applies to this street.

Pullman Street is also a two-way roadway with one travel lane in each direction. It serves many commercial and industrial land uses. It is approximately 1,700 feet (one third of a mile) long and it starts at West Mountain Street and terminates at Brooks Street. The pavement width is 30 feet except for 200 feet in front of the proposed site and the Market 32 supermarket where the pavement width increases to 44 feet in order to provide a two-lane approach at West Mountain Street with a dedicated right-turn lane. Except for the Market 32 property frontage, there are no sidewalks on this street. Again, like Brooks Street, there are no speed limit signs posted, but the statutory prima facia speed limit of 30 mph applies to this street.

Intersection of West Mountain Street and Pullman Street is a signalized “T” intersection with two lane approaches. The westbound approach consists of a through lane and a shared through and left lane. The eastbound approach also has two lanes, one for through and a second lane for through and right movements. This signal system was installed primarily to accommodate traffic to and from the supermarket when it was developed in the mid-2000s. This traffic signal system has been advantageous for motorists getting to and from other businesses along this street.

Intersection of West Mountain Street and Brooks Street is also a “T” intersection with two lane approaches on West Mountain Street and a single lane approach on Brooks Street. It too is fully signalized, and the signal system for this location was installed to serve patrons of the former Showcase Cinemas when it was developed. This signal system has been valuable to countless other land uses along Brooks Street.

Traffic Volumes

To evaluate the traffic volumes for the intersections in the study area, new traffic counts were collected. It should be noted that although traffic volumes were at historic lows during COVID-19, traffic volumes have finally stabilized. Nevertheless, the new traffic counts may potentially undercount the baseline for which future years are based. Therefore, the peak hour traffic counts were adjusted to pre-COVID-19 conditions using *massDOT* historic traffic data and guidelines.

The new peak hour turning movement counts were obtained to reflect the current traffic conditions in the area. The new counts were collected on Saturday, April 6, 2024, during a two-hour period between 11 AM and 1 PM, as well as on Tuesday, April 9, 2024, during two-hour periods between the hours of 7-9 AM and 4-6 PM at peak commuter periods.

To establish the present baseline volumes, the intersection turning movement counts were adjusted and normalized into the present year (baseline) utilizing the *massDOT* factor as described below. The COVID-19 adjusted peak hour turning movement counts are summarized in the following Table 1. They are also depicted in the following Figure 2.

Table 1 - COVID Adjusted Volumes

West Mountain Street at Pullman Street						West Mountain Street at Brooks Street							
	EB T	EB R	WB L	WB T	NB L	NB R		EB T	EB R	WB L	WB T	NB L	NB R
AM Peak	583	110	69	268	55	71	AM Peak	675	71	11	324	48	16
PM Peak	368	164	159	627	199	181	PM Peak	515	47	22	834	49	15
Sat Peak	383	128	136	390	124	134	Sat Peak	502	15	9	507	11	7

A more concise method of adjusting the turning movement counts is using the revised *massDOT* Guidance on Traffic Count Data. The *massDOT* Yearly Growth Rates data for a period before the COVID-19 pandemic from 2014-2019 are shown in the Technical Appendix section of this report. The growth rates go back to 2014, and therefore, the rates were averaged and then expanded to a five-year period to adjust for the COVID-19 pandemic and then a five-year period to account for the future no-build and build conditions. The average annual growth rate was calculated at 0.0034. This rate was multiplied by five to get the total increased rate of 0.0175 for the COVID-19 adjustment (for baseline) and then the resultant was multiplied by this rate another five times to get the total increase rate of 0.0175 for future no build conditions. Therefore, the turning movement counts were increased by these factors. Again, as per *massDOT* Guidance on Traffic Count Data, this increase also accounts for all future traffic from any other additional developments that may take place in the general area of the proposed development site between now and the year 2029.

Additionally, the *massDOT* Highway Division provides statewide traffic data collection that includes weekday seasonal factors. To evaluate the potential for seasonal fluctuation of traffic volumes on roadways near the proposed site, weekday seasonal factors were obtained from the *massDOT* Statewide Traffic Data Collection. The data indicated that the seasonal factor for traffic collected during the month of April is 0.92 for U4-7 category roadways. Usually, the TMCs are multiplied by the factor of 0.92 to reflect those of the yearly average. Therefore, the extrapolated data were further adjusted to reflect those of an average year. A copy of adjustment factors is presented in the Technical Appendix section of this report. The seasonally adjusted turning movement counts for the present time (baseline) are shown below in Table 2 and Figure 3.

Table 2 – Seasonally Adjusted Volumes

West Mountain Street at Pullman Street						West Mountain Street at Brooks Street							
	EB T	EB R	WB L	WB T	NB L	NB R		EB T	EB R	WB L	WB T	NB L	NB R
AM Peak	536	101	63	247	51	65	AM Peak	621	65	10	298	44	15
PM Peak	339	151	146	577	183	167	PM Peak	474	43	20	767	45	14
Sat Peak	352	118	125	359	114	123	Sat Peak	462	14	8	466	10	6

Typically, the PM peak period has the higher volumes, and is considered the critical peak. As is the case here, higher traffic volumes also occur during the PM peak period at the intersection of West Mountain and Pullman Streets while the higher traffic volumes occur during AM peak hour for the intersection of West Mountain and Brooks Streets. However, all three peak periods are evaluated in this traffic study.

The percentage of truck traffic at permanent counting station #S17-042-348-02 along West Mountain Street was recorded by the *massDOT* at 1.9%. This rate includes all vehicles having three axles or more, some of these include single unit tree axel trucks that provide services to the residential properties along West Mountain Street. This rate is considered average for roadways having similar characteristics. Again, Figure 3 depicts the baseline turning movement counts that were adjusted to reflect an average year for the year 2024.

Figure 2
Existing Turning Movement Counts COVID Adjusted





Figure 3
Seasonally Adjusted Baseline Turning Movement Counts



Safety Concerns

Sight Distances: The available sight distances for the proposed driveway were evaluated. The examination of the proposed Pullman Street driveway showed that the available sight distance to the right (south) is 465 feet. The available sight distance to the left (north) for this driveway was measured at 150 feet all the way to the signalized intersection. Photographs showing the available sight distances are provided and are shown below.

Since no speed limit signs are posted along Pullman Street, the statutory prima facia speed limit of 30 mph applies. It is noted that due to the proximity of the site driveway to the signalized intersection of West Mountain Street and Pullman Street, most vehicles traveling in the southerly direction do not reach 30-mph speed until they are long past the proposed site, particularly when starting from a standing stop after the traffic signal turns green.

Based on Basic Design Controls for roadway design, Stopping Sight Distances are calculated using the formula $d=(V*V)/(30*f)$, plus the time required for perception and reaction by drivers (2.5 seconds). V is approach speed in mph, and $f=0.28-0.35$. The stopping sight distances are calculated and are provided in Exhibit 3-8 of the 2006 *massDOT* Project Development and Design Guide. A copy of this exhibit is presented in the Technical Appendix section of this report. The required stopping sight distance for a speed of 30 miles per hour is 200 feet. Therefore, the available sight distance far exceeds 300' to the right (south). As stated herein above, traffic from the left (north) does not have the distance required to reach 30 mph.

From proposed driveway looking to the left (north)



From proposed driveway looking to the right (south)



As demonstrated herein above, available sight distances are greater than the required values. Therefore, proper sight distances will be provided in both directions.

Accidents: The latest accident data compiled by the *massDOT* were obtained and reviewed for a period of January 1, 2020, through March 23, 2024. This review summarizes the total number of accidents that occurred at each of these two intersections during this period, and is listed in Table 3, below. It is noted that a total of eight accidents occurred during this period at the intersection of West Mountain Street and Pullman Street with no personal injuries, while a total of 14 accidents were reported during the same period at the intersection of West Mountain Street and Brooks Street, five of which involved nonfatal injuries. None of the West Mountain and Pullman Streets intersection accidents took place during peak traffic periods. Five of the accidents at the intersection of West Mountain and Brooks Streets occurred during peak periods. The breakdown of all accidents at these two intersections is also presented below in Table 3.

Using the baseline turning movement counts compiled during traffic surveys of these two intersections, accident rates were calculated in accidents per million vehicles entering each intersection. Utilizing the *massDOT* prescribed methodology, the accident rates for these intersections were calculated at lower to significantly lower than the *massDOT*'s latest available rate of 0.89 for signalized intersections on roadways in District 3 of the *massDOT*, in which the City of Worcester is located. A summary of the accident rates is also included in the following Table 3. A copy of the accident rate calculation is included in the Technical Appendix section of this report. Also included in the Technical Appendix section of this report is a copy of the

massDOT Average Crash Rates for signalized and unsignalized intersections throughout the Commonwealth of Massachusetts.

The above accident analysis indicates that there are no potential safety deficiencies associated with any of these intersections.

Table 3 - Vehicle Crash Summary (Jan 1, 2020-March 23, 2024)

	Pullman St W Mountain St	Brooks St W Mountain St
Intersection	Signalized	Signalized
Calculated Crash Rate	0.30	0.77
massDOT Av Rate	0.89	0.89
Year		
2020	3	3
2021	2	2
2022	2	2
2023	1	7
2024	0	0
Total	8	14
Collision Type		
Angle	6	7
Head-On	0	3
Rear-end	2	1
Sideswipe	0	1
Single Vehicle	0	1
Unknown	0	1
Total	8	14
Severity		
Fatal Injury	0	0
Non-Fatal Injury	0	5
Property Damage	8	9
Total	8	14
Time of Day		
7:00 AM to 9:00 AM	0	1
4:00 PM to 6:00 PM	0	2
Other Times	8	11
Total	8	14
Pavement Conditions		
Dry	5	8
Wet	2	5
Snow	1	1
Total	8	14

Source: massDOT Crash Portal Jan 1, 2020-March 23, 2024

Existing Conditions Summary

West Mountain Street can be characterized as a two-way roadway with two travel lanes in each direction in the immediate vicinity of the proposed fast casual restaurant. It is an urban arterial roadway. The roadway width is approximately 50' in the surrounding area of the proposed fast

Proposed Restaurant at 79 Pullman Street
casual restaurant site. On-street parking is not permitted along this section of the street, and all properties provide off-street parking. Finally, there are no bike lanes on the surrounding streets leading to this site.

The current land use designation for the site of the proposed redevelopment is ML 0.5 and MG 0.5 as established by the City of Worcester and is the site of former Sylvan Learning Center.

3

FUTURE CONDITIONS

Where possible, traffic volumes in the study area are projected to post-development levels. Projected traffic volumes include the existing traffic data obtained from the new turning movement counts, adjusted, and normalized into the year 2024 to account for the COVID-19 pandemic and to represent the post-pandemic baseline, then projected into the future no build (year 2029) to reflect increases due to future area projects, and finally, added to the new traffic expected to be generated by the proposed fast casual restaurant development to represent future build conditions.

Site-Generated Traffic

The magnitude of traffic volumes that will be generated by the proposed development was projected by using the 11th Edition (latest) of *Trip Generation¹ Manual* plus its supplement published by the Institute of Transportation Engineers (ITE).

Based on the ITE *Trip Generation Manual*, the rates at which the proposed land use generates traffic vary depending upon the time of day. These rates were used to calculate the number of trips expected to be generated by the proposed fast casual restaurant development during an average weekday, morning, afternoon, and Saturday peak traffic periods. To obtain the most accurate forecast and to be consistent with the guidelines established by the *massDOT*, when available, the fitted curves in the *Trip Generation Manual* were used to forecast trips to and from the proposed site for daily, AM, PM, and Saturday peak hours. The ITE Trip Generation pages are presented in the Technical Appendix section of this report. The resulting trips and their directional distribution for this site are shown in the following Table 4.

TABLE 4
ITE Trip Generation for Fast Casual Restaurant Development
2,328 sf Restaurant - ITE LU Code 930

	Daily	%In	%Out	AM Pk	%In	%Out	PM Pk	%In	%Out	Sat Pk	%In	%Out
Trip Rate	97.14	50%	50%	1.43	50%	50%	12.55	55%	45%	32.65	55%	45%
Trips	226	113	113	3	2	1	26*	14*	12*	76	42	34

* Fitted Curve values were used as they were greater than Average values

As can be seen in Table 4 above, the total number of new trips expected to be generated by the proposed fast casual restaurant development results in the highest traffic during Saturday peak period, thus making the Saturday peak hour the critical peak. In standard traffic engineering


practice, the critical peak period trips are usually used to evaluate the worst-case scenario. However, since the area roadway peak traffic occurs during AM and PM peak periods, all three AM, PM and Saturday peak traffic periods were evaluated for both signalized intersections.

Trip Distribution and Assignment

Because such factors as population density, land use, availability of major highways in the area, and other demographics that make up the traffic patterns within a community, the directional distribution of the projected site-generated trips to and from the proposed restaurant development site was based on the existing traffic patterns within the immediate vicinity of the site and based on the knowledge of local traffic patterns. The turning movement traffic counts for the intersection of West Mountain Street with Brooks Street and Pullman Street are good indicators of the traffic patterns in this area.

Using this information, the projected new site-generated trips from the above table 4 are proportionally assigned to each approach of these intersections. As shown in table 4 above and Figure 4 below, during AM peak period, a sum of two vehicles would be arriving at the proposed development site and one vehicle would be departing from the site in both directions along Pullman Street via the proposed site driveway. During PM peak period, a total of 14 vehicles are expected to arrive and 12 vehicles are expected to depart from the proposed site via the proposed site driveway. During a Saturday peak hour, a total of 42 vehicles are expected to arrive and 34 vehicles are expected to exit the site. Finally, a total of 113 vehicles are expected to arrive and 113 vehicles are expected to depart from the proposed restaurant site during a 24-hour period on an average day.

Figure 4
Trip Generation and Distribution



Site Access and Circulation

Site access and internal traffic circulation were evaluated as part of assessing the proposed residential development site. Access to the proposed site is achieved through a driveway located on Pullman Street approximately 150 feet south of the West Mountain Street intersection. The proposed site driveway will provide full access to all parking spaces and the drive-through lane with an escape lane in a safe manner as required by the City of Worcester Zoning ordinances. The site driveway is 24 feet in width to accommodate two-way traffic in and out of the site.

Also, as stated earlier, a total of 29 parking spaces are proposed, two of which will be designed and designated as van accessible handicap parking. This translates into 12.5 parking spaces per 1,000 sf of floor area. A total of eight of the proposed parking spaces will be diagonal and the remaining spaces will be at 90 degrees.

As for the length of the drive through lane, a 180-foot stacking lane is proposed. Although this is shorter than that required by the Zoning ordinances of the City of Worcester for traditional fast food restaurants, it should suffice for this particular land use with a digital pickup lane. It is noted that this type of restaurant is different from the traditional fast-food restaurants as no menu board

will be provided. All orders are processed and paid for ahead of time before a patron arrives at the site. That means people arrive at the drive through window just to pick up an order. As such, the pickup time for each order is significantly shorter than those associated with traditional fast-food restaurants where a patron will have to view the menu board, then place an order, pull up to the window, pay for the order, and pick up the order. Assuming one third of all trips to the site are to use the digital pickup lane to pick up an order, during a Saturday peak a total of 14 pickup orders will be processed. This translates into more than four minutes between each pickup. In absolute worst-case scenario, if it is assumed half of the Saturday peak trips are to use the digital pickup lane, we are talking about nearly three minutes between orders. Therefore, the stacking lane is not expected to surpass or even reach the length of the proposed 180 feet digital pickup lane.

The magnitude of parking spaces that will be required by the proposed restaurant development was forecasted by using the 6th Edition of *Parking Generation Manual*¹ also published by the ITE. Based on the latest ITE *Parking Generation Manual*, the rates at which fast casual restaurant (land use 930) generate demand for parking vary depending upon the time of day. The demand for off-street parking is greatest during midday for lunch and slightly less during the afternoon peak period for dinner. The average peak period parking demand for fast casual restaurants on a weekday is 9.77 vehicles per 1,000 sf of floor area and 7.97 parking spaces per 1,000 sf of floor area on Saturdays. This translates into anywhere from 28% to 57% more available parking spaces than will be needed during an average weekday or on a Saturday.

¹ *Parking Generation*, Institute of Transportation Engineers; Washington, DC

4

TRAFFIC OPERATIONS

Measuring existing traffic volumes and projecting future traffic volumes quantifies traffic flow within the study area. To assess the quality of traffic flow, intersection capacity analyses were performed to measure projected future conditions with the implementation of the proposed restaurant development project. Intersection capacity analyses provide an indication of how well roadway facilities and their components serve the traffic demands placed upon them. This section includes potential on-site and off-site mitigation improvements that may be necessary to minimize the impact of the proposed restaurant development on the adjacent roadway.

Traffic Operations Measures

Level of service (LOS) is the term used to demonstrate the different operating conditions which occur on a given roadway segment or intersection under different traffic volume conditions. LOS is a qualitative measure of the effect of several factors including roadway geometry, speed, travel delay, signal timing, freedom to maneuver and safety. The driveway of the proposed fast casual restaurant is treated as a stop-controlled intersection for the purpose of this evaluation. The criteria used to analyze the proposed driveway at Pullman Street are based on the Highway Capacity Manual.

The LOS concept is an indicator of the operational qualities of a roadway or an intersection. Six LOSs are defined for each type of facility. They are given letter designations from “A” to “F”. LOS “A” represents the best operating conditions, while LOS “F” represents the worst. Typically, LOS “D” is considered acceptable for arterial roadways during critical peak hour conditions, but LOS “E” may also be acceptable under some circumstances.

The LOS designation is reported differently for signalized and unsignalized intersections. For signalized intersections, the analysis considers the operation of all traffic entering the intersection, and a LOS designation can be calculated for overall conditions at the intersection. For an unsignalized intersection, however, the analysis assumes that through traffic on major roadways is not affected by traffic on side streets (streets with lower volumes and/or ones under stop sign control). Therefore, a LOS designation is typically calculated for the controlled movements (minor street approaches and major street left-turn movements). As described in the following paragraphs, capacity or LOS analyses were considered for year 2024 existing, year 2029 future no build, and year 2029 future build conditions for morning, evening, and Saturday peak hours at the above-mentioned intersections, including the proposed site driveway.

Existing Conditions

Intersection capacity analyses were performed for both intersections during morning, evening, and Saturday peak traffic periods. These intersections are the only locations within the immediate vicinity of the proposed development site that may be affected by the traffic expected to be generated by the proposed fast casual restaurant development.


The analysis concluded that LOS “C” or better is calculated for all approaches of the intersection of West Mountain Street and Brooks Street during all three peak periods. Also, the analysis showed that LOS “D” or better is calculated for all approaches of the intersection of West Mountain Street and Pullman Street. A summary of intersection analyses results for existing conditions is shown below in Table 5.

Future Conditions

Capacity analyses for the future year peak hour traffic operations were performed for the year 2029 volumes during all three peak periods with and without the proposed fast casual restaurant project in place. A summary of intersection analyses results for both future no-build and future build conditions is also shown below in Table 5.

As noted earlier in this report, in projecting the year 2029 future no-build traffic volumes, the latest *massDOT* available statistics were used. As stated earlier under the Traffic Volumes section, the growth rates that go back to 2014 were averaged and then applied to expand to a five-year period to represent the buildout year. The average annual growth rate over the past five-year period was calculated at 0.0034. Therefore, the baseline volumes were increased by that rate over five years or a factor of 0.0175. Figure 5 shows the volumes for the future no-build conditions for both intersections within the study area. The projected future no build year (2029) traffic should also account for any future developments in the general area of the proposed site.

Figure 5
Future No Build Turning Movement Counts



The intersection LOSs for the year 2029 no-build conditions were calculated for the approaches of these two intersections and are expected to be the same as those under existing conditions.

Build traffic volumes were determined by projecting site-generated traffic volumes and distributing those volumes over the intersections within the study area, and finally, adding them to the future no-build conditions volumes. Figure 6 shows future build conditions traffic volumes for both intersections, including the proposed site driveway that will form a three-legged intersection with Pullman Street.


To assess the potential traffic impact of the proposed development on these two intersections, all traffic to and from the site was distributed along Pullman Street and two nearby signalized intersections. This will result in the assessment of these intersections under worst-case scenarios. The above Figures 3, 5 and 6 show the traffic volumes at all intersections for the AM, PM, and Saturday peak hours under existing, future no-build, and future build conditions.

The intersection analysis for the year 2029 build conditions were performed for approaches of both intersections including the site driveway. The analysis revealed that under future build conditions, all existing intersections will continue to operate at the same LOSs as those under the future no-build conditions.

Again, the above-mentioned LOSs for both signalized intersections under existing and for future no-build and future build conditions are indicative of no impact associated with the development of the proposed fast casual restaurant project.

A summary of intersection analyses for all intersections, including the proposed driveway that forms the third leg of the intersection of Pullman Street and the site driveway is also provided below in Table 5. Finally, the computer printout of the above-mentioned intersection analysis is presented and included in the Technical Appendix section of this report.

Figure 6
Future Build Turning Movement Counts



**Table 5
Intersection Analysis**

Intersestion of West Mountain Street and Brooks Street

Existing Conditions	AM Peak			PM Peak		
	EB	WB	NB	EB	WB	NB
V/C	0.52	0.2	0.16	0.41	0.49	0.16
App Delay	17	9.3	19.8	23.9	16.4	20.5
App LOS	B	A	B	C	B	C
95% Queue	181	66	46	189	238	49
Int LOS	B			B		

Future No Build Conditions

	EB	WB	NB	EB	WB	NB
V/C	0.53	0.2	0.17	0.42	0.5	0.16
App Delay	17.1	9.3	19.9	24	16.5	20.9
App LOS	B	A	B	C	B	C
95% Queue	184	67	47	193	244	50
Int LOS	B			B		

Future Build Conditions

	EB	WB	NB	EB	WB	NB
V/C	0.53	0.2	0.17	0.42	0.5	0.16
App Delay	17.1	9.3	19.9	24	16.5	20.9
App LOS	B	A	B	C	B	C
95% Queue	185	67	47	194	244	50
Int LOS	B			B		

Intersestion of West Mountain Street and Pullman Street

Existing Conditions	AM Peak			PM Peak		
	EB	WB	NB	EB	WB	NB
V/C	0.83	0.23	0.17	0.44	0.48	0.61
App Delay	35.6	10.1	15.1	23.4	9.9	23.7
App LOS	D	B	B	C	A	C
95% Queue	265	74	58	181	168	195
Int LOS	C			B		

Future No Build Conditions

	EB	WB	NB	EB	WB	NB
V/C	0.84	0.23	0.18	0.44	0.48	0.62
App Delay	36.4	10.2	15.1	23.6	10	23.7
App LOS	D	B	B	C	A	C
95% Queue	271	75	60	184	172	198
Int LOS	C			B		

Future Build Conditions

	EB	WB	NB	EB	WB	NB
V/C	0.85	0.23	0.18	0.44	0.49	0.63
App Delay	36.6	10.2	15.1	23.4	10	23.8
App LOS	D	B	B	C	A	C
95% Queue	272	75	60	184	173	202
Int LOS	C			B		

Intersestion of Site Driveway and Pullman Street

Future Build Conditions	AM Peak			PM Peak		
	EB	NB	SB	EB	NB	SB
V/C	0	0.01	0.11	0.03	0.01	0.2
App Delay	9.2	0.7	0	12.5	0.3	0
Lane LOS	A	A		B	A	
Queue ft	0	1	0	2	1	0
ICU LOS	A			A		

5

FINDINGS

This traffic study has been conducted to evaluate the potential traffic impacts associated with the proposed fast casual restaurant development site located west of Pullman Street and just to the south of West Mountain Street in Worcester, Massachusetts utilizing new traffic data that were collected in April of 2024. This study includes the evaluation of two signalized intersections in close proximity of the proposed site which are likely to be impacted by any traffic from the proposed restaurant development project. An evaluation of the area roadway to identify capacity constraints was performed for existing, future no-build, and future build conditions. Future analyses have determined that the site-generated traffic volumes are not significant, and they can safely be accommodated with the existing roadways and the proposed site driveway. These analyses demonstrated that with the additional traffic volumes associated with the proposed restaurant development, the intersection LOSs would not degrade and remain at those of existing and future no build conditions. The analysis also showed that the approaches of the intersection of Pullman Street and the site driveway will be operating at LOS “B” or better during all three peak periods.

Also, the accident analysis for the intersections in the study area revealed that accident rates are lower than those of similar intersections, further signifying there are no particular safety issues associated with these intersections.

Although there are no bike lane designations on the streets leading to the proposed site, it would be helpful to provide a bike rack on the site to accommodate the needs of those who may ride their bicycles to the proposed restaurant.

As stated earlier, the percentage of truck traffic at permanent counting station #S17-042-348-02 along West Mountain Street was recorded by the *massDOT* at 1.9%. This value is considered average for roadways having similar characteristics.

Finally, due to the very low levels of new traffic associated with the proposed restaurant, the length of the drive-through lane (digital pickup lane) should sufficiently accommodate the demand at this location. As established herein above, even if 50% of the Saturday peak trips to the site were to use the drive through window for picking up orders, ample time would be available, thus no measurable queueing should occur.

Conclusion & Recommendations

It is concluded that the area roadways within the vicinity of the proposed development site have enough capacity to safely serve the anticipated additional traffic associated with the proposed fast casual restaurant. The level of service evaluation presented above is an indicator of the quality of traffic flow through the area. This evaluation indicates that the LOSs are not expected to change or should not degrade at either of the two signalized intersections studied.

It should be noted that the applicant will need to maintain any landscaped area along the frontage of the proposed property to further enhance the sight distances for motorists leaving the site.

Therefore, to maintain optimum safety and efficiency, the following improvements are recommended.


- The site frontage on the east side of Pullman Street should be clear of future tall landscaping vegetation that could impede the line of sight of motorists leaving the site via the proposed driveway.
- Any landscaping along the frontage of the proposed site on Pullman Street should be limited to vegetation varieties that do not grow higher than 2.5 feet to ensure the best sight distances are maintained.
- It is recommended that a double yellow center line be installed in the driveway area to help maintain safe two-way traffic.
- It is recommended that a Stop Bar be installed for the eastbound traffic exiting the site.
- It is recommended that a MUTCD standard stop sign be installed for the eastbound traffic leaving the site and entering Pullman Street traffic.
- Finally, it is recommended that a bike rack be provided to accommodate cyclists that may frequent the proposed restaurant. Such a bike rack could be installed just south of the building and north of the HP parking spaces, or alternatively it could be installed in one of the parking spaces closest to the building.

Appendix

Accurate Counts
978-664-2565

N/S Street : Brooks Street
E/W Street : W Mountain Street
City/State : Worcester, MA
Weather : Clear

File Name : 20140001
Site Code : 20140001
Start Date : 4/9/2024
Page No : 2




Peak Hour Analysis From 07:00 AM to 08:45 AM - Peak 1 of 1
Peak Hour for Each Approach Begins at:

	07:30 AM			08:00 AM			07:30 AM		
+0 mins.	3	69	72	14	2	16	169	21	190
+15 mins.	6	87	93	17	4	21	191	18	209
+30 mins.	1	88	89	9	4	13	156	14	170
+45 mins.	1	74	75	13	4	17	147	17	164
Total Volume	11	318	329	53	14	67	663	70	733
% App. Total	3.3	96.7		79.1	20.9		90.5	9.5	
PHF	.458	.903	.884	.779	.875	.798	.868	.833	.877
Cars	11	312	323	50	12	62	652	70	722
% Cars	100	98.1	98.2	94.3	85.7	92.5	98.3	100	98.5
Trucks	0	6	6	3	2	5	11	0	11
% Trucks	0	1.9	1.8	5.7	14.3	7.5	1.7	0	1.5

Accurate Counts
978-664-2565

N/S Street : Brooks Street
E/W Street : W Mountain Street
City/State : Worcester, MA
Weather : Clear

File Name : 20140001
Site Code : 20140001
Start Date : 4/9/2024
Page No : 2




Peak Hour Analysis From 04:00 PM to 05:45 PM - Peak 1 of 1
Peak Hour for Each Approach Begins at:

	04:15 PM			04:00 PM			04:00 PM		
+0 mins.	7	196	203	22	5	27	139	10	149
+15 mins.	5	224	229	11	1	12	127	8	135
+30 mins.	2	201	203	12	7	19	137	11	148
+45 mins.	8	199	207	14	3	17	119	13	132
Total Volume	22	820	842	59	16	75	522	42	564
% App. Total	2.6	97.4		78.7	21.3		92.6	7.4	
PHF	.688	.915	.919	.670	.571	.694	.939	.808	.946
Cars	22	818	840	58	16	74	509	40	549
% Cars	100	99.8	99.8	98.3	100	98.7	97.5	95.2	97.3
Trucks	0	2	2	1	0	1	13	2	15
% Trucks	0	0.2	0.2	1.7	0	1.3	2.5	4.8	2.7

Accurate Counts
978-664-2565

N/S Street : Brooks Street
E/W Street : W Mountain Street
City/State : Worcester, MA
Weather : Cloudy

File Name : 201400S1
Site Code : 20140001
Start Date : 4/6/2024
Page No : 2




Peak Hour Analysis From 11:00 AM to 12:45 PM - Peak 1 of 1
Peak Hour for Each Approach Begins at:

	11:30 AM			11:00 AM			11:45 AM		
+0 mins.	0	125	125	4	6	10	134	5	139
+15 mins.	0	133	133	5	3	8	122	1	123
+30 mins.	4	115	119	8	4	12	101	5	106
+45 mins.	2	136	138	3	1	4	136	4	140
Total Volume	6	509	515	20	14	34	493	15	508
% App. Total	1.2	98.8		58.8	41.2		97	3	
PHF	.375	.936	.933	.625	.583	.708	.906	.750	.907
Cars	6	509	515	20	14	34	493	14	507
% Cars	100	100	100	100	100	100	100	93.3	99.8
Trucks	0	0	0	0	0	0	0	1	1
% Trucks	0	0	0	0	0	0	0	6.7	0.2

Accurate Counts
978-664-2565

N/S Street : Pullman Street
E/W Street : W Mountain Street
City/State : Worcester, MA
Weather : Clear

File Name : 20140002
Site Code : 20140002
Start Date : 4/9/2024
Page No : 2




Peak Hour Analysis From 07:00 AM to 08:45 AM - Peak 1 of 1
Peak Hour for Each Approach Begins at:

	07:15 AM			08:00 AM			07:30 AM		
+0 mins.	15	65	80	17	16	33	146	27	173
+15 mins.	8	60	68	16	20	36	177	22	199
+30 mins.	21	77	98	14	18	32	130	29	159
+45 mins.	18	69	87	18	26	44	120	30	150
Total Volume	62	271	333	65	80	145	573	108	681
% App. Total	18.6	81.4		44.8	55.2		84.1	15.9	
PHF	.738	.880	.849	.903	.769	.824	.809	.900	.856
Cars	57	266	323	59	74	133	568	102	670
% Cars	91.9	98.2	97	90.8	92.5	91.7	99.1	94.4	98.4
Trucks	5	5	10	6	6	12	5	6	11
% Trucks	8.1	1.8	3	9.2	7.5	8.3	0.9	5.6	1.6

Accurate Counts
978-664-2565

N/S Street : Pullman Street
E/W Street : W Mountain Street
City/State : Worcester, MA
Weather : Clear

File Name : 20140002
Site Code : 20140002
Start Date : 4/9/2024
Page No : 2




Peak Hour Analysis From 04:00 PM to 05:45 PM - Peak 1 of 1
Peak Hour for Each Approach Begins at:

	04:15 PM			04:15 PM			04:00 PM		
+0 mins.	34	167	201	41	40	81	108	43	151
+15 mins.	46	151	197	65	45	110	80	46	126
+30 mins.	37	142	179	47	38	85	106	42	148
+45 mins.	39	156	195	43	55	98	89	34	123
Total Volume	156	616	772	196	178	374	383	165	548
% App. Total	20.2	79.8		52.4	47.6		69.9	30.1	
PHF	.848	.922	.960	.754	.809	.850	.887	.897	.907
Cars	143	614	757	195	164	359	373	160	533
% Cars	91.7	99.7	98.1	99.5	92.1	96	97.4	97	97.3
Trucks	13	2	15	1	14	15	10	5	15
% Trucks	8.3	0.3	1.9	0.5	7.9	4	2.6	3	2.7

Accurate Counts
978-664-2565

N/S Street : Pullman Street
E/W Street : W Mountain Street
City/State : Worcester, MA
Weather : Cloudy

File Name : 201400S2
Site Code : 20140002
Start Date : 4/6/2024
Page No : 2



Peak Hour Analysis From 11:00 AM to 12:45 PM - Peak 1 of 1
Peak Hour for Each Approach Begins at:

	12:00 PM			11:15 AM			11:45 AM		
+0 mins.	37	89	126	41	20	61	95	41	136
+15 mins.	29	100	129	28	28	56	93	29	122
+30 mins.	35	92	127	30	33	63	78	28	106
+45 mins.	37	109	146	33	42	75	110	28	138
Total Volume	138	390	528	132	123	255	376	126	502
% App. Total	26.1	73.9		51.8	48.2		74.9	25.1	
PHF	.932	.894	.904	.805	.732	.850	.855	.768	.909

**Exhibit 3-8
Motor Vehicle Stopping Sight Distances**

Design Speed	Stopping Sight Distance (ft) by Percent Grade (%)						
	0	Downgrade			Upgrade		
		3	6	9	3	6	9
20	115	116	120	126	109	107	104
25	155	158	165	173	147	143	140
30	200	205	215	227	200	184	179
35	250	257	271	287	237	229	222
40	305	315	333	354	289	278	269
45	360	378	400	427	344	331	320
50	425	446	474	507	405	388	375
55	495	520	553	593	469	450	433
60	570	598	638	686	538	515	495
65	645	682	728	785	612	584	561
70	730	771	825	891	690	658	631
75	820	866	927	1003	772	736	704

Source: A Policy on Geometric Design of Streets and Highways, AASHTO, Washington DC, 2004. Chapter 3 Elements of Design

Massachusetts Highway Department
 Statewide Traffic Data Collection
 2019 Weekday Seasonal Factors

Factor Group	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	Axle Factor
R1	1.22	1.14	1.12	1.06	1.00	0.96	0.87	0.85	0.96	0.99	1.04	1.12	0.85
R2	0.95	0.96	0.98	0.97	0.97	0.93	0.97	0.94	0.96	0.90	0.92	0.93	0.96
R3	1.15	1.06	1.07	1.00	0.89	0.88	0.89	0.89	0.95	0.92	1.02	1.01	0.97
R4-R7	1.09	1.09	1.11	1.02	0.96	0.92	0.89	0.89	0.99	0.98	1.09	1.13	0.98
U1-Boston	1.03	1.01	0.98	0.94	0.94	0.92	0.95	0.93	0.94	0.94	0.97	1.04	0.96
U1-Essex	1.09	1.06	1.03	0.99	0.94	0.90	0.88	0.86	0.93	0.94	0.99	1.06	0.93
U1-Southeast	1.06	1.05	1.01	0.97	0.95	0.93	0.93	0.90	0.94	0.94	0.98	1.04	0.98
U1-West	1.19	1.14	1.09	0.95	0.92	0.89	0.89	0.86	0.91	0.95	0.97	1.07	0.84
U1-Worcester	1.02	1.04	0.97	0.94	0.93	0.91	0.95	0.91	0.93	0.92	0.95	1.10	0.88
U2	1.01	1.00	0.94	0.93	0.91	0.89	0.93	0.90	0.90	0.91	0.94	1.02	0.99
U3	1.06	1.03	0.98	0.94	0.93	0.91	0.95	0.91	0.92	0.93	0.97	1.00	0.98
U4-U7	1.01	1.00	0.95	0.92	0.88	0.86	0.92	0.91	0.92	0.94	0.99	1.04	0.99
Rec - East	1.04	1.16	1.12	0.98	0.92	0.88	0.77	0.81	0.94	1.02	1.08	1.12	0.99
Rec - West	1.30	1.23	1.32	1.18	0.95	0.82	0.70	0.69	0.97	0.96	1.16	1.15	0.98

Round off:
 0-999 = 10
 >1000 = 100

U = Urban
 R = Rural

- 1 - Interstate
- 2 - Freeway and Expressway
- 3 - Other Principal Arterial
- 4 - Minor Arterial
- 5 - Major Collector
- 6 - Minor Collector
- 7 - Local Road and Street

Recreational - East Group - Cape Cod (all towns) including the town of Plymouth south of Route 3A (stations 7014,7079,7080,7090,7091,7092,7093,7094,7095,7096,7097,7108 and 7178), Martha's Vineyard and Nantucket. Recreational - West Group - Continuous Stations 2 and 189 including stations 1066,1067,1083,1084,1085,1086,1087,1088,1089,1090,1091,1092,1093,1094,1095,1096,1097,1098,1099,1100,1101,1102,1103,1104,1105,1106,1107,1108,1113,1114,1116,2196,2197 and 2198.
--

5/31/2020

Average Crash Rates, per Million Entering Vehicles, by Intersection Type
 (Based upon crash information queried on June 26, 2018)

Location	Signalized Intersections	Unsignalized Intersections
Statewide	0.78	0.57
District 1*	0.80*	0.44*
District 2	0.89	0.62
District 3	0.89	0.61
District 4	0.73	0.57
District 5	0.75	0.57
District 6	0.71	0.52

Location	Signalized Intersections	Unsignalized Intersections
-----------------	---------------------------------	-----------------------------------

* - District 1 should use Statewide Rates due to low sample total

Fast Casual Restaurant (930)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA
On a: Weekday


Setting/Location: General Urban/Suburban
Number of Studies: 1
Avg. 1000 Sq. Ft. GFA: 1
Directional Distribution: 50% entering, 50% exiting

Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate	Range of Rates	Standard Deviation
97.14	97.14 - 97.14	***

Data Plot and Equation

Caution – Small Sample Size



Fast Casual Restaurant (930)


Vehicle Trip Ends vs: 1000 Sq. Ft. GFA
On a: Weekday,
Peak Hour of Adjacent Street Traffic,
One Hour Between 7 and 9 a.m.
Setting/Location: General Urban/Suburban
 Number of Studies: 1
 Avg. 1000 Sq. Ft. GFA: 1
 Directional Distribution: 50% entering, 50% exiting

Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate	Range of Rates	Standard Deviation
1.43	1.43 - 1.43	***

Data Plot and Equation

Caution – Small Sample Size




Fast Casual Restaurant (930)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA
On a: Weekday,
Peak Hour of Adjacent Street Traffic,
One Hour Between 4 and 6 p.m.
Setting/Location: General Urban/Suburban
Number of Studies: 15
Avg. 1000 Sq. Ft. GFA: 3
Directional Distribution: 55% entering, 45% exiting

Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate	Range of Rates	Standard Deviation
12.55	5.94 - 27.40	5.52



Fast Casual Restaurant (930)

Vehicle Trip Ends vs: 1000 Sq. Ft. GFA
On a: Saturday, Peak Hour of Generator


Setting/Location: General Urban/Suburban
Number of Studies: 2
Avg. 1000 Sq. Ft. GFA: 5
Directional Distribution: 55% entering, 45% exiting

Vehicle Trip Generation per 1000 Sq. Ft. GFA

Average Rate	Range of Rates	Standard Deviation
32.64	32.26 - 33.00	***

Data Plot and Equation

Caution - Small Sample Size




Fast Casual Restaurant (930)

Peak Period Parking Demand vs: 1000 Sq. Ft. GFA
 On a: Weekday (Monday - Friday)
 Setting/Location: General Urban/Suburban
 Number of Studies: 8
 Avg. 1000 Sq. Ft. GFA: 3.1

Peak Period Parking Demand per 1000 Sq. Ft. GFA

Average Rate	Range of Rates	33rd / 85th Percentile	95% Confidence Interval	Standard Deviation: (Coeff. of Variation)
9.77	5.86 - 15.00	8.57 / 13.61	***	2.71 (28%)

Data Plot and Equation




Fast Casual Restaurant (930)

Peak Period Parking Demand vs: 1000 Sq. Ft. GFA
On a: Saturday
Setting/Location: General Urban/Suburban
Number of Studies: 3
Avg. 1000 Sq. Ft. GFA: 3.5

Peak Period Parking Demand per 1000 Sq. Ft. GFA

Average Rate	Range of Rates	33rd / 85th Percentile	95% Confidence Interval	Standard Deviation (Coeff. of Variation)
7.97	6.32 - 10.34	6.67 / 10.34	***	1.89 (24%)

Data Plot and Equation






INTERSECTION CRASH RATE WORKSHEET

CITY/TOWN : Worcester COUNT DATE : Apr-24
 DISTRICT : 3 UNSIGNALIZED : SIGNALIZED :

~ INTERSECTION DATA ~

MAJOR STREET : West Mountain Street
 MINOR STREET(S) : Pullman Street



PEAK HOUR VOLUMES

APPROACH :	1	2	3	4	5	Total Peak Hourly Approach Volume
DIRECTION :	EB	WB	NB			
PEAK HOURLY VOLUMES (AM/PM) :	490	723	350			1,563

" K " FACTOR : INTERSECTION ADT (V) = TOTAL DAILY APPROACH VOLUME :

TOTAL # OF CRASHES : # OF YEARS : AVERAGE # OF CRASHES PER YEAR (A) :

CRASH RATE CALCULATION : RATE = $\frac{(A * 1,000,000)}{(V * 365)}$

Comments : Significantly lower than 0.89 for signalized intersections in massDOT D3 Worcester is in
 Project Title & Date: 14-Apr-24




INTERSECTION CRASH RATE WORKSHEET

CITY/TOWN : Worcester COUNT DATE : _____
 DISTRICT : 3 UNSIGNALIZED : SIGNALIZED :

~ INTERSECTION DATA ~

MAJOR STREET : West Mountain Street
 MINOR STREET(S) : Brooks Street

INTERSECTION DIAGRAM
(Label Approaches)



PEAK HOUR VOLUMES

APPROACH :	1	2	3	4	5	Total Peak Hourly Approach Volume	
DIRECTION :	EB	WB	NB				
PEAK HOURLY VOLUMES (AM/PM) :	686	308	59			1,053	
" K " FACTOR :	0.090					INTERSECTION ADT (V) = TOTAL DAILY APPROACH VOLUME :	11,700
TOTAL # OF CRASHES :	14	# OF YEARS :	4.25	AVERAGE # OF CRASHES PER YEAR (A) :		3.29	

CRASH RATE CALCULATION : RATE = $\frac{(A * 1,000,000)}{(V * 365)}$

Comments : Lower than 0.89 for signalized intersections in D3 of massDOT Worcester is located in
 Project Title & Date: 14-Apr-24

Proposed Restaurant at 79 Pullman Street

RMV Crash Number	City Town Name	Crash Date	Crash Time	Crash Severity	Maximum Injury Severity Reported	Number of Vehicles	Total Nonfatal Injuries	Total Fatal Injuries	Manner of Collision	Vehicle Action Prior to Crash	Most Harmful Events	Vehicle Configuration	Road Surface Condition	Ambient Light	Weather Condition	At Roadway Intersection	Distance From Nearest Roadway Intersection	Distance From Nearest Exit	Vulnerable User Type	X Coordinate	Y Coordinate
4915976	WORCESTER	03-May-2020	8:25 PM	Property damage only (none injured)	No Apparent Injury (O)	2	0	0	Rear-end	V1: Slowing or stopped in traffic / V2: vehicle in traffic / Not reported	V1:(Collision with motor vehicle in traffic)	V1:(Light truck(van, mini-van, pickup, sport utility))	Dry	Dusk	Clear		MOUNTAIN STREET WEST / PULLMAN STREET			175479.1817	897181.6118
4916828	WORCESTER	27-Aug-2020	12:08 PM	Property damage only (none injured)	No Apparent Injury (O)	2	0	0	Rear-end	V1: Travelling straight ahead / V2: Slowing or stopped in traffic	V1:(Collision with motor vehicle in traffic)	V1:(Light truck(van, mini-van, pickup, sport utility)) / V2:(Light truck(van, mini-van, pickup, sport utility))	Dry	Daylight	Clear		71 PULLMAN STREET			175435.83445838	897085.55776169
4928680	WORCESTER	02-Sep-2020	7:44 PM	Property damage only (none injured)	No Apparent Injury (O)	2	0	0	Angle	V1: Turning left / V2: Travelling straight ahead	V1:(Collision with motor vehicle in traffic) / V2:(Collision with motor vehicle in traffic)	V1:(Passenger car) / V2:(Light truck(van, mini-van, pickup, sport utility))	Wet	Dark - lighted roadway	Clear	PULLMAN STREET / MOUNTAIN STREET WEST	PULLMAN STREET / MOUNTAIN STREET WEST			175479.1817	897181.6118
4947580	WORCESTER	19-Feb-2021	11:46 AM	Property damage only (none injured)	No Apparent Injury (O)	1	0	0	Head-on	V1: Travelling straight ahead	V1:(Collision with utility pole)	V1:(Passenger car)	Snow	Daylight	Cloudy/ Cloudy		51 PULLMAN STREET			175403.92167513	897014.76010058
4946544	WORCESTER	17-Mar-2021	3:15 PM	Non-fatal injury	Suspected Minor Injury (B)	2	1	0	Angle	V1: Turning left / V2: Travelling straight ahead	V1:(Collision with motor vehicle in traffic) / V2:(Collision with motor vehicle in traffic)	V1:(Passenger car) / V2:(Light truck(van, mini-van, pickup, sport utility))	Dry	Daylight	Clear	MOUNTAIN STREET EAST / PULLMAN STREET	MOUNTAIN STREET EAST / PULLMAN STREET			175479.1817	897181.6118
5080712	WORCESTER	30-Jan-2022	12:50 PM	Property damage only (none injured)	No Apparent Injury (O)	2	0	0	Angle	V1: Turning left / V2: Travelling straight ahead	V1:(Collision with motor vehicle in traffic) / V2:(Collision with motor vehicle in traffic)	V1:(Light truck(van, mini-van, pickup, sport utility)) / V2:(Passenger car)	Wet	Daylight	Clear	MOUNTAIN STREET WEST / PULLMAN STREET	MOUNTAIN STREET WEST / PULLMAN STREET			175479.1817	897181.6118
5087978	WORCESTER	20-Mar-2022	3:31 PM	Property damage only (none injured)	No Apparent Injury (O)	2	0	0	Angle	V1: Not reported / V2: Leaving traffic lane	V1:(Collision with motor vehicle in traffic)	V1:(Passenger car) / V2:(Light truck(van, mini-van, pickup, sport utility))	Dry	Daylight	Clear	PULLMAN STREET / MOUNTAIN STREET WEST /	PULLMAN STREET / MOUNTAIN STREET WEST /			175479.1817	897181.6118
5324409	WORCESTER	06-Nov-2023	12:50 PM	Property damage only (none injured)	No Apparent Injury (O)	2	0	0	Angle	V1: Travelling straight ahead / V2: Turning left	V1:(Collision with motor vehicle in traffic) / V2:(Collision with motor vehicle in traffic)	V1:(Light truck(van, mini-van, pickup, sport utility)) / V2:(Light truck(van, mini-van, pickup, sport utility))	Dry	Daylight	Clear	MOUNTAIN STREET WEST Rte / PULLMAN STREET Rte	MOUNTAIN STREET WEST Rte / PULLMAN STREET Rte			175479.1817	897181.6118

Proposed Restaurant at 79 Pullman Street

RMV Crash Number	City Town Name	Crash Date	Crash Time	Crash Severity	Maximum Injury Severity Reported	Numb er of Vehicl es	Total Nonfa tal Injurie s	Total Fatal Injurie s	Manner of Collision	Vehicle Action Prior to Crash	Most Harmful Events	Vehicle Configurat ion	Road Surfac e Conditio n	Ambient Light	Weath er Conditio n	At Roadway Intersectio n	Distance From Nearest Roadway Intersectio n	Distan ce From Neares t Exit	Vulnerab le User Type	X Coordina te	Y Coordina te
4916657	WORCESTER	17-Jul-2020	7:48 PM	Property damage only (none injured)	No Apparent Injury (O)	2	0	0	Angle	V1: Travelling straight ahead / V2: Travelling straight ahead	V1:(Collision with motor vehicle in traffic) / V2:(Collision with motor vehicle in traffic)	V1:(Passenger car) / V2:(Light truck(van, mini-van, pickup, sport utility))	Dry	Daylight	Clear	MOUNTAIN STREET WEST / BROOKS STREET	MOUNTAIN STREET WEST / BROOKS STREET			175334.4455	897272.778
4902800	WORCESTER	17-Jul-2020	8:09 PM	Property damage only (none injured)	No Apparent Injury (O)	2	0	0	Head-on	V1: Travelling straight ahead / V2: Turning left	V1:(Collision with motor vehicle in traffic) / V2:(Collision with motor vehicle in traffic)	V1:(Light truck(van, pickup, sport utility)) / V2:(Light truck(van, mini-van, pickup, sport utility))	Dry	Dusk	Clear/Clear	MOUNTAIN STREET WEST / BROOKS STREET	MOUNTAIN STREET WEST / BROOKS STREET			175334.4455	897272.778
4892649	WORCESTER	17-Oct-2020	9:00 AM	Property damage only (none injured)	No Apparent Injury (O)	2	0	0	Head-on	V1: Travelling straight ahead / V2: Slowing or stopped in traffic	V1:(Collision with parked motor vehicle) / V2:(Collision with parked motor vehicle)	V1:(Light truck(van, mini-van, pickup, sport utility)) / V2:(Passenger car)	Snow	Daylight	Cloudy/Rain	MOUNTAIN STREET WEST / BROOKS STREET	MOUNTAIN STREET WEST / BROOKS STREET			175437.4942	897208.2992
4961069	WORCESTER	15-Apr-2021	5:12 PM	Property damage only (none injured)	No Apparent Injury (O)	2	0	0	Angle	V1: Turning left / V2: Travelling straight ahead	V1:(Collision with motor vehicle in traffic) / V2:(Collision with motor vehicle in traffic)	V1:(Passenger car) / V2:(Light truck(van, mini-van, pickup, sport utility))	Wet	Daylight	Rain	BROOKS STREET / MOUNTAIN STREET WEST	BROOKS STREET / MOUNTAIN STREET WEST			175437.4942	897208.2992
5011604	WORCESTER	13-Aug-2021	6:17 PM	Non-fatal injury	Suspected Minor Injury (B)	2	1	0	Angle	V1: Turning left / V2: Travelling straight ahead	V1:(Collision with motor vehicle in traffic) / V2:(Collision with motor vehicle in traffic)	V1:(Light truck(van, mini-van, pickup, sport utility)) / V2:(Light truck(van, mini-van, pickup, sport utility))	Dry	Daylight	Clear	MOUNTAIN STREET WEST / BROOKS STREET	MOUNTAIN STREET WEST / BROOKS STREET			175437.4942	897208.2992
5017976	WORCESTER	01-Sep-2021	11:46 AM	Non-fatal injury	Possible Injury (C)	2	1	0	Front to Rear	V1: Slowing or stopped in traffic / V2: Travelling straight ahead	V1:(Collision with motor vehicle in traffic) / V2:(Collision with motor vehicle in traffic)	V1:(Passenger car) / V2:(Passenger car)	Wet	Daylight	Rain	BROOKS STREET / MOUNTAIN STREET WEST			175437.4942	897208.2992	
5031726	WORCESTER	24-Sep-2021	9:27 AM	Property damage only (none injured)	No Apparent Injury (O)	2	0	0	Angle	V1: Travelling straight ahead / V2: Not reported	V1:(Collision with motor vehicle in traffic)	V1:(Passenger car)	Wet	Daylight	Rain/Rain	BROOKS STREET / MOUNTAIN STREET WEST / MOUNTAIN STREET WEST	79 BROOKS STREET / MOUNTAIN STREET WEST			175437.4942	897208.2992

W Mountain St at Brooks St AM Peak Existing Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑	↑↑		
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.985				0.969		
Flt Protected				0.997	0.963		
Satd. Flow (prot)	3486	0	0	3529	1738	0	
Flt Permitted				0.905	0.963		
Satd. Flow (perm)	3486	0	0	3203	1738	0	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	18				17		
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	621	65	10	298	44	15	
Peak Hour Factor	0.87	0.83	0.46	0.90	0.78	0.88	
Adj. Flow (vph)	714	78	22	331	56	17	
Lane Group Flow (vph)	792	0	0	353	73	0	
Turn Type			pm+pt				
Protected Phases	2		1	6	3		9
Permitted Phases			6				
Minimum Split (s)	40.0		10.0	40.0	25.0		8.0
Total Split (s)	40.0	0.0	10.0	50.0	25.0	0.0	8.0
Total Split (%)	48%	0%	12%	60%	30%	0%	10%
Maximum Green (s)	36.0		6.0	46.0	21.0		4.0
Yellow Time (s)	3.0		3.0	3.0	3.0		3.5
All-Red Time (s)	1.0		1.0	1.0	1.0		0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0		
Flash Dont Walk (s)	11.0		11.0	11.0	11.0		
Pedestrian Calls (#/hr)	0		0	0	0		
Act Effct Green (s)	36.0			46.0	21.0		
Actuated g/C Ratio	0.43			0.55	0.25		
v/c Ratio	0.52			0.20	0.16		
Uniform Delay, d1	16.7			9.2	18.3		
Delay	17.0			9.3	19.8		
LOS	B			A	B		
Approach Delay	17.0			9.3	19.8		
Approach LOS	B			A	B		
Queue Length 50th (ft)	140			44	22		
Queue Length 95th (ft)	181			66	46		
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							
Turn Bay Length (ft)							
50th Bay Block Time %							

W Mountain St at Brooks St AM Peak Existing Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
------------	-----	-----	-----	-----	-----	-----	----

95th Bay Block Time %
 Queuing Penalty (veh)

Intersection Summary

Area Type: Other
 Cycle Length: 83
 Actuated Cycle Length: 83
 Offset: 0 (0%), Referenced to phase 2:EBT and 6:WBTL, Start of Green
 Natural Cycle: 85
 Control Type: Pretimed
 Maximum v/c Ratio: 0.52
 Intersection Signal Delay: 14.9 Intersection LOS: B
 Intersection Capacity Utilization 33.1% ICU Level of Service A

Splits and Phases: 1: West Mountain St & Pullman St

ø1	ø2	ø3	ø9
10 s	40 s	25 s	8 s
ø6			
50 s			

W Mountain St at Brooks St AM Peak Future No Build Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑	↘↘		
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.985				0.969		
Flt Protected				0.997	0.963		
Satd. Flow (prot)	3486	0	0	3529	1738	0	
Flt Permitted				0.905	0.963		
Satd. Flow (perm)	3486	0	0	3203	1738	0	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	18				17		
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	632	66	10	303	45	15	
Peak Hour Factor	0.87	0.83	0.46	0.90	0.78	0.88	
Adj. Flow (vph)	726	80	22	337	58	17	
Lane Group Flow (vph)	806	0	0	359	75	0	
Turn Type			pm+pt				
Protected Phases	2		1	6	3		9
Permitted Phases			6				
Minimum Split (s)	40.0		10.0	40.0	25.0		8.0
Total Split (s)	40.0	0.0	10.0	50.0	25.0	0.0	8.0
Total Split (%)	48%	0%	12%	60%	30%	0%	10%
Maximum Green (s)	36.0		6.0	46.0	21.0		4.0
Yellow Time (s)	3.0		3.0	3.0	3.0		3.5
All-Red Time (s)	1.0		1.0	1.0	1.0		0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0		
Flash Dont Walk (s)	11.0		11.0	11.0	11.0		
Pedestrian Calls (#/hr)	0		0	0	0		
Act Effct Green (s)	36.0			46.0	21.0		
Actuated g/C Ratio	0.43			0.55	0.25		
v/c Ratio	0.53			0.20	0.17		
Uniform Delay, d1	16.8			9.2	18.5		
Delay	17.1			9.3	19.9		
LOS	B			A	B		
Approach Delay	17.1			9.3	19.9		
Approach LOS	B			A	B		
Queue Length 50th (ft)	143			45	23		
Queue Length 95th (ft)	184			67	47		
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							
Turn Bay Length (ft)							
50th Bay Block Time %							

W Mountain St at Brooks St AM Peak Future No Build Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
------------	-----	-----	-----	-----	-----	-----	----

95th Bay Block Time %
 Queuing Penalty (veh)

Intersection Summary

Area Type: Other
 Cycle Length: 83
 Actuated Cycle Length: 83
 Offset: 0 (0%), Referenced to phase 2:EBT and 6:WBTL, Start of Green
 Natural Cycle: 85
 Control Type: Pretimed
 Maximum v/c Ratio: 0.53
 Intersection Signal Delay: 15.0 Intersection LOS: B
 Intersection Capacity Utilization 33.5% ICU Level of Service A

Splits and Phases: 1: West Mountain St & Pullman St

ø1	ø2	ø3	ø9
10 s	40 s	25 s	8 s
ø6			
50 s			

W Mountain St at Brooks St AM Peak Future Build Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑		↘↗	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.985			0.969			
Flt Protected				0.997	0.963		
Satd. Flow (prot)	3486	0	0	3529	1738	0	
Flt Permitted				0.904	0.963		
Satd. Flow (perm)	3486	0	0	3199	1738	0	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	18				17		
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	633	66	10	303	45	15	
Peak Hour Factor	0.87	0.83	0.46	0.90	0.78	0.88	
Adj. Flow (vph)	728	80	22	337	58	17	
Lane Group Flow (vph)	808	0	0	359	75	0	
Turn Type		pm+pt					
Protected Phases	2		1	6	3		9
Permitted Phases			6				
Minimum Split (s)	40.0		10.0	40.0	25.0		8.0
Total Split (s)	40.0	0.0	10.0	50.0	25.0	0.0	8.0
Total Split (%)	48%	0%	12%	60%	30%	0%	10%
Maximum Green (s)	36.0		6.0	46.0	21.0		4.0
Yellow Time (s)	3.0		3.0	3.0	3.0		3.5
All-Red Time (s)	1.0		1.0	1.0	1.0		0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0		
Flash Dont Walk (s)	11.0		11.0	11.0	11.0		
Pedestrian Calls (#/hr)	0		0	0	0		
Act Effct Green (s)	36.0			46.0	21.0		
Actuated g/C Ratio	0.43			0.55	0.25		
v/c Ratio	0.53			0.20	0.17		
Uniform Delay, d1	16.8			9.2	18.5		
Delay	17.1			9.3	19.9		
LOS	B			A	B		
Approach Delay	17.1			9.3	19.9		
Approach LOS	B			A	B		
Queue Length 50th (ft)	144			45	23		
Queue Length 95th (ft)	185			67	47		
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							
Turn Bay Length (ft)							
50th Bay Block Time %							

W Mountain St at Brooks St AM Peak Future Build Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
95th Bay Block Time %							
Queuing Penalty (veh)							
Intersection Summary							
Area Type:	Other						
Cycle Length:	83						
Actuated Cycle Length:	83						
Offset:	0 (0%), Referenced to phase 2:EBT and 6:WBTL, Start of Green						
Natural Cycle:	85						
Control Type:	Pretimed						
Maximum v/c Ratio:	0.53						
Intersection Signal Delay:	15.0			Intersection LOS: B			
Intersection Capacity Utilization	33.5%			ICU Level of Service A			

Splits and Phases: 1: West Mountain St & Pullman St

ø1	ø2	ø3	ø9
10 s	40 s	25 s	8 s
ø6			
50 s			

W Mountain St at Brooks St PM Peak Existing Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑	↘↗		
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.986				0.963		
Flt Protected				0.998	0.965		
Satd. Flow (prot)	3490	0	0	3532	1731	0	
Flt Permitted				0.928	0.965		
Satd. Flow (perm)	3490	0	0	3284	1731	0	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	12				19		
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	474	43	20	767	45	14	
Peak Hour Factor	0.94	0.81	0.69	0.92	0.67	0.57	
Adj. Flow (vph)	504	53	29	834	67	25	
Lane Group Flow (vph)	557	0	0	863	92	0	
Turn Type			pm+pt				
Protected Phases	2		1	6	3		9
Permitted Phases			6				
Minimum Split (s)	45.0		15.0	45.0	35.0		8.0
Total Split (s)	45.0	0.0	15.0	60.0	39.0	0.0	8.0
Total Split (%)	42%	0%	14%	56%	36%	0%	7%
Maximum Green (s)	41.0		11.0	56.0	35.0		4.0
Yellow Time (s)	3.0		3.0	3.0	3.0		3.5
All-Red Time (s)	1.0		1.0	1.0	1.0		0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0		
Flash Dont Walk (s)	11.0		11.0	11.0	11.0		
Pedestrian Calls (#/hr)	0		0	0	0		
Act Effct Green (s)	41.0			56.0	35.0		
Actuated g/C Ratio	0.38			0.52	0.33		
v/c Ratio	0.41			0.49	0.16		
Uniform Delay, d1	23.6			16.1	20.1		
Delay	23.9			16.4	20.5		
LOS	C			B	C		
Approach Delay	23.9			16.4	20.5		
Approach LOS	C			B	C		
Queue Length 50th (ft)	142			187	33		
Queue Length 95th (ft)	189			238	49		
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							
Turn Bay Length (ft)							
50th Bay Block Time %							

W Mountain St at Brooks St PM Peak Existing Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
95th Bay Block Time %							
Queuing Penalty (veh)							
Intersection Summary							
Area Type:	Other						
Cycle Length:	107						
Actuated Cycle Length:	107						
Offset:	92 (86%), Referenced to phase 2:EBT and 6:WBTL, Start of Green						
Natural Cycle:	105						
Control Type:	Pretimed						
Maximum v/c Ratio:	0.49						
Intersection Signal Delay:	19.4			Intersection LOS: B			
Intersection Capacity Utilization	42.3%			ICU Level of Service A			

Splits and Phases: 1: West Mountain St & Pullman St

ø1	ø2	ø3	
15 s	45 s	39 s	8 s
ø6			
60 s			

W Mountain St at Brooks St PM Peak Future No Build Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑	↘		
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.986				0.964		
Flt Protected				0.998	0.965		
Satd. Flow (prot)	3490	0	0	3532	1733	0	
Flt Permitted				0.928	0.965		
Satd. Flow (perm)	3490	0	0	3284	1733	0	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	12				18		
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	482	44	20	780	46	14	
Peak Hour Factor	0.94	0.81	0.69	0.92	0.67	0.57	
Adj. Flow (vph)	513	54	29	848	69	25	
Lane Group Flow (vph)	567	0	0	877	94	0	
Turn Type			pm+pt				
Protected Phases	2		1	6	3		9
Permitted Phases			6				
Minimum Split (s)	45.0		15.0	45.0	35.0		8.0
Total Split (s)	45.0	0.0	15.0	60.0	39.0	0.0	8.0
Total Split (%)	42%	0%	14%	56%	36%	0%	7%
Maximum Green (s)	41.0		11.0	56.0	35.0		4.0
Yellow Time (s)	3.0		3.0	3.0	3.0		3.5
All-Red Time (s)	1.0		1.0	1.0	1.0		0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0		
Flash Dont Walk (s)	11.0		11.0	11.0	11.0		
Pedestrian Calls (#/hr)	0		0	0	0		
Act Effct Green (s)	41.0			56.0	35.0		
Actuated g/C Ratio	0.38			0.52	0.33		
v/c Ratio	0.42			0.50	0.16		
Uniform Delay, d1	23.7			16.2	20.5		
Delay	24.0			16.5	20.9		
LOS	C			B	C		
Approach Delay	24.0			16.5	20.9		
Approach LOS	C			B	C		
Queue Length 50th (ft)	145			192	34		
Queue Length 95th (ft)	193			244	50		
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							
Turn Bay Length (ft)							
50th Bay Block Time %							

W Mountain St at Brooks St PM Peak Future No Build Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
------------	-----	-----	-----	-----	-----	-----	----

95th Bay Block Time %
 Queuing Penalty (veh)

Intersection Summary

Area Type: Other
 Cycle Length: 107
 Actuated Cycle Length: 107
 Offset: 92 (86%), Referenced to phase 2:EBT and 6:WBTL, Start of Green
 Natural Cycle: 105
 Control Type: Pretimed
 Maximum v/c Ratio: 0.50
 Intersection Signal Delay: 19.5
 Intersection LOS: B
 Intersection Capacity Utilization 42.9%
 ICU Level of Service A

Splits and Phases: 1: West Mountain St & Pullman St

ø1	ø2	ø3	
15 s	45 s	39 s	8 s
ø6			
60 s			

W Mountain St at Brooks St PM Peak Future Build Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑	↑↑		
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.986				0.964		
Flt Protected				0.998	0.965		
Satd. Flow (prot)	3490	0	0	3532	1733	0	
Flt Permitted				0.928	0.965		
Satd. Flow (perm)	3490	0	0	3284	1733	0	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	12				18		
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	485	44	20	783	46	14	
Peak Hour Factor	0.94	0.81	0.69	0.92	0.67	0.57	
Adj. Flow (vph)	516	54	29	851	69	25	
Lane Group Flow (vph)	570	0	0	880	94	0	
Turn Type		pm+pt					
Protected Phases	2		1	6	3		9
Permitted Phases			6				
Minimum Split (s)	45.0		15.0	45.0	35.0		8.0
Total Split (s)	45.0	0.0	15.0	60.0	39.0	0.0	8.0
Total Split (%)	42%	0%	14%	56%	36%	0%	7%
Maximum Green (s)	41.0		11.0	56.0	35.0		4.0
Yellow Time (s)	3.0		3.0	3.0	3.0		3.5
All-Red Time (s)	1.0		1.0	1.0	1.0		0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0		
Flash Dont Walk (s)	11.0		11.0	11.0	11.0		
Pedestrian Calls (#/hr)	0		0	0	0		
Act Effct Green (s)	41.0			56.0	35.0		
Actuated g/C Ratio	0.38			0.52	0.33		
v/c Ratio	0.42			0.50	0.16		
Uniform Delay, d1	23.7			16.2	20.5		
Delay	24.0			16.5	20.9		
LOS	C			B	C		
Approach Delay	24.0			16.5	20.9		
Approach LOS	C			B	C		
Queue Length 50th (ft)	145			192	34		
Queue Length 95th (ft)	194			244	50		
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							
Turn Bay Length (ft)							
50th Bay Block Time %							

W Mountain St at Brooks St PM Peak Future Build Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
95th Bay Block Time %							
Queuing Penalty (veh)							
Intersection Summary							
Area Type:	Other						
Cycle Length:	107						
Actuated Cycle Length:	107						
Offset:	92 (86%), Referenced to phase 2:EBT and 6:WBTL, Start of Green						
Natural Cycle:	105						
Control Type:	Pretimed						
Maximum v/c Ratio:	0.50						
Intersection Signal Delay:	19.5			Intersection LOS: B			
Intersection Capacity Utilization	43.0%			ICU Level of Service A			

Splits and Phases: 1: West Mountain St & Pullman St

ø1	ø2	ø3	
15 s	45 s	39 s	8 s
ø6			
60 s			

W Mountain St at Brooks St Sat Peak Existing Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑	↘		
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.995				0.943		
Flt Protected				0.999	0.972		
Satd. Flow (prot)	3522	0	0	3536	1707	0	
Flt Permitted				0.946	0.972		
Satd. Flow (perm)	3522	0	0	3348	1707	0	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	5				11		
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	462	14	8	466	10	6	
Peak Hour Factor	0.94	0.81	0.69	0.92	0.67	0.57	
Adj. Flow (vph)	491	17	12	507	15	11	
Lane Group Flow (vph)	508	0	0	519	26	0	
Turn Type			pm+pt				
Protected Phases	2		1	6	3		9
Permitted Phases			6				
Minimum Split (s)	40.0		10.0	40.0	25.0		8.0
Total Split (s)	40.0	0.0	10.0	50.0	25.0	0.0	8.0
Total Split (%)	48%	0%	12%	60%	30%	0%	10%
Maximum Green (s)	36.0		6.0	46.0	21.0		4.0
Yellow Time (s)	3.0		3.0	3.0	3.0		3.5
All-Red Time (s)	1.0		1.0	1.0	1.0		0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0		
Flash Dont Walk (s)	11.0		11.0	11.0	11.0		
Pedestrian Calls (#/hr)	0		0	0	0		
Act Effct Green (s)	36.0			46.0	21.0		
Actuated g/C Ratio	0.43			0.55	0.25		
v/c Ratio	0.33			0.28	0.06		
Uniform Delay, d1	15.4			9.7	13.5		
Delay	15.6			9.8	17.1		
LOS	B			A	B		
Approach Delay	15.6			9.8	17.1		
Approach LOS	B			A	B		
Queue Length 50th (ft)	87			68	6		
Queue Length 95th (ft)	124			96	17		
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							
Turn Bay Length (ft)							
50th Bay Block Time %							

W Mountain St at Brooks St Sat Peak Existing Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
95th Bay Block Time %							
Queuing Penalty (veh)							
Intersection Summary							
Area Type:	Other						
Cycle Length:	83						
Actuated Cycle Length:	83						
Offset:	9 (11%), Referenced to phase 2:EBT and 6:WBTL, Start of Green						
Natural Cycle:	85						
Control Type:	Pre-timed						
Maximum v/c Ratio:	0.33						
Intersection Signal Delay:	12.8			Intersection LOS: B			
Intersection Capacity Utilization	26.3%			ICU Level of Service A			

Splits and Phases: 1: West Mountain St & Pullman St

ø1	ø2	ø3	ø9
10 s	40 s	25 s	8 s
ø6			
50 s			

W Mountain St at Brooks St Sat Peak Future No Build Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↔	↔		
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.995				0.943		
Flt Protected				0.999	0.972		
Satd. Flow (prot)	3522	0	0	3536	1707	0	
Flt Permitted				0.946	0.972		
Satd. Flow (perm)	3522	0	0	3348	1707	0	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	5				11		
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	470	14	8	474	10	6	
Peak Hour Factor	0.94	0.81	0.69	0.92	0.67	0.57	
Adj. Flow (vph)	500	17	12	515	15	11	
Lane Group Flow (vph)	517	0	0	527	26	0	
Turn Type			pm+pt				
Protected Phases	2		1	6	3		9
Permitted Phases			6				
Minimum Split (s)	40.0		10.0	40.0	25.0		8.0
Total Split (s)	40.0	0.0	10.0	50.0	25.0	0.0	8.0
Total Split (%)	48%	0%	12%	60%	30%	0%	10%
Maximum Green (s)	36.0		6.0	46.0	21.0		4.0
Yellow Time (s)	3.0		3.0	3.0	3.0		3.5
All-Red Time (s)	1.0		1.0	1.0	1.0		0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0		
Flash Dont Walk (s)	11.0		11.0	11.0	11.0		
Pedestrian Calls (#/hr)	0		0	0	0		
Act Effct Green (s)	36.0			46.0	21.0		
Actuated g/C Ratio	0.43			0.55	0.25		
v/c Ratio	0.34			0.28	0.06		
Uniform Delay, d1	15.4			9.7	13.5		
Delay	15.6			9.8	17.1		
LOS	B			A	B		
Approach Delay	15.6			9.8	17.1		
Approach LOS	B			A	B		
Queue Length 50th (ft)	90			70	6		
Queue Length 95th (ft)	127			98	17		
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							
Turn Bay Length (ft)							
50th Bay Block Time %							

W Mountain St at Brooks St Sat Peak Future No Build Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
95th Bay Block Time %							
Queuing Penalty (veh)							
Intersection Summary							
Area Type:	Other						
Cycle Length:	83						
Actuated Cycle Length:	83						
Offset:	9 (11%), Referenced to phase 2:EBT and 6:WBTL, Start of Green						
Natural Cycle:	85						
Control Type:	Pretimed						
Maximum v/c Ratio:	0.34						
Intersection Signal Delay:	12.8			Intersection LOS: B			
Intersection Capacity Utilization	26.6%			ICU Level of Service A			

Splits and Phases: 1: West Mountain St & Pullman St

ø1	ø2	ø3	ø9
10 s	40 s	25 s	8 s
ø6			
50 s			

W Mountain St at Brooks St Sat Peak Future Build Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑	↘↗		
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.995				0.943		
Flt Protected				0.999	0.972		
Satd. Flow (prot)	3522	0	0	3536	1707	0	
Flt Permitted				0.946	0.972		
Satd. Flow (perm)	3522	0	0	3348	1707	0	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	5				11		
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	480	14	8	483	10	6	
Peak Hour Factor	0.94	0.81	0.69	0.92	0.67	0.57	
Adj. Flow (vph)	511	17	12	525	15	11	
Lane Group Flow (vph)	528	0	0	537	26	0	
Turn Type			pm+pt				
Protected Phases	2		1	6	3		9
Permitted Phases			6				
Minimum Split (s)	40.0		10.0	40.0	25.0		8.0
Total Split (s)	40.0	0.0	10.0	50.0	25.0	0.0	8.0
Total Split (%)	48%	0%	12%	60%	30%	0%	10%
Maximum Green (s)	36.0		6.0	46.0	21.0		4.0
Yellow Time (s)	3.0		3.0	3.0	3.0		3.5
All-Red Time (s)	1.0		1.0	1.0	1.0		0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0		
Flash Dont Walk (s)	11.0		11.0	11.0	11.0		
Pedestrian Calls (#/hr)	0		0	0	0		
Act Effct Green (s)	36.0			46.0	21.0		
Actuated g/C Ratio	0.43			0.55	0.25		
v/c Ratio	0.35			0.29	0.06		
Uniform Delay, d1	15.5			9.7	13.5		
Delay	15.7			9.9	17.1		
LOS	B			A	B		
Approach Delay	15.7			9.9	17.1		
Approach LOS	B			A	B		
Queue Length 50th (ft)	92			72	6		
Queue Length 95th (ft)	129			100	17		
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							
Turn Bay Length (ft)							
50th Bay Block Time %							

W Mountain St at Brooks St Sat Peak Future Build Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
------------	-----	-----	-----	-----	-----	-----	----

95th Bay Block Time %
 Queuing Penalty (veh)

Intersection Summary

Area Type: Other
 Cycle Length: 83
 Actuated Cycle Length: 83
 Offset: 9 (11%), Referenced to phase 2:EBT and 6:WBTL, Start of Green
 Natural Cycle: 85
 Control Type: Pretimed
 Maximum v/c Ratio: 0.35
 Intersection Signal Delay: 12.8 Intersection LOS: B
 Intersection Capacity Utilization 26.9% ICU Level of Service A

Splits and Phases: 1: West Mountain St & Pullman St

ø1	ø2	ø3	ø9
10 s	40 s	25 s	8 s
ø6			
50 s			

W Mountain St at Pullman St AM Peak Existing Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↕↕			↕↕	↘	↗	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Storage Length (ft)		0	0		0	200	
Storage Lanes		0	0		1	1	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.978					0.850	
Flt Protected				0.989	0.950		
Satd. Flow (prot)	3461	0	0	3500	1770	1583	
Flt Permitted				0.627	0.950		
Satd. Flow (perm)	3461	0	0	2219	1770	1583	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	19					84	
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	536	101	63	247	51	65	
Peak Hour Factor	0.81	0.90	0.74	0.88	0.90	0.77	
Adj. Flow (vph)	662	112	85	281	57	84	
Lane Group Flow (vph)	774	0	0	366	57	84	
Turn Type			pm+pt			Perm	
Protected Phases	6		5	2	4		9
Permitted Phases			2				4
Minimum Split (s)	30.0		30.0	30.0	30.0	30.0	8.0
Total Split (s)	30.0	0.0	30.0	60.0	30.0	30.0	8.0
Total Split (%)	31%	0%	31%	61%	31%	31%	8%
Maximum Green (s)	24.0		24.0	54.0	24.0	24.0	4.0
Yellow Time (s)	4.0		4.0	4.0	4.0	4.0	3.5
All-Red Time (s)	2.0		2.0	2.0	2.0	2.0	0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0	5.0	
Flash Dont Walk (s)	11.0		11.0	11.0	11.0	11.0	
Pedestrian Calls (#/hr)	0		0	0	0	0	
Act Effct Green (s)	26.0			56.0	26.0	26.0	
Actuated g/C Ratio	0.27			0.57	0.27	0.27	
v/c Ratio	0.83			0.23	0.12	0.17	
Uniform Delay, d1	33.0			10.0	27.3	0.0	
Delay	35.6			10.1	27.8	6.6	
LOS	D			B	C	A	
Approach Delay	35.6			10.1	15.1		
Approach LOS	D			B	B		
Queue Length 50th (ft)	234			53	27	0	
Queue Length 95th (ft)	265			74	58	24	
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							


W Mountain St at Pullman St AM Peak Existing Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Turn Bay Length (ft)							200
50th Bay Block Time %							
95th Bay Block Time %							
Queuing Penalty (veh)							

Intersection Summary	
Area Type:	Other
Cycle Length:	98
Actuated Cycle Length:	98
Offset:	30 (31%), Referenced to phase 6:EBT, Start of Green
Natural Cycle:	100
Control Type:	Pretimed
Maximum v/c Ratio:	0.83
Intersection Signal Delay:	26.1
Intersection LOS:	C
Intersection Capacity Utilization	47.1%
ICU Level of Service	A

Splits and Phases: 1: West Mountain St & Pullman St



W Mountain St at Pullman St AM Peak Future No Build Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑	↘	↗	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Storage Length (ft)		0	0		0	200	
Storage Lanes		0	0		1	1	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.978					0.850	
Flt Protected				0.989	0.950		
Satd. Flow (prot)	3461	0	0	3500	1770	1583	
Flt Permitted				0.620	0.950		
Satd. Flow (perm)	3461	0	0	2194	1770	1583	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	19					86	
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	545	103	64	251	52	66	
Peak Hour Factor	0.81	0.90	0.74	0.88	0.90	0.77	
Adj. Flow (vph)	673	114	86	285	58	86	
Lane Group Flow (vph)	787	0	0	371	58	86	
Turn Type			pm+pt			Perm	
Protected Phases	6		5	2	4		9
Permitted Phases			2				4
Minimum Split (s)	30.0		30.0	30.0	30.0	30.0	8.0
Total Split (s)	30.0	0.0	30.0	60.0	30.0	30.0	8.0
Total Split (%)	31%	0%	31%	61%	31%	31%	8%
Maximum Green (s)	24.0		24.0	54.0	24.0	24.0	4.0
Yellow Time (s)	4.0		4.0	4.0	4.0	4.0	3.5
All-Red Time (s)	2.0		2.0	2.0	2.0	2.0	0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0	5.0	
Flash Dont Walk (s)	11.0		11.0	11.0	11.0	11.0	
Pedestrian Calls (#/hr)	0		0	0	0	0	
Act Effct Green (s)	26.0			56.0	26.0	26.0	
Actuated g/C Ratio	0.27			0.57	0.27	0.27	
v/c Ratio	0.84			0.23	0.12	0.18	
Uniform Delay, d1	33.2			10.1	27.3	0.0	
Delay	36.4			10.2	27.8	6.5	
LOS	D			B	C	A	
Approach Delay	36.4			10.2	15.1		
Approach LOS	D			B	B		
Queue Length 50th (ft)	239			54	28	0	
Queue Length 95th (ft)	271			75	60	24	
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							

W Mountain St at Pullman St AM Peak Future No Build Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Turn Bay Length (ft)	200						
50th Bay Block Time %							
95th Bay Block Time %							
Queuing Penalty (veh)							

Intersection Summary	
Area Type:	Other
Cycle Length:	98
Actuated Cycle Length:	98
Offset:	30 (31%), Referenced to phase 6:EBT, Start of Green
Natural Cycle:	100
Control Type:	Pretimed
Maximum v/c Ratio:	0.84
Intersection Signal Delay:	26.6
Intersection LOS:	C
Intersection Capacity Utilization	47.6%
ICU Level of Service	A


Splits and Phases: 1: West Mountain St & Pullman St



W Mountain St at Pullman St AM Peak Future Build Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑	↘	↗	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Storage Length (ft)		0	0		0	200	
Storage Lanes		0	0		1	1	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.978					0.850	
Frt Protected				0.989	0.950		
Satd. Flow (prot)	3461	0	0	3500	1770	1583	
Frt Permitted				0.619	0.950		
Satd. Flow (perm)	3461	0	0	2191	1770	1583	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	19					86	
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	545	104	64	251	52	66	
Peak Hour Factor	0.81	0.90	0.74	0.88	0.90	0.77	
Adj. Flow (vph)	673	116	86	285	58	86	
Lane Group Flow (vph)	789	0	0	371	58	86	
Turn Type			pm+pt			Perm	
Protected Phases	6		5	2	4		9
Permitted Phases			2			4	
Minimum Split (s)	30.0		30.0	30.0	30.0	30.0	8.0
Total Split (s)	30.0	0.0	30.0	60.0	30.0	30.0	8.0
Total Split (%)	31%	0%	31%	61%	31%	31%	8%
Maximum Green (s)	24.0		24.0	54.0	24.0	24.0	4.0
Yellow Time (s)	4.0		4.0	4.0	4.0	4.0	3.5
All-Red Time (s)	2.0		2.0	2.0	2.0	2.0	0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0	5.0	
Flash Dont Walk (s)	11.0		11.0	11.0	11.0	11.0	
Pedestrian Calls (#/hr)	0		0	0	0	0	
Act Effct Green (s)	26.0			56.0	26.0	26.0	
Actuated g/C Ratio	0.27			0.57	0.27	0.27	
v/c Ratio	0.85			0.23	0.12	0.18	
Uniform Delay, d1	33.2			10.1	27.3	0.0	
Delay	36.6			10.2	27.8	6.5	
LOS	D			B	C	A	
Approach Delay	36.6			10.2	15.1		
Approach LOS	D			B	B		
Queue Length 50th (ft)	240			54	28	0	
Queue Length 95th (ft)	272			75	60	24	
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							


W Mountain St at Pullman St AM Peak Future Build Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Turn Bay Length (ft)	200						
50th Bay Block Time %							
95th Bay Block Time %							
Queuing Penalty (veh)							

Intersection Summary	
Area Type:	Other
Cycle Length:	98
Actuated Cycle Length:	98
Offset:	30 (31%), Referenced to phase 6:EBT, Start of Green
Natural Cycle:	100
Control Type:	Pretimed
Maximum v/c Ratio:	0.85
Intersection Signal Delay:	26.7
Intersection LOS:	C
Intersection Capacity Utilization	47.7%
ICU Level of Service	A

Splits and Phases: 1: West Mountain St & Pullman St



W Mountain St at Pullman St PM Peak Existing Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↕↕			↕↕	↘	↗	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Storage Length (ft)		0	0		0	200	
Storage Lanes		0	0		1	1	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.954					0.850	
Flt Protected				0.989	0.950		
Satd. Flow (prot)	3376	0	0	3500	1770	1583	
Flt Permitted				0.614	0.950		
Satd. Flow (perm)	3376	0	0	2173	1770	1583	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	70					206	
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	339	151	146	577	183	167	
Peak Hour Factor	0.89	0.90	0.85	0.92	0.75	0.81	
Adj. Flow (vph)	381	168	172	627	244	206	
Lane Group Flow (vph)	549	0	0	799	244	206	
Turn Type			pm+pt			Prot	
Protected Phases	6		5	2	4	4	9
Permitted Phases			2				
Minimum Split (s)	44.0		30.0	30.0	29.0	29.0	8.0
Total Split (s)	44.0	0.0	30.0	74.0	29.0	29.0	8.0
Total Split (%)	40%	0%	27%	67%	26%	26%	7%
Maximum Green (s)	38.0		24.0	68.0	23.0	23.0	4.0
Yellow Time (s)	4.0		4.0	4.0	4.0	4.0	3.5
All-Red Time (s)	2.0		2.0	2.0	2.0	2.0	0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0	5.0	
Flash Dont Walk (s)	11.0		11.0	11.0	11.0	11.0	
Pedestrian Calls (#/hr)	0		0	0	0	0	
Act Effct Green (s)	40.0			70.0	25.0	25.0	
Actuated g/C Ratio	0.36			0.63	0.23	0.23	
v/c Ratio	0.44			0.48	0.61	0.40	
Uniform Delay, d1	23.2			9.8	38.6	0.0	
Delay	23.4			9.9	39.4	5.1	
LOS	C			A	D	A	
Approach Delay	23.4			9.9	23.7		
Approach LOS	C			A	C		
Queue Length 50th (ft)	134			132	157	0	
Queue Length 95th (ft)	181			168	195	38	
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							


W Mountain St at Pullman St PM Peak Existing Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Turn Bay Length (ft)							200
50th Bay Block Time %							
95th Bay Block Time %							4%
Queuing Penalty (veh)							3

Intersection Summary	
Area Type:	Other
Cycle Length:	111
Actuated Cycle Length:	111
Offset:	94 (85%), Referenced to phase 6:EBT, Start of Green
Natural Cycle:	115
Control Type:	Pretimed
Maximum v/c Ratio:	0.61
Intersection Signal Delay:	17.5
Intersection LOS:	B
Intersection Capacity Utilization	61.7%
ICU Level of Service	B


Splits and Phases: 1: West Mountain St & Pullman St



W Mountain St at Pullman St PM Peak Future No Build Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↕↕			↕↕	↕	↕	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Storage Length (ft)		0	0		0	200	
Storage Lanes		0	0		1	1	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.954					0.850	
Flt Protected				0.989	0.950		
Satd. Flow (prot)	3376	0	0	3500	1770	1583	
Flt Permitted				0.611	0.950		
Satd. Flow (perm)	3376	0	0	2162	1770	1583	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	70					210	
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	344	154	149	587	186	170	
Peak Hour Factor	0.89	0.90	0.85	0.92	0.75	0.81	
Adj. Flow (vph)	387	171	175	638	248	210	
Lane Group Flow (vph)	558	0	0	813	248	210	
Turn Type			pm+pt			Prot	
Protected Phases	6		5	2	4	4	9
Permitted Phases			2				
Minimum Split (s)	44.0		30.0	30.0	29.0	29.0	8.0
Total Split (s)	44.0	0.0	30.0	74.0	29.0	29.0	8.0
Total Split (%)	40%	0%	27%	67%	26%	26%	7%
Maximum Green (s)	38.0		24.0	68.0	23.0	23.0	4.0
Yellow Time (s)	4.0		4.0	4.0	4.0	4.0	3.5
All-Red Time (s)	2.0		2.0	2.0	2.0	2.0	0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0	5.0	
Flash Dont Walk (s)	11.0		11.0	11.0	11.0	11.0	
Pedestrian Calls (#/hr)	0		0	0	0	0	
Act Effct Green (s)	40.0			70.0	25.0	25.0	
Actuated g/C Ratio	0.36			0.63	0.23	0.23	
v/c Ratio	0.44			0.48	0.62	0.40	
Uniform Delay, d1	23.3			9.9	38.7	0.0	
Delay	23.6			10.0	39.5	5.0	
LOS	C			A	D	A	
Approach Delay	23.6			10.0	23.7		
Approach LOS	C			A	C		
Queue Length 50th (ft)	136			135	160	0	
Queue Length 95th (ft)	184			172	198	38	
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							

W Mountain St at Pullman St PM Peak Future No Build Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Turn Bay Length (ft)							200
50th Bay Block Time %							
95th Bay Block Time %							5%
Queuing Penalty (veh)							5

Intersection Summary

Area Type:	Other
Cycle Length:	111
Actuated Cycle Length:	111
Offset:	94 (85%), Referenced to phase 6:EBT, Start of Green
Natural Cycle:	115
Control Type:	Pretimed
Maximum v/c Ratio:	0.62
Intersection Signal Delay:	17.6
Intersection Capacity Utilization	62.6%
Intersection LOS:	B
ICU Level of Service	B

Splits and Phases: 1: West Mountain St & Pullman St



W Mountain St at Pullman St PM Peak Future Build Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑		↗	↗
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Storage Length (ft)		0	0		0	200	
Storage Lanes		0	0		1	1	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.953			0.850			
Flt Protected				0.989	0.950		
Satd. Flow (prot)	3373	0	0	3500	1770	1583	
Flt Permitted				0.608	0.950		
Satd. Flow (perm)	3373	0	0	2152	1770	1583	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	73					212	
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	344	157	152	587	189	172	
Peak Hour Factor	0.89	0.90	0.85	0.92	0.75	0.81	
Adj. Flow (vph)	387	174	179	638	252	212	
Lane Group Flow (vph)	561	0	0	817	252	212	
Turn Type			pm+pt			Prot	
Protected Phases	6		5	2	4	4	9
Permitted Phases			2				
Minimum Split (s)	44.0		30.0	30.0	29.0	29.0	8.0
Total Split (s)	44.0	0.0	30.0	74.0	29.0	29.0	8.0
Total Split (%)	40%	0%	27%	67%	26%	26%	7%
Maximum Green (s)	38.0		24.0	68.0	23.0	23.0	4.0
Yellow Time (s)	4.0		4.0	4.0	4.0	4.0	3.5
All-Red Time (s)	2.0		2.0	2.0	2.0	2.0	0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0	5.0	
Flash Dont Walk (s)	11.0		11.0	11.0	11.0	11.0	
Pedestrian Calls (#/hr)	0		0	0	0	0	
Act Effct Green (s)	40.0			70.0	25.0	25.0	
Actuated g/C Ratio	0.36			0.63	0.23	0.23	
v/c Ratio	0.44			0.49	0.63	0.41	
Uniform Delay, d1	23.2			9.9	38.8	0.0	
Delay	23.4			10.0	39.6	5.0	
LOS	C			A	D	A	
Approach Delay	23.4			10.0	23.8		
Approach LOS	C			A	C		
Queue Length 50th (ft)	137			136	163	0	
Queue Length 95th (ft)	184			173	202	38	
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							

W Mountain St at Pullman St PM Peak Future Build Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Turn Bay Length (ft)							200
50th Bay Block Time %							
95th Bay Block Time %							6%
Queuing Penalty (veh)							6

Intersection Summary

Area Type:	Other
Cycle Length:	111
Actuated Cycle Length:	111
Offset:	94 (85%), Referenced to phase 6:EBT, Start of Green
Natural Cycle:	115
Control Type:	Pretimed
Maximum v/c Ratio:	0.63
Intersection Signal Delay:	17.6
Intersection LOS:	B
Intersection Capacity Utilization	63.1%
ICU Level of Service	B

Splits and Phases: 1: West Mountain St & Pullman St



W Mountain St at Pullman St Sat Peak Existing Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑	↘	↗	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Storage Length (ft)		0	0		0	200	
Storage Lanes		0	0		1	1	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.959					0.850	
Flt Protected				0.988	0.950		
Satd. Flow (prot)	3394	0	0	3497	1770	1583	
Flt Permitted				0.577	0.950		
Satd. Flow (perm)	3394	0	0	2042	1770	1583	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	45					168	
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	352	118	125	359	114	123	
Peak Hour Factor	0.86	0.77	0.93	0.89	0.81	0.73	
Adj. Flow (vph)	409	153	134	403	141	168	
Lane Group Flow (vph)	562	0	0	537	141	168	
Turn Type			pm+pt			Perm	
Protected Phases	6		5	2	4		9
Permitted Phases			2			4	
Minimum Split (s)	30.0		44.0	30.0	30.0	30.0	8.0
Total Split (s)	30.0	0.0	44.0	74.0	30.0	30.0	8.0
Total Split (%)	27%	0%	39%	66%	27%	27%	7%
Maximum Green (s)	24.0		38.0	68.0	24.0	24.0	4.0
Yellow Time (s)	4.0		4.0	4.0	4.0	4.0	3.5
All-Red Time (s)	2.0		2.0	2.0	2.0	2.0	0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0	5.0	
Flash Dont Walk (s)	11.0		11.0	11.0	11.0	11.0	
Pedestrian Calls (#/hr)	0		0	0	0	0	
Act Effct Green (s)	26.0			70.0	26.0	26.0	
Actuated g/C Ratio	0.23			0.63	0.23	0.23	
v/c Ratio	0.68			0.30	0.34	0.34	
Uniform Delay, d1	35.9			9.3	35.9	0.0	
Delay	36.3			9.4	36.4	5.5	
LOS	D			A	D	A	
Approach Delay	36.3			9.4	19.6		
Approach LOS	D			A	B		
Queue Length 50th (ft)	180			83	85	0	
Queue Length 95th (ft)	227			108	128	24	
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							


W Mountain St at Pullman St Sat Peak Existing Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Turn Bay Length (ft)							200
50th Bay Block Time %							
95th Bay Block Time %							
Queuing Penalty (veh)							

Intersection Summary	
Area Type:	Other
Cycle Length:	112
Actuated Cycle Length:	112
Offset:	30 (27%), Referenced to phase 6:EBT, Start of Green
Natural Cycle:	115
Control Type:	Pretimed
Maximum v/c Ratio:	0.68
Intersection Signal Delay:	22.4
Intersection LOS:	C
Intersection Capacity Utilization	49.1%
ICU Level of Service	A

Splits and Phases: 1: West Mountain St & Pullman St



W Mountain St at Pullman St Sat Peak Future No Build Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑		↖	↗
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Storage Length (ft)		0	0		0	200	
Storage Lanes		0	0		1	1	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.959					0.850	
Flt Protected				0.988	0.950		
Satd. Flow (prot)	3394	0	0	3497	1770	1583	
Flt Permitted				0.568	0.950		
Satd. Flow (perm)	3394	0	0	2010	1770	1583	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	45					171	
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	358	120	127	365	116	125	
Peak Hour Factor	0.86	0.77	0.93	0.89	0.81	0.73	
Adj. Flow (vph)	416	156	137	410	143	171	
Lane Group Flow (vph)	572	0	0	547	143	171	
Turn Type			pm+pt			Perm	
Protected Phases	6		5	2	4		9
Permitted Phases			2			4	
Minimum Split (s)	30.0		44.0	30.0	30.0	30.0	8.0
Total Split (s)	30.0	0.0	44.0	74.0	30.0	30.0	8.0
Total Split (%)	27%	0%	39%	66%	27%	27%	7%
Maximum Green (s)	24.0		38.0	68.0	24.0	24.0	4.0
Yellow Time (s)	4.0		4.0	4.0	4.0	4.0	3.5
All-Red Time (s)	2.0		2.0	2.0	2.0	2.0	0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0	5.0	
Flash Dont Walk (s)	11.0		11.0	11.0	11.0	11.0	
Pedestrian Calls (#/hr)	0		0	0	0	0	
Act Effct Green (s)	26.0			70.0	26.0	26.0	
Actuated g/C Ratio	0.23			0.63	0.23	0.23	
v/c Ratio	0.70			0.31	0.35	0.34	
Uniform Delay, d1	36.1			9.3	35.9	0.0	
Delay	36.5			9.4	36.5	5.5	
LOS	D			A	D	A	
Approach Delay	36.5			9.4	19.6		
Approach LOS	D			A	B		
Queue Length 50th (ft)	184			85	86	0	
Queue Length 95th (ft)	232			111	130	24	
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							

W Mountain St at Pullman St Sat Peak Future No Build Conditions




Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Turn Bay Length (ft)	200						
50th Bay Block Time %							
95th Bay Block Time %							
Queuing Penalty (veh)							

Intersection Summary

Area Type:	Other
Cycle Length:	112
Actuated Cycle Length:	112
Offset:	30 (27%), Referenced to phase 6:EBT, Start of Green
Natural Cycle:	115
Control Type:	Pretimed
Maximum v/c Ratio:	0.70
Intersection Signal Delay:	22.5
Intersection LOS:	C
Intersection Capacity Utilization	49.7%
ICU Level of Service	A

Splits and Phases: 1: West Mountain St & Pullman St



W Mountain St at Pullman St Sat Peak Future Build Conditions

	→	↘	↙	←	↖	↗	
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Lane Configurations	↑↑			↑↑	↘	↗	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Storage Length (ft)		0	0		0	200	
Storage Lanes		0	0		1	1	
Total Lost Time (s)	4.0	4.0	4.0	4.0	4.0	4.0	
Turning Speed (mph)		9	15		15	9	
Lane Util. Factor	0.95	0.95	0.95	0.95	1.00	1.00	
Frt	0.957					0.850	
Flt Protected				0.987	0.950		
Satd. Flow (prot)	3387	0	0	3493	1770	1583	
Flt Permitted				0.545	0.950		
Satd. Flow (perm)	3387	0	0	1929	1770	1583	
Right Turn on Red		Yes				Yes	
Satd. Flow (RTOR)	51					182	
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Link Speed (mph)	30			30	30		
Link Distance (ft)	1572			4656	2800		
Travel Time (s)	35.7			105.8	63.6		
Volume (vph)	358	130	138	365	125	133	
Peak Hour Factor	0.86	0.77	0.93	0.89	0.81	0.73	
Adj. Flow (vph)	416	169	148	410	154	182	
Lane Group Flow (vph)	585	0	0	558	154	182	
Turn Type			pm+pt			Perm	
Protected Phases	6		5	2	4		9
Permitted Phases			2			4	
Minimum Split (s)	30.0		44.0	30.0	30.0	30.0	8.0
Total Split (s)	30.0	0.0	44.0	74.0	30.0	30.0	8.0
Total Split (%)	27%	0%	39%	66%	27%	27%	7%
Maximum Green (s)	24.0		38.0	68.0	24.0	24.0	4.0
Yellow Time (s)	4.0		4.0	4.0	4.0	4.0	3.5
All-Red Time (s)	2.0		2.0	2.0	2.0	2.0	0.5
Lead/Lag	Lag		Lead				
Lead-Lag Optimize?	Yes		Yes				
Walk Time (s)	5.0		5.0	5.0	5.0	5.0	
Flash Dont Walk (s)	11.0		11.0	11.0	11.0	11.0	
Pedestrian Calls (#/hr)	0		0	0	0	0	
Act Effct Green (s)	26.0			70.0	26.0	26.0	
Actuated g/C Ratio	0.23			0.63	0.23	0.23	
v/c Ratio	0.71			0.32	0.37	0.36	
Uniform Delay, d1	35.9			9.4	36.1	0.0	
Delay	36.3			9.5	36.8	5.3	
LOS	D			A	D	A	
Approach Delay	36.3			9.5	19.7		
Approach LOS	D			A	B		
Queue Length 50th (ft)	187			87	94	0	
Queue Length 95th (ft)	236			113	139	24	
Internal Link Dist (ft)	1492			4576	2720		
50th Up Block Time (%)							
95th Up Block Time (%)							


W Mountain St at Pullman St Sat Peak Future Build Conditions



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR	ø9
Turn Bay Length (ft)							200
50th Bay Block Time %							
95th Bay Block Time %							
Queuing Penalty (veh)							

Intersection Summary	
Area Type:	Other
Cycle Length:	112
Actuated Cycle Length:	112
Offset:	30 (27%), Referenced to phase 6:EBT, Start of Green
Natural Cycle:	115
Control Type:	Pretimed
Maximum v/c Ratio:	0.71
Intersection Signal Delay:	22.4
Intersection LOS:	C
Intersection Capacity Utilization	51.1%
ICU Level of Service	A

Splits and Phases: 1: West Mountain St & Pullman St



Pullman St at Site Driveway AM Peak Build Conditions



Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	W			↑		↑
Sign Control	Stop			Free	Free	
Grade	0%					
Volume (veh/h)	0	1	11	108	167	1
Peak Hour Factor	0.92	0.92	0.90	0.77	0.89	0.89
Hourly flow rate (veh/h)	0	1	12	140	188	1
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type: None						
Median storage (veh)						
vC, conflicting volume	353	188	189			
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
tC, single (s)	6.4	6.2	4.1			
tC, 2 stage (s)						
tF (s)	3.5	3.3	2.2			
p0 queue free %	100	100	99			
cM capacity (veh/h)	639	854	1385			
Direction, Lane #	EB 1	NB 1	SB 1			
Volume Total	1	152	189			
Volume Left	0	12	0			
Volume Right	1	0	1			
cSH	854	1385	1700			
Volume to Capacity	0.00	0.01	0.11			
Queue Length (ft)	0	1	0			
Control Delay (s)	9.2	0.7	0.0			
Lane LOS	A	A				
Approach Delay (s)	9.2	0.7	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay			0.3			
Intersection Capacity Utilization			19.9%	ICU Level of Service	A	

Pullman St at Site Driveway PM Peak Build Conditions



Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↔			↑	↓	↙
Sign Control	Stop			Free	Free	
Grade	0%			0%	0%	
Volume (veh/h)	5	7	10	356	303	6
Peak Hour Factor	0.87	0.87	0.78	0.78	0.92	0.92
Hourly flow rate (veh/h)	6	8	13	456	329	7
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type						
Median storage (veh)						
vC, conflicting volume	815	333	336			
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
tC, single (s)	6.4	6.2	4.1			
tC, 2 stage (s)						
tF (s)	3.5	3.3	2.2			
p0 queue free %	98	99	99			
cM capacity (veh/h)	344	709	1223			
Direction, Lane #	EB 1	NB 1	SB 1			
Volume Total	14	469	336			
Volume Left	6	13	0			
Volume Right	8	0	7			
cSH	491	1223	1700			
Volume to Capacity	0.03	0.01	0.20			
Queue Length (ft)	2	1	0			
Control Delay (s)	12.5	0.3	0.0			
Lane LOS	B	A				
Approach Delay (s)	12.5	0.3	0.0			
Approach LOS	B					
Intersection Summary						
Average Delay			0.4			
Intersection Capacity Utilization			40.5%	ICU Level of Service	A	

Pullman St at Site Driveway Sat Peak Build Conditions



Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	T			T	T	
Sign Control	Stop			Free	Free	
Grade	0%			0%	0%	
Volume (veh/h)	17	17	21	241	247	21
Peak Hour Factor	0.87	0.87	0.78	0.78	0.92	0.92
Hourly flow rate (veh/h)	20	20	27	309	268	23
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None					
Median storage (veh)						
vC, conflicting volume	643	280	291			
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
tC, single (s)	6.4	6.2	4.1			
tC, 2 stage (s)						
tF (s)	3.5	3.3	2.2			
p0 queue free %	95	97	98			
cM capacity (veh/h)	429	759	1270			
Direction, Lane #						
	EB 1	NB 1	SB 1			
Volume Total	39	336	291			
Volume Left	20	27	0			
Volume Right	20	0	23			
cSH	548	1270	1700			
Volume to Capacity	0.07	0.02	0.17			
Queue Length (ft)	6	2	0			
Control Delay (s)	12.1	0.8	0.0			
Lane LOS	B	A				
Approach Delay (s)	12.1	0.8	0.0			
Approach LOS	B					
Intersection Summary						
Average Delay			1.1			
Intersection Capacity Utilization			39.5%	ICU Level of Service	A	