

# **STORMWATER MANAGEMENT REPORT**

## **MULTI-FAMILY DWELLING**

**214 HAMILTON STREET  
WORCESTER, MA 01604**

**Prepared by:**

**FODERA Engineering  
28 Harbor Street, Suite 204  
Danvers, MA 01923**

**Prepared for (Applicant):**

**Tal Patlazhan  
REI Group LLC  
51 Pleasant St, # 731  
Malden, MA 02148**

**Date:**

**September 20, 2023**



**FODERA  
ENGINEERING**

## TABLE OF CONTENTS

<b><u>1.0: INTRODUCTION</u></b> .....	1
<b><u>2.0: EXISTING CONDITIONS</u></b> .....	1
2.1: EXISTING SITE CONDITONS.....	1
2.2: SITE SOILS & GROUNDWATER.....	1
2.3: EXISTING UTILITIES & STORMWATER INFRASTRUCTURE.....	1
<b><u>3.0: PROPOSED CONDITIONS</u></b> .....	2
3.1: PROPOSED SITE CONDITONS.....	2
3.2: PROPOSED UTILITIES & STORMWATER INFRASTRUCTURE.....	2
<b><u>4.0: MASSACHUSETTS STORMWATER MANAGEMENT STANDARDS</u></b> .....	2
4.1: STANDARD 1 – No New Untreated Stormwater Discharges.....	2
4.2: STANDARD 2 – Peak Rate Of Discharge.....	2
4.3: STANDARD 3 – Groundwater Recharge.....	4
4.4: STANDARD 4 – Water Quality.....	5
4.5: STANDARD 5 – Land Uses With Higher Pollution Prevention Loads.....	6
4.6: STANDARD 6 – Critical Areas.....	6
4.7: STANDARD 7 – Redevelopment Projects.....	6
4.8: STANDARD 8 – Temporary Erosion, Sedimentation, And Pollution.....	7
4.8.1: STABILIZATION SCHEDULE.....	7
4.8.2: POTENTIAL STORMWATER CONTAMINANTS.....	8
4.9: STANDARD 9 – Long-Term Operation And Maintenance Plan.....	8
4.9.1: STRUCTURAL POLLUTANT CONTROLS AND MAINTENANCE.....	8
4.10: STANDARD 10 – Prohibited Illicit Discharges.....	10

## TABLE OF CONTENTS

### **APPENDIX A – SITE CONDITIONS**

    Soil Data

    NOAA Rainfall Data

### **APPENDIX B – STORMWATER CALCAULATIONS**

    Standard 2 – Peak Rate of Runoff

    Standard 3 – Groundwater Recharge

    Standard 4 – Water Quality

### **APPENDIX C – Operation and Maintenance**

    Maintenance Logs and StormTech O&M Manual

## **1.0: INTRODUCTION**

The proposed project is the redevelopment of an existing four-unit building, into a proposed eight-unit building. The parcel is identified parcel ID: 18-46-1. The lot is 12,500 square feet (sf) with frontage on Hamilton Street and Warner Ave.

Stormwater design for the project has been designed in accordance with standards set forth in the Massachusetts Stormwater Handbook.

## **2.0: EXISTING CONDITIONS**

### **2.1: EXISTING SITE CONDITONS**

The existing lot currently has a four-story building on site with a curb cut on Warner Ave and a paved parking area on the south side of the property. The property is a corner lot with abutters to the east and south. About half the lot is pervious with grassed surface and the other half is impervious with pavement and building coverage.

The frontage along Hamilton Street is relatively flat, however, topography drops steeply to the south. Hamilton Street has about a 15% drop, and the site has similar characteristics. Elevations drop about twenty (20) feet from the north to south.

### **2.2: SITE SOILS & GROUNDWATER**

Site soils were determined by test pit. A certified soil evaluator from Quetti Design Group evaluated the soils on August 31, 2023. The Estimate Seasonal High Water Table (ESHWT) was determined to be twenty-two (22) inches below grade at elevation 74.7 with respect to the vertical datum on the accompanied site plans dated 9/20/23. The soils are a dense gravelly fine sandy loam with an associated Rawl's Rate of 0.52 inches per hour. This Rawl's Rate is associated with a Hydrologic Soil Group B (HSG-B). Please refer to Appendix A for the test pit report.

### **2.3: EXISTING UTILITIES & STORMWATER INFRASTRUCTURE**

The existing dwelling on site is serviced by public and private utilities. Public water and sanitary sewer provided by the city of Worcester are currently in place for the existing building. Gas and electricity separately are also in place. There are no known stormwater facilities currently on site to mitigate on-site runoff and is therefore discharged overland into the public rights-of-ways and abutting properties. There is an existing stormwater collection system within Hamilton Street north of the site, and southerly downgradient on Warner Avenue. Runoff from the site is directed to the south abutting properties and southerly on Warner Ave.

### **3.0: PROPOSED CONDITIONS**

#### **3.1: PROPOSED SITE CONDITONS**

The project proposes to keep the existing structure, and to add an addition to expand the footprint. Additional ground parking, new utilities, and stormwater recharge will all be included.

#### **3.2: PROPOSED UTILITIES & STORMWATER INFRASTRUCTURE**

The proposed project will utilize all available public and private utilities. Existing utility connections will be cut and capped for the connections of new utility services. Proposed domestic water service and fire protection line will be tapped from the water main in Warner Ave. Sewer services will be connected by gravity flow to the sewer main in Warner Ave. Electric and gas services will be installed in coordination with their respective utility companies.

Stormwater measures are proposed to mitigate site improvements. Stormwater from the roof will be discharge by downspouts and flow overland to the proposed catch basin on site. The catch basin is then directed to the subsurface infiltration system. The infiltration system is made from twelve (12) SC-740 StormTech chambers. The first row will be an Isolator row for runoff treatment. All runoff that will not be captured to the infiltration system will be directed overland towards Warner Avenue. No new runoff will be added and the site will be improved from the existing conditions. The following sections demonstrate compliance with stormwater regulations.

### **4.0: MASSACHUSETTS STORMWATER MANAGEMENT STANDARDS**

#### **4.1: STANDARD 1 – NO NEW UNTREATED STORMWATER DISCHARGES**

The Massachusetts Stormwater Handbook has been revised to meet wetland regulations, 310 CMR 10.00 and water quality regulations, 314 CMR 9.00. Volume 1, Chapter 1 of the handbook states that new stormwater conveyances shall not discharge untreated stormwater directly to open waters or wetlands of the Commonwealth. The level of stormwater treatment depends on project location and site soils and are regulated by requirements in the following standards.

The proposed development project has been designed in accordance with the Massachusetts Stormwater Handbook and Standards. All new stormwater conveyances will be treated in compliance with the following standards. Computations and strategies in the following section will demonstrate compliance.

#### **4.2: STANDARD 2 – PEAK RATE OF DISCHARGE**

Development projects resulting in new impervious surfaces generates stormwater runoff at high flow rates than previous site conditions. Standard 2 has been made for developments to attenuate runoff flow rates and to not exceed previously developed conditions. This Standard requires that the post-development peak discharge rate is equal to or less than the pre-development rate from the 2-, 10-, 25-, and 100-year, 24-hour storms.

The drainage analysis was performed using the Soil Conservation Service (SCS) TR-55 and TR-20 methodologies and the computer program HydroCAD 10.00 by HydroCAD Software Solutions, LLC. The analysis was performed on the 2-, 10-, 25-, and 100-year frequency rainfall events. The events were based on the 24 hour type-III duration storm. The 'time of concentration' (Tc) for each watershed was determined by finding the time necessary for runoff to travel from the most hydraulically distant point in the watershed to the point of concentration. The travel path was drawn based on the topography and the time was calculated using the TR-55 Method and HydroCAD. A minimum Tc of 5.0 minutes was used. Curve numbers were developed for each of the different use categories and hydrologic soil group types within each sub-area. The curve numbers were based on the SCS TR-55 methodology and are included in the HydroCAD input and output found in the Attachments. Rainfall depths were acquired from National Oceanic and Atmospheric Administration (NOAA), Atlas 14, Volume 10 for the specific site location. NOAA rainfall data is attached in Appendix A and the associated rainfall depths are summarized below.

<u>Storm Event</u>	<u>Rainfall Depth</u>
2-Year	3.19 inches
10-Year	4.92 inches
25-Year	6.01 inches
100-Year	7.68 inches

The overall site was analyzed with two (2) discharge points: Discharge Point 1 (DP1) being directed to the south abutters, and Discharge Point 2 (DP2) being directed towards Warner Ave. Subcatchment areas were separated accordingly. The following assumptions were made for the purpose of this hydrologic analysis:

- Whenever possible, the property line and/or an arbitrary line, outside the limit of proposed work was delineated as the watershed boundary.
- The total watershed area for the existing condition is used as the comparison base for the watershed area in the proposed condition.
- There are no known existing roof runoff discharge connection and is assumed to runoff from surface overland.

Existing Subcatchment areas E1 and E2 are associated to DP1 and DP2, respectively. Similarly, proposed subcatchment areas P1 and P2 are associated to DP1 and DP2. Proposed subcatchment P1 is further divided into sub-sections P1A and P1B. P1A is overland runoff directed to southerly abutters, and P1B is runoff directed to the infiltration system. The proposed infiltration system will have an overflow weir off the top of the retaining wall against the parking area, and near the catch basin. In the event of an extreme storm, overflow would flow over the wall and onto a rip-rap surface towards the southerly abutters. The peak rates of runoff towards the abutters is reduced in the post-development condition.

All subcatchment areas between pre- and post-development have times of concentrations to be 5.0 minutes. A summary of the pre- and post-development peak rate of discharge are in Table 4.2(1). HydroCAD calculations for peak rate discharges can be found in Appendix B.

**EXISTING SUBCATCHMENT AREAS**

E1 – Overland Runoff to southerly abutters (9,975 sf)

Impervious – 4,400 sf

Pervious (grassed) – 5,575 sf

E2 – Overland Runoff to Warner Ave (2,525 sf)

Impervious – 1,805 sf

Pervious (grassed) – 720 sf

**PROPOSED SUBCATCHMENT AREAS**

P1A – Overland Runoff to southerly abutters (785 sf)

Pervious (grassed) – 785 sf

P1B – Runoff to Recharge System, Overflow to southerly abutters (8,835 sf)

Impervious – 6,860 sf

Pervious – 1,975 sf

P2 – Overland Runoff towards Warner Ave (2,880 sf)

Impervious – 1,975 sf

Pervious (grassed) – 905 sf

**Table 4.2(1): Peak Rate of Discharge Summary**

	DP1 – to South Abutter		DP2 – to Warner Ave	
Storm Intensity	PRE, *cfs	POST *cfs	PRE, *cfs	**POST *cfs
2-year Storm 3.19 inches	0.33	0.02	0.13	0.15
10-year Storm 4.92 inches	0.71	0.47	0.24	0.27
25-year Storm 6.01 inches	0.97	0.96	0.31	0.35
100-year Storm 7.68 inches	1.38	1.36	0.41	0.47

\* Flow rate, cfs = cubic-feet per second

\*\* minimal increase is considered insignificant and commonly accepted.

HydroCAD reports of existing and proposed peak rate discharges can be found in Appendix B.

**4.3: STANDARD 3 – GROUNDWATER RECHARGE**

As impervious surfaces are constructed from developments, exposed natural surfaces decrease resulting in the loss of natural rainfall infiltration from the new impervious surfaces. Standard 3 was implemented to design for recharge to, at a minimum, meet the natural conditions prior to constructed impervious surfaces. The post-development impervious area and properties of site soils are used to assist in determining the volume required for groundwater recharge.

As discussed in previous sections, data from NRCS determined site soils to be classified as hydraulic group “B”. Refer to Appendix A for soil reports.

The method used to determine the required recharge volume for this project is the “static method” as detailed in Volume 3, Chapter 1 of the Massachusetts Stormwater Handbook. The static method is computed by the assumption that no infiltration occurs until the infiltration system is filled to the elevation associated with the required recharge volume. Computations to determine the required recharge volume use the rates specified by Rawls 1982. The associated Rawls rate below is multiplied by the added impervious area from the development to determine the required recharge volume.

Rawls rate: Hydraulic group B = 0.35 inches of runoff

Once the required recharge volume is determined, appropriate sizing of bottom area for the infiltration system is used to determine the drawdown time. Drawdown time is the time of required recharge volume to fully infiltrate through the bottom bed of the system and is calculated using the equation below.

$$Time_{drawdown} = \frac{Rv}{(K)(Bottom\ Area)}$$

Where:

Rv = Storage Volume

K = Saturated Hydraulic Conductivity for the static method (Rawls Rate)

Bottom Area = Bottom Area of Recharge Structure

The proposed project has one (1) recharge system and is two (2) feet above the ESHGT. The system is made up of StormTech® SC-740 chambers. All computations for Standard 3 are in Appendix B and demonstrate that the proposed project meets this standard.

#### **4.4: STANDARD 4 – WATER QUALITY**

Runoff from impervious surfaces flow overland and gather solids as the stormwater is directed into conveyance systems and can have adverse effects to water pollution. Standard 4 was implemented for stormwater management systems to be designed to remove 80% of the average annual post-development load of Total Suspended Solids (TSS). Runoff volume requiring appropriate TSS treatment is known as the required water quality volume.

Water quality volume for the proposed project is calculated by the post-development impervious ground area multiplied by one-half (0.5) inch of runoff. Soil tests determined site soils to have an infiltration rate of 0.52 inches/ hour, as determined by the 1982 Rawls Rates displayed in Table 4.4(1).

**Table 4.4(1): Rawls Rates**

Texture Class	NRCS Hydrologic Soil Group (HSG)	Infiltration Rate Inches/Hour
Loam	B	0.52

The proposed recharge system provides sufficient volume to demonstrate that the required water quality volume is fully contained within each system. Computations for TSS removal are required as pre-treatment prior to stormwater discharge. Pre-treatment prior to groundwater recharge is achieved, however, all runoff directed to the recharge system is roof runoff and is classified as “clean” runoff.

The Massachusetts Stormwater Handbook state that this standard is met when:

- a) Suitable practices for source control and pollution prevention are identified in a long-term pollution prevention plan, and thereafter are implemented and maintained;
- b) Structural stormwater best management practices are sized to capture the required water quality volume as determined in accordance with the Massachusetts Stormwater Handbook; and
- c) Pretreatment is provided in accordance with the Massachusetts Stormwater Handbook.

The proposed project meets this standard, and all computations are in Appendix B.

#### **4.5: STANDARD 5 – LAND USES WITH HIGHER POLLUTION PREVENTION LOADS**

For land uses with higher potential pollutant loads, source control and pollution prevention shall be implemented to eliminate or reduce the discharge of stormwater runoff from such land uses to the maximum extent practicable. Due to the generally low-intensity-use of the proposed project, the site is not considered a Land Use with High Potential Pollutant Loads (LUHPPL).

#### **4.6: STANDARD 6 – CRITICAL AREAS**

Stormwater discharges within the Zone II or Interim Wellhead Protection Area of a public water supply, and stormwater discharges near or to any other critical area, require the use of the specific source control and pollution prevention measures and the specific structural stormwater best management practices determined by the Department to be suitable for managing discharges to such areas, as provided in the Massachusetts Stormwater Handbook. The project site does not discharge to a critical area and therefore, Standard 6 is not applicable.

#### **4.7: STANDARD 7 – REDEVELOPMENT PROJECTS**

For purposes of the Stormwater Management Standards, redevelopment projects are defined to include the following:

1. Maintenance and improvement of existing roadways, including widening less than a single lane, adding shoulders, correcting substandard intersections, improving existing drainage systems, and repaving;
2. Development, rehabilitation, expansion and phased projects on previously developed sites, provided the redevelopment results in no net increase in impervious area; and
3. Remedial projects specifically designed to provide improved stormwater management, such as projects to separate storm drains and sanitary sewers and stormwater retrofit projects.



All redevelopment projects must fully comply with the provisions of the Stormwater Management Standards requiring the development and implementation of a construction period erosion and sedimentation control plan, a pollution prevention plan, an operation and maintenance plan, and the prohibition of illicit discharges. All redevelopment projects are also required to meet the following Standards only to the maximum extent practicable: Standard 2, Standard 3, and the pretreatment and structural stormwater best management practice requirements of Standards 4, 5, and 6.

The proposed project does not fit the category of a redevelopment since there is a net increase of impervious area and therefore, Standard 7 is not applicable.

**4.8: STANDARD 8 – TEMPORARY EROSION, SEDIMENTATION, AND POLLUTION PREVENTION**

During land disturbance and construction activities, project proponents must implement controls that prevent erosion, control sediment movement, and stabilize exposed soils to prevent pollutants from moving offsite or entering wetlands or waters. Land disturbance activities include demolition, construction, clearing, excavation, grading, filling, and reconstruction. Please refer to the Massachusetts Erosion and Sediment Control Guidelines for Urban and Suburban Areas provided by MassDEP for more detailed information.

Erosion control silt fence will be provided around the perimeter of the site, as well as installing inlet protection silt bags in nearby and new catch basins. With proper care and maintenance as outlined within this report, it is determined that these barriers will suffice as sedimental transfer protection to outside areas.

**4.8.1: STABILIZATION SCHEDULE**

The site shall be controlled and maintained with stabilization methods on disturbed areas. Disturbed areas are areas that will be exposed of dirt from construction activities. A temporary vegetative cover will be established on areas of exposed soils (including stockpiles) as described in Table 4.8.1(1). Disturbed areas shall be periodically inspected and after ever storm event of 0.5” of rainfall.

**Table 4.8.1(1): Temporary Construction Stabilization Schedule**

Area requiring permanent stabilization	Time frame to apply erosion controls
Any disturbed areas within 50 feet of a surface water of the State and not at final grade	Within two days of the most recent disturbance if the area will remain idle for more than 14 days
For all construction activities, any disturbed areas that will be dormant for more than fourteen (14) days but less than one year, and not within 50 feet of a surface water of the State	Within five (5) days of the most recent disturbance within the area. For residential subdivisions, disturbed areas must be stabilized at least seven days prior to transfer of permit coverage for the individual lot(s).
Disturbed areas that will be idle over winter	Prior to the onset of winter weather

#### 4.8.2: POTENTIAL STORMWATER CONTAMINANTS

The purpose of this section is to identify methods to minimize potential pollutants that could impact storm water during construction. Pollutants that result from clearing, grading, excavation, and building materials and have the potential to be present in stormwater runoff.

To minimize the potential for stormwater contamination the following practices shall be followed:

- No solid or liquid waste, including building materials or their packaging, shall be discharged in stormwater runoff.
- Concrete trucks are not permitted to wash out directly into storm sewers, streams or drainage channels.
- Off-site tracking of sediments by construction vehicles must be minimized.
- Contaminated soils or soils where construction site chemicals have been spilled must be removed from the site and disposed of in accordance with federal, state and local regulations.
- Stormwater that comes in contact with contaminated soils or solid & industrial waste must be collected and disposed of as a wastewater.
- Fuel tanks and drums or other containers holding construction site chemicals must be stored within a diked area.
- Sediment-laden trench or groundwater must pass through a sediment-settling pond, or be dewatered in place using a sump pit, filter bag or other comparable method, prior to being discharged from the site.
- Trench and ground water free from sediment or other pollutants may be discharged without treatment, provided this water does not become pollutant-laden by traversing over disturbed soils or other pollutant sources.

#### **4.9: STANDARD 9 – LONG-TERM OPERATION AND MAINTENANCE PLAN**

The goal of the operation and maintenance plan is to protect resources in the region that may be adversely impacted by the proposed development. Water quality treatment measures and the implementation of Best Management Practices (BMP's) for structural controls will result in the treatment of site stormwater and the removal of a minimum of 80% of the TSS load in runoff prior to discharge from the site, consistent with the MA Stormwater Management Handbook.

The stormwater management system will be owned by the current and future landowner(s) who will be responsible for operation and maintenance. The estimated operation and maintenance budget is estimated to be approximately \$2,000 (two-thousand) annually. Inspections shall be made for the following maintenance systems and shall be recorded with information of the inspection date, inspector's name, system inspected, findings of inspection, and actions made for maintenance. A log for these inspections is attached in Appendix C.

#### 4.9.1: STRUCTURAL POLLUTANT CONTROLS AND MAINTENANCE

The proposed stormwater management system(s) is(are) designed to protect runoff water quality through the removal of sediment and pollutants. Structural pollutant controls used to separate and capture stormwater pollutants are described below.

(1) Catch Basins / Inlets & Manholes

Proposed catch basins/ inlets at the site will be equipped with deep sumps and hooded outlets that trap debris, sediments, and floating contaminants, which are the largest constituents of urban runoff. The proper removal of sediments and associated pollutants and trash occurs only when catch basin inlets and sumps are cleaned out regularly. The more frequent the cleaning, the less likely sediments will be re-suspended and subsequently discharged. In addition, frequent cleaning also results in more volume available for future deposition and enhances overall performance.

*Maintenance: All catch basins and inlets will be inspected at a minimum of at least once per year and cleaned when the sump has accumulated to a depth of one (1) foot of sediment. Sediment and/or floatable pollutants will be pumped from the inlet drain opening and disposed of at an approved offsite facility in accordance with all applicable regulations. Any structural damage or other indication of malfunction will be reported to the site manager and repaired as necessary. During colder periods, catch basin and inlet grates will be kept free of snow and ice. During warmer periods, catch basin and inlet grates will be kept free of leaves, litter, sand, and debris. Regular maintenance and cleaning of catch basins and inlets will assure adequate performance of these structures.*

(2) Subsurface Infiltration System

The stormwater management system includes a subsurface infiltration system to provide water quality treatment and recharge, as well as attenuate peak flows. The maintenance of the system may affect the functioning of stormwater management practices.

*Maintenance: Visual inspection of the subsurface infiltration system will occur twice per year and after every major storm during the first 3 months of operation. Remove any debris that might clog the system. If water is observed and it is at least 72 hours after a rain event, the system will require to be cleaned to remove any built-up sediment.*

(3) Subsurface Infiltration System Isolator Row

The stormwater management system(s) include the use of an isolator row in the subsurface infiltration system to enhance total suspended solids removal and provide easier access for cleaning and maintenance. The proper function of these items is crucial to providing adequate groundwater recharge and flood control.

*Maintenance: Subsurface infiltration system isolator row may affect the functioning of stormwater management practices. Visual inspection of the isolator row through the inspection port is to occur every six months in the first year of use. After the first year of use, visually inspect annually at a minimum. The isolator row shall be cleaned when the average depth of sediment exceeds three (3) inches. Refer to StormTech® Isolator Row O&M manual for cleaning*

*procedure. For more information and details on maintenance and cleaning of this particular product, it is recommended to seek advice from the manufacturer - StormTech®. StormTech® can be contacted by phone at 888-892-2694.*

#### **4.10: STANDARD 10 – PROHIBITED ILLICIT DISCHARGES**

Standard 10 prohibits illicit discharges to stormwater management systems. The stormwater management system is the system for conveying, treating, and infiltrating stormwater on-site, including stormwater best management practices and any pipes intended to transport stormwater to the groundwater, a surface water, or municipal separate storm sewer system. Illicit discharges to the stormwater management system are discharges that are not entirely comprised of stormwater.

Proponents of projects within Wetlands jurisdiction must demonstrate compliance with this requirement by submitting to the issuing authority an Illicit Discharge Compliance Statement verifying that no illicit discharges exist on the site and by including in the pollution prevention plan measures to prevent illicit discharges to the stormwater management system, including wastewater discharges and discharges of stormwater contaminated by contact with process wastes, raw materials, toxic pollutants, hazardous substances, oil, or grease.

#### Illicit Discharge Compliance Statement

The proposed project at 214 Hamilton Street in Worcester, Massachusetts has been designed in accordance with the Massachusetts Stormwater Handbook and demonstrates that all proponents of the stormwater management design systems do not contain any new illicit discharges, in accordance with Standard 10. Please refer to the following appendices and civil design plans for compliance.



Giovanni G. Fodera, PE, LSIT  
*President | Principal Engineer*  
**FODERA Engineering**  
28 Harbor St., Suite 204  
Danvers, MA 01923

Date: September 20, 2023

**APPENDIX A – SITE CONDITIONS**  
**Soil Testing Report**



551 Dorchester Ave #21  
Boston, MA 02127  
T: 413-281-6615  
Kevin@quettidesigngroup.com

September 1, 2023

Quetti Project #285

Tal Klayman  
REI Group LLC  
108 Bayreuth Place  
Cary, North Carolina 27513

### **214 Hamilton Street, Worcester, MA - Test Pit Report**

Dear Mr. Klayman,

A test pit was conducted at the multi-family residence at the location noted above for the purposes of determining consistency or deviation of the soils in relation to the United States Department of Agriculture's (USDA) Natural Resources Conservation Service (NRCS) database. The attached exhibits include a site plan showing the approximate location of the test pits and soil profile. The test pit was during Quetti Design Group's site visit at 11:00 AM on Thursday, August 31, 2023. The observations are described below.

The property is defined in the NRCS database as having Paxton-Urban land complex, with 8 to 15 percent slopes. Paxton soils are classified as having a hydrologic soil group (HSG) rating C, and Urban Land a HSG D.

#### **Soil Observations:**

##### **Test Pit #1**

The test pit was divided into three layers for the purposes of analysis and report. Layer 1, the shallowest, was observed at 10 inches thick and consisted of a fine sandy loam fill material and was consistent with expectations for urban land. Layer 2 was observed at 32 inches thick and consisted of fine sandy loam. Layer 3 was observed at 54 inches thick to the bottom of excavation and consisted of a dense gravelly fine sandy loam layer. No groundwater was observed (likely due to the test being performed in late summer), but soil mottling was observed 22 inches below grade, indicating the presence of high groundwater. Based on this opinion, we would recommend a conservative Rawl's Infiltration Rate of 0.52 inches per hour be used for infiltration system design in this area due to the densic material observed within the C layer.

Paxton soils are known for being well drained. The infiltration design shall be designed to provide a minimum of 2 feet of vertical separation from groundwater and drawdown within the required 72-hour period as required by the Massachusetts Stormwater Handbook. All attempts to keep excavated land lower than surrounding lands (while maintaining proper erosion controls) should be exercised to help mitigate off-site runoff potential. The contractor shall construct and maintain erosion and sediment control measures in accordance with the latest edition of "Massachusetts Erosion and Sediment Control Guidelines for Urban and Suburban Areas" prepared by the DEP and as directed by the local permitting authority. The contractor shall notify the engineer if any discrepancies from the data in this report are observed in the field prior to construction.


This analysis shall only be used for stormwater infiltration use to help determine the rate at which the system may drain. No other use is expressed or implied.

Respectfully submitted,



Kevin Quetti, PE  
Principal Engineer  
Quetti Design Group

**Test Pit #1 Photo and Profile Sketch (Not to Scale)**








Custom Soil Resource Report  
Soil Map (214 Hamilton Street, Worcester, MA)



Map Scale: 1:2,140 if printed on A landscape (11" x 8.5") sheet.



## Worcester County, Massachusetts, Northeastern Part

### 72A—Whitman fine sandy loam, 0 to 3 percent slopes

#### Map Unit Setting

*National map unit symbol:* 2zggp  
*Elevation:* 0 to 1,080 feet  
*Mean annual precipitation:* 36 to 71 inches  
*Mean annual air temperature:* 39 to 55 degrees F  
*Frost-free period:* 140 to 240 days  
*Farmland classification:* Not prime farmland

#### Map Unit Composition

*Whitman and similar soils:* 80 percent  
*Minor components:* 20 percent  
*Estimates are based on observations, descriptions, and transects of the mapunit.*

#### Description of Whitman

##### Setting

*Landform:* Drumlins, ground moraines, hills, drainageways, depressions  
*Landform position (two-dimensional):* Toeslope  
*Landform position (three-dimensional):* Base slope  
*Down-slope shape:* Concave  
*Across-slope shape:* Concave  
*Parent material:* Coarse-loamy lodgment till derived from granite and gneiss and/or schist

##### Typical profile

*O<sub>i</sub> - 0 to 1 inches:* peat  
*A - 1 to 10 inches:* fine sandy loam  
*B<sub>g</sub> - 10 to 17 inches:* gravelly fine sandy loam  
*C<sub>dg</sub> - 17 to 61 inches:* fine sandy loam

##### Properties and qualities

*Slope:* 0 to 3 percent  
*Depth to restrictive feature:* 7 to 38 inches to densic material  
*Drainage class:* Very poorly drained  
*Runoff class:* Negligible  
*Capacity of the most limiting layer to transmit water (K<sub>sat</sub>):* Very low to moderately low (0.00 to 0.14 in/hr)  
*Depth to water table:* About 0 to 6 inches  
*Frequency of flooding:* None  
*Frequency of ponding:* Frequent  
*Maximum salinity:* Nonsaline (0.0 to 1.9 mmhos/cm)  
*Available water supply, 0 to 60 inches:* Low (about 3.0 inches)

##### Interpretive groups

*Land capability classification (irrigated):* None specified  
*Land capability classification (nonirrigated):* 5w  
*Hydrologic Soil Group:* D  
*Ecological site:* F144AY041MA - Very Wet Till Depressions  
*Hydric soil rating:* Yes

**Minor Components**

**Ridgebury**

*Percent of map unit:* 10 percent  
*Landform:* Ground moraines, hills, drainageways, drumlins, depressions  
*Landform position (two-dimensional):* Footslope, toeslope  
*Landform position (three-dimensional):* Head slope, base slope  
*Down-slope shape:* Concave  
*Across-slope shape:* Concave  
*Hydric soil rating:* Yes

**Scarboro**

*Percent of map unit:* 6 percent  
*Landform:* Outwash terraces, outwash deltas, drainageways, depressions  
*Landform position (three-dimensional):* Tread  
*Down-slope shape:* Concave  
*Across-slope shape:* Concave  
*Hydric soil rating:* Yes

**Swansea**

*Percent of map unit:* 3 percent  
*Landform:* Marshes, bogs, swamps  
*Down-slope shape:* Concave  
*Across-slope shape:* Concave  
*Hydric soil rating:* Yes

**Woodbridge**

*Percent of map unit:* 1 percent  
*Landform:* Ground moraines, hills, drumlins  
*Landform position (two-dimensional):* Summit, backslope, footslope  
*Landform position (three-dimensional):* Crest, side slope  
*Down-slope shape:* Concave  
*Across-slope shape:* Linear  
*Hydric soil rating:* No

**602—Urban land**

**Map Unit Setting**

*National map unit symbol:* w3q8  
*Mean annual precipitation:* 32 to 50 inches  
*Mean annual air temperature:* 45 to 50 degrees F  
*Frost-free period:* 145 to 240 days  
*Farmland classification:* Not prime farmland

**Map Unit Composition**

*Urban land:* 100 percent  
*Estimates are based on observations, descriptions, and transects of the mapunit.*

## Description of Urban Land

### Setting

*Parent material:* Excavated and filled land

## 622C—Paxton-Urban land complex, 8 to 15 percent slopes

### Map Unit Setting

*National map unit symbol:* 2w67n

*Elevation:* 0 to 1,030 feet

*Mean annual precipitation:* 36 to 71 inches

*Mean annual air temperature:* 39 to 55 degrees F

*Frost-free period:* 140 to 240 days

*Farmland classification:* Not prime farmland

### Map Unit Composition

*Paxton and similar soils:* 45 percent

*Urban land:* 35 percent

*Minor components:* 20 percent

*Estimates are based on observations, descriptions, and transects of the mapunit.*

## Description of Paxton

### Setting

*Landform:* Ground moraines, hills, drumlins

*Landform position (two-dimensional):* Backslope

*Landform position (three-dimensional):* Side slope

*Down-slope shape:* Convex, linear

*Across-slope shape:* Convex

*Parent material:* Coarse-loamy lodgment till derived from gneiss, granite, and/or schist

### Typical profile

*Ap - 0 to 8 inches:* fine sandy loam

*Bw1 - 8 to 15 inches:* fine sandy loam

*Bw2 - 15 to 26 inches:* fine sandy loam

*Cd - 26 to 65 inches:* gravelly fine sandy loam

### Properties and qualities

*Slope:* 8 to 15 percent

*Depth to restrictive feature:* 20 to 39 inches to densic material

*Drainage class:* Well drained

*Runoff class:* Medium

*Capacity of the most limiting layer to transmit water (Ksat):* Very low to moderately low (0.00 to 0.14 in/hr)

*Depth to water table:* About 18 to 37 inches

*Frequency of flooding:* None

*Frequency of ponding:* None

*Maximum salinity:* Nonsaline (0.0 to 1.9 mmhos/cm)

*Available water supply, 0 to 60 inches:* Low (about 4.1 inches)

## Custom Soil Resource Report

### Interpretive groups

*Land capability classification (irrigated):* None specified  
*Land capability classification (nonirrigated):* 3e  
*Hydrologic Soil Group:* C  
*Ecological site:* F144AY007CT - Well Drained Dense Till Uplands  
*Hydric soil rating:* No

### Description of Urban Land

#### Typical profile

*M - 0 to 10 inches:* cemented material

#### Properties and qualities

*Slope:* 8 to 15 percent  
*Depth to restrictive feature:* 0 inches to manufactured layer  
*Runoff class:* Very high  
*Capacity of the most limiting layer to transmit water (Ksat):* Very low (0.00 to 0.00 in/hr)  
*Available water supply, 0 to 60 inches:* Very low (about 0.0 inches)

### Interpretive groups

*Land capability classification (irrigated):* None specified  
*Land capability classification (nonirrigated):* 8  
*Hydrologic Soil Group:* D  
*Hydric soil rating:* Unranked

### Minor Components

#### Udorthents

*Percent of map unit:* 9 percent  
*Down-slope shape:* Linear  
*Across-slope shape:* Linear  
*Hydric soil rating:* No

#### Canton

*Percent of map unit:* 7 percent  
*Landform:* Hills  
*Landform position (two-dimensional):* Backslope  
*Landform position (three-dimensional):* Side slope  
*Down-slope shape:* Convex, linear  
*Across-slope shape:* Convex  
*Hydric soil rating:* No

#### Woodbridge

*Percent of map unit:* 3 percent  
*Landform:* Ground moraines, hills, drumlins  
*Landform position (two-dimensional):* Summit, backslope, footslope  
*Landform position (three-dimensional):* Crest, side slope  
*Down-slope shape:* Concave  
*Across-slope shape:* Linear  
*Hydric soil rating:* No

#### Ridgebury

*Percent of map unit:* 1 percent  
*Landform:* Drumlins, depressions, ground moraines, hills, drainageways  
*Landform position (two-dimensional):* Footslope, toeslope  
*Landform position (three-dimensional):* Head slope, base slope

## Custom Soil Resource Report

*Down-slope shape:* Concave, linear  
*Across-slope shape:* Concave, linear  
*Hydric soil rating:* Yes

## **NOAA Rainfall Data**





**NOAA Atlas 14, Volume 10, Version 3**  
**Location name: Worcester, Massachusetts, USA\***  
**Latitude: 42.257°, Longitude: -71.7718°**  
**Elevation: 552 ft\*\***  
 \* source: ESRI Maps  
 \*\* source: USGS



**POINT PRECIPITATION FREQUENCY ESTIMATES**

Sanja Perica, Sandra Pavlovic, Michael St. Laurent, Carl Trypaluk, Dale Unruh, Orlan Wilhite

NOAA, National Weather Service, Silver Spring, Maryland

[PF\\_tabular](#) | [PF\\_graphical](#) | [Maps & aerials](#)

**PF tabular**

<b>PDS-based point precipitation frequency estimates with 90% confidence intervals (in inches)<sup>1</sup></b>										
Duration	Average recurrence interval (years)									
	1	2	5	10	25	50	100	200	500	1000
5-min	0.342 (0.272-0.426)	0.403 (0.320-0.502)	0.503 (0.397-0.629)	0.585 (0.460-0.737)	0.699 (0.529-0.921)	0.785 (0.581-1.06)	0.874 (0.625-1.23)	0.970 (0.657-1.40)	1.10 (0.717-1.66)	1.21 (0.766-1.86)
10-min	0.485 (0.385-0.603)	0.571 (0.453-0.712)	0.712 (0.563-0.891)	0.829 (0.651-1.04)	0.990 (0.750-1.30)	1.11 (0.823-1.50)	1.24 (0.885-1.74)	1.38 (0.933-1.99)	1.56 (1.02-2.36)	1.72 (1.09-2.64)
15-min	0.570 (0.453-0.710)	0.672 (0.533-0.837)	0.838 (0.662-1.05)	0.976 (0.767-1.23)	1.16 (0.882-1.54)	1.31 (0.968-1.76)	1.46 (1.04-2.04)	1.62 (1.10-2.34)	1.84 (1.20-2.77)	2.02 (1.28-3.11)
30-min	0.773 (0.614-0.962)	0.911 (0.723-1.14)	1.14 (0.899-1.42)	1.32 (1.04-1.67)	1.58 (1.20-2.09)	1.78 (1.32-2.40)	1.98 (1.42-2.78)	2.20 (1.49-3.18)	2.50 (1.63-3.77)	2.74 (1.74-4.23)
60-min	0.975 (0.775-1.21)	1.15 (0.913-1.43)	1.44 (1.14-1.80)	1.67 (1.32-2.11)	2.00 (1.52-2.64)	2.25 (1.66-3.03)	2.50 (1.79-3.51)	2.78 (1.88-4.03)	3.17 (2.06-4.76)	3.47 (2.20-5.35)
2-hr	1.23 (0.985-1.52)	1.46 (1.17-1.81)	1.84 (1.47-2.29)	2.16 (1.71-2.70)	2.59 (1.98-3.41)	2.92 (2.18-3.93)	3.26 (2.36-4.59)	3.66 (2.49-5.27)	4.24 (2.76-6.34)	4.72 (3.00-7.22)
3-hr	1.41 (1.13-1.74)	1.68 (1.35-2.08)	2.13 (1.70-2.64)	2.50 (1.99-3.12)	3.02 (2.31-3.96)	3.40 (2.55-4.57)	3.80 (2.77-5.35)	4.28 (2.92-6.15)	5.00 (3.26-7.46)	5.61 (3.57-8.55)
6-hr	1.77 (1.43-2.17)	2.13 (1.72-2.61)	2.72 (2.19-3.35)	3.21 (2.56-3.98)	3.89 (3.00-5.08)	4.39 (3.31-5.88)	4.93 (3.61-6.91)	5.58 (3.81-7.96)	6.56 (4.30-9.72)	7.40 (4.72-11.2)
12-hr	2.19 (1.78-2.67)	2.66 (2.16-3.25)	3.43 (2.77-4.20)	4.07 (3.27-5.01)	4.94 (3.83-6.42)	5.59 (4.24-7.45)	6.29 (4.63-8.77)	7.13 (4.89-10.1)	8.41 (5.52-12.4)	9.49 (6.07-14.3)
24-hr	2.61 (2.13-3.15)	3.19 (2.60-3.86)	4.14 (3.36-5.03)	4.92 (3.98-6.02)	6.01 (4.69-7.76)	6.81 (5.20-9.02)	7.68 (5.68-10.6)	8.73 (6.01-12.3)	10.3 (6.80-15.1)	11.7 (7.50-17.5)
2-day	2.96 (2.44-3.56)	3.64 (2.99-4.38)	4.75 (3.89-5.74)	5.68 (4.62-6.90)	6.94 (5.46-8.93)	7.88 (6.06-10.4)	8.90 (6.64-12.3)	10.2 (7.02-14.2)	12.1 (8.00-17.6)	13.8 (8.87-20.5)
3-day	3.22 (2.66-3.85)	3.95 (3.26-4.74)	5.15 (4.23-6.20)	6.14 (5.01-7.44)	7.51 (5.92-9.61)	8.51 (6.56-11.2)	9.61 (7.19-13.2)	11.0 (7.60-15.3)	13.1 (8.66-18.9)	14.9 (9.61-22.0)
4-day	3.45 (2.86-4.12)	4.22 (3.49-5.05)	5.47 (4.51-6.57)	6.52 (5.33-7.87)	7.95 (6.28-10.1)	9.00 (6.96-11.8)	10.2 (7.61-13.9)	11.6 (8.03-16.1)	13.8 (9.14-19.9)	15.7 (10.1-23.1)
7-day	4.12 (3.43-4.90)	4.95 (4.12-5.90)	6.32 (5.23-7.55)	7.45 (6.13-8.95)	9.00 (7.14-11.4)	10.2 (7.86-13.2)	11.4 (8.55-15.5)	12.9 (8.99-17.8)	15.2 (10.1-21.8)	17.1 (11.1-25.1)
10-day	4.78 (4.00-5.67)	5.65 (4.72-6.70)	7.07 (5.88-8.42)	8.25 (6.82-9.89)	9.88 (7.85-12.4)	11.1 (8.60-14.3)	12.4 (9.27-16.7)	13.9 (9.71-19.1)	16.2 (10.8-23.1)	18.1 (11.7-26.4)
20-day	6.82 (5.74-8.03)	7.75 (6.51-9.13)	9.26 (7.75-11.0)	10.5 (8.73-12.5)	12.2 (9.75-15.2)	13.5 (10.5-17.2)	14.9 (11.1-19.6)	16.3 (11.5-22.3)	18.3 (12.3-26.0)	19.9 (12.9-28.9)
30-day	8.53 (7.21-10.0)	9.49 (8.00-11.1)	11.0 (9.28-13.0)	12.3 (10.3-14.6)	14.1 (11.3-17.4)	15.5 (12.0-19.5)	16.9 (12.5-22.0)	18.2 (12.9-24.7)	20.0 (13.4-28.2)	21.3 (13.9-30.8)
45-day	10.7 (9.04-12.5)	11.6 (9.87-13.6)	13.3 (11.2-15.6)	14.6 (12.2-17.3)	16.4 (13.2-20.1)	17.9 (13.9-22.4)	19.3 (14.3-24.9)	20.6 (14.6-27.8)	22.1 (14.9-31.0)	23.2 (15.1-33.4)
60-day	12.4 (10.6-14.5)	13.5 (11.4-15.7)	15.1 (12.8-17.7)	16.5 (13.9-19.5)	18.4 (14.8-22.5)	19.9 (15.5-24.8)	21.4 (15.9-27.4)	22.6 (16.0-30.4)	24.0 (16.2-33.6)	24.9 (16.3-35.7)


<sup>1</sup> Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS). Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values. Please refer to NOAA Atlas 14 document for more information.

[Back to Top](#)


**PF graphical**

PDS-based depth-duration-frequency (DDF) curves

Latitude: 42.2570°, Longitude: -71.7718°



Average recurrence interval (years)
1
2
5
10
25
50
100
200
500
1000



Duration	
5-min	2-day
10-min	3-day
15-min	4-day
30-min	7-day
60-min	10-day
2-hr	20-day
3-hr	30-day
6-hr	45-day
12-hr	60-day
24-hr	

[Back to Top](#)

**Maps & aerials**

**Small scale terrain**




Large scale terrain



Large scale map



Large scale aerial



[Back to Top](#)

---

[US Department of Commerce](#)  
[National Oceanic and Atmospheric Administration](#)  
[National Weather Service](#)  
[National Water Center](#)  
1325 East West Highway  
Silver Spring, MD 20910  
Questions?: [HDSC.Questions@noaa.gov](mailto:HDSC.Questions@noaa.gov)

[Disclaimer](#)

**APPENDIX B – STORMWATER CALCULATIONS**

**Standard 2 – Peak Rate of Runoff**


**Standard 3 – Groundwater Recharge**

**Standard 4 – Water Quality**

## **Standard 2 – Peak Rate of Runoff**

DP1


DP2



T

WARNER AVENUE


HAMILTON STREET




SCALE  
1 inch = 20 ft.

**PRE-DEVELOPMENT DRAINAGE MAP**



SCALE: 1" = 20'



To South Abutter



To Warner Ave





**2023-09-19\_PRE-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Pre Construction Runoff  
Type III 24-hr 2-Year Rainfall=3.19"

Printed 9/20/2023

Page 2

**Summary for Subcatchment E1: To South Abutter**

Runoff = 0.33 cfs @ 12.08 hrs, Volume= 0.023 af, Depth> 1.20"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 2-Year Rainfall=3.19"

	Area (sf)	CN	Description
*	4,400	98	Impervious, HSG A
	5,575	61	>75% Grass cover, Good, HSG B
	9,975	77	Weighted Average
	5,575		55.89% Pervious Area
	4,400		44.11% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E1: To South Abutter**

Hydrograph



**2023-09-19\_PRE-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Pre Construction Runoff  
Type III 24-hr 2-Year Rainfall=3.19"

Printed 9/20/2023

Page 3

**Summary for Subcatchment E2: To Warner Ave**

Runoff = 0.13 cfs @ 12.07 hrs, Volume= 0.009 af, Depth> 1.90"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 2-Year Rainfall=3.19"

	Area (sf)	CN	Description
*	1,805	98	Impervious, HSG A
	720	61	>75% Grass cover, Good, HSG B
	2,525	87	Weighted Average
	720		28.51% Pervious Area
	1,805		71.49% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E2: To Warner Ave**

Hydrograph



**2023-09-19\_PRE-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Pre Construction Runoff  
Type III 24-hr 10-Year Rainfall=4.92"

Printed 9/20/2023

Page 4

**Summary for Subcatchment E1: To South Abutter**

Runoff = 0.71 cfs @ 12.08 hrs, Volume= 0.049 af, Depth> 2.55"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 10-Year Rainfall=4.92"

	Area (sf)	CN	Description
*	4,400	98	Impervious, HSG A
	5,575	61	>75% Grass cover, Good, HSG B
	9,975	77	Weighted Average
	5,575		55.89% Pervious Area
	4,400		44.11% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E1: To South Abutter**

Hydrograph



**2023-09-19\_PRE-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Pre Construction Runoff  
Type III 24-hr 10-Year Rainfall=4.92"

Printed 9/20/2023

Page 5

**Summary for Subcatchment E2: To Warner Ave**

Runoff = 0.24 cfs @ 12.07 hrs, Volume= 0.017 af, Depth> 3.49"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 10-Year Rainfall=4.92"

	Area (sf)	CN	Description
*	1,805	98	Impervious, HSG A
	720	61	>75% Grass cover, Good, HSG B
	2,525	87	Weighted Average
	720		28.51% Pervious Area
	1,805		71.49% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E2: To Warner Ave**

Hydrograph



**2023-09-19\_PRE-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Pre Construction Runoff  
 Type III 24-hr 25-Year Rainfall=6.01"

Printed 9/20/2023

Page 6

**Summary for Subcatchment E1: To South Abutter**


Runoff = 0.97 cfs @ 12.07 hrs, Volume= 0.066 af, Depth> 3.48"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 25-Year Rainfall=6.01"

	Area (sf)	CN	Description
*	4,400	98	Impervious, HSG A
	5,575	61	>75% Grass cover, Good, HSG B
	9,975	77	Weighted Average
	5,575		55.89% Pervious Area
	4,400		44.11% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E1: To South Abutter**



**2023-09-19\_PRE-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Pre Construction Runoff  
Type III 24-hr 25-Year Rainfall=6.01"

Printed 9/20/2023

Page 7

**Summary for Subcatchment E2: To Warner Ave**

Runoff = 0.31 cfs @ 12.07 hrs, Volume= 0.022 af, Depth> 4.52"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 25-Year Rainfall=6.01"

	Area (sf)	CN	Description
*	1,805	98	Impervious, HSG A
	720	61	>75% Grass cover, Good, HSG B
	2,525	87	Weighted Average
	720		28.51% Pervious Area
	1,805		71.49% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E2: To Warner Ave**

Hydrograph



**2023-09-19\_PRE-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Pre Construction Runoff  
Type III 24-hr 100-Year Rainfall=7.68"

Printed 9/20/2023

Page 8

**Summary for Subcatchment E1: To South Abutter**


Runoff = 1.38 cfs @ 12.07 hrs, Volume= 0.095 af, Depth> 4.98"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 100-Year Rainfall=7.68"

	Area (sf)	CN	Description
*	4,400	98	Impervious, HSG A
	5,575	61	>75% Grass cover, Good, HSG B
	9,975	77	Weighted Average
	5,575		55.89% Pervious Area
	4,400		44.11% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E1: To South Abutter**



**2023-09-19\_PRE-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Pre Construction Runoff  
Type III 24-hr 100-Year Rainfall=7.68"

Printed 9/20/2023

Page 9

**Summary for Subcatchment E2: To Warner Ave**

Runoff = 0.41 cfs @ 12.07 hrs, Volume= 0.030 af, Depth> 6.13"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 100-Year Rainfall=7.68"

	Area (sf)	CN	Description
*	1,805	98	Impervious, HSG A
	720	61	>75% Grass cover, Good, HSG B
	2,525	87	Weighted Average
	720		28.51% Pervious Area
	1,805		71.49% Impervious Area



Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E2: To Warner Ave**

Hydrograph










SCALE  
1 inch = 20 ft.

**POST-DEVELOPMENT DRAINAGE MAP**

SCALE: 1" = 20'



# 2023-09-19\_POST-DRAINAGE\_MASTER

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff

Type III 24-hr 2-Year Rainfall=3.19"

Printed 9/20/2023

Page 2

## Summary for Subcatchment P1A: To South Abutter

Runoff = 0.01 cfs @ 12.11 hrs, Volume= 0.001 af, Depth> 0.44"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 2-Year Rainfall=3.19"

Area (sf)	CN	Description
785	61	>75% Grass cover, Good, HSG B
785		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

## Subcatchment P1A: To South Abutter

Hydrograph



**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff  
Type III 24-hr 2-Year Rainfall=3.19"

Printed 9/20/2023

Page 3

**Summary for Subcatchment P1B: To Catch Basin**

Runoff = 0.53 cfs @ 12.07 hrs, Volume= 0.036 af, Depth> 2.16"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 2-Year Rainfall=3.19"

	Area (sf)	CN	Description
*	6,860	98	Impervious, HSG A
	1,975	61	>75% Grass cover, Good, HSG B
	8,835	90	Weighted Average
	1,975		22.35% Pervious Area
	6,860		77.65% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P1B: To Catch Basin**

Hydrograph



**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff  
 Type III 24-hr 2-Year Rainfall=3.19"

Printed 9/20/2023

Page 4

**Summary for Subcatchment P2: To Warner Ave**

Runoff = 0.15 cfs @ 12.07 hrs, Volume= 0.010 af, Depth> 1.82"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 2-Year Rainfall=3.19"

Area (sf)	CN	Description
1,975	98	Unconnected pavement, HSG A
905	61	>75% Grass cover, Good, HSG B
2,880	86	Weighted Average
905		31.42% Pervious Area
1,975		68.58% Impervious Area
1,975		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P2: To Warner Ave**

Hydrograph




### Summary for Reach DP1: Design Point 1

Inflow Area = 0.221 ac, 71.31% Impervious, Inflow Depth > 0.24" for 2-Year event  
Inflow = 0.02 cfs @ 14.71 hrs, Volume= 0.004 af  
Outflow = 0.02 cfs @ 14.71 hrs, Volume= 0.004 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

### Reach DP1: Design Point 1

Hydrograph



**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff

Type III 24-hr 2-Year Rainfall=3.19"

Printed 9/20/2023

Page 6

**Summary for Pond 1P: Infiltration Basin**

Inflow Area = 0.203 ac, 77.65% Impervious, Inflow Depth > 2.16" for 2-Year event  
 Inflow = 0.53 cfs @ 12.07 hrs, Volume= 0.036 af  
 Outflow = 0.02 cfs @ 14.72 hrs, Volume= 0.012 af, Atten= 95%, Lag= 158.6 min  
 Discarded = 0.01 cfs @ 9.13 hrs, Volume= 0.008 af  
 Primary = 0.02 cfs @ 14.72 hrs, Volume= 0.004 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
 Peak Elev= 81.36' @ 14.72 hrs Surf.Area= 506 sf Storage= 1,084 cf

Plug-Flow detention time= 295.7 min calculated for 0.012 af (32% of inflow)  
 Center-of-Mass det. time= 164.4 min ( 969.9 - 805.6 )

Volume	Invert	Avail.Storage	Storage Description
#1A	76.70'	487 cf	<b>15.75'W x 32.10'L x 3.50'H Field A</b> 1,769 cf Overall - 551 cf Embedded = 1,218 cf x 40.0% Voids
#2A	77.20'	551 cf	<b>ADS StormTech SC-740 +Cap x 12 Inside #1</b> Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 12 Chambers in 3 Rows
#3	81.20'	1,388 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc) -Impervious
		2,426 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.20	1	0	0
81.50	1,000	150	150
82.00	3,950	1,238	1,388

Device	Routing	Invert	Outlet Devices
#1	Discarded	76.70'	<b>0.520 in/hr Exfiltration over Surface area</b>
#2	Primary	81.35'	<b>3.0' long (Profile 14) Broad-Crested Rectangular Weir</b> Head (feet) 1.97 2.46 2.95 3.94 4.92 Coef. (English) 3.37 3.37 3.37 3.37 3.37

**Discarded OutFlow** Max=0.01 cfs @ 9.13 hrs HW=76.75' (Free Discharge)  
 ↳1=Exfiltration (Exfiltration Controls 0.01 cfs)

**Primary OutFlow** Max=0.02 cfs @ 14.72 hrs HW=81.36' (Free Discharge)  
 ↳2=Broad-Crested Rectangular Weir (Weir Controls 0.02 cfs @ 0.41 fps)

**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff  
Type III 24-hr 2-Year Rainfall=3.19"

Printed 9/20/2023

Page 7

**Pond 1P: Infiltration Basin - Chamber Wizard Field A**

**Chamber Model = ADS\_StormTech SC-740 +Cap (ADS StormTech® SC-740 with cap length)**

Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf

Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

51.0" Wide + 6.0" Spacing = 57.0" C-C Row Spacing

4 Chambers/Row x 7.12' Long +0.81' Cap Length x 2 = 30.10' Row Length +12.0" End Stone x 2 = 32.10' Base Length

3 Rows x 51.0" Wide + 6.0" Spacing x 2 + 12.0" Side Stone x 2 = 15.75' Base Width

6.0" Stone Base + 30.0" Chamber Height + 6.0" Stone Cover = 3.50' Field Height

12 Chambers x 45.9 cf = 551.3 cf Chamber Storage

1,769.3 cf Field - 551.3 cf Chambers = 1,218.0 cf Stone x 40.0% Voids = 487.2 cf Stone Storage

Chamber Storage + Stone Storage = 1,038.5 cf = 0.024 af



Overall Storage Efficiency = 58.7%

Overall System Size = 32.10' x 15.75' x 3.50'

12 Chambers

65.5 cy Field


45.1 cy Stone





### Pond 1P: Infiltration Basin

Hydrograph



# 2023-09-19\_POST-DRAINAGE\_MASTER

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff

Type III 24-hr 10-Year Rainfall=4.92"

Printed 9/20/2023

Page 9

## Summary for Subcatchment P1A: To South Abutter

Runoff = 0.03 cfs @ 12.08 hrs, Volume= 0.002 af, Depth> 1.32"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 10-Year Rainfall=4.92"

Area (sf)	CN	Description
785	61	>75% Grass cover, Good, HSG B
785		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

## Subcatchment P1A: To South Abutter

Hydrograph



**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff  
 Type III 24-hr 10-Year Rainfall=4.92"

Printed 9/20/2023

Page 10

**Summary for Subcatchment P1B: To Catch Basin**


Runoff = 0.90 cfs @ 12.07 hrs, Volume= 0.064 af, Depth> 3.80"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 10-Year Rainfall=4.92"

	Area (sf)	CN	Description
*	6,860	98	Impervious, HSG A
	1,975	61	>75% Grass cover, Good, HSG B
	8,835	90	Weighted Average
	1,975		22.35% Pervious Area
	6,860		77.65% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P1B: To Catch Basin**



**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff  
Type III 24-hr 10-Year Rainfall=4.92"

Printed 9/20/2023

Page 11

**Summary for Subcatchment P2: To Warner Ave**

Runoff = 0.27 cfs @ 12.07 hrs, Volume= 0.019 af, Depth> 3.39"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 10-Year Rainfall=4.92"

Area (sf)	CN	Description
1,975	98	Unconnected pavement, HSG A
905	61	>75% Grass cover, Good, HSG B
2,880	86	Weighted Average
905		31.42% Pervious Area
1,975		68.58% Impervious Area
1,975		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P2: To Warner Ave**

Hydrograph




### Summary for Reach DP1: Design Point 1

Inflow Area = 0.221 ac, 71.31% Impervious, Inflow Depth > 1.77" for 10-Year event  
Inflow = 0.47 cfs @ 12.20 hrs, Volume= 0.032 af  
Outflow = 0.47 cfs @ 12.20 hrs, Volume= 0.032 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

### Reach DP1: Design Point 1

Hydrograph



**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff  
Type III 24-hr 10-Year Rainfall=4.92"

Printed 9/20/2023

Page 13

**Summary for Pond 1P: Infiltration Basin**

Inflow Area = 0.203 ac, 77.65% Impervious, Inflow Depth > 3.80" for 10-Year event  
 Inflow = 0.90 cfs @ 12.07 hrs, Volume= 0.064 af  
 Outflow = 0.46 cfs @ 12.20 hrs, Volume= 0.039 af, Atten= 49%, Lag= 7.5 min  
 Discarded = 0.01 cfs @ 7.43 hrs, Volume= 0.009 af  
 Primary = 0.45 cfs @ 12.20 hrs, Volume= 0.031 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
 Peak Elev= 81.48' @ 12.20 hrs Surf.Area= 506 sf Storage= 1,166 cf

Plug-Flow detention time= 171.4 min calculated for 0.039 af (61% of inflow)  
 Center-of-Mass det. time= 70.1 min ( 860.0 - 789.8 )

Volume	Invert	Avail.Storage	Storage Description
#1A	76.70'	487 cf	<b>15.75'W x 32.10'L x 3.50'H Field A</b> 1,769 cf Overall - 551 cf Embedded = 1,218 cf x 40.0% Voids
#2A	77.20'	551 cf	<b>ADS StormTech SC-740 +Cap x 12 Inside #1</b> Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 12 Chambers in 3 Rows
#3	81.20'	1,388 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc) -Impervious
		2,426 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.20	1	0	0
81.50	1,000	150	150
82.00	3,950	1,238	1,388

Device	Routing	Invert	Outlet Devices
#1	Discarded	76.70'	<b>0.520 in/hr Exfiltration over Surface area</b>
#2	Primary	81.35'	<b>3.0' long (Profile 14) Broad-Crested Rectangular Weir</b> Head (feet) 1.97 2.46 2.95 3.94 4.92 Coef. (English) 3.37 3.37 3.37 3.37 3.37

**Discarded OutFlow** Max=0.01 cfs @ 7.43 hrs HW=76.75' (Free Discharge)  
 ↳1=Exfiltration (Exfiltration Controls 0.01 cfs)

**Primary OutFlow** Max=0.45 cfs @ 12.20 hrs HW=81.48' (Free Discharge)  
 ↳2=Broad-Crested Rectangular Weir (Weir Controls 0.45 cfs @ 1.20 fps)

**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff

Type III 24-hr 10-Year Rainfall=4.92"

Printed 9/20/2023

Page 14

**Pond 1P: Infiltration Basin - Chamber Wizard Field A**

**Chamber Model = ADS\_StormTech SC-740 +Cap (ADS StormTech® SC-740 with cap length)**

Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf

Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

51.0" Wide + 6.0" Spacing = 57.0" C-C Row Spacing

4 Chambers/Row x 7.12' Long +0.81' Cap Length x 2 = 30.10' Row Length +12.0" End Stone x 2 = 32.10' Base Length

3 Rows x 51.0" Wide + 6.0" Spacing x 2 + 12.0" Side Stone x 2 = 15.75' Base Width

6.0" Stone Base + 30.0" Chamber Height + 6.0" Stone Cover = 3.50' Field Height

12 Chambers x 45.9 cf = 551.3 cf Chamber Storage

1,769.3 cf Field - 551.3 cf Chambers = 1,218.0 cf Stone x 40.0% Voids = 487.2 cf Stone Storage

Chamber Storage + Stone Storage = 1,038.5 cf = 0.024 af



Overall Storage Efficiency = 58.7%

Overall System Size = 32.10' x 15.75' x 3.50'

12 Chambers


65.5 cy Field

45.1 cy Stone



### Pond 1P: Infiltration Basin

Hydrograph





# 2023-09-19\_POST-DRAINAGE\_MASTER

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff

Type III 24-hr 25-Year Rainfall=6.01"

Printed 9/20/2023

Page 16

## Summary for Subcatchment P1A: To South Abutter

Runoff = 0.04 cfs @ 12.08 hrs, Volume= 0.003 af, Depth> 2.01"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 25-Year Rainfall=6.01"

Area (sf)	CN	Description
785	61	>75% Grass cover, Good, HSG B
785		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

## Subcatchment P1A: To South Abutter

Hydrograph



**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff  
 Type III 24-hr 25-Year Rainfall=6.01"

Printed 9/20/2023

Page 17

**Summary for Subcatchment P1B: To Catch Basin**


Runoff = 1.14 cfs @ 12.07 hrs, Volume= 0.082 af, Depth> 4.85"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 25-Year Rainfall=6.01"

	Area (sf)	CN	Description
*	6,860	98	Impervious, HSG A
	1,975	61	>75% Grass cover, Good, HSG B
	8,835	90	Weighted Average
	1,975		22.35% Pervious Area
	6,860		77.65% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P1B: To Catch Basin**



**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff  
 Type III 24-hr 25-Year Rainfall=6.01"

Printed 9/20/2023

Page 18

**Summary for Subcatchment P2: To Warner Ave**

Runoff = 0.35 cfs @ 12.07 hrs, Volume= 0.024 af, Depth> 4.42"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 25-Year Rainfall=6.01"

Area (sf)	CN	Description
1,975	98	Unconnected pavement, HSG A
905	61	>75% Grass cover, Good, HSG B
2,880	86	Weighted Average
905		31.42% Pervious Area
1,975		68.58% Impervious Area
1,975		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P2: To Warner Ave**

Hydrograph




### Summary for Reach DP1: Design Point 1

Inflow Area = 0.221 ac, 71.31% Impervious, Inflow Depth > 2.77" for 25-Year event  
Inflow = 0.96 cfs @ 12.12 hrs, Volume= 0.051 af  
Outflow = 0.96 cfs @ 12.12 hrs, Volume= 0.051 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

### Reach DP1: Design Point 1

Hydrograph



**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff  
Type III 24-hr 25-Year Rainfall=6.01"

Printed 9/20/2023

Page 20

**Summary for Pond 1P: Infiltration Basin**

Inflow Area = 0.203 ac, 77.65% Impervious, Inflow Depth > 4.85" for 25-Year event  
 Inflow = 1.14 cfs @ 12.07 hrs, Volume= 0.082 af  
 Outflow = 0.93 cfs @ 12.12 hrs, Volume= 0.057 af, Atten= 18%, Lag= 3.2 min  
 Discarded = 0.01 cfs @ 6.58 hrs, Volume= 0.009 af  
 Primary = 0.93 cfs @ 12.12 hrs, Volume= 0.048 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
 Peak Elev= 81.55' @ 12.12 hrs Surf.Area= 506 sf Storage= 1,249 cf

Plug-Flow detention time= 148.0 min calculated for 0.057 af (70% of inflow)  
 Center-of-Mass det. time= 56.2 min ( 839.5 - 783.2 )

Volume	Invert	Avail.Storage	Storage Description
#1A	76.70'	487 cf	<b>15.75'W x 32.10'L x 3.50'H Field A</b> 1,769 cf Overall - 551 cf Embedded = 1,218 cf x 40.0% Voids
#2A	77.20'	551 cf	<b>ADS StormTech SC-740 +Cap x 12 Inside #1</b> Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 12 Chambers in 3 Rows
#3	81.20'	1,388 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc) -Impervious
		2,426 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.20	1	0	0
81.50	1,000	150	150
82.00	3,950	1,238	1,388

Device	Routing	Invert	Outlet Devices
#1	Discarded	76.70'	<b>0.520 in/hr Exfiltration over Surface area</b>
#2	Primary	81.35'	<b>3.0' long (Profile 14) Broad-Crested Rectangular Weir</b> Head (feet) 1.97 2.46 2.95 3.94 4.92 Coef. (English) 3.37 3.37 3.37 3.37 3.37

**Discarded OutFlow** Max=0.01 cfs @ 6.58 hrs HW=76.75' (Free Discharge)  
 ↳1=Exfiltration (Exfiltration Controls 0.01 cfs)

**Primary OutFlow** Max=0.92 cfs @ 12.12 hrs HW=81.55' (Free Discharge)  
 ↳2=Broad-Crested Rectangular Weir (Weir Controls 0.92 cfs @ 1.51 fps)

**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff

Type III 24-hr 25-Year Rainfall=6.01"

Printed 9/20/2023

Page 21

**Pond 1P: Infiltration Basin - Chamber Wizard Field A**

**Chamber Model = ADS\_StormTech SC-740 +Cap (ADS StormTech® SC-740 with cap length)**

Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf

Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

51.0" Wide + 6.0" Spacing = 57.0" C-C Row Spacing

4 Chambers/Row x 7.12' Long +0.81' Cap Length x 2 = 30.10' Row Length +12.0" End Stone x 2 = 32.10' Base Length

3 Rows x 51.0" Wide + 6.0" Spacing x 2 + 12.0" Side Stone x 2 = 15.75' Base Width

6.0" Stone Base + 30.0" Chamber Height + 6.0" Stone Cover = 3.50' Field Height

12 Chambers x 45.9 cf = 551.3 cf Chamber Storage

1,769.3 cf Field - 551.3 cf Chambers = 1,218.0 cf Stone x 40.0% Voids = 487.2 cf Stone Storage

Chamber Storage + Stone Storage = 1,038.5 cf = 0.024 af



Overall Storage Efficiency = 58.7%

Overall System Size = 32.10' x 15.75' x 3.50'

12 Chambers


65.5 cy Field

45.1 cy Stone



### Pond 1P: Infiltration Basin

Hydrograph



# 2023-09-19\_POST-DRAINAGE\_MASTER

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff

Type III 24-hr 100-Year Rainfall=7.68"

Printed 9/20/2023

Page 23

## Summary for Subcatchment P1A: To South Abutter

Runoff = 0.07 cfs @ 12.08 hrs, Volume= 0.005 af, Depth> 3.20"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 100-Year Rainfall=7.68"

Area (sf)	CN	Description
785	61	>75% Grass cover, Good, HSG B
785		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

## Subcatchment P1A: To South Abutter

Hydrograph





**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff  
Type III 24-hr 100-Year Rainfall=7.68"

Printed 9/20/2023

Page 24

**Summary for Subcatchment P1B: To Catch Basin**


Runoff = 1.50 cfs @ 12.07 hrs, Volume= 0.110 af, Depth> 6.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 100-Year Rainfall=7.68"

	Area (sf)	CN	Description
*	6,860	98	Impervious, HSG A
	1,975	61	>75% Grass cover, Good, HSG B
	8,835	90	Weighted Average
	1,975		22.35% Pervious Area
	6,860		77.65% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P1B: To Catch Basin**



**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff  
Type III 24-hr 100-Year Rainfall=7.68"

Printed 9/20/2023

Page 25

**Summary for Subcatchment P2: To Warner Ave**

Runoff = 0.47 cfs @ 12.07 hrs, Volume= 0.033 af, Depth> 6.02"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
Type III 24-hr 100-Year Rainfall=7.68"

Area (sf)	CN	Description
1,975	98	Unconnected pavement, HSG A
905	61	>75% Grass cover, Good, HSG B
2,880	86	Weighted Average
905		31.42% Pervious Area
1,975		68.58% Impervious Area
1,975		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P2: To Warner Ave**

Hydrograph




### Summary for Reach DP1: Design Point 1

Inflow Area = 0.221 ac, 71.31% Impervious, Inflow Depth > 4.33" for 100-Year event  
Inflow = 1.36 cfs @ 12.11 hrs, Volume= 0.080 af  
Outflow = 1.36 cfs @ 12.11 hrs, Volume= 0.080 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

### Reach DP1: Design Point 1

Hydrograph



**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff  
Type III 24-hr 100-Year Rainfall=7.68"

Printed 9/20/2023

Page 27

**Summary for Pond 1P: Infiltration Basin**

Inflow Area = 0.203 ac, 77.65% Impervious, Inflow Depth > 6.49" for 100-Year event  
 Inflow = 1.50 cfs @ 12.07 hrs, Volume= 0.110 af  
 Outflow = 1.31 cfs @ 12.11 hrs, Volume= 0.085 af, Atten= 13%, Lag= 2.5 min  
 Discarded = 0.01 cfs @ 5.36 hrs, Volume= 0.010 af  
 Primary = 1.30 cfs @ 12.11 hrs, Volume= 0.075 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs  
 Peak Elev= 81.60' @ 12.11 hrs Surf.Area= 506 sf Storage= 1,325 cf

Plug-Flow detention time= 128.0 min calculated for 0.085 af (77% of inflow)  
 Center-of-Mass det. time= 47.9 min ( 823.6 - 775.7 )

Volume	Invert	Avail.Storage	Storage Description
#1A	76.70'	487 cf	<b>15.75'W x 32.10'L x 3.50'H Field A</b> 1,769 cf Overall - 551 cf Embedded = 1,218 cf x 40.0% Voids
#2A	77.20'	551 cf	<b>ADS StormTech SC-740 +Cap x 12 Inside #1</b> Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap 12 Chambers in 3 Rows
#3	81.20'	1,388 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc) -Impervious
		2,426 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.20	1	0	0
81.50	1,000	150	150
82.00	3,950	1,238	1,388

Device	Routing	Invert	Outlet Devices
#1	Discarded	76.70'	<b>0.520 in/hr Exfiltration over Surface area</b>
#2	Primary	81.35'	<b>3.0' long (Profile 14) Broad-Crested Rectangular Weir</b> Head (feet) 1.97 2.46 2.95 3.94 4.92 Coef. (English) 3.37 3.37 3.37 3.37 3.37

**Discarded OutFlow** Max=0.01 cfs @ 5.36 hrs HW=76.75' (Free Discharge)  
 ↳1=Exfiltration (Exfiltration Controls 0.01 cfs)

**Primary OutFlow** Max=1.29 cfs @ 12.11 hrs HW=81.60' (Free Discharge)  
 ↳2=Broad-Crested Rectangular Weir (Weir Controls 1.29 cfs @ 1.70 fps)

**2023-09-19\_POST-DRAINAGE\_MASTER**

Prepared by {enter your company name here}

HydroCAD® 10.10-3a s/n 11112 © 2020 HydroCAD Software Solutions LLC

Post Construction Runoff

Type III 24-hr 100-Year Rainfall=7.68"

Printed 9/20/2023

Page 28

**Pond 1P: Infiltration Basin - Chamber Wizard Field A**

**Chamber Model = ADS\_StormTech SC-740 +Cap (ADS StormTech® SC-740 with cap length)**

Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf

Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

51.0" Wide + 6.0" Spacing = 57.0" C-C Row Spacing

4 Chambers/Row x 7.12' Long +0.81' Cap Length x 2 = 30.10' Row Length +12.0" End Stone x 2 = 32.10' Base Length

3 Rows x 51.0" Wide + 6.0" Spacing x 2 + 12.0" Side Stone x 2 = 15.75' Base Width

6.0" Stone Base + 30.0" Chamber Height + 6.0" Stone Cover = 3.50' Field Height

12 Chambers x 45.9 cf = 551.3 cf Chamber Storage

1,769.3 cf Field - 551.3 cf Chambers = 1,218.0 cf Stone x 40.0% Voids = 487.2 cf Stone Storage

Chamber Storage + Stone Storage = 1,038.5 cf = 0.024 af



Overall Storage Efficiency = 58.7%

Overall System Size = 32.10' x 15.75' x 3.50'

12 Chambers


65.5 cy Field

45.1 cy Stone



### Pond 1P: Infiltration Basin

Hydrograph



### **Standard 3 – Groundwater Recharge**



*Project:* Multi-Family Dwelling, High Rise  
*Address:* 214 Hamilton Street, Worcester MA  
*Calculated By:* Giovanni G. Fodera, P.E.  
*Date:* 9/20/2023

**Standard 3 in the Massachusetts Stormwater Handbook, completed in accordance with 310 CMR 10.00 and 314 CMR 9.00**

**RECHARGE VOLUME CALCULATIONS, VOLUME**

The intent of this standard is to ensure that the infiltration volume of precipitation into the ground under post-development conditions is at least as much as the infiltration volume under pre-development conditions. Standard 3 requires the restoration of recharge, using infiltration measures and careful site design. Through judicious use of low impact development techniques and other approaches that minimize impervious surfaces and mimic natural conditions, new developments can approximate pre-development recharge for most storms.

**Soil Evaluation:** Soil test were completed by a MassDEP approved soil evaluator on August 31, 2023 by observation holes and determined the soils to be Sandy Loam. Sandy Loam is categorized as Hydrologic Soil Group B (HSG-B).

Hydrologic Group Volume to Recharge (x Total Impervious Area)			
Hydrologic Soil Group	Soil Texture	Target Depth Factor (F)	
A	Sand	0.60	inches
B	Loam	0.35	inches
C	Silty Loam	0.25	inches
D	Clay	0.10	inches

Impervious Area Analysis:	Pre-Development	Post-Development	Δ Impervious Area
	Impervious Area	Impervious Area	
Total	6,205	8,835	<b>2,630</b>

Required Recharge Volume:	Added Impervious Area (sf)	Target Depth (in)	Volume Required (cf)*
		2,630	0.35

Required minimum 65% of site impervious directed to infiltration systems = 5,743 sf  
 Amount of site impervious directed to infiltration systems = 6,860 sf  
 Capture Area Adjustment (post dev. imp. area/imp. area routed through infiltration systems) = 1.288  
**Therefore, total required recharge volume = 99 cf**

**Recharge Volume Provided:** Infiltration Basin  
 Impervious area contributing to Basin 1: 6,860 sf  
 Total Basin 1 volume (per HydroCAD): **1,038 cf**

<b>Total Volume of Recharge =</b>	<b>1,038</b>	<b>&gt;</b>	<b>99</b>	<b>(standard is met)</b>
-----------------------------------	--------------	-------------	-----------	--------------------------



Standard 3 in the Massachusetts Stormwater Handbook, completed in accordance with 310 CMR 10.00 and 314 CMR 9.00

## RECHARGE VOLUME CALCULATIONS, DRAWDOWN TIME

The intent of this standard is to ensure that the infiltration volume of precipitation into the ground under post-development conditions is at least as much as the infiltration volume under pre-development conditions. Standard 3 requires the restoration of recharge, using infiltration measures and careful site design. Through judicious use of low impact development techniques and other approaches that minimize impervious surfaces and mimic natural conditions, new developments can approximate pre-development recharge for most storms. The intent of this calculation is to size an infiltration system that will approximate the annual recharge from the existing conditions.

**Soil Evaluation:** Soil test were completed by a MassDEP approved soil evaluator on August 31, 2023 by observation holes and determined the soils to be Sandy Loam. Sandy Loam is categorized as Hydrologic Soil Group B (HSG-B).

Rawl's Rates		
Texture Class	NRCS HSG	K
Sand	A	8.27
Loamy Sand	A	2.41
Sandy Loam	B	1.02
Loam	B	0.52
Silt Loam	C	0.27
Sandy Clay Loam	C	0.17
Clay Loam	D	0.09
Silty Clay Loam	D	0.06
Sandy Clay	D	0.05
Silty Clay	D	0.04
Clay Loam	D	0.02

### Required Drawdown

**Time:** Drawdown time calculated below must meet a minimum of 72 hours to conform to the MA Stormwater Handbook.

$$Time_{drawdown} = \frac{R_v}{(K)(Bottom\ Area)}$$

R<sub>v</sub> = Storage Volume

K = Saturated Hydraulic Conductivity for the static method (Rawls Rate)

Bottom Area = Bottom Area of Recharge Structure

### Infiltration Basin

R<sub>v</sub> (cu-ft) = 1,038

K = 0.52

Bottom Area (sq-ft) = 505

<b>Drawdown Time (hrs) = 3.95</b>	<b>(Conforms to Standard 3)</b>
-----------------------------------	---------------------------------

## **Standard 4 – Water Quality**



*Project:* Multi-Family Dwelling, High Rise  
*Address:* 214 Hamilton Street, Worcester MA  
*Calculated By:* Giovanni G. Fodera, P.E.  
*Date:* 9/20/2023

**Standard 4 in the Massachusetts Stormwater Handbook, completed in accordance with 310 CMR 10.00 and 314 CMR 9.00**

**WATER QUALITY CALCULATIONS, WQ VOLUME**

Runoff from impervious surfaces flow overland and gather solids as the stormwater is directed into conveyance systems, and can have adverse effects to water pollution. Standard 4 was implemented for stormwater management systems to be designed to remove 80% of the average annual post-development load of Total Suspended Solids (TSS). Runoff volume requiring appropriate TSS treatment is known as the required water quality volume.

**Pavement Area Analysis:**

	Pre-Development Impervious Area	Post-Development Impervious Area	Δ Impervious Area
Total Pavement	6,205	8,835	<b>2,630</b>

**Land Type:** 1" of runoff multiplied by post-development impervious area for sites located in LUHPPL, rapid infiltration rates, Zone II, Interim Wellhead Protection Areas, or critical areas.  
 0.5" of runoff multiplied by post-development impervious area for all other land types.

**Design Calculation:** WQ Volume = 0.5" x post-development impervious area  
 (Site is in an area of all other land types)

**Required Water Quality Volume:**

Post-development Impervious Area (sf)	Target Depth (in)	Volume Required (cf)*
2,630	0.5	110

**Total required WQ volume = 110 cf**

**Basin Volume Provided:**

**Infiltration Basin**  
 Total Basin 1 volume (per HydroCAD): **1,038 cf**

<b>Total WQ Volume Recharged =</b>	<b>1,038</b>	<b>&gt;</b>	<b>110</b>	<b>(standard is met)</b>
------------------------------------	--------------	-------------	------------	--------------------------



Project: Multi-Family Dwelling, High Rise  
Address: 214 Hamilton Street, Worcester MA  
Calculated By: Giovanni G. Fodera, P.E.  
Date: 9/20/2023

**Standard 4 in the Massachusetts Stormwater Handbook, completed in accordance with 310 CMR 10.00 and 314 CMR 9.00**

**WATER QUALITY CALCULATIONS, TSS REMOVAL**

Runoff from impervious surfaces flow overland and gather solids as the stormwater is directed into conveyance systems, and can have adverse effects to water pollution. Standard 4 was implemented for stormwater management systems to be designed to remove 80% of the average annual post-development load of Total Suspended Solids (TSS). Runoff volume requiring appropriate TSS treatment is known as the required water quality volume.

<b>Treatment Train:</b>		<b>1. Catch Basin with Deep Sump &amp; Hood</b> <b>2. Isolator Row</b>			
Pretreatment BMP	B	C	D	E	F
	TSS Removal Rate	Starting TSS Load	Amount Removed (BxC)	Remaining Load (C-D)	TSS Removal Rate
<b>Deep Sump and Hooded Catch Basin</b>	<b>0.25</b>	<b>1.00</b>	<b>0.25</b>	<b>0.75</b>	<b>25%</b>
Treatment BMP	B	C	D	E	F
	TSS Removal Rate	Starting TSS Load	Amount Removed (BxC)	Remaining Load (C-D)	TSS Removal Rate
<b>Subsurface Infiltration Structure</b>	<b>0.80</b>	<b>0.75</b>	<b>0.60</b>	<b>0.15</b>	<b>85%</b>
		<b>Pretreatment TSS Removal = 25% (standard is met)</b>			
		<b>Treatment TSS Removal = 85% (standard is met)</b>			
<b>Note: Roof runoff does not require pretreatment</b>					

**APPENDIX C – Operation and Maintenance  
Maintenance Logs**

**OPERATION & MAINTENANCE LOG**

**214 Hamilton Street  
Worcester, MA 01604**

**Inspection Date:** \_\_\_\_\_

**Inspector's Name:** \_\_\_\_\_

<p><u>Catch Basin / Manholes:</u> Inspect at least four times per year and cleaned when the sump is half full of sediment</p>		
<p><u>Subsurface Infiltration and Isolator Row:</u> Inspect through inspection port as detailed in the Long- Term Operation and Maintenance Plan, and/ or as detailed in the StormTech® Isolator Row O&amp;M Manual.</p>		