


LAKE VIEW PLAYGROUND IMPROVEMENTS

125 COBURN AVENUE, WORCESTER, MASSACHUSETTS
CITY OF WORCESTER, DEPARTMENT OF PARKS, RECREATION & CEMETERY
CONSTRUCTION DOCUMENTS - SPRING 2026



ERIC D. BATISTA, CITY MANAGER

ROBERT C. ANTONELLI, JR., COMMISSIONER
DEPARTMENT OF PARKS, RECREATION, AND CEMETERY



INDEX OF DRAWINGS:

- SHEET L-1: EXISTING CONDITIONS
- SHEET L-2: SITE PREPARATION & DEMOLITION PLAN
- SHEET L-3: LAYOUT & MATERIALS PLANS
- SHEET L-4: GRADING PLANS
- SHEET L-5: PLANTING & SODDING PLAN
- SHEETS L-6 - L-11: CONSTRUCTION DETAILS
- SHEET C-1: DRAINAGE, EROSION CONTROL, & WATER SERVICE PLAN
- SHEET C-2: CIVIL DETAILS
- SHEET C-3: CIVIL DETAILS & NOTES
- SHEET IR-1: IRRIGATION PLAN
- SHEET IR-2: IRRIGATION DETAILS
- SHEET E-1: ELECTRICAL SITE PLAN
- SHEET E-2: SECURITY SYSTEM CONDUIT PLAN
- SHEETS E-3 - E-11: ELECTRICAL DETAILS

PLANS PREPARED BY:

LANDSCAPE ARCHITECT:



earthdesign
LANDSCAPE ARCHITECTURE

280 BEVERLY ROAD
WORCESTER, MA 01605
508-852-2644 • www.edlandarch.com

CIVIL ENGINEER:

**QUINN
ENGINEERING, INC.**
P.O. Box 107
Paxton, Massachusetts 01612
(508)753-7999 Fax:(508)795-0939

ELECTRICAL ENGINEER:



IRRIGATION DESIGNER:





LEGEND:

- HYDRANT
- ◎ WATER / GAS GATE
- Ⓜ DRAIN MANHOLE
- Ⓜ SEWER MANHOLE
- METAL POST
- STONE BOUND
- ▣ CATCH BASIN
- ◆ BENCHMARK
- ⊕ RAILROAD SPIKE FOUND
- UTILITY POLE
- TREE
- B-1 SOIL BORING LOCATIONS - REFER TO SPECIFICATIONS FOR CORRESPONDING BORING LOGS BY SOIL X CORP.
- B-3
- B-2
- B-4

NOTES:

- 1) EXISTING CONDITIONS INFORMATION WAS OBTAINED FROM A SURVEY TITLED "PLAN SHOWING EXISTING CONDITIONS SURVEYED FOR EARTH DESIGN LANDSCAPE ARCHITECTURE, LLC, LAKE VIEW PARK, WORCESTER, MASSACHUSETTS" AND DATED DECEMBER 6, 2022, BY JARVIS LAND SURVEY, INC., SHREWSBURY, MASSACHUSETTS. JARVIS LAND SURVEY LATER REVISED THIS SURVEY TO INCLUDE CONTOURS AT 1' INTERVALS INSTEAD OF 2'.
- 2) ALL EXISTING UTILITY LOCATIONS ARE APPROXIMATE. THE CONTRACTOR SHALL NOTIFY "DIG-SAFE" AT 1-888-344-7233 AT LEAST 72 HOURS BEFORE EXCAVATING ON SITE.
- 4) SOIL BORINGS SHOWN ON THIS SHEET CORRESPOND TO BORING LOGS BY SOIL X CORP INCLUDED WITH THE SPECIFICATIONS. THESE BORINGS ARE FOR THE PURPOSE OF PROVIDING INFORMATION ON PHYSICAL SOIL CHARACTERISTICS ONLY, AND ARE NOT TO BE CONFUSED WITH SEPARATE BORINGS & SAMPLES TAKEN & DESCRIBED IN REPORT BY BETA GROUP REGARDING SOIL CONTAMINANTS.

PROJECT: LAKE VIEW PLAYGROUND

CLIENT:
CITY OF
WORCESTER



DATE: 11-22-24



SCALE: 1" = 20'

EXISTING CONDITIONS

SHEET 1 - 1




PROJECT:
LAKE VIEW
PLAYGROUND

CLIENT:
CITY OF
WORCESTER


DATE: 11-22-24

REVISIONS:

NO.	DATE	DESCRIPTION




**SITE PREPARATION
& DEMOLITION PLAN**
SHEET L-2




LAYOUT & MATERIALS PLAN - TOTAL SITE

SCALE: 1" = 20'




LAYOUT PLAN - PLAY EQUIPMENT & SURFACING PATTERN

SCALE: 1" = 10'




LAYOUT & MATERIALS PLAN - CONCRETE WALKWAY AREAS & AMENITIES

SCALE: 1" = 10'




LAYOUT PLAN - PLAY STRUCTURE SAFETY ZONES

SCALE: 1" = 20'




GENERAL NOTES:

- 1) POINT OF BEGINNING FOR LAYOUT IS SOUTHEAST PROPERTY CORNER.
- 2) THE CONTRACTOR SHALL CONTACT OWNER'S REPRESENTATIVE TO INSPECT ALL LAYOUT STAKING PRIOR TO CONSTRUCTION.
- 3) THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS ON THE GROUND AND REPORT ANY DISCREPANCIES IMMEDIATELY TO THE OWNER'S REPRESENTATIVE.
- 4) THE CONTRACTOR SHALL AVOID ROUTING UTILITIES BENEATH FURNISHINGS AND EQUIPMENT THAT INCLUDE FOOTINGS.
- 5) SEE INDIVIDUAL PLAN VIEWS FOR ADDITIONAL NOTES.




LEGEND:


<u>PROPOSED:</u>	
	DETAIL NUMBER SHEET NUMBER
	P.C. CONCRETE SURFACE (ON LAYOUT & MATERIALS PLAN FOR TOTAL SITE)
	BITUMINOUS SURFACE (BEYOND COURT - ON LAYOUT & MATERIALS PLAN FOR TOTAL SITE)
	4" THICK CONCRETE (ON L&M PLAN FOR CONCRETE AREAS & AMENITIES)
	6" THICK CONCRETE (ON L&M PLAN FOR CONCRETE AREAS & AMENITIES)
	ELECTRICAL CABINET PAD (ON L&M PLAN FOR CONCRETE AREAS & AMENITIES - FOR THICKNESS SEE DETAIL D-L6)
R	RADIUS
TYP.	TYPICAL
EXP. JT.	EXPANSION JOINT
	FENCE WITH MOW STRIP
	FENCE WITHOUT MOW STRIP
SL 	SPORTS LIGHT POST
PL 	PATHWAY LIGHT POST
UTILITY POLE (IN RIGHT-OF-WAY)	

LAYOUT AND MATERIALS PLANS

SHEET 1 3



GRADING PLAN - TOTAL SITE



GRADING PLAN - PLAYGROUND HILLS

SCALE: 1" = 10'

PROJECT: LAKE VIEW PLAYGROUND IMPROVEMENTS

CLIENT:
CITY OF WORCESTER

DATE: 11-22-24

VISIONS:

N

SCALE: VARIES

GRADING PLANS

SHEET L-4


LEGEND:

EXISTING:

<u>PROPOSED:</u>	
(H L6)	DETAIL NUMBER SHEET NUMBER
TYP.	TYPICAL
HP	HIGH POINT
LP	LOW POINT
X 390.69	SPOT GRADE
— (391) —	CONTOUR
— — ← — —	SWALE (H L6)
	HYDRANT
	WATER / GAS GATE
	DRAIN MANHOLE
	SEWER MANHOLE
	METAL POST
	STONE BOUND
●	CATCH BASIN / DRAIN BASIN (DB)
	BENCHMARK
	RAILROAD SPIKE FOUND
	UTILITY POLE
=====	FENCE WITH MOW STRIP
=====	FENCE WITHOUT MOW STRIP

NOTES:

- 1) THE CONTRACTOR SHALL CONTACT THE OWNER'S REPRESENTATIVE TO CHECK ROUGH AND FINAL GRADES.
- 2) THE CONTRACTOR SHALL VERIFY ALL GRADES ON THE GROUND AND REPORT ANY DISCREPANCIES TO THE OWNER'S REPRESENTATIVE.
- 3) ALL GRADING SHALL BE SMOOTH AND CONTINUOUS WHERE PROPOSED GRADES MEET EXISTING GRADES
- 4) SEE CIVIL PLANS FOR STORM DRAINAGE AND EROSION CONTROL.
- 5) SEE SHEET L-5 FOR LOAMING AND SODDING.
- 6) SEE SHEET L-2 FOR REMOVAL & DISPOSAL OF EXISTING SOIL FROM PROPOSED LAWN AREA. IN ADDITION TO THE LAWN SOIL, ALL EXCESS SOIL SHALL BE REMOVED FROM THE SITE AND DISPOSED IN ACCORDANCE WITH THE EARTHWORK SECTION OF THE SPECIFICATIONS. (ALL EXISTING SOIL CONTAINS ELEVATED ARSENIC CONCENTRATIONS.)



LEGEND:

EXI

PROPOSED:

DETAIL NUMBER
SHEET NUMBER

TYPICAL

TREE

NOTES:


1. PLANT SPECIES, CULTIVARS, SIZES, AND LOCATIONS SHALL NOT BE CHANGED EXCEPT BY PERMISSION OF THE LANDSCAPE ARCHITECT OR OWNER'S REPRESENTATIVE. THE CONTRACTOR SHALL CHECK PLANT MATERIAL FROM NURSERIES BEFORE ACCEPTING PLANTS, TO MAKE SURE THERE ARE NO UNAUTHORIZED SUBSTITUTES. ALTERNATE CULTIVARS OF THE SAME SPECIES SHALL NOT BE SUBSTITUTED WITHOUT LANDSCAPE ARCHITECT'S OR OWNER'S REPRESENTATIVE'S APPROVAL.
2. LOAM & SOD ALL AREAS DISTURBED BY CONSTRUCTION, WHERE OTHER SURFACE MATERIALS ARE NOT SPECIFIED. SEE SPECIFICATIONS FOR REQUIREMENTS.
3. SEE DETAIL SHEETS FOR TREE PLANTING REQUIREMENTS, IN ADDITION TO SPECIFICATIONS.
4. CONTRACTOR SHALL MOW EXISTING LAWN AREAS IN THE PARK THAT ARE OUTSIDE OF THE CONSTRUCTION LIMITS AT LEAST EVERY 2 WEEKS EXCEPT IN WINTER, THROUGHOUT THE CONSTRUCTION PERIOD.

PROJECT: LAKE VIEW PLAYGROUND

CLIENT:
**CITY OF
WORCESTER**


DATE: 11-22-24


PLANT SCHEDULE					
SYMBOL	QTY.	BOTANICAL NAME	COMMON NAME	MINIMUM SIZE AT PLANTING	PLANT SPACING & NOTES
TREES:					
QBI	1	QUERCUS BICOLOR	SWAMP WHITE OAK	3.5" CAL.	B&B. PLANT 34' FROM NEAREST EXISTING TREE



PLANTING AND SODDING PLAN

SHEET 1 - 5





A
L7
VINYL-COATED CHAIN LINK FENCE


NOT TO SCALE

NOTES:


- 1) ALL PORTIONS OF FENCING SHALL BE PVC COATED, BLACK COLOR, AS SPECIFIED.
- 2) INSTALL FENCE FABRIC ON STREET SIDE WHERE FENCING IS NEAR PROPERTY LINES; AND ON OUTSIDE OF BASKETBALL COURT ELSEWHERE.
- 3) WIRE TIES SHALL BE SPACED 12" ALONG RAILS AND LINE POSTS.
- 4) POST FOOTING DIAMETER SHALL BE 12" FOR POSTS LESS THAN 4" DIA.; AND 16" FOR 4" DIA. POSTS.
- 5) FOR FENCES LOWER THAN 6' HEIGHT, NO INTERMEDIATE RAIL IS REQUIRED. FOR FENCES AT LEAST 6' HIGH BUT LESS THAN 8', 1 INTERMEDIATE RAIL IS REQUIRED. FOR FENCES 8' TO 10' HIGH, 2 INTERMEDIATE RAILS ARE REQUIRED.
- 6) ATTACH NEW FENCE TO EXISTING FENCE AT PROPERTY EDGES
- 7) ALSO SEE SPECIFICATIONS.

NOTES:


- 1) MOW STRIPS ARE ONLY INCLUDED BELOW 10' HIGH FENCES ON NORTH AND SOUTH SIDES OF BASKETBALL COURT. (OTHER FENCING IS WITHIN ASPHALT OR CONCRETE SURFACE AREAS.) SEE DETAIL D-L9 FOR LAYOUT OF THESE FENCES / MOW STRIPS.
- 2) ALSO SEE SEPARATE DETAILS FOR CHAIN LINK FENCE AND FOR CONCRETE JOINTS (P.C. CONCRETE PAVEMENT AND EXPANSION JOINT DETAILS).
- 3) SLOPE ACROSS MOW STRIP SHALL BE 1.5%, IN DIRECTION OF SLOPE PROPOSED FOR ADJACENT AREA OF PARK -- SEE GRADING PLAN.
- 4) DO NOT EXTEND REBAR THROUGH EXPANSION JOINTS.



B
L7
MOW STRIP AT FENCE



CROSS SECTION VIEW




C
L7
ELEVATION
SINGLE GATE -- VINYL-COATED CHAIN LINK FENCE

NOT TO SCALE

NOTES:

- 1) SEE VINYL-COATED CHAIN LINK FENCE DETAIL FOR ADDITIONAL REQUIREMENTS
- 2) ALL PORTIONS OF FENCING SHALL BE PVC COATED, BLACK COLOR, AS SPECIFIED.
- 3) SEE PLANS FOR GATE SWING ORIENTATION.



D
L7
ELEVATION
DOUBLE GATE -- VINYL-COATED CHAIN LINK FENCE

NOT TO SCALE

PROJECT:
LAKE VIEW
PLAYGROUND

CLIENT:
CITY OF
WORCESTER

DATE: 11-22-24


REVISIONS:

NO.	DATE	DESCRIPTION


SCALE: NONE

DETAILS


SHEET L-7




A L8 SECTION NOT TO SCALE




D L8 SECTION NOT TO SCALE




B L8 ELEVATION NOT TO SCALE



C L8 ELEVATIONS NOT TO SCALE



E L8 SECTION NOT TO SCALE



F L8 ELEVATIONS NOT TO SCALE

PROJECT:
LAKE VIEW
PLAYGROUND

CLIENT:
CITY OF
WORCESTER

DATE: 11-22-24

REVISIONS:

NO. DATE DESCRIPTION

SCALE: NONE

DETAILS

SHEET L-8



This technical diagram illustrates a cross-section of a fence post installation. The post is labeled 'FENCE POST (TYPICAL)' and is shown in a vertical orientation. A dimension line indicates a distance of '6"' from the base of the post to the 'TOP OF FOOTING BELOW BITUMINOUS LAYERS'. The post is set into a concrete footing, which is labeled 'CONCRETE POST FOOTING (TYP.) - SEE CHAIN LINK FENCING DETAIL'. The surface layers above the post are described as 'EDGE OF BITUMINOUS LAYERS & COURT COLOR (FLUSH WITH ADJACENT SURFACES)'. To the right of the post, a vertical stack of materials is shown: '1-1/2" BITU TOP COUR' (partially cut off) and '2" BITUMIN BINDER CO' (partially cut off). The total height of these layers is indicated as '12"'. The diagram also shows 'ADJACENT SURFACE (P.C. CONCRETE OR ASPHALT -- DEPTHS VARY -- SEE OTHER DETAILS)' adjacent to the post. The base of the post is shown in contact with a lawn area, indicated by a hatched pattern.

A L9 BASKETBALL COURT SURFACING

NOT TO SCALE

SECTION VIEW: MOW STRIP EDGE

Technical drawing of a basketball goal assembly. The drawing shows a vertical post with a horizontal crossbar and a net. A dimension line indicates a width of 6'-0" between the post and the net. A height dimension of 10'-0" is shown from the ground to the top of the post. A callout points to the post with the text: "BASKETBALL GOAL (WITH SQUARE POST) -- SEE SPECS AND LAYOUT DETAIL FOR COURT." Another callout points to the ground surface with the text: "BITUMINOUS COURT SURFACING -- SEE SEPARATE DETAIL". The drawing also shows a cross-section of the ground surface, which is a layer of gravel over a concrete base.

BASKETBALL GOAL

NOT TO SCALE

C ALUMINUM TEAM BENCH

NOT TO SCALE

This architectural diagram provides a detailed layout of a basketball court and its surrounding fence and gates. The court is 50' 0" wide and 94' 0" long, with a total width of 114' 0" from the center of the fence on the east end to the edge of the court surface on the west end. The court features a center circle (R 2'), free throw circles (R 6'), and a key (lane). The backboard (typ.) is positioned at the center of the basket (typ.). The diagram also shows a double gate (D L7) on the north side and a 4' wide single gate (C L7) on the east side. A walkway is located on the north side, and a lawn is on the south side. The court is surrounded by a 4' high chain-link fence, with a mow strip along the north side. The fence is connected to an existing 4' high fence on the east and south sides. Team benches are centered on the half court, and fence posts are typically installed every 10' on the center. The diagram also includes labels for 'PLAYGROUND' and 'LAWN'.

EDGE OF COURT SURFACE (6" OUTSIDE OF CENTER OF FENCE)

10' HIGH CHAIN-LINK FENCE WITH MOW STRIP ALONG THIS SIDE - ALSO SEE LAYOUT PLAN (OF TOTAL SITE) AND SEPARATE DETAILS. (A L7) (B L7)

10' HIGH CHAIN-LINK FENCE (NO MOW STRIP) - SEE LAYOUT & MATERIALS PLAN AND SEPARATE DETAIL. (A L7)

4' HIGH CHAIN-LINK FENCE ALONG THIS SIDE (NO MOW STRIP) - SEE LAYOUT & MATERIALS PLAN AND SEPARATE DETAIL. (A L7)

4' WIDE SINGLE GATE (C L7)

WALKWAY & 4' HIGH FENCE BEYOND COURT - SEE LAYOUT & MATERIALS PLAN

BASKETBALL COURT SURFACING

TEAM BENCH, CENTERED ON HALF COURT

18" FROM BACK OF BENCH TO FENCE

LAKE VIEW STREET

10' HIGH CHAIN-LINK FENCE WITH MOW STRIP ALONG THIS SIDE - ALSO SEE LAYOUT PLAN (OF TOTAL SITE) AND SEPARATE DETAILS. (A L7) (B L7)

4' HIGH FENCE BEYOND COURT CONNECTED TO EXISTING 4' FENCE (SEE LAYOUT & MATERIALS PLAN)

PLAYGROUND

END LINE (TYP.)

GOAL POST (TYP.)

SIDE LINE (TYP.)

FREE THROW CIRCLE (TYP.)

KEY (LANE), TYP.

BASKET (TYP.)

BACKBOARD (TYP.)

3-POINT LINE, (TYP.)

50'- 0"

10'- 0" (TO FENCE)

10'- 0" (TO FENCE)

25'- 0"

CENTER LINE

CENTER CIRCLE

R 2'

R 6'

15'- 0"

4'- 0"

1'- 7"- 0"

8"

3'

12'- 6" (TO FENCE)

50'- 0"

14'- 9"

6'- 0"

6'- 0"

14'- 9"

4'- 3"

7'- 0"

10'- 0" (TO FENCE)

10'- 0"

6"

47'- 0"

114'- 0" (FROM CENTER OF FENCE ON EAST END TO EDGE OF COURT ON WEST END)

EDGE OF COURT SURFACE

LAWN

72'- 6"

(TO CENTERS OF FENCE POSTS)

NOTES

- 1) COURT SHALL HAVE 3 PREMIUM SURFACE COLORS TO BE SELECTED BY OWNER -- SEE SPECS.
- 2) DIMENSIONS SHOWN ARE TYPICAL FOR BOTH ENDS OF COURT.
- 3) DIMENSIONS ARE TO CENTERS OF FENCE POSTS (UNLESS OTHERWISE NOTED) AND TO CENTER OF BASKETBALL GOAL POSTS.
- 4) DIMENSIONS ARE TO INSIDE EDGES OF END LINES & SIDE LINES.
- 5) DIMENSIONS ARE TO OUTSIDE EDGES OF 3 POINT LINE, FREE THROW RADIUS, AND KEY.
- 6) DIMENSIONS ARE TO FRONT OF BACKBOARD.
- 7) ALL LINES AND MARKS ARE 2" WIDE, WHITE COLOR, UNLESS OTHERWISE NOTED.
- 8) SEE SEPARATE DETAILS FOR FENCE, GATES, BENCHES, BASKETBALL GOALS, AND COURT

BASKETBALL COURT LAYOUT


SCALE: 1" = 10'

SCALE: 1" = 100'

SCALE: AS NOTED


DETAILS

SHEET 1 8





A RESILIENT SURFACING
 L10 SECTION NOT TO SCALE

B CURB EDGE AT RESILIENT SURFACING
 L10 SECTION NOT TO SCALE






C RESILIENT SURFACING ON HILLS
 L10 SECTION NOT TO SCALE



NOTES:

- 1) PLAY EQUIPMENT SHOWN INCLUDE GENERAL DEPICTIONS ONLY - SEE MANUFACTURER'S INSTALLATION INSTRUCTIONS FOR ADDITIONAL INFORMATION, INCLUDING POST & FOOTING DETAILS. ALL FOOTINGS SHALL BE AT LEAST 48" DEEP (BELOW FINISHED GRADE).
- 2) SEE 10-SCALE GRAIDING PLAN FOR ELEVATIONS.
- 3) PLAY EQUIPMENT ON HILLS SHALL BE SUPPLIED BY PLAYWORLD (PLAYWORLD.COM, LOCAL REP. PHONE # 508-688-7007)



D PLAY EQUIPMENT ON HILLS
 L10 ELEVATIONS NOT TO SCALE

PROJECT:
LAKE VIEW
PLAYGROUND

CLIENT:
CITY OF
WORCESTER

DATE: 11-22-24


REVISIONS:

NO.	DATE	DESCRIPTION

SCALE: NONE

DETAILS


SHEET L-10



A COMPOSITE PLAY STRUCTURE

L11 SECTION

NOT TO SCALE



B PAINTED HOPSCOTCH GAMES

L11 SECTION

NOT TO SCALE

NOTES:

1. PAINT COLOR FOR LINES AND NUMBERS SHALL BE BLACK, AND THE SHAPES INSIDE THE LINES SHALL BE PAINTED WITH 4 DIFFERENT COLORS SELECTED BY THE OWNER'S REPRESENTATIVE, IN REPEATING SEQUENTIAL ORDER ACCORDING TO THE NUMBERED SHAPES.
2. LINES SHALL BE 2" WIDE. DIMENSIONS ARE TO CENTERS OF LINES.
3. SEE SPECS FOR ADDITIONAL PAINT REQUIREMENTS.
4. HOPSCOTCH GAME ON RIGHT SHALL BE CENTERED BETWEEN JOINTS & EDGE OF PAVEMENT - SEE 10 SCALE LAYOUT PLAN.
5. HOPSCOTCH GAME ON LEFT SHALL BE CENTERED BETWEEN EDGE OF PAVEMENT AND 2ND JOINT TO SOUTH, AND SEPARATED FROM OTHER GAME AS DIMENSIONED.

PROJECT:
LAKE VIEW
PLAYGROUND

CLIENT:
CITY OF
WORCESTER

DATE: 11-22-24


REVISIONS:

NO.	DATE	DESCRIPTION

SCALE: NONE

DETAILS

SHEET L-11



GENERAL NOTES:

1. ALL REQUIRED PERMITS SHALL BE SECURED PRIOR TO COMMENCING WORK. PRIOR TO COMMENCING ANY WORK ONSITE, CONTRACTOR SHALL NOTIFY THE CITY OF WORCESTER PLANNING AND ENGINEERING DEPARTMENTS, BUILDING DEPARTMENT, CONSERVATION COMMISSION, DEPARTMENT OF PUBLIC WORKS, SCHOOL DEPARTMENT, POLICE AND FIRE DEPARTMENTS.
2. ALL WORK SHALL CONFORM TO THE CITY OF WORCESTER REGULATIONS, ZONING ORDINANCE, CONSERVATION COMMISSION LOCAL ORDINANCE OR OTHER REGULATIONS AS APPLICABLE. ALL REQUIREMENTS OF THE CITY OF WORCESTER ARE HEREBY MADE CONDITIONS OF THIS WORK.
3. CONTRACTOR SHALL CONTROL AIRBORNE DUST WITH USE OF SPRAYED WATER AS REQUIRED TO MINIMIZE IMPACT ON NEIGHBORING PROPERTIES. USE OF CALCIUM CHLORIDE OR OTHER CHEMICALS IS NOT PERMITTED.
4. CONTRACTOR SHALL RETAIN A LICENSED SURVEYOR TO LAY OUT THE SITE CONSTRUCTION, WHO CERTIFY THAT ALL LOCATIONS ARE AS PER PLAN.
5. PROVIDE A 4' DEEP SUMP AT THE PROPOSED NYOPLAST AREA DRAIN.
6. SEVENTY TWO HOURS PRIOR TO COMMENCING ANY EXCAVATION, THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 811. THE CONTRACTOR SHALL COORDINATE INSTALLATION OF NEW UTILITIES WITH THE VICINITY OF EXISTING UTILITIES (UNDERGROUND AND OVERHEAD) WITH THE APPROPRIATE UTILITY.
7. INTERIM AND/OR PERMANENT SOIL STABILIZATION MEASURE SHALL BE INSTITUTED AS SOON AS PRACTICABLE, BUT NO MORE THAN 14 DAYS AFTER CONSTRUCTION ACTIVITY HAS TEMPORARILY OR PERMANENTLY CEASED ON THAT PORTION OF THE SITE.
8. REMOVE ALL TOPSOIL, SUBSOIL, PRIOR TO PLACING ANY FILL ONSITE. WHERE GRAVEL IS CALLED FOR ONSITE, CONTRACTOR MAY UTILIZE ONSITE MATERIALS, IF APPROVED BY OWNER.
9. CONTRACTOR SHALL MAINTAIN COMPLETE RECORDS OF AS-BUILT LOCATIONS OF ALL UNDERGROUND AND ABOVE GROUND FACILITIES. PROVIDE THE OWNER WITH COMPLETE AS-BUILT PLANS UPON COMPLETION OF PROJECT, INCLUDING UTILITIES NOT INDICATED ON THIS PLAN.
10. CONSTRUCTION SEQUENCE:
ALL WORK OF THIS PROJECT SHALL PROCEED ACCORDING TO THE FOLLOWING PROPOSED SEQUENCE:
 - 1.) EROSION CONTROL PROVISIONS IN PLACE
 - 2.) CLEARING/GRUBBING
 - 3.) CONSTRUCTION OF STORMWATER FACILITIES AND THEN SITE DEVELOPMENT CONSTRUCTION.
11. CONTRACTOR SHALL PLACE A MINIMUM OF 6" (COMPACTED DEPTH) OF GOOD QUALITY LOAM AND GRASS SEED IN ALL AREAS NOT SUBJECT TO RESTORATION BY ANY OTHER MEANS.
12. THE CONTRACTOR SHALL BE RESPONSIBLE TO COORDINATE HIS WORK WITH MUNICIPALITY TO LIMIT THE POTENTIAL DISRUPTIONS TO THE GENERAL PUBLIC. SHALL EMPLOY DUE CARE AND CAUTION TO PROTECT THE PUBLIC FROM DANGERS ASSOCIATED WITH THE OPERATION. SHALL INSTALL TEMPORARY FENCES, BARRICADES AND SIGNAGE TO ENSURE THAT NO PERSONS ENTER THE WORK AREA. SHALL COORDINATE POLICE DETAILS AS REQUIRED FOR WORK TO BE CONDUCTED IN THE STREET. SHALL EMPLOY DUE CARE WHEN WORKING AROUND PEDESTRIAN AND VEHICLE TRAFFIC.
13. NO EXCAVATION SHALL TAKE PLACE ONSITE UNTIL ALL SEDIMENTATION CONTROLS (STRAW WATTLES, TEMP BASINS, ETC.) ARE FULLY INSTALLED AS PER PLAN. FOLLOWING COMPLETION OF GRADING IN ANY AREA CONTRACTOR SHALL ACT TO PLACE PERMANENT SURFACE FINISH OR TO STABILIZE SURFACE SOILS AGAINST EROSION. LOAM AND SEED SHALL BE PLACED IMMEDIATELY UPON FINAL GRADING.
14. THE CONTRACTOR SHALL BE RESPONSIBLE TO ENSURE THAT THE PROPOSED CONSTRUCTION ACTIVITIES DO NOT DAMAGE OR UNDERMINE EXISTING SLOPES, BUILDINGS, WALLS, STRUCTURES, ETC. IN THE AREA AROUND THE CONSTRUCTION. REPAIR OF EXISTING SLOPES, BUILDINGS, WALLS, STRUCTURES, ETC. THAT ARE DAMAGED OR UNDERMINED BY THE CONTRACTORS WORK SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
15. EXISTING UTILITY LOCATIONS ARE APPROXIMATE ARE TO BE FIELD VERIFIED. QUINN ENGINEERING, INC. DOES NOT WARRANT THAT ALL EXISTING UTILITIES HAVE BEEN INDICATED. THE CONTRACTOR IS RESPONSIBLE FOR COORDINATING THE EXISTING UTILITY LOCATIONS AND ENSURING THAT THE PROPOSED WORK DOES NOT CONFLICT WITH THE EXISTING UTILITIES NOT SHOWN.
16. SEWERS SHOULD BE LAID AT A MINIMUM OF 10 FEET, HORIZONTALLY, FROM ANY EXISTING OR PROPOSED WATER MAIN. SHOULD LOCAL CONDITIONS PREVENT LATERAL SEPARATION OF 10 FEET TO A WATER MAIN, THE WATER MAIN SHOULD BE LAID IN A SEPARATE TRENCH AND THE ELEVATION OF THE CROWN OF THE SEWER PLACED AT LEAST 18 INCHES BELOW THE INVERT OF THE WATER MAIN. WHENEVER SEWERS MUST CROSS UNDER WATER MAINS, THE SEWER SHOULD BE LAID AT SUCH AN ELEVATION THAT THE CROWN OF THE SEWER IS AT LEAST 18 INCHES BELOW THE INVERT OF THE WATER MAIN. WHEN THE ELEVATION OF THE SEWER CAN NOT BE VARIED TO MEET THIS REQUIREMENT, THE WATER MAIN SHOULD BE RELOCATED TO PROVIDE THIS SEPARATION OR CONSTRUCTED WITH MECHANICAL-JOINT PIPE FOR A DISTANCE OF 10 FEET ON EACH SIDE OF THE SEWER. ONE FULL LENGTH OF WATER MAIN SHOULD BE CENTERED OVER THE SEWER SO THAT BOTH JOINTS WILL BE AS FAR FROM THE SEWER AS POSSIBLE. WHEN IT IS IMPOSSIBLE TO OBTAIN HORIZONTAL OR VERTICAL SEPARATION AS STIPULATED ABOVE, BOTH SEWER AND WATER MAIN SHOULD BE ENCASED IN CONCRETE FOR 10 FEET EITHER SIDE OF THE CROSSING.
17. THE GROUND IMMEDIATELY ADJACENT TO FOUNDATIONS SHALL BE SLOPED AWAY FROM THE BUILDING, IN ACCORDANCE WITH 780 CMR 1813.7, AT A SLOPE OF NOT LESS THAN 1:12 FOR A MINIMUM DISTANCE OF 10 FEET MEASURED PERPENDICULAR TO THE FACE OF THE WALL. OTHER APPROVED ALTERNATE METHODS OF DIVERTING WATER AWAY FROM THE FOUNDATION MAY BE ACCEPTABLE.
18. REINFORCED CONCRETE PIPE:
 - A. SHALL BE CLASS V CONCRETE.
 - B. SHALL CONFORM TO ASTM C76, WALL B.
 - C. JOINT MATERIAL TO BE RUBBER GASKET

CONSTRUCTION PERIOD POLLUTION PREVENTION PLAN NOTES:

1. CONTROLS TO REDUCE POLLUTANTS:
 - A.) THE FOLLOWING IS A BRIEF DESCRIPTION OF EACH BMP IMPLEMENTED TO CONTROL POLLUTANTS IN STORM WATER DISCHARGES.
 - 1.) EROSION CONTROLS: STRAW WATTLES PROVIDE MEASURES OF CONTROLLING EROSION AND SEDIMENTATION AND SHALL BE IMPLEMENTED BY THE CONTRACTOR WHERE NEEDED TO PREVENT SEDIMENT FROM LEAVING THE WORK SITE.
 - 2.) TEMPORARY CONSTRUCTION ENTRANCES OF CRUSHED STONE SHALL BE IMPLEMENTED BY THE CONTRACTOR WHEN NEEDED TO PREVENT SEDIMENT FROM TRACKING OFF-SITE AND INTO EXISTING ROADWAYS.
 - B.) DISTURBED AREAS NOT SUBJECT TO RESTORATION BY OTHER MEANS SHALL BE STABILIZED UPON FINISH GRADING WITH 6" OF LOAM AND GRASS SEED. AREAS SLOPED AT GREATER THAN 3:1 SHALL BE STABILIZED WITH GEOTEXTILE FABRIC.
 - C.) THE FOLLOWING RECORDS SHOULD BE MAINTAINED BY THE OPERATOR AS PART OF THE POLLUTION PREVENTION PLAN.
 1. DATES WHEN MAJOR GRADING ACTIVITIES OCCUR.
 2. DATES WHEN CONSTRUCTION ACTIVITIES TEMPORARILY OR PERMANENTLY CEASE ON A PORTION OF THE SITE.
 3. DATES WHEN STABILIZATION MEASURES ARE INITIATED.
 - D.) STRAW WATTLES, SILT FENCE, STONE CONSTRUCTION ENTRANCES, EARTH DIKES, TEMPORARY DRAINAGE SWALES, INTERCEPTOR DIKES AND SWALES, AND OTHER STRUCTURAL PRACTICES SHALL BE EMPLOYED BY THE SITE CONTRACTOR TO DIRECT STORMWATER RUNOFF FROM DISTURBED AREAS TO AREAS WHERE DISCHARGE IS ACCEPTABLE. THE APPROPRIATE LOCATION AND INSTALLATION TIMING SHALL BE DETERMINED BY THE SITE CONTRACTOR.
 - E.) THE DISCHARGE OF SOLID MATERIALS, INCLUDING BUILDING MATERIALS, TO ANY RESOURCE AREAS IS PROHIBITED.
 - F.) THE CONTRACTOR SHALL MINIMIZE VEHICLE TRACKED SEDIMENT ONTO THE SURROUNDING ROADWAYS. AIRBORNE DUST SHALL BE CONTROLLED WITH WATER.
 - G.) CONSTRUCTION MATERIALS AND CONSTRUCTION WASTE MATERIALS ASSOCIATED WITH THE PROPOSED DEVELOPMENT SHALL BE STORED IN A MANNER THAT MINIMIZES EXPOSURE TO STORMWATER, IE USE OF TARPAULINS, INSIDE STORAGE, ETC. MATERIALS AND WASTE SHALL BE MAINTAINED IN AN ORDERLY MANNER AND SHALL BE COLLECTED IMMEDIATELY UPON SPILLS OR DISPERSION.
 - H.) DURING CONSTRUCTION, POLLUTANTS FROM SOURCES OTHER THAN THE CONSTRUCTION ACTIVITIES ARE NOT EXPECTED.

LONG TERM POLLUTION PREVENTION PLAN MEASURES:

LONG TERM POLLUTION PREVENTION PLAN MEASURES:

1. GOOD HOUSEKEEPING PRACTICES SHALL BE EMPLOYED IN MAINTENANCE OF THE STORMWATER SYSTEM AND ON SITE AREAS. THE MINIMUM HOUSEKEEPING PRACTICES ARE IDENTIFIED IN THE STORMWATER COLLECTION AND TREATMENT SYSTEM OPERATION AND MAINTENANCE PLAN.
2. STORAGE OF MATERIALS AND WASTE PRODUCTS SHALL BE STORED IN A MANNER THAT MINIMIZES EXPOSURE TO STORMWATER, IE USE OF TARPAULINS, INSIDE STORAGE, ETC. MATERIALS AND WASTE SHALL BE MAINTAINED IN AN ORDERLY MANNER AND SHALL BE COLLECTED IMMEDIATELY UPON SPILLS OR DISPERSION.
3. VEHICLE WASHING SHOULD OCCUR IN ACCORDANCE WITH THE "ILLEGITIMATE AND NON STORMWATER DISCHARGES" PORTION OF THE STORMWATER POLLUTION PREVENTION PLAN NOTES.
4. LONG TERM MAINTENANCE OF THE STORMWATER SYSTEM SHALL FOLLOW THE OPERATION AND MAINTENANCE REQUIREMENTS ON THESE PLANS AT A MINIMUM.
5. PARTIES RESPONSIBLE FOR MAINTENANCE OF THE STORMWATER SYSTEM SHOULD BE FAMILIAR WITH "CLEAN UP OF SITES AND SPILLS" INFORMATION AVAILABLE ON THE MA DEP WEB SITE (CURRENTLY AVAILABLE AT <http://www.mass.gov/dep/cleanup/laws/spillmgm.doc>) AND SHOULD BE PREPARED TO ACT ACCORDINGLY IN THE EVENT OF A SPILL.
6. THE MINIMUM PRACTICES EMPLOYED IN INSPECTION AND MAINTENANCE OF THE ON SITE AREAS AND STORMWATER SYSTEM COMPONENTS ARE IDENTIFIED IN THE STORMWATER COLLECTION AND TREATMENT SYSTEM OPERATION AND MAINTENANCE PLAN.
7. THE MASSACHUSETTS BUREAU OF FARM PRODUCTS & PLANT INDUSTRIES FACT SHEET FOR "PROTECTING WATER RESOURCES FROM FERTILIZER" RECOMMENDS THAT:
 - UNUSED FERTILIZER SHOULD BE REMOVED FROM THE SPREADER AND RETURNED TO THE ORIGINAL BAG OR CONTAINER FOR FUTURE USE. STORE UNUSED FERTILIZER IN A DRY PLACE AWAY FROM ANY WATER SOURCE.
 - IF STORED FERTILIZER GETS WET YOU NOT ONLY LOSE NUTRIENT VALUE, THERE IS POTENTIAL FOR NITRATES TO LEACH INTO WATER SOURCES.
8. MANAGEMENT OF HERBICIDES AND PESTICIDES SHOULD BE CONDUCTED IN ACCORDANCE WITH GUIDELINES AVAILABLE ON THE MA DEP WEB SITE (CURRENTLY AVAILABLE AT <http://www.mass.gov/dep/recycle/hazardous/pesticid.htm>)
9. MANAGEMENT OF PET WASTE SHOULD BE CONDUCTED IN ACCORDANCE WITH THE GUIDELINES AVAILABLE ON THE MA DEP WEB SITE (CURRENTLY AVAILABLE AT <http://www.mass.gov/dep/water/resources/petwaste.pdf>)
10. OPERATION AND MAINTENANCE OF ANY ON SITE SEPTIC SYSTEM SHOULD BE CONDUCTED IN ACCORDANCE 310 CMR 15.00.
11. SOLID WASTE SHOULD BE MANAGED IN ACCORDANCE WITH LOCAL, STATE, FEDERAL REGULATIONS AND GUIDELINES.
12. SNOW DISPOSAL SHALL BE CONDUCTED IN ACCORDANCE WITH THE MA DEP GUIDELINE BRPG01-01 (CURRENTLY AVAILABLE AT <http://www.mass.gov/dep/water/laws/snowdisp.htm>)
13. USE OF SALT ON ROADS AND WALKS IS TO BE MINIMIZED. STORAGE OF SNOW SALT AND OTHER DE-ICING MATERIALS SHALL BE IN ACCORDANCE WITH MA DEP POLICY DWSG97-1 (CURRENTLY AVAILABLE AT <http://www.mass.gov/dep/water/laws/saltgui.doc>)
14. THE FOLLOWING PAVEMENT SWEEPING SCHEDULE IS RECOMMENDED WITH SWEEPING SCHEDULED PRIMARILY IN THE SPRING AND FALL:
 - QUARTERLY AVERAGE USING A HIGH EFFICIENCY VACUUM SWEEPER
 - QUARTERLY AVERAGE USING A REGENERATIVE AIR SWEEPER
 - MONTHLY AVERAGE USING A MECHANICAL SWEEPER (ROTARY BROOM)
15. SWEEPINGS SHOULD BE HANDLED IN ACCORDANCE WITH MA DEP POLICY #BRP-94-092.

13. ILLICIT DISCHARGES TO THE STORMWATER SYSTEM ARE PROHIBITED.
14. FOR LAND USES NEAR CRITICAL AREAS OR FROM LAND USED WITH HIGHER POTENTIAL POLLUTANT LOADS THE STORMWATER SYSTEM SHOULD BE PROVIDED WITH A SHUTDOWN DEVICE.
15. PARTIES RESPONSIBLE FOR MAINTENANCE OF THE STORMWATER SYSTEM SHOULD BECOME FAMILIAR WITH THE REQUIREMENTS OF:
 - THE STORMWATER POLLUTION PREVENTION PLAN AND NOTES
 - THE STORMWATER COLLECTION AND TREATMENT SYSTEM OPERATION AND MAINTENANCE PLAN
 - THESE LONG TERM POLLUTION PREVENTION PLAN MEASURES
16. IN THE CASE OF AN EMERGENCY DIAL 911 OR CONTACT:

MASS DEP CENTRAL REGION
8 NEW BOND STREET
WORCESTER, MA 01606
(508) 792-7650

 earthdesign
LANDSCAPE ARCHITECTURE

LANDSCAPE ARCHITECTURE
280 BEVERLY ROAD • WORCESTER, MA 01605
508-852-2644 • info@edlandarch.com

QUINN ENGINEERING, INC.

**P.O. Box 107
Paxton, Massachusetts 01612
(508)753-7999 Fax:(508)795-0939**




PROJECT: LAKE VIEW PLAYGROUND IMPROVEMENTS


CLIENT:
CITY OF WORCESTER

DATE: 11-22-24

REVISIONS:		
NO.	DATE	DESCRIPTION
	12/20/24	CONS COMM COMMENTS



DRAINAGE, EROSION CONTROL, & WATER SERVICE SHEET C-1



SC-740 STORMTECH CHAMBER SPECIFICATIONS

1. CHAMBERS SHALL BE STORMTECH SC-740.
2. CHAMBERS SHALL BE ARCH-SHAPED AND SHALL BE MANUFACTURED FROM VIRGIN, IMPACT-MODIFIED POLYPROPYLENE COPOLYMERS.
3. CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
4. CHAMBER ROWS SHALL PROVIDE CONTINUOUS, UNOBSTRUCTED INTERNAL SPACE WITH NO INTERNAL SUPPORTS THAT WOULD IMPEDE FLOW OR LIMIT ACCESS FOR INSPECTION.
5. THE STRUCTURAL DESIGN OF THE CHAMBERS, THE STRUCTURAL BACKFILL, AND THE INSTALLATION REQUIREMENTS SHALL ENSURE THAT THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET FOR: 1) LONG-DURATION DEAD LOADS AND 2) SHORT-DURATION LIVE LOADS, BASED ON THE AASHTO DESIGN TRUCK WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCE.
6. CHAMBERS SHALL BE DESIGNED, TESTED AND ALLOWABLE LOAD CONFIGURATIONS DETERMINED IN ACCORDANCE WITH ASTM F2787, "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS". LOAD CONFIGURATIONS SHALL INCLUDE: 1) INSTANTANEOUS AASHTO DESIGN TRUCK LIVE LOAD ON DESIGN ROW, 2) MAXIMUM PERMANENT (75-YR) COVER LOAD AND 3) ALLOWABLE COVER WITH PARKED (1-WEEK) AASHTO DESIGN TRUCK.
7. REQUIREMENTS FOR HANDLING AND INSTALLATION:
 - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
 - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 1.50 INCHES.
 - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, a) THE ARCH STIFFNESS CONSTANT SHALL BE GREATER THAN OR EQUAL TO 550 LB/FT², THE ASC IS DEFINED IN SECTION 6.2.8 OF ASTM F2418, AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.
8. ONLY CHAMBERS THAT ARE APPROVED BY THE SITE DESIGN ENGINEER WILL BE ALLOWED. UPGRADE UPON REQUEST BY THE SITE DESIGN ENGINEER OR OWNER. THE CHAMBER MANUFACTURER SHALL SUBMIT A STRUCTURAL EVALUATION FOR APPROVAL BEFORE DELIVERY. THE OWNER OR SITE DESIGN ENGINEER IS RESPONSIBLE FOR THE APPROVAL.
9. THE STRUCTURAL EVALUATION SHALL BE SEALED BY A REGISTERED PROFESSIONAL ENGINEER.
10. THE STRUCTURAL EVALUATION SHALL DEMONSTRATE THAT THE SAFETY FACTORS ARE GREATER THAN OR EQUAL TO 1.05 FOR THE 75-YEAR PERMANENT LOAD AND 1.05 FOR THE 20-YEAR DESIGN LOAD, IN ACCORDANCE WITH ASTM F2787 AND BY SECTIONS 3 AND 12.12 OF THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS FOR THERMOPLASTIC PLASTIC CHAMBERS.
11. THE TEST DERIVED CREEP MODULUS AS SPECIFIED IN ASTM F2418 SHALL BE USED FOR PERMANENT DEAD LOAD DESIGN EXCEPT THAT IT SHALL BE THE 75-YEAR MODULUS USED FOR DESIGN.
12. CHAMBERS AND END CAPS SHALL BE PRODUCED AT AN ISO 9001 CERTIFIED MANUFACTURING FACILITY.

IMPORTANT - NOTES FOR THE BIDDING AND INSTALLATION OF THE SC-740 SYSTEM


1. STORMTECH SC-740 CHAMBERS SHALL NOT BE INSTALLED UNTIL THE MANUFACTURER'S REPRESENTATIVE HAS COMPLETED A PRE-CONSTRUCTION MEETING WITH THE INSTALLERS.
2. STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
3. CHAMBERS ARE NOT TO BE BACKFILLED WITH A DOZER OR AN EXCAVATOR SITUATED OVER THE CHAMBERS. STORMTECH RECOMMENDS A BACKFILL METHODS:
 - STONE SHOOTER LOCATED OFF THE CHAMBER BED.
 - BACKFILL AS ROWS ARE BUILT USING AN EXCAVATOR ON THE FOUNDATION STONE OR SUBGRADE.
 - BACKFILL FROM OUTSIDE THE EXCAVATION USING A LONG BOOM HOE OR EXCAVATOR.
4. THE FOUNDATION STONE SHALL BE LEVELLED AND COMPAKTED PRIOR TO PLACING CHAMBERS.
5. JOINTS BETWEEN CHAMBERS SHALL BE PROPERLY SEALED PRIOR TO PLACING STONE.
6. MAINTAIN MINIMUM - 6" (150 mm) SPACING BETWEEN THE CHAMBER ROWS.
7. EMBEDMENT STONE SURROUNDING CHAMBERS MUST BE A CLEAN, CRUSHED, ANGULAR STONE 3/4"-2" (20-50 mm).
8. THE CONTRACTOR MUST REPORT ANY DISCREPANCIES WITH CHAMBER FOUNDATION MATERIALS BEARING CAPACITIES TO THE SITE DESIGN ENGINEER.
9. ADS RECOMMENDS THE USE OF "FLEXSTORM CATCH IT" INSERTS DURING CONSTRUCTION FOR ALL INLETS TO PROTECT THE SUBSURFACE STORMWATER MANAGEMENT SYSTEM FROM CONSTRUCTION SITE RUNOFF.

NOTES FOR CONSTRUCTION EQUIPMENT


1. STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
2. THE USE OF CONSTRUCTION EQUIPMENT OVER SC-740 CHAMBERS IS LIMITED:
 - NO EQUIPMENT IS ALLOWED ON BARE CHAMBERS.
 - NO EQUIPMENT (DUMP LOADERS, DUMP TRUCKS, OR EXCAVATORS) ARE ALLOWED UNTIL PROPER FILL DEPTHS ARE REACHED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
 - WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT CAN BE FOUND IN THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
3. FULL 36" (900 mm) STABILIZED COVER MATERIALS OVER THE CHAMBERS IS REQUIRED FOR DUMP TRUCK TRAVEL OR DUMPING.

USE OF A DOZER TO PUSH BACKFILLED STONE BETWEEN THE ROWS OF CHAMBERS MAY CAUSE DAMAGE TO THE CHAMBERS AND IS NOT AN ACCEPTABLE BACKFILL METHOD. ANY CHAMBERS DAMAGED BY THE "DUMP AND PUSH" METHOD ARE NOT COVERED UNDER THE STORMTECH STANDARD WARRANTY.


CONTACT STORMTECH AT 1-888-892-2694 WITH ANY QUESTIONS ON INSTALLATION REQUIREMENTS OR WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT.







INSERTA-TEE SIDE INLET DETAIL





SC-740 ISOLATOR ROW PLUS DETAIL



SC-740 CROSS SECTION DETAIL



SC-740 TECHNICAL SPECIFICATIONS



ACCEPTABLE FILL MATERIALS: STORMTECH SC-740 CHAMBER SYSTEMS

MATERIAL LOCATION	DESCRIPTION	AASHTO MATERIAL CLASSIFICATIONS	COMPACTION / DENSITY REQUIREMENT
D	FINAL FILL: FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'D' LAYER.	ANY SOIL/ROCK MATERIALS, NATIVE SOILS, OR PER ENGINEER'S PLANS. CHECK PLANS FOR PAVEMENT SUBGRADE REQUIREMENTS.	N/A
C	INITIAL FILL: FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 18" (450 mm) ABOVE THE TOP OF THE CHAMBER. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'C' LAYER.	GRANULAR WELL-GRADED SOIL/AGGREGATE MIXTURES, <35% FINES OR PROCESSED AGGREGATE. MOST PAVEMENT SUBBASE MATERIALS CAN BE USED IN LIEU OF THIS LAYER.	AASHTO M145 ¹ A-1, A-2, A-3 OR AASHTO M45 ² 3, 357, 4, 467, 5, 56, 57, 6, 67, 68, 7, 78, 8, 9, 10
B	EMBEDMENT STONE: FILL MATERIAL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.	CLEAN, CRUSHED, ANGULAR STONE OR RECYCLED CONCRETE ³	AASHTO M43 ³ 3, 357, 4, 467, 5, 56, 57
A	FOUNDATION STONE: FILL BELOW CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) UP TO THE FOOT (BOTTOM) OF THE CHAMBER.	CLEAN, CRUSHED, ANGULAR STONE OR RECYCLED CONCRETE ³	AASHTO M43 ³ 3, 357, 4, 467, 5, 56, 57


PLEASE NOTE:
 1. THE LISTED AASHTO DESIGNATIONS ARE FOR GRADING ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR. FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE".
 2. STANDARD COMPACTION REQUIREMENTS ARE MET FOR A LOCATION MATERIALS WHEN PLACED AND COMPAKTED IN 6" (150 mm) MAX LIFTS USING TWO FULL COVERS WITH A VIBRATORY COMPAKATOR.
 3. WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD LOAD CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAKING OR DRAGGING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.

4. ONCE LAYER 'C' IS PLACED, ANY SOIL/MATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.

5. WHERE RECYCLED CONCRETE AGGREGATE IS USED IN LAYERS 'A' OR 'B' THE MATERIAL SHOULD ALSO MEET THE ACCEPTABILITY CRITERIA OUTLINED IN TECHNICAL NOTE 6.20 "RECYCLED CONCRETE STRUCTURAL BACKFILL".

INSPECTION & MAINTENANCE

1. INSPECT ISOLATOR ROW PLUS FOR SEDIMENT
 - INSPECTION PORTS (IF PRESENT)
 - REMOVE THE LID AND DRAIN LINE
 - INSPECT AND DRAIN FLEXSTORM FILTER IF INSTALLED
 - USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW PLUS THROUGH OUTLET PIPE
 - IF SEDIMENT IS AT OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
2. ALL CORDS AND END CAPS
1. REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW PLUS
 - USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW PLUS THROUGH OUTLET PIPE
 - IF SEDIMENT IS AT OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
3. MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
4. LOWER A CAMERA INTO ISOLATOR ROW PLUS FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
- IF SEDIMENT IS AT OR



Providing innovative design solutions for irrigation worldwide


- 20 Merrit Parkway
Nashua, NH 03062
(978) 433.8972
- 14509 S. Old Statesville Rd., Suite 100
Huntersville, NC 28078
(704) 843.3688

PROJECT: LAKE VIEW PLAYGROUND

CLIENT:
**CITY OF
WORCESTER**


DATE: 11-22-24

REVISIONS:



IRRIGATION PLAN

SHEET IR-1




IRRIGATION NOTES

1. COORDINATE FINAL LOCATION OF SPRINKLERS AND NOZZLE SELECTION WITH FINAL APPROVED FIELD LAYOUT.
2. PIPE AND VALVE LOCATIONS ARE DIAGRAMMATIC, CONTRACTOR SHALL FIELD VERIFY.
3. VALVES AND VALVE BOXES SHALL BE PLACED, WHERE POSSIBLE, AS SHOWN.
4. CONTROL WIRE SHALL BE #14 GAUGE SINGLE STRAND, RED FOR TURF ZONES, COMMON WIRE SHALL BE #14 GAUGE SINGLE STRAND WHITE AND SPARE WIRES, INSTALLED WHERE SHOWN, SHALL BE #14 GAUGE SINGLE STRAND BLUE.
5. QUICK COUPLING VALVE SHALL BE INSTALLED ON 1 INCH PVC SWING JOINT WITH BRASS INSERT AND STABILIZER. (SEE DETAIL)
6. ROTARY SPRINKLERS SHALL BE INSTALLED ON SWING PIPE ASSEMBLIES, MINIMUM LENGTH TO BE 6 INCHES, 18 INCH MAXIMUM.
7. IRRIGATION SYSTEM IS DESIGNED FOR SEPARATE WATER SUPPLY TO PROVIDE 20 GPM MAX FROM NEW POTABLE SERVICE. SYSTEM TO PRODUCE 60-PSI DYNAMIC PRESSURE AT IRRIGATION CONTRACTOR'S POINT OF CONNECTION IN LANDSCAPED AREA.
8. CONTRACTOR SHALL TEST DYNAMIC PRESSURE BEFORE STARTING WORK, REPORT ANY DEVIATION FROM PRESSURE REQUIRED TO OWNER'S REPRESENTATIVE BEFORE CONTINUING.
9. INSTALL CONTROLLER IN ENCLOSURE, GENERALLY WHERE SHOWN ON THE DRAWINGS, HARD WIRE TO 120 VOLT, DEDICATED 20 AMP CIRCUIT, POWER SUPPLY USING LICENSED ELECTRICIAN. ROUTE ALL ZONE AND SPARE WIRES TO CONTROLLER VIA 1-1/2" CONDUIT THROUGH ENCLOSURE BASE. SEE CIVIL DRAWINGS FOR SIZE AND SHAPE OF CONCRETE PAD.
10. INSTALL WIRELESS RAIN SENSOR ON LIGHT POLE WHERE DIRECTED BY OWNER'S REPRESENTATIVE. INSTALL RAIN SENSOR RECEIVER INSIDE CONTROLLER PEDESTAL.
11. COORDINATE LOCATION OF EXISTING AND FUTURE UTILITIES ON SITE AND CONTACT PROPER AUTHORITIES AND UTILITY COMPANIES BEFORE THE START OF WORK.
12. FLUSH ALL LATERAL LINES BEFORE INSTALLING SPRINKLERS.
13. SPRINKLERS FOR TURF SHALL HAVE 6 INCH POP UP HEIGHT.
14. CONTRACTOR MUST SUBMIT SHOP PRODUCT DRAWINGS AS PER THE WRITTEN SPECIFICATIONS TO THE IRRIGATION CONSULTANT FOR APPROVAL PRIOR TO ORDERING MATERIAL AND BEGINNING WORK.
15. ANY AND ALL MATERIAL SUBSTITUTIONS WHICH VARY FROM THE SPECIFIED PRODUCTS MUST BE SUBMITTED TO THE IRRIGATION CONSULTANT FOR APPROVAL AS PART OF THE SUBMITTAL PROCESS.
16. ONCE APPROVED SUBMITTALS HAVE BEEN RETURNED TO THE CONTRACTOR, WORK MAY BEGIN. THE IRRIGATION CONSULTANT MUST BE NOTIFIED A MINIMUM OF 7-DAYS IN ADVANCE OF THE START OF WORK TO COORDINATE ON-SITE SUPERVISION AND ADMINISTRATION.
17. SEE IRRIGATION DETAILS AND SPECIFICATIONS SECTION FOR ADDITIONAL NECESSARY INFORMATION.


IRRIGATION LEGEND

SYMBOL	PSI	SPACING	DESCRIPTION
	50	35'	
	50	25'	ROTARY SPRINKLER WITH CHECK VALVE (STANDARD NOZZLES)
	50	18'	
			1" 24 VOLT ELECTRIC ZONE VALVE (SEE VALVE DESIGNATORS FOR FLOW)
			1-1/2" ISOLATION GATE VALVE
			1" QUICK COUPLING VALVE
_____			1" LATERAL PIPING (SEE LATERAL PIPE SCHEDULE FOR SIZES)
— · — · —			1-1/2" CLASS-200 PVC MAINLINE PIPING
			AUTOMATIC WIRELESS RAIN SENSOR
			AUTOMATIC CONTROLLER IN STAINLESS PEDESTAL
			FLOW METER/NORMALLY OPEN MASTER VALVE
— — — — —			1-1/2" ELECTRICAL CONDUIT


VALVE DESIGNATION:




LATERAL PIPE SCHEDULE	
FLOW	PIPE SIZE / TYPE
0-12 GPM	1 INCH 100 PSI POLYETHYLENE OR CLASS-200 PVC
12-22 GPM	1-1/4 INCH 100 PSI POLYETHYLENE OR CLASS-200 PVC




1 ROTARY SPRINKLER DETAIL
NO SCALE




2 ROTARY SPRINKLER DETAIL
(WITH POLYETHYLENE LATERAL LINE) NO SCALE




3 24 VOLT ELECTRIC VALVE DETAIL
(WITH POLYETHYLENE LATERAL LINE) NO SCALE




4 24 VOLT ELECTRIC VALVE DETAIL
NO SCALE




5 TRENCH AND WIRE DETAIL
NO SCALE




6 QUICK COUPLING VALVE DETAIL
NO SCALE




7 ISOLATION GATE VALVE DETAIL
NO SCALE




8 MASTER VALVE AND FLOW METER
NO SCALE




9 OUTDOOR CONTROLLER ENCLOSURE DETAIL
NO SCALE




10 CONTROLLER GROUNDING DETAIL-PROFILE
NO SCALE




11 CONTROLLER GROUNDING DETAIL-PLAN
NO SCALE




12 RAIN SENSOR MOUNTING DETAIL
NO SCALE




13 PIPE AND WIRE SLEEVE DETAIL
NO SCALE



14 WIRE SPLICING DETAIL
NO SCALE



15 VALVE BOX INSTALLATION DETAIL
NO SCALE



Providing innovative design solutions for irrigation worldwide.

— 20 Merrit Parkway
Nashua, NH 03062
(603) 433-8972

— 14509 S. Old Statesville Rd., Suite 109
Huntersville, NC 28078
(704) 245-3688

www.灌溉consulting.com

PROJECT:
LAKE VIEW
PLAYGROUND

CLIENT:
CITY OF
WORCESTER


DATE: 11-22-24

REVISIONS:
NO. DATE DESCRIPTION

SCALE: N.T.S.

IRRIGATION DETAILS

SHEET IR-2






KEYED NOTES

1. HANDHOLE FOR POWER, 24" W X 36" L X 22".
2. EXISTING OVERHEAD WIRES.
3. ELECTRIC CABINET, NEMA 3R STAINLESS STEEL.
4. MUSCO LIGHTING CONTROL CABINETS, LOCATED IN ELECTRICAL CABINET.
5. EXISTING UTILITY POLE.
6. LIGHT FIXTURE / ARM, SHALL BE LOCATED MINIMUM 10' FROM OVERHEAD ELECTRICAL WIRES. FIELD COORDINATE DIMENSION PRIOR TO INSTALLATION.
7. FURNISH AND INSTALL AN EXHAUST FAN IN THE CABINET FOR 24HR OPERATION. WIRE TO CIRCUIT PP-18. CARRY IN BID \$1000.00 FOR FURNISHING AND INSTALLING THE EXHAUST FAN.

GENERAL NOTES

1. CARRY IN BID 110' OF CONDUIT, FEEDER AND TRENCHING FOR ELECTRICAL SECONDARY SERVICE FROM THE ELECTRICAL CABINET TO THE UTILITY POLE.
2. CARRY IN BID 175' OF CONDUIT, CABLEING AND TRENCHING FOR COMMUNICATION (INTERNET SERVICE) FROM THE ELECTRICAL CABINET TO THE UTILITY POLE.
3. ALL SPORTS LIGHT FIXTURES ARE TO BE WIRED VIA RELAYS IN THE LIGHTING CONTROL SYSTEM CABINET.
4. ALL PATHWAY LIGHT FIXTURES ARE TO BE CONTROLLED VIA PHOTOCELL.
5. THE FOLLOWING SHALL BE WIRED VIA MUSCO LIGHTING CONTROLLER:
 - MUSCO SPORTS LIGHTS.
 - SECURITY LIGHTS ON MUSCO POLES.
 - ALL PATHWAY LIGHTS (TYPE ZP).
 - GAZEBO LIGHT (TYPE A).
 - GAZEBO DUPLEX RECEPTACLE.


KEYED NOTES

TAG	DESCRIPTION	FED FROM	VOLTAGE	FEEDER / CABLE
 P	PATHWAY LIGHT FIXTURE WITH INTEGRAL GFCI RECEPTACLE	ELECTRICAL PANEL	120/240V 120V	2#6 AWG & 1#8 AWG GND FOR LIGHT AND 2#6 AWG & 1#8 AWG GND FOR RECEPTACLE. SEE WIRING DIAGRAM.
 SF	SPORTS FIELD POLE MOUNTED LIGHT FIXTURE MUSCO SECURITY LIGHT	MUSCO PANEL MUSCO PANEL	240V 240V	2#6 AWG & 1#8 AWG GND (LIGHTING) 2#6 AWG & 1#8 AWG GND (LIGHTING)
 D	DUPLEX RECEPTACLE FOR CAMERA MOUNTED ON SPORTS FIELD LIGHT POLE. INSTALL RECEPTACLE IN ENCLOSURE. ENCLOSURE BASIS OF DESIGN BY MUSCO, ECE 48" CABINET. MOUNT ENCLOSURE MINIMUM 10' ABOVE GRADE.	PANEL PP	120V	2#6 AWG & 1#8 AWG GND (LIGHTING) PROVIDE INLINE FUSES

WIRE SCHEDULE


- 2-6 2#6 AWG & 1#8 AWG GND FOR LIGHT IN 2'C
- 4-6 2#6 AWG & 1#8 GND FOR LIGHT AND 2#6 AWG & 1#8 AWG GND FOR GFCI RECEPTACLE IN 2'C
- 6-6 2#6 AWG & 1#8 GND FOR PATHWAY LIGHT POLE AND 4#6 AWG & 1#8 AWG GND FOR GFCI RECEPTACLE IN 2'C
- 6-6A 4#6 AWG & 1#8 AWG GND FOR MUSCO LIGHT POLE AND 2#6 AWG & 1#8 AWG GND FOR CEMERA DUPLEX RECEPTACLE IN 2'C
- 8-6 2#6 AWG & 1#8 GND FOR PATHWAY LIGHT POLE IN 2'C AND 6#6 AWG & 1#8 AWG GND FOR GFCI RECEPTACLE IN 2'C
- 10-6 2#6 AWG & 1#8 GND FOR PATHWAY LIGHT POLE AND 4#6 AWG & 1#8 AWG GND FOR GFCI RECEPTACLES IN 2'C AND 4#6 AWG & 1#8 AWG GND FOR GFCI RECEPTACLES IN 2'C
- 10-6A 4#6 AWG & 1#8 AWG GND FOR MUSCO LIGHT POLE AND 2#6 AWG & 1#8 AWG GND FOR CEMERA DUPLEX RECEPTACLE IN 2'C AND 2#6 AWG & 1#8 AWG GND FOR PATHWAY LIGHT POLE AND 2#6 AWG & 1#8 AWG GND FOR GFCI DUPLEX RECEPTACLE IN 2'C

LEGEND

 - GFCI RECEPTACLE WITH WHILE IN-USE COVER
WP,WIC

LIGHTING FIXTURE SCHEDULE

CALLOUT	DESCRIPTION	MOUNTING	MODEL	VOLTS
A	8" SURFACE MOUNT FIXTURE	SURFACE	DMF DC4-SM-W-M-D-25-GA-0-00-00-30K-BK-T-00-R	120V 1P 2W
P1	SPORTS AND SECURITY LIGHT	POLE	SEE SPORT AND SECURITY LIGHT FIXTURE SCHEDULE	240V 2P 2W
P2	SPORTS AND SECURITY LIGHT	POLE	SEE SPORT AND SECURITY LIGHT FIXTURE SCHEDULE	240V 2P 2W
ZP	WALKWAY LIGHT FIXTURE	POLE	PROVIDE LIGHT FIXTURE WITH 16'-0" POLE SEE DRAWING E-3 FOR SPECIFICATIONS	240V 2P 2W




PROJECT:
LAKE VIEW
PLAYGROUND
IMPROVEMENTS

CLIENT:
CITY OF WORCESTER

DATE: 11-22-24

REVISIONS:

NO.	DATE	DESCRIPTION



ELECTRICAL SITE PLAN
SHEET E-1



80 BEVERLY ROAD • WORCESTER, MA 01605
978-852-2644 • info@edlandarch.com

88-832-2044 • info@california.com



Front Street, FL 3, Worcester, MA 01608

www.artengineering.us

www.aerofiles.com

Digitized by srujanika@gmail.com

GENERAL NOTES


1. CARRY IN BID 175' OF CONDUIT, CABLING AND TRENCHING FOR COMMUNICATIONS (INTERNET SERVICE) FROM THE ELECTRICAL CABINET TO THE UTILITY POLE.
2. SEE FRONT END DOCUMENTS FOR SECURITY CAMERA REQUIREMENTS.

KEYED NOTES

① HANHOLE FOR COMMUNICATIONS, 24"W X 36"L X 22"D. PROVIDE 2"C BETWEEN HANHOLES AND 1"C FROM HANHOLE TO THE POLE.

WIRE SCHEDULE

2C 2" HDPE CONDUIT FOR CAMERA



PROJECT: LAKE VIEW PLAYGROUND IMPROVEMENTS

CLIENT:
CITY OF WORCESTER

DATE: 11-22-24

REVISED EDITIONS:





SCALE: 1" = 20'

0' 10' 20' 40'

SECURITY SYSTEM CONDUIT PLAN

SHEET E 2



System Requirements: Control System Summary

Project Name: Lake View Playground | Project #: 2394600
Control System ID: 1 of 1
Distribution Panel Location/ID: Service 1

Project Information

Control System			Project Notes:		
Control System ID:			1 of 1		
Control System Type:			Control-Link® Control and Monitoring Systems		
Communication Type:			Powerline-PT		
Power Requirements			Equipment Listing		
Control cabinet(s):			Description	Qty	Size (in.)
Control voltage (phase to neutral)			120/60		
VA loading - Inrush			2043.0	Control and monitoring cabinet -	1 24 X 48
VA loading - Sealed			232.0	primary	
Lighting Circuits:			Contactors, 30 amperes	6	-
Voltage/Hertz/Phase			240/60/1	Off/On/Auto switches	5 *


Important Notes:

1. Please confirm that the lighting circuit voltage listed above is accurate for this facility. This is the voltage/phase being connected and utilized at each lighting pole's electrical components enclosure disconnect. Inaccurate voltage/phase can result in additional costs and delays. Contact your Musco sales representative to confirm this item.
2. In a 3 phase design, all 3 phases are to be run to each pole location. Musco's single phase luminaires come pre-wired to utilize all 3 phases across the entire facility.
3. One contactor is required for each circuit at each pole location. Contactors are 3 pole and 100% rated for the published continuous load.
4. If the lighting system will be fed from more than one distribution location, additional equipment may be required. Contact your Musco sales representative.
5. Size overcurrent devices using the full load amps column of the Circuit Summary by Switch chart (Minimum power factor is 0.9). Size conduit per code unless otherwise specified as larger to allow for harness connectors.
6. Avoid use of in-ground junction/pull boxes when possible. If used, all wire connectors must be UL listed for Wet Locations to prevent leakage current.
7. Control power wiring must be in separate conduit from line or load power wiring. Communication cables must be in separate conduit from any power wiring.
8. Refer to Installation Instructions for more details on equipment information and the installation requirements.

System Requirements: Control System Summary

Project Name: Lake View Playground | Project #: 2394600
Control System ID: 1 of 1
Distribution Panel Location/ID: Service 1

Equipment Layout and Connection Details



ID	Description	ID	Description
1a	Line power to contactors, and equipment grounding conductor. Requires one circuit per contactor, size wiring per load and voltage drop.	1	Control and monitoring cabinet - primary
1b	Load power from contactors, and equipment grounding conductor. Requires one circuit per contactor, size wiring per load and voltage drop.		
2a	Control power with equipment ground to control cabinet. Requires dedicated 20 A circuit. Provide transformer if control voltage not present.		

System Requirements: Control System Summary

Project Name: Lake View Playground | Project #: 2394600
Control System ID: 1 of 1
Distribution Panel Location/ID: Service 1

Circuit Summary

Switching Schedule	
Field/Switch Description	Switches
Basketball	1
Security	2
Pathway	3
Gazebo Light	4
Gazebo Duplex	5

Control Module ID: 1

Circuit Summary by Switch						
Switch	Zone Description	Pole ID	Qty of Fixtures	Full load amperes	Contactor Size (Amps)	Cabinet #
1	Basketball	P1	2	5.54	30	C1
	Basketball	P2	2	5.54	30	C2
2	Security	P1, P2	2	86	30	C1
3	Pathway	ZP	1	1	30	C1
4	Gazebo Light	A	1	1	30	C1
5	Gazebo Duplex		1	1	30	C6

Sales Representative: Mike Berry | Project Engineer: Tanner Lanphier | Scan: 2394600 | Document ID: 2394600P1V3C2-1119130720

www.musco.com | lighting@musco.com

Page 1 of 3 – 19-November-2024

Sales Representative: Mike Berry | Project Engineer: Tanner Lanphier | Scan: 2394600 | Document ID: 2394600P1V3C2-1119130720

www.musco.com | lighting@musco.com

Page 2 of 3 – 19-November-2024

Meet code requirements and save money with Bussmann™ series in-line fuse holders

Superior circuit protection in roadway and street lighting applications is key to keeping the lights reliable and safe. Using in-line fuse holders that can adequately withstand the lighting environment can make it easier to apply superior circuit protection.


In fact, **breakaway capability** and **submersibility** are quickly becoming preferred features. Many states already mandate breakaway fuse holders in roadway lighting applications to ensure safe disconnection in the event of a knockdown or if maintenance is required. Submersibility and waterproof requirements have also been enforced as street lighting is prone to wet conditions.

Bussmann series HEB and HEX breakaway in-line fuse holders are **UL® Recognized as fuse holders** and meet breakaway and submersibility requirements. What's more, they can help you realize a reduction in labor time, tools needed and maintenance costs when used as a standard solution.

Specific codes and regulations for street lighting vary by state, for example: Florida Department of Transportation's *Standard Specifications for Road and Bridge Construction, Section 992*.

992.2.6 In-Line Fuse Holders
In line fuse holders shall be of a breakaway connection and be UL® recognized per Guide IZL12 and listed for 500V. The wire connections in the fuse holders shall be of the copper set-screw type. Fused connections shall utilize a FNQ 10 amp time delay fuse rated for 500V. Fuses shall be UL listed to Standard 240-14. The rating for the fuse holders shall be water resistant or submersible rated.

HEB breakaway, single-pole holder



HEB - A W - RYC-A

Catalog symbol	Loadside terminal	Lineside terminal	Terminal type	Wire range*	Terminal type	Wire range*
RLC-A	Cu crimp	#8-16	Cu crimp	#8-16		
RLC-B	Cu crimp	#8-16	Cu crimp	#8-16		
RLC-C	Cu crimp	#8-16	Cu crimp	#8-16		
A	Cu crimp	#8-16	Cu setscrew	#8-16		
RLC-J	Cu crimp	#8-16	Cu setscrew	#8-16		
RYC	Cu crimp	#8-16	Cu dual setscrew	#8-16		
RLA	Cu crimp	#8-16	Al setscrew	#8-16		
RYA	Cu crimp	#8-16	Al dual setscrew	#8-16		
RLC-A	Cu crimp	#6	Cu crimp	#8-16		
B	RLC-B	#6	Cu crimp	#8-16		
RYC	Cu crimp	#6	Cu dual setscrew	#8-16		
RLC-J	Cu setscrew	#6	Cu setscrew	#8-16		
RYC	Cu setscrew	#6	Cu dual setscrew	#8-16		
J	RLC-J	#6	Cu setscrew	#8-16		
RYC	Cu setscrew	#6	Cu dual setscrew	#8-16		
K	RLC-J	#6	Cu dual setscrew	#8-16		
RYC	Cu dual setscrew	#6	Cu dual setscrew	#8-16		
L	RLC-J	#6	Cu dual setscrew	#8-16		
RYA	Al setscrew	#6	Al dual setscrew	#8-16		

See data sheet No. 2127 for more detail.
* Solid/stranded conductors unless otherwise noted.
1 Not dual wire rated. One wire per opening.

HET neutral single-pole holder

Provides means of conductor continuity
Permanent, solid neutral for use in conjunction with the HEB holder
Identifiable by white, plastic coupling nut
Can be used in place of HEB with a supplemental dummy fuse "neutral," Bussmann series NNB
See data sheet No. 2125 for more detail.

See data sheet No. 2125 for more detail.



Lake View Playground		
Worcester, MA		
Grid Summary		
Name: Spill at 100' (Cd)		
Spacing: 30.0'		
Height: 5.0' above grade		
Illumination Summary		
MAINTAINED MAX CANDLES (per fixture)		
Scale: Average: Entire Grid		
Maximum: 254		
Minimum: 0		
Avg/Min: 2		
Max/Min: 254		
UG Indirect: 0.00		
UG Direct: 0.00		
No. of Points: 31		
LUMINAIRE INFORMATION		
Aperture: 4.00'		
A: 2.16		
No. of Luminaires: 4		
Total Load: 2.16 KVA		

Guaranteed Performance: The ILLUMINATION described above is guaranteed per your Musco Warranty document and includes a 0.95 diff. and 0.95 reflector.

Field Measurements: Individual field measurements may vary from computer-calculated predictions and should be taken in accordance with IESNA RP-1-15.

Electrical System Requirements: Refer to Amperage Draw Chart and/or the "Musco Control System Summary" for electrical sizing.

Installation Requirements: Results assume ± 3% nominal voltage at line side of the driver and structures located within 3 feet (1m) of design locations.




PROJECT:
LAKE VIEW
PLAYGROUND
IMPROVEMENTS

CLIENT:
CITY OF WORCESTER

DATE: 11-22-24

REVISIONS:

NO.	DATE	DESCRIPTION



ELECTRICAL DETAILS

SHEET E-5




280 BEVERLY ROAD • WORCESTER, MA 01605
508-852-2644 • info@edlandarch.com

280 BEVERLY ROAD • WORCESTER, MA 01603
508-852-2644 • info@edlandarch.com



38 Front Street, FL 3, Worcester, MA 01608
www.artengineering.us

www.artengineering.us



A circular seal for a Massachusetts professional electrical engineer. The outer ring contains the text "COMMONWEALTH OF MASSACHUSETTS" at the top and "PROFESSIONAL ELECTRICAL ENGINEER" at the bottom. The inner circle contains "AZIM" at the top, "S." in the middle, "RAWJI" below it, and "No. 41765" at the bottom. The seal is signed "Azim S. Rawji" at the bottom.

PROJECT: LAKE VIEW PLAYGROUND IMPROVEMENTS

CLIENT:

REVISIONS:

N

ELECTRICAL DETAILS

SHEET E-6

Lake View Playground
Worcester, MA

Lighting System

Pole/Fixture Summary

Pole ID	Pole Height	Mtg Height	Fixture Qty	Luminaire Type	Load	Circuit
P1-P2	40'	40'	2	TLC-LED-550	1.08 kW	A
		25'	1	CREE OSQ	0.13 kW	B
			6		2.38 kW	

Circuit Summary

Circuit	Description	Load	Fixture Qty
A	Basketball	2.16 kW	4
B	Security	0.20 kW	2

Fixture Type Summary

Type	Source	Wattage	Lumens	L80	L50	L70	Quantity
CREE OSQ	LED 5700K - 70 CRI	100W	14,743	-	-	-	2
TLC-LED-550	LED 5700K - 75 CRI	540W	67,000	>120,000	>120,000	>120,000	4


Single Luminaire Amperage Draw Chart

Driver Specifications (50 min power factor)		Line Amperage Per Luminaire (max draw)					
Single Phase Voltage		208	220	240	277	347	380
(60)	(60)	(60)	(60)	(60)	(60)	(60)	(60)
CREE OSQ		-	-	0.3	-	0.2	
TLC-LED-550		3.2	3.0	2.8	2.4	1.9	1.6

Light Level Summary

Calculation Grid Summary

Grid Name	Calculation Metric	Ave	Min	Max	Max/Min	Ave/Min	Circuits	Fixture Qty
Basketball	Horizontal Illuminance	30.88	19	59	2.03	1.62	A	4
	Spill at 100'	0.00	0	0	-	-	A	4
	Spill at 100'	0.00	0	0	-	-	A	4
	Max Vertical Illuminance Metric	28.46	0	254	-	-	A	4
	Spill at 100' (Cd)							




ENGINEERED DESIGN By: T.Lanphier • File #239460B • 30-Oct-24

Equipment List For Areas Shown

QTY	LOCATION	SIZE	GRADE ELEVATION	ABOVE GRADE LEVEL	Luminaires		
					LUMINAIRE TYPE	QTY/POLE	THIS GRID
2	P1-P2	40'	-	40'	TLC-LED-550	2	0
					CREE OSQ	1	1
					Totals	6	4

*Above Grade level relative to the field



SCALE IN FEET 1:30
0' 30' 60'
ENGINEERED DESIGN By: T.Lanphier • File #239460B • 30-Oct-24

Pole location(s) dimensions are relative
to 0.0 reference point(s)



Not to be reproduced in whole or part without the written consent of Musco Sports Lighting, LLC. ©1981, 2023 Musco Sports Lighting, LLC.

PROJECT SUMMARY

Lake View Playground
Worcester, MA

Grid Summary

Name	Basketball
Size	30' x 50'
Spacing	30.0'
Height	3.0' above grade

Illumination Summary

Maintained Horizontal Footcandles	Entire Grid
Guaranteed Average	30
Scatterage	30.88
Minimum	39
Avg/Min	1.62
Guaranteed Max/Min	2.5
Scatterage	23
UG (adjacent pts)	1.38
CU	0.57
No. of Poles	50
LUMINAIRE INFORMATION	
Applied Circuits	A
No. of Luminaires	4
Total Load	2.16 kW

Guaranteed Performance: The ILLUMINATION described above is guaranteed per your Musco Warranty document and includes the following performance guarantees:
Field Measurements: Individual field measurements may vary from computer-calculated predictions and should be taken in accordance with the IESNA Standard.
Electrical System Requirements: Refer to Amperage Draw Chart and/or the "Musco Control System Summary" for electrical system requirements.
Installation Requirements: Results assume +3% nominal voltage at line side of the driver and structures located within 3 feet (1m) of design locations.

REVISIONS:

NO.	DATE	DESCRIPTION



PROJECT:
LAKE VIEW
PLAYGROUND
IMPROVEMENTS

CLIENT:
CITY OF WORCESTER

DATE: 11-22-24

REVISIONS:

NO.	DATE	DESCRIPTION



Not to be reproduced in whole or part without the written consent of Musco Sports Lighting, LLC. ©1981, 2023 Musco Sports Lighting, LLC.

ILLUMINATION SUMMARY


ELECTRICAL DETAILS

SHEET E-7

Datasheet: OSQ Area Luminaire on Light-Structure System™

Electrical Data

Rated wattage per luminaire¹.....130-168 W
Input voltage 120-277V or 347-480V, 50/60Hz
Driver configuration Integral
Driver Efficiency >90%
Starting (inrush) current..... 73A, 120μs
Power factor > 0.9
Total Harmonic Distortion < 20%
Operating temperature range -40°C - +35°C (-40°F - +95°F)
Dimming mode² 0-10V dimming to 10%



	120 Vac	208 Vac	240 Vac	277 Vac	347 Vac	480 Vac
Max operating current³	1.41 A	0.84 A	0.73 A	0.64 A	0.50 A	0.37 A


Footnotes:
1) Rated wattage is the power consumption, including driver efficiency losses, at stabilized operation in 23°C ambient temperature environment.

2) Dimming controls not provided by Musco. Driver provides 10V source current at 0.15 mA, compliant with IEC 60929 Annex E dimming standard.

3) Operating current based on 25 degree C.

Notes

1. Use thermal magnetic HID-rated or D-curve circuit breakers.



MUSCO.

2

SECURITY LIGHTING DETAIL

Cree is registered trademark of Cree, Inc.
Patent www.cree.com/patents. • ©2016 Musco Sports Lighting, LLC • Cree OSQ Series 120-480V - M-2175-en04-2
www.musco.com • lighting@musco.com

Installation Instructions: Light-Structure System™

Precast Concrete Base

Overview

The precast concrete base is set directly into the ground, backfilled with concrete, and allowed to cure for 12 to 24 hours. The base is designed for easy slip-fit connection to the galvanized steel pole. The remaining components — steel pole, poletop luminaire assembly, electrical components enclosure, and wire harness — are assembled as a unit and set onto the base. The base includes an integrated lightning ground system.

Tools/Materials Needed

Musco Supplied

- Field Aiming Diagram*
- Musco Foundation and Pole Assembly Drawing* or alternate foundation design
- Steel bar
- Wooden base wedges
- Level with shim for tapered base
- $\frac{5}{32}$ in hex key

Contractor Supplied

- Conduit for underground wiring
- Concrete backfill
- Water pump (as needed)

Installation Procedure

1 Verify pole ID on concrete base matches pole location on *Field Aiming Diagram*.


2 For options on poor soil conditions, alternative installation methods, or if there are any issues with pole locations given, contact your local Musco representative. Your project engineer's name appears on *Field Aiming Diagram*.

Note: Use only project-specific foundation designs as detailed on *Musco Foundation and Pole Assembly Drawing* or alternate foundation design plan.

3 Mark pole locations per *Field Aiming Diagram*.

4 Excavate holes to size and depth given on *Musco Foundation and Pole Assembly Drawing* or alternate foundation design.

Warning
Fall hazard
Cover holes or install fencing for fall safety.



MUSCO.

8



LIGHT POLE INSTALLATION DETAILS

©2015, 2019 Musco Sports Lighting, LLC • LED ECE 9 • M-1917-en04-6
www.musco.com • lighting@musco.com

Installation Instructions: Light-Structure System™

Precast Concrete Base

3 Sling and lower base into hole. Orient wire access hole to accommodate incoming supply wiring. Snip banding and remove tab protectors.



4 Plumb base and wedge into position. Use supplied level with shim on upper end against base. Shim accommodates taper of base. Top of base is beveled. Keep level at least 6 in (150 mm) from top when plumbing.

5 Remove any water from hole to avoid weakening foundation. Water in hole during concrete pour can also cause hollow center of base to fill with concrete.

6 If backfilling to finished grade with concrete instead of compacted fill, be sure to maintain wire access.

7 Backfill with concrete per *Musco Foundation and Pole Assembly Drawing* or alternate foundation design.

MUSCO.

9

LIGHT POLE INSTALLATION DETAILS

©2015, 2019 Musco Sports Lighting, LLC • LED ECE 9 • M-1917-en04-6
www.musco.com • lighting@musco.com




PROJECT:
LAKE VIEW
PLAYGROUND
IMPROVEMENTS

CLIENT:
CITY OF WORCESTER

DATE: 11-22-24


REVISIONS:

NO.	DATE	DESCRIPTION




ELECTRICAL
DETAILS

SHEET E-8




LIGHTING CONTROL PANEL AND ENCLOSURE DETAIL

TS



DISTRIBUTION RISER

NTS



PICAL POLE RISER DETAIL

GENERAL NOTES



280 BEVERLY ROAD • WORCESTER, MA 01605
508-852-2644 • info@edlandarch.com



38 Front Street, FL 3, Worcester, MA 01608
www.artengineering.us

1. THE UTILITY COMPANY SHALL DESIGNATE CONDUIT RISER LOCATION ON THE POLE. ALL PRIMARY RISERS SHALL BE GALVANIZED STEEL, THIS INCLUDES THE 90 DEGREE SWEEP. PER NEC ALL STEEL RISERS MUST BE BONDED 6" DOWN FROM TOP OF RISER AND THE BOND MUST BE AT LEAST 8' HIGH FROM FINISHED GRADE.

2. THE ELECTRICAL CONTRACTOR IS RESPONSIBLE FOR PROVIDING AND INSTALLING THE BOND CLAMPS AND THE TAP. THE UTILITY COMPANY WILL MAKE THE BOND CONNECTION FROM THAT RISER BOND TAP TO THE GROUND SYSTEM ON THE POLE. SPARE RISER SWEEP SHALL BE BONDED ALSO. RISER SWEEP IN DIRECT BURIED APPLICATIONS SHALL BE CONCRETE ENCASED.

KEYED NOTES

① U GUARD

② GALVANIZED STEEL CONDUIT AND BEND ARE TO BE USED, THEY SHALL BE GROUNDED BY BONDING TO AN APPROVED U-BOLT TYPE GROUND CLAMP 6"(150mm) FROM TO OF THE CONDUIT. A 24" (600mm) CONDUCTOR SHALL BE PROVIDED TO EXTEND TO THE UTILITY COMPANY'S GROUNDING CONDUCTOR. THE CONDUCTOR SHALL BE SIZED AS REQUIRED BY THE NATIONAL ELECTRICAL CODE. ARTICLE 250, BUT IN NO CASE SHALL IT BE SMALLER THAN #4 AWG COPPER. USE CORROSION RESISTANT BENDS IN LOCATIONS SUBJECT TO HIGHWAY SALTING.

③ GALVANIZED STEEL CONDUIT, GALVANIZED STEEL SWEEP, ATTACHMENT CLAMPS, GROUNDING CLAMP AND 24" GROUNDING CONDUCTOR SHALL BE FURNISHED AND INSTALLED BY THE ELECTRICAL SUBCONTRACTOR. NORMALLY, THE CONDUIT SHALL RISE ON THE SIDE OF THE POLE AWAY FROM TRAFFIC UP TO 8 FT. (2.5m) TO 11 FT. (3.4m). CONSULT UTILITY COMPANY FOR PROPER LOCATION ON POLE.

④ PIPE STRAPS, INSTALL AT NOT MORE THAN 30" (750mm) INTERVALS.

⑤ THE CONDUIT BURIAL DEPTH SHALL BE 30" (750mm) MINIMUM.

1. ALL RACEWAY SHALL BE CONCEALED UNLESS OTHERWISE NOTED. PROVIDE PULL STRINGS FOR ALL RACEWAYS. COORDINATE ROUTING OF ALL EXPOSED CONDUITS WITH THE ARCHITECT.

2. THE SIZES OF ELECTRICAL RACEWAY SHALL BE AS INDICATED ON THE CONTRACT DRAWINGS AND SHALL MEET THE REQUIREMENTS OF THE LOCAL ELECTRIC CODE, 1" MINIMUM, OR AS SHOWN ELSEWHERE.

3. CONDUIT FOR WIRING CONCEALED IN FLOOR SLABS, OR BELOW GRADE SHALL BE 1" MINIMUM.

4. ALL WORK INCLUDING DEVICES, OUTLETS, FIXTURES, WIRING, CONDUIT, RACEWAY, EQUIPMENT, ETC SHOWN ON THE ELECTRICAL PLANS IS NEW WORK AND SHALL BE FURNISHED AND INSTALLED BY THE ELECTRICAL SUBCONTRACTOR OR THEIR SUB-CONTRACTORS, UNLESS NOTED OTHERWISE.

5. ALL NEW OUTLETS, DEVICES, FIXTURES, WIRING, CONDUIT, RACEWAY, EQUIPMENT, ETC SHOWN ON THE ELECTRICAL PLANS SHALL BE PROVIDED WITH ALL PARTS AND ACCESSORIES FOR A COMPLETE INSTALLATION.

6. ALL WIRE AND CABLE FOR POWER, LIGHTING, CONTROL INDICATION, ALARM, SIGNAL AND COMMUNICATION SYSTEM, UNLESS OTHERWISE NOTED, SHALL HAVE TYPE THHN INSULATION AND SHALL BE RATED FOR 600V MINIMUM.

7. MINIMUM WIRE SHALL BE #12. ALL WIRING SHALL BE NEW, UNLESS NOTED OTHERWISE. WIRING IN EXCESS OF 70 FEET FOR 120/208V AND 165 FEET FOR 277/480V MUST BE SIZED FOR VOLTAGE DROP. UPGRADE FEEDER SIZES IN ACCORDANCE WITH THE NEC. LIMIT VOLTAGE DROP TO LESS THAN 3%. FEEDERS SHALL FOLLOW SIMILAR GUIDELINES AND BE LIMITED TO 2% DROP.

8. ALL WIRING INSTALLATION SHALL BE COLOR CODED AS PER THE ELECTRICAL CODE. ALL CONDUCTORS SHALL BE STRANDED TYPE.

9. CIRCUIT RUNS ARE SHOWN DIAGRAMMATICALLY ONLY AND SHALL BE INSTALLED IN A MANNER TO PREVENT CONFLICTS WITH EQUIPMENT AND FIXTURES.

10. ALL WIRING, INCLUDING BUT NOT LIMITED TO VIDEO SURVEILLANCE SYSTEM, SOUND SYSTEM, ACCESS CONTROL, FIRE ALARM, LIGHTING CONTROL, LOW VOLTAGE SYSTEMS, DATA, VOICE, BRANCH CIRCUITS AND FEEDERS SHALL BE INSTALLED IN RIGID METAL CONDUIT WHERE EXPOSED. EMT IS ALLOWED IF NOT SUBJECT TO SEVERE PHYSICAL DAMAGE.

11. WIRING (NOT SHOWN) FOR THE VIDEO SURVEILLANCE SYSTEM, SOUND SYSTEM, ACCESS CONTROL, LIGHTING CONTROL, LOW VOLTAGE SYSTEMS, SHALL BE FURNISHED AND INSTALLED AS PER MANUFACTURER'S RECOMMENDATIONS, SEE ELECTRICAL SPECIFICATIONS FOR ADDITIONAL SCOPE OF WORK. EXPOSED

TS

NOTES:

1. THE ELECTRICAL SUBCONTRACTOR SHALL VERIFY THE CONDUIT LAYOUT WITH THE UTILITY COMPANIES PRIOR TO INSTALLATION.
2. THE PRIMARY ELECTRICAL CONDUITS SHALL BE ENCASED IN MIN. 3" OF 3000 PSI CONCRETE, COMPLY WITH UTILITY COMPANY REQUIREMENTS FOR REBAR AND STIRRUP REQUIREMENTS.
3. ALL OTHER CONDUITS SHALL BE ENCASED IN 3" OF 3000 PSI CONCRETE WHEN CROSSING ROADWAYS, DRIVEWAYS AND OTHER VEHICULAR TRAFFIC AREAS.
4. EXCAVATION, CONCRETE AND BACKFILLING SHALL BE BY THE GENERAL CONTRACTOR. CONDUIT AND WIRING SHALL BE BY THE ELECTRICAL SUBCONTRACTOR.
5. HANDHOLES SHALL BE AASHTO 20 RATED WITH BOLTED HEAVY DUTY COVERS. COVERS SHALL READ "ELECTRIC", "TELEPHONE" OR "CATV" DEPENDING ON THE APPLICATION.
6. CONDUITS SHALL BE SCHEDULE 80 PVC, UNLESS NOTED OTHERWISE.
7. ALL SWEEPS AT FOUNDATIONS AND RISERS SHALL HAVE A MINIMUM RADIUS OF 36". THE RISER SWEEP SHALL BE
13. CONDUIT AND WIRING (NOT SHOWN) FOR THE HVAC CONTROL EQUIPMENT AND MISCELLANEOUS DEVICES, OUTLET, SWITCHES, JUNCTION, PULL AND TERMINAL BOXES SHALL BE PROVIDED WITH NEMA ENCLOSURE SUITABLE TO THE ENVIRONMENT.
14. ALL WIRING DEVICES, PANEL BOARDS, DISTRIBUTION BOARDS, MOTORS, ETC., SHALL BE GROUNDED AS PER ELECTRIC CODE.
15. ALL WORK SHALL BE INSTALLED IN FULL ACCORDANCE WITH LOCAL, STATE & FEDERAL CODES, STATE AND LOCAL AUTHORITIES. FILE ALL PLANS, OBTAIN ALL PERMITS, PAY ALL FEES, SCHEDULE ALL INSPECTIONS, MAKE ALL TESTS AND OBTAIN ALL APPROVALS REQUIRED. THE ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE LATEST ADOPTED EDITION OF NATIONAL ELECTRIC CODE AND LOCAL AUTHORITIES HAVING JURISDICTION. ALL COMPONENTS SHALL BE UL LISTED.
16. WHERE CONFLICTS ARE FOUND BETWEEN DRAWINGS, SPECIFICATIONS, LAWS & ORDINANCES, THE MOST STRINGENT SHALL APPLY.
17. SUBMIT FOR APPROVAL, COMPLETE SHOP DRAWINGS, LIST OF MATERIALS AND DETAILED DATA OF EQUIPMENT GIVING THE MANUFACTURERS NAME, CATALOG NUMBER, SIZE, CAPACITY AND DIMENSIONS. SUBMIT SHOP DRAWINGS FOR APPROVAL ONLY AFTER VERIFYING ALL DIMENSIONS, CONFIRM THAT THE EQUIPMENT, DEVICES, FIXTURES, ETC. CAN BE INSTALLED WITHOUT MODIFICATIONS. NO EQUIPMENT SHALL BE INSTALLED OR FABRICATED WITHOUT OBTAINING APPROVAL. ANY MODIFICATIONS REQUIRED, SHALL BE PROVIDED AT NO ADDITIONAL COST TO THE OWNER.
18. SUBMIT FOR APPROVAL PRODUCTS THAT ARE APPROVED EQUAL ONLY. IT SHALL BE THE RESPONSIBILITY OF THE ELECTRICAL SUBCONTRACTOR TO VERIFY THAT

ELECTRICAL CABINET

PROVIDE OUTDOOR NE MA 3R STAINLESS STEEL, TO CONTAIN 120/240V PANELBOARDS, RECEPTACLES, ETC. FOR POWER, WITH SPACE FOR FUTURE EQUIPMENT

CONTRACTOR TO SIZE CABINET TO COORDINATE WITH SIZES OF PANELBOARD AND EQUIPMENT TO BE INSTALLED WITHIN CABINETS. DIMENSIONS SHOWN ARE TYPICAL AND ARE FOR REFERENCE ONLY. CABINET TO BE SIMILAR TO CABINETS INSTALLED AT THE RECENTLY RENOVATED PARKS (LIST PROVIDED UPON REQUEST). CABINET TO INCLUDE ALL EQUIPMENT SHOWN OR IMPLIED AND ALL EQUIPMENT SHALL BE INSTALLED INSIDE OF CABINET WITHOUT PHYSICAL CONFLICTS AND PER NEC. CABINET TO BE SIZED FOR ALL NECESSARY CONDUITS, WHETHER ACTIVE, SPARE OR FUTURE AS LISTED ON PANELBOARD SCHEDULES.

CABINETS TO BE MANUFACTURED FROM 11 GAUGE MINIMUM STAINLESS STEEL WITH 12 GAUGE STEEL PANEL, MOUNTED INSIDE. CABINETS TO HAVE INTEGRAL KEYED LOCKING MECHANISM, KEYED ALIKE, WITH PROVISION FOR PAD-LOCK. CABINETS SHALL BE VENTILATED TYPE AND FACTORY PAINTED BLACK POWDER-COAT. CABINETS TO HAVE DOOR HOLD-OPEN LATCHES.

New Panel			MOUNTING SURFACE		VOLTS 240/120V 2P 3W		MAIN BKR 200	
PP			FED FROM UTILITY		BUS AMPS 200		LUGS STANDARD	
			NEUTRAL 100%		AIC 22,000			
CKT #	CKT BKR	CIRCUIT DESCRIPTION	CKT #	CKT BKR	CIRCUIT DESCRIPTION			
1	20/2	MUSCO SPORTS LIGHTS - WIRED VIA MUSCO LIGHTING CONTROLS	a 2	20/1	RECEPTACLE - CAMERA			
3			b 4	20/1	RECEPTACLE - CAMERA			
5	20/2	MUSCO SPORTS LIGHTS - WIRED VIA MUSCO LIGHTING CONTROLS	a 6	20/1	RECEPTACLE - CAMERA			
7			b 8	20/1	RECEPTACLE - CAMERA			
9	20/2	MUSCO SECURITY LIGHTS - WIRED VIA MUSCO LIGHTING CONTROLS	a 10	20/1	RECEPTACLE - CAMERA			
11			b 12	20/1	RECEPTACLE - CAMERA			
13	20/1	PATHWAY LIGHTING - WIRED VIA MUSCO LIGHTING CONTROLS	a 14	20/1	RECEPTACLE - CAMERA			
15			b 16	20/1	RECEPTACLE - CAMERA			
17	20/1	GAZEBO LIGHTING - WIRED VIA MUSCO LIGHTING CONTROLS	a 18	20/1	EXHAUST FAN			
19	20/1	GAZEBO-RECEPTACLE-WIRED VIA MUSCO LIGHTING CONTROLS	b 20	20/1	SPARE			
21	20/1	SPARE	a 22	20/1	SPARE			
23	20/1	SPARE	b 24	20/1	SPARE			
25	20/1	SPARE	a 26	20/1	SPARE			
27	-/1	SPACE	b 28	-/1	SPACE			
29	-/1	SPACE	a 30	-/1	SPACE			
31	-/1	SPACE	b 32	-/1	SPACE			
33	-/1	SPACE	a 34	-/1	SPACE			
35	-/1	SPACE	b 36	-/1	SPACE			
37	-/1	SPACE	a 38	-/1	SPACE			
39	-/1	SPACE	b 40	-/1	SPACE			
41	-/1	SPACE	a 42	-/1	SPACE			



PROJECT: LAKE VIEW PLAYGROUND IMPROVEMENTS


CLIENT:
CITY OF WORCESTER

DATE: 11-22-24




ELECTRICAL DETAILS

SHEET F-10



TYPICAL PRE-CAST CONCRETE HANDHOLE
NOT TO SCALE



TYPICAL HANDHOLE COVER
NOT TO SCALE

NOTES:

- ELECTRIC HANDHOLES ARE TO BE STRONG, LIGHTWEIGHT, AND NON-CONDUCTIVE, AND SHOWN ON THE CONTRACT DRAWINGS. ELECTRIC HANDHOLES SHALL BE ULTRAVIOLET (UV) RESISTANT, ALONG WITH BEING UNAFFECTED BY MOISTURE, FREEZING TEMPERATURES, SOIL, AND SUB-SOIL CHEMICALS. ELECTRIC HANDHOLES TO BE PRECAST CONCRETE, AS APPROVED BY ENGINEER. MINIMUM HANDHOLE SIZE IS 24" W X 36" L X 22" D (INSIDE DIMENSIONS) FOR COMMUNICATION HOLE AND 10" W X 18" X 15" D FOR ELECTRIC HANDHOLES.

2. ELECTRIC HANDHOLES TO BE PRECAST CONCRETE. MINIMUM HANDHOLE SIZE IS 24" W X 36" L X 22" D (INSIDE DIMENSIONS) FOR COMMUNICATION HOLE AND 10" W X 18" X 15" D FOR ELECTRIC HANDHOLES.

3. HANDHOLES SHALL BE PROVIDED WITH CAST IRON COVERS, WITH AN "ELECTRIC" LOGO FOR POWER AND "COMMUNICATIONS" LOGO FOR AUDIO, ETC. HANDHOLES AND COVERS SHALL BE DESIGNED FOR STREET-RATED LOADS (APPROXIMATELY 10,000 POUNDS). DESIGN OF THE STEEL: AASHTO HS-20 OR ANSI/SCTE 77-2002 TIER 15 LOADING, WITH A MINIMUM DESIGN LOAD OF 15,000 LBS FOR BOTH THE HANDHOLE BOX AND COVERS SHALL MEET THE REQUIREMENTS OF THE LAST EDITION OF THE NATIONAL ELECTRIC CODE WITH REGARD TO STRUCTURAL INTEGRITY, INSULATION METHODS, GROUNDING OF THE COVER AND METALLIC PARTS, ETC. HANDHOLES SHALL BE UL LISTED FOR THE INTENDED USE (MOISTURE AND FREEZE RESISTANT AND ABLE TO WITHSTAND SOIL CHEMICALS).


4. COLOR OF ELECTRIC HANDHOLES AND COVERS TO BE GREEN IN GRASS AREAS, AS APPROVED BY ENGINEER. HANDHOLES TO BE INSTALLED PLUSH WITH FINAL GRADE.

5. HANDHOLES FOR TELEPHONE AND CATV ARE TO BE PER THE LOCAL UTILITY REQUIREMENTS, WITH COVER LOGOS PER THE UTILITIES.

6. CONDUITS IN HANDHOLES SHALL BE SWEPT UP USING 45 DEGREE SWEEPS, TERMINATING A MINIMUM OF 4-INCHES ABOVE THE GRAVEL SUB-SURFACE. CONDUITS SHALL ENTER FROM EACH END, BELOW THE BOTTOM OF EACH HANDHOLE, WITHIN AN AREA 1/3 OF THE LENGTH FROM THE END OF THE HANDHOLE.


7. THE ELECTRICAL SUBCONTRACTOR IS RESPONSIBLE FOR FURNISHING AND INSTALLING ALL THE REQUIRED CONDUIT AND WIRING TO THE HANDHOLES.

8. THE ELECTRICAL SUBCONTRACTOR IS RESPONSIBLE FOR FURNISHING PRE-CAST HANDHOLES, TO BE INSTALLED BY GENERAL CONTRACTOR.



NOTES:

- INSTALLATION TYPICAL FOR LANDSCAPED OR PAVED SIDEWALK AREAS. HANDHOLE SHALL NOT BE LOCATED IN TRAFFIC AREAS. COORDINATE COVER AND FRAME COLOR OF HANDHOLE.
- PROVIDE IN-LINE, WATERPROOF FUSE HOLDER-BUSS "TRON", TYPE HEB OR HEX, AS REQUIRED.




PROJECT:
LAKE VIEW
PLAYGROUND
IMPROVEMENTS



CLIENT:
CITY OF WORCESTER

DATE: 11-22-24

REVISIONS:
NO. DATE DESCRIPTION



ELECTRICAL
DETAILS
SHEET E-11



3 SITE LIGHTING / POWER CONDUIT DETAIL

NTS

3

HANDHOLE / CONDUIT AT POLE BASE DETAIL

NTS