

**TECHNICAL SPECIFICATIONS SITEWORK CONSTRUCTION**

**East Park Renovation  
180 Shrewsbury Street  
Worcester, Massachusetts 01604**

*Prepared for:*

**The City of Worcester  
Department of Public Works and Parks  
50 Officer Manny Familia Way  
Worcester, Massachusetts 01605**

*Prepared by:*

**Beals and Thomas, Inc.  
144 Turnpike Road  
Southborough, MA 01772-2104**

**Issue Date: 06/16/2023  
B+T Job Number: 3131.02**

**SITEWORK CONSTRUCTION**

<u>Section No.</u>	<u>Title</u>
024120	SELECTIVE SITE DEMOLITION
033053	MISCELLANEOUS CAST-IN-PLACE CONCRETE
129300	SITE FURNISHINGS
260000	ELECTRICAL
265668	EXTERIOR ATHLETIC LIGHTING
311000	SITE CLEARING
312000	EARTH MOVING
312319	DEWATERING
315000	EXCAVATION SUPPORT AND PROTECTION
321216	ASPHALT PAVING
321313	CONCRETE PAVING
321373	CONCRETE PAVING JOINT SEALANTS
321723	PAVEMENT MARKINGS
323113	CHAIN LINK FENCES AND GATES
323223	SEGMENTAL RETAINING WALLS
328400	IRRIGATION
329200	TURF AND GRASSES
329300	PLANTS
330500	COMMON WORK RESULTS FOR UTILITIES
334200	STORMWATER CONVEYANCE

## SECTION 024120 - SELECTIVE SITE DEMOLITION

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.
- B. Stormwater Pollution Prevention Plan and NPDES Construction General Permit.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Demolition and removal of selected site elements.
  - 2. Salvage of existing items to be reused or recycled.
- B. Related Requirements:
  - 1. Section 311000 "Site Clearing" for site clearing and removal of above- and below-grade improvements not part of selective site demolition

#### 1.3 DEFINITIONS

- A. Remove: Detach items from existing construction and dispose of them off-site unless indicated to be salvaged or reinstalled.
- B. Remove and Salvage: Detach items from existing construction, in a manner to prevent damage, and deliver to Owner ready for reuse.
- C. Remove and Reinstall: Detach items from existing construction, in a manner to prevent damage, prepare for reuse, and reinstall where indicated.
- D. Existing to Remain: Leave existing items that are not to be removed and that are not otherwise indicated to be salvaged or reinstalled.
- E. Dismantle: To remove by disassembling or detaching an item from a surface, using gentle methods and equipment to prevent damage to the item and surfaces; disposing of items unless indicated to be salvaged or reinstalled.

#### 1.4 MATERIALS OWNERSHIP

- A. Unless otherwise indicated, demolition waste becomes property of Contractor.
- B. Historic items, relics, antiques, and similar objects including, but not limited to, cornerstones and their contents, commemorative plaques and tablets, and other items of interest or value to Owner that may be uncovered during demolition remain the property of Owner.
  - 1. Carefully salvage in a manner to prevent damage and promptly return to Owner.

#### 1.5 PREINSTALLATION MEETINGS

- A. Predemolition Conference: Conduct conference at Project site.
  - 1. Inspect and discuss condition of construction to be selectively demolished.
  - 2. Review and finalize selective site demolition schedule and verify availability of materials, demolition personnel, equipment, and facilities needed to make progress and avoid delays.
  - 3. Review requirements of work performed by other trades that rely on substrates exposed by selective site demolition operations.
  - 4. Review areas where existing construction is to remain and requires protection.

#### 1.6 INFORMATIONAL SUBMITTALS

- A. Schedule of Selective Site Demolition Activities: Indicate the following:
  - 1. Detailed sequence of selective site demolition and removal work, with starting and ending dates for each activity.
  - 2. Interruption of utility services. Indicate how long utility services will be interrupted.
  - 3. Coordination for shutoff, capping, and continuation of utility services.
- B. Inventory: Submit a list of items to be removed and salvaged and deliver to Owner prior to start of demolition.
- C. Predemolition Photographs or Video: Show existing conditions of adjoining construction, including finish surfaces, that might be misconstrued as damage caused by demolition operations. Comply with Section 013233 "Photographic Documentation." Submit before Work begins.
- D. Warranties: Documentation indicating that existing warranties are still in effect after completion of selective site demolition.

#### 1.7 CLOSEOUT SUBMITTALS

- A. Inventory: Submit a list of items that have been removed and salvaged.

#### SELECTIVE SITE DEMOLITION

024120 - 2

- B. Landfill Records: Indicate receipt and acceptance of hazardous wastes by a landfill facility licensed to accept hazardous wastes.

## 1.8 FIELD CONDITIONS

- A. Owner will occupy portions of site immediately adjacent to selective site demolition area. Conduct selective site demolition so Owner's operations will not be disrupted.
- B. Conditions existing at time of inspection for bidding purpose will be maintained by Owner as far as practical.
- C. Notify Owner of discrepancies between existing conditions and Drawings before proceeding with selective site demolition.
- D. Hazardous Materials: It is not expected that hazardous materials will be encountered in the Work.
  - 1. If suspected hazardous materials are encountered, do not disturb; immediately notify Owner. Hazardous materials will be removed by Owner under a separate contract.
- E. Storage or sale of removed items or materials on-site is not permitted.
- F. Utility Service: Maintain existing utilities indicated to remain in service and protect them against damage during selective site demolition operations.
  - 1. Maintain fire-protection facilities in service during selective site demolition operations.

## PART 2 - PRODUCTS

### 2.1 PERFORMANCE REQUIREMENTS

- A. Regulatory Requirements: Comply with governing EPA notification regulations before beginning selective site demolition. Comply with hauling and disposal regulations of authorities having jurisdiction.
- B. Standards: Comply with ASSE A10.6 and NFPA 241.

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- A. Verify that utilities have been disconnected and capped before starting selective site demolition operations.

## SELECTIVE SITE DEMOLITION

024120 - 3

- B. Review Project Record Documents of existing construction or other existing condition information provided by Owner. Owner does not guarantee that existing conditions are same as those indicated in Project Record Documents.
- C. Survey existing conditions and correlate with requirements indicated to determine extent of selective site demolition required.
- D. When unanticipated mechanical, electrical, or structural elements that conflict with intended function or design are encountered, investigate and measure the nature and extent of conflict. Promptly submit a written report to Owner.
- E. Survey of Existing Conditions: Record existing conditions by use of preconstruction photographs or video.
  - 1. Inventory and record the condition of items to be removed and salvaged.
  - 2. Before selective site demolition or removal of existing elements that will be reproduced or duplicated in final Work, make permanent record of measurements, materials, and construction details required to make exact reproduction.

### 3.2 UTILITY SERVICES AND MECHANICAL/ELECTRICAL SYSTEMS

- A. Existing Services/Systems to Remain: Maintain services/systems indicated to remain and protect them against damage.
- B. Existing Services/Systems to Be Removed, Relocated, or Abandoned: Locate, identify, disconnect, and seal or cap off utility services and mechanical/electrical systems serving areas to be selectively demolished.
  - 1. Owner will arrange to shut off indicated services/systems when requested by Contractor.
  - 2. Arrange to shut off utilities with utility companies.
  - 3. If services/systems are required to be removed, relocated, or abandoned, provide temporary services/systems that bypass area of selective site demolition and that maintain continuity of services/systems to other parts of site.
  - 4. Disconnect, demolish, and remove fire-suppression systems, plumbing, and HVAC systems, equipment, and components indicated on Drawings to be removed.
    - a. Piping to Be Removed: Remove portion of piping indicated to be removed and cap or plug remaining piping with same or compatible piping material.
    - b. Piping to Be Abandoned in Place: Drain piping and cap or plug piping with same or compatible piping material and leave in place.
    - c. Equipment to Be Removed: Disconnect and cap services and remove equipment.
    - d. Equipment to Be Removed and Reinstalled: Disconnect and cap services and remove, clean, and store equipment; when appropriate, reinstall, reconnect, and make equipment operational.

### SELECTIVE SITE DEMOLITION

024120 - 4

- e. Equipment to Be Removed and Salvaged: Disconnect and cap services and remove equipment and deliver to Owner.
- f. Ducts to Be Removed: Remove portion of ducts indicated to be removed and plug remaining ducts with same or compatible ductwork material.
- g. Ducts to Be Abandoned in Place: Cap or plug ducts with same or compatible ductwork material and leave in place.

### 3.3 PROTECTION

- A. Temporary Protection: Provide temporary barricades and other protection required to prevent injury to people and damage to adjacent buildings and facilities to remain.
  - 1. Provide protection to ensure safe passage of people around selective site demolition area and to and from occupied portions of building.
  - 2. Provide temporary weather protection, during interval between selective site demolition of existing construction on exterior surfaces and new construction, to prevent water leakage and damage to structure and interior areas.
  - 3. Protect work that is to remain or that is exposed during selective site demolition operations.
  - 4. Cover and protect furniture, furnishings, and equipment that have not been removed.
- B. Temporary Shoring: Design, provide, and maintain shoring, bracing, and structural supports as required to preserve stability and prevent movement, settlement, or collapse of construction and finishes to remain, and to prevent unexpected or uncontrolled movement or collapse of construction being demolished.
  - 1. Strengthen or add new supports when required during progress of selective site demolition.
- C. Remove temporary barricades and protections where hazards no longer exist.

### 3.4 SELECTIVE SITE DEMOLITION, GENERAL

- A. General: Demolish and remove existing construction only to the extent required by new construction and as indicated. Use methods required to complete the Work within limitations of governing regulations and as follows:
  - 1. Proceed with selective site demolition systematically, from higher to lower level.
  - 2. Neatly cut openings and holes plumb, square, and true to dimensions required. Use cutting methods least likely to damage construction to remain or adjoining construction. Use hand tools or small power tools designed for sawing or grinding, not hammering and chopping. Temporarily cover openings to remain.
  - 3. Cut or drill from the exposed or finished side into concealed surfaces to avoid marring existing finished surfaces.

4. Do not use cutting torches until work area is cleared of flammable materials. At concealed spaces, such as duct and pipe interiors, verify condition and contents of hidden space before starting flame-cutting operations. Maintain portable fire-suppression devices during flame-cutting operations.
  5. Maintain adequate ventilation when using cutting torches.
  6. Remove decayed, vermin-infested, or otherwise dangerous or unsuitable materials and promptly dispose of off-site.
  7. Locate selective site demolition equipment and remove debris and materials so as not to impose excessive loads on supporting walls, floors, or framing.
  8. Dispose of demolished items and materials promptly.
- B. Site Access and Temporary Controls: Conduct selective site demolition and debris-removal operations to ensure minimum interference with roads, streets, walks, walkways, and other adjacent occupied and used facilities.
- C. Removed and Salvaged Items:
1. Clean salvaged items.
  2. Pack or crate items after cleaning. Identify contents of containers.
  3. Store items in a secure area until delivery to Owner.
  4. Transport items to Owner's storage area designated by Owner.
  5. Protect items from damage during transport and storage.
- D. Removed and Reinstalled Items:
1. Clean and repair items to functional condition adequate for intended reuse.
  2. Pack or crate items after cleaning and repairing. Identify contents of containers.
  3. Protect items from damage during transport and storage.
  4. Reinstall items in locations indicated. Comply with installation requirements for new materials and equipment. Provide connections, supports, and miscellaneous materials necessary to make item functional for use indicated.
- E. Existing Items to Remain: Protect construction indicated to remain against damage and soiling during selective site demolition. When permitted by Owner, items may be removed to a suitable, protected storage location during selective site demolition and cleaned and reinstalled in their original locations after selective site demolition operations are complete.
- 3.5 SELECTIVE SITE DEMOLITION PROCEDURES FOR SPECIFIC MATERIALS
- A. Concrete: Demolish in sections. Cut concrete full depth at junctures with construction to remain and at regular intervals using power-driven saw, and then remove concrete between saw cuts.
- B. Masonry: Demolish in small sections. Cut masonry at junctures with construction to remain, using power-driven saw, and then remove masonry between saw cuts.



- C. Concrete Slabs-on-Grade: Saw-cut perimeter of area to be demolished, and then break up and remove.

### 3.6 DISPOSAL OF DEMOLISHED MATERIALS

- A. Remove demolition waste materials from Project site and dispose of them in an EPA-approved construction and demolition waste landfill acceptable to authorities having jurisdiction.
  - 1. Do not allow demolished materials to accumulate on-site.
  - 2. Remove and transport debris in a manner that will prevent spillage on adjacent surfaces and areas.
- B. Burning: Do not burn demolished materials.

### 3.7 CLEANING

- A. Clean adjacent structures and improvements of dust, dirt, and debris caused by selective demolition operations. Return adjacent areas to condition existing before selective site demolition operations began.

### 3.8 SELECTIVE SITE DEMOLITION SCHEDULE

- A. Remove: Dead or leaning trees, bituminous concrete pavement, cape cod berm, portion of encroaching fence, chain link fence, and specified trees beyond limit of clearing as indicated in Project Record Documents.
- B. Remove and Salvage: East-west trail sign to the east of the site as indicated in Project Record Documents.
- C. Remove and Reinstall: Utility poles and associated overhead wires, and sewer manhole covers as indicated in Project Record Documents.
- D. Existing to Remain: Encroaching wood deck, hydrants, utility poles, water services, east-west trail sign to the west of the site, and sewer services as indicated in Project Record Documents.

END OF SECTION 024120

## SECTION 033053 - MISCELLANEOUS CAST-IN-PLACE CONCRETE

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section includes cast-in-place concrete, labor and equipment, reinforcement, concrete materials, mixture design, placement procedures, and finishes for the following site improvements:
  - 1. Concrete mow-strip
  - 2. Concrete curb
  - 3. Fence footings
  - 4. Site furnishings concrete pads and footings
- B. Related Sections:
  - 1. Section 312000 "Earth Moving" for drainage fill under slabs-on-grade.

#### 1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product indicated.
- B. Other Action Submittal:
  - 1. Design Mixtures: For each concrete mixture.

#### 1.4 QUALITY ASSURANCE

- A. Ready-Mix-Concrete Manufacturer Qualifications: A firm experienced in manufacturing ready-mixed concrete products and that complies with ASTM C 94/C 94M requirements for production facilities and equipment.
- B. Comply with the following sections of ACI 301, unless modified by requirements in the Contract Documents:
  - 1. "General Requirements."
  - 2. "Formwork and Formwork Accessories."

## MISCELLANEOUS CAST-IN-PLACE CONCRETE

033053 - 1

3. "Reinforcement and Reinforcement Supports."
4. "Concrete Mixtures."
5. "Handling, Placing, and Constructing."
6. "Lightweight Concrete."

- C. Comply with ACI 117, "Specifications for Tolerances for Concrete Construction and Materials."

## PART 2 - PRODUCTS

### 2.1 FORMWORK

- A. Furnish formwork and formwork accessories according to ACI 301.

### 2.2 STEEL REINFORCEMENT

- A. Recycled Content of Steel Products: Postconsumer recycled content plus one-half of pre-consumer recycled content not less than 25 percent.
- B. Reinforcing Bars: ASTM A 615/A 615M, Grade 60, deformed.
- C. Plain-Steel Wire: ASTM A 82/A 82M, as drawn.
- D. Plain-Steel Welded Wire Reinforcement: ASTM A 185/A 185M, fabricated from as-drawn steel wire into flat sheets.
- E. Deformed-Steel Welded Wire Reinforcement: ASTM A 497/A 497M, flat sheet.

### 2.3 CONCRETE MATERIALS

- A. Cementitious Material: Use the following cementitious materials, of the same type, brand, and source throughout Project:
1. Portland Cement: ASTM C 150, Type I.
- B. Normal-Weight Aggregate: ASTM C 33, graded, 1-1/2-inch nominal maximum aggregate size.
- C. Water: ASTM C 94/C 94M.

### 2.4 ADMIXTURES

- A. Air-Entraining Admixture: ASTM C 260.

## MISCELLANEOUS CAST-IN-PLACE CONCRETE

033053 - 2

- B. Chemical Admixtures: Provide admixtures certified by manufacturer to be compatible with other admixtures and that will not contribute water-soluble chloride ions exceeding those permitted in hardened concrete. Do not use calcium chloride or admixtures containing calcium chloride.
1. Water-Reducing Admixture: ASTM C 494/C 494M, Type A.
  2. Retarding Admixture: ASTM C 494/C 494M, Type B.
  3. Water-Reducing and Retarding Admixture: ASTM C 494/C 494M, Type D.
  4. High-Range, Water-Reducing Admixture: ASTM C 494/C 494M, Type F.
  5. High-Range, Water-Reducing and Retarding Admixture: ASTM C 494/C 494M, Type G.
  6. Plasticizing and Retarding Admixture: ASTM C 1017/C 1017M, Type II.

## 2.5 CURING MATERIALS

- A. Evaporation Retarder: Waterborne, monomolecular film forming; manufactured for application to fresh concrete.

## 2.6 CONCRETE MIXTURES

- A. Comply with ACI 301 requirements for concrete mixtures.
- B. Normal-Weight Concrete: Prepare design mixes, proportioned according to ACI 301, as follows:
1. Minimum Compressive Strength: 4000 psi at 28 days.
  2. Maximum Water-Cementitious Materials Ratio: 0.45.
  3. Slump Limit: 4 inches, plus or minus 1 inch.
  4. Air Content: Maintain within range permitted by ACI 301.

## 2.7 CONCRETE MIXING

- A. Ready-Mixed Concrete: Measure, batch, mix, and deliver concrete according to ASTM C 94/C 94M and furnish batch ticket information.
1. When air temperature is above 90 deg F, reduce mixing and delivery time to 60 minutes.
- B. Project-Site Mixing: Measure, batch, and mix concrete materials and concrete according to ASTM C 94/C 94M. Mix concrete materials in appropriate drum-type batch machine mixer.
1. For mixer capacity of 1 cu. yd. or smaller, continue mixing at least 1-1/2 minutes, but not more than 5 minutes after ingredients are in mixer, before any part of batch is released.
  2. For mixer capacity larger than 1 cu. yd., increase mixing time by 15 seconds for each additional 1 cu. yd..

## MISCELLANEOUS CAST-IN-PLACE CONCRETE

033053 - 3

3. Provide batch ticket for each batch discharged and used in the Work, indicating Project identification name and number, date, mix type, mix time, quantity, and amount of water added. Record approximate location of final deposit in structure.

## PART 3 - EXECUTION

### 3.1 FORMWORK

- A. Design, construct, erect, brace, and maintain formwork according to ACI 301.

### 3.2 EMBEDDED ITEMS

- A. Place and secure anchorage devices and other embedded items required for adjoining work attached to or supported by cast-in-place concrete. Use setting drawings, templates, diagrams, instructions, and directions furnished with items to be embedded.

### 3.3 STEEL REINFORCEMENT

- A. Comply with CRSI's "Manual of Standard Practice" for fabricating, placing, and supporting reinforcement.

### 3.4 CONCRETE PLACEMENT

- A. Comply with ACI 301 for placing concrete.
- B. Before test sampling and placing concrete, water may be added at Project site, subject to limitations of ACI 301.
- C. Do not add water to concrete during delivery, at Project site, or during placement.
- D. Consolidate concrete with mechanical vibrating equipment.

### 3.5 CONCRETE PROTECTING AND CURING

- A. General: Protect freshly placed concrete from premature drying and excessive cold or hot temperatures. Comply with ACI 306.1 for cold-weather protection and with ACI 301 for hot-weather protection during curing.
- B. Evaporation Retarder: Apply evaporation retarder to concrete surfaces if hot, dry, or windy conditions cause moisture loss approaching 0.2 lb/sq. ft. x h before and during finishing operations. Apply according to manufacturer's written instructions after placing, screeding, and bull floating or darbying concrete, but before float finishing.

## MISCELLANEOUS CAST-IN-PLACE CONCRETE

033053 - 4

- C. Begin curing after finishing concrete but not before free water has disappeared from concrete surface.
- D. Curing Methods: Cure formed and unformed concrete for at least seven days:
  - 1. Curing Compound: Apply uniformly in continuous operation by power spray or roller according to manufacturer's written instructions. Recoat areas subjected to heavy rainfall within three hours after initial application. Maintain continuity of coating and repair damage during curing period.

### 3.6 FIELD QUALITY CONTROL

- A. Testing Agency: Engage a qualified testing agency to perform tests and inspections.
- B. Tests: Perform according to ACI 301.
  - 1. Testing Frequency: One composite sample shall be obtained for each day's pour of each concrete mix exceeding 5 cu. yd. but less than 25 cu. yd., plus one set for each additional 50 cu. yd. or fraction thereof.

### 3.7 REPAIRS

- A. Remove and replace concrete that does not comply with requirements in this Section.

END OF SECTION 033053

## SECTION 129300 - SITE FURNISHINGS

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Bike Rack
  - 2. Trash Receptacles
  - 3. Player Benches
  - 4. Bleachers

#### 1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product.
  - 1. Bike Rack
  - 2. Trash receptacles
  - 3. Player Benches
  - 4. Bleachers
- B. Samples: For each exposed product and for each color and texture specified.
- C. Samples for Initial Selection: For units with factory-applied finishes.
- D. Shop Drawings: Shop drawings or manufacturer's specifications shall be submitted for all work furnished in this Section, in accordance with the provisions of the Special Conditions Section of the Contract Specifications.

#### 1.4 CLOSEOUT SUBMITTALS

- A. Maintenance Data: For site furnishings to include in maintenance manuals.

1.5 WARRANTY/GUARANTEE

- A. The Contractor/Manufacturer's Representative shall provide information on the equipment manufacturer's warranty/guarantee with bid.

PART 2 - PRODUCTS

2.1 HARDWARE AND FASTENERS:

- A. All hardware and fasteners shall be zinc-coated, except for reinforcing bars. Nuts and bolts shall be Grade A steel, hexagon-type. Washers shall be carbon steel.

2.2 SITE FURNISHINGS

- A. 1 Bike Rack: Shall be furnished by the Owner and to be installed by the Contractor as indicated on Drawings.
- B. 2 Trash Receptacles: This shall be City Standard surface-mounted model 84-32-BT, black color, by DuMor Site Furnishings, Inc., Mifflintown, PA (phone #800-598-4018) or approved equal.
- C. 2 Player Benches: This shall be 24' direct bury "DD" Permanent In-ground Square Tube Bench model BE-DD02400 by National Recreation Systems or approved equal.
- D. 1 ADA Bleacher: This shall be Non-Elevated Aluminum 5 Row x 24'-0" Bleachers model NA-0524DLX\_CL by National recreation Systems or approved equal.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine areas and conditions, with Installer present, for compliance with requirements for correct and level finished grade, mounting surfaces, installation tolerances, and other conditions affecting performance of the Work.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

SITE FURNISHINGS

129300 - 2



### 3.2 INSTALLATION, GENERAL

- A. Comply with manufacturer's written installation instructions unless more stringent requirements are indicated. Complete field assembly of site furnishings where required.
- B. Unless otherwise indicated, install site furnishings after landscaping and paving have been completed.
- C. Install site furnishings level, plumb, true, and securely anchored at locations indicated on Drawings.
- D. Post Setting: Set cast-in support posts in concrete footing with smooth top, shaped to shed water. Protect portion of posts above footing from concrete splatter. Verify that posts are set plumb or at correct angle and are aligned and at correct height and spacing. Hold posts in position during placement and finishing operations until concrete is sufficiently cured.
- E. Site Furnishings: Assemble furnishings in accordance with manufacturer's written instructions and install in accordance with the Drawings.

END OF SECTION 129300

**SECTION 26 00 00**  
**ELECTRICAL**

**PART 1 - GENERAL**

**1.01 DESCRIPTION**

- A. The City of Worcester Bid Form, General Conditions, Supplementary Conditions, and applicable parts of the Special Conditions form a part of this Specification and the Contractor shall consult them in detail for instructions.
- B. The Contractor shall provide all labor, equipment, and materials; and perform all operations necessary to complete the work of this section as indicated on the Drawings and specified herein which shall include but is not limited to the following:
  - 1. Parking area lighting
  - 2. Security lighting
  - 3. Security camera system
  - 4. All other work shown on the Drawings and included in these Specifications
- C. The Contractor shall furnish a complete, working finished product, which meets all applicable codes and standards, and the intent and specific requirements of the Drawings and specifications for this project. All materials and all work, which may be reasonably implied as being incidental to the work of this Section, shall be furnished at no extra cost to the Owner.

**1.02 RELATED WORK SPECIFIED IN OTHER SECTIONS**

- A. Section 32 12 16 – Bituminous Concrete
- B. Section 03 30 53 – Cast-in-Place Concrete

**1.03 RELATED DOCUMENTS**

- A. Drawings and general provisions of Contract, including General and Supplementary Conditions, apply to work of this section.
- B. The Contractor must be familiar with all other Sections of this specifications and the associated Drawings, which affect the scope of work. The General Conditions, all Supplementary and Special Conditions, and all other sections of this specification shall be adhered to, as they apply to this Section. Where paragraphs of this Section conflict with similar paragraphs elsewhere, the more stringent requirements shall prevail.

**1.04 REFERENCE STANDARDS AND SPECIFICATIONS**

- A. Perform work strictly as required by rules, regulations, standards, codes, ordinances,

and laws of local, state, and federal government, and other authorities that have lawful jurisdiction.

- B. All materials and installations shall be in accordance with the latest edition of the Massachusetts Electrical Code, and all applicable local codes and ordinances. Materials and equipment shall be listed by Underwriters Laboratories (UL).
- C. Except as modified by governing codes and by the Contract Documents, the Contractor shall comply with applicable provisions and recommendations of the following:
  - 1. American National Standards Institute - ANSI
  - 2. American Society for Testing & Materials - ASTM
  - 3. Illuminating Engineering Society - IES
  - 4. Institute of Electrical & Electronics Engineers - IEEE
  - 5. Insulated Cable Engineers' Association - ICEA
  - 6. National Electrical Code - NEC
  - 7. National Electrical Manufacturer's Association - NEMA
  - 8. National Electrical Safety Code - NESC
  - 9. InterNational Electrical Testing Association - NETA
  - 10. National Fire Protection Association - NFPA
  - 11. Occupational Safety & Health Administration - OSHA
  - 12. Underwriter's Laboratories, Inc. - UL

The above listed codes and standards are referenced to establish minimum requirements and wherever this Section requires higher grades of materials and workmanship than required by the listed codes and standards, this Section shall apply. In the event a conflict occurs between the above listed codes and standards and this Section, the more stringent requirement shall govern.

#### **1.05 SITE VISIT**

- A. Each bidder shall visit the site of the proposed work and fully acquaint himself with the conditions there relating to construction and labor, and should fully inform himself as to the facilities involved, and the difficulties and restrictions attending the performance of the Contract.
- B. The Bidder shall thoroughly examine and familiarize himself with Drawings, Technical Specifications and all other Bid and Contract Documents. The Contractor, by the execution of the Contract, shall in no way be relieved of any obligation under it due to his failure to receive or examine any form or legal document or to visit the site and acquaint himself with the conditions there existing and the Owner will be justified in rejecting any claim thereof.

#### **1.06 AS-BUILT DRAWINGS:**

- A. After completion of the electrical installation, the Contractor shall furnish an "as-built" drawings showing all conduits, cables, cabinets, transformers, light poles, etc. to scale with dimensions where required. Instruction sheets and parts lists covering all operating equipment will be bound into a folder and furnished to the Owner in duplicate.

**1.07 INSTRUCTIONS:**

- A. Within 10 days, after completion and testing of the system, the Contractor shall instruct the Owner's personnel in the proper operations and maintenance of the system, in a 2 hour training session.
- B. The Contractor shall furnish at least two (2) complete sets of operating and instruction manuals for the equipment provided under this Contract. These manuals shall detail the operation, testing, and maintenance of the electrical equipment and systems. Manuals shall be provided upon Engineer's request or upon project completion, whichever comes first.

**1.08 GUARANTEE**

- A. Guarantee work of this Section in writing for one year from date of Owner's acceptance. Repair or replace defective materials, equipment, workmanship, and installation that develop within this period, promptly and to Owner's satisfaction and correct damage caused in making necessary repairs or replacements under guarantee with no extra cost to Owner. Contractor shall transfer all equipment warranties for lighting and other systems to Owner.

**1.09 SUBMITTALS**

- A. Within 10 days after Award of General Contract, submit shop drawings and product data on below listed items for approval. Submit copies as requested.
- B. Check, stamp and mark with project name shop drawings and product data before submitting for approval. Specifically indicate on shop drawing transmittal form or by separate letter any deviations from Contract Documents because of standard shop practice or other reason. Rectify with no extra cost to Owner, deviations which escape Engineer's scrutiny and have not been indicated on shop drawings.
- C. List of materials and equipment requiring shop drawings shall include:
  - 1. Conduits and Wiring
  - 2. Panelboards
  - 3. Service Cabinets and Equipment
  - 4. Transformer Foundations
  - 5. Meter Sockets
  - 6. Circuit Breakers
  - 7. Concrete Products and Light Bases
  - 8. Wiring Devices and Receptacles
  - 9. Pathway Lighting

## 10. Handholes

The Engineer's review shall be only for conformance with the design concept of the project and compliance with the specifications and Drawings. The responsibility of, and the necessity of, furnishing materials and workmanship required by the specifications and Drawings which may not be indicated on the shop drawings is included under the work of this Section.

### 1.10 INSPECTIONS AND FEES

- A. Obtain all necessary permits and licenses, file necessary plans and pay all fees for permits and inspections. Permit fees are the responsibility of the Contractor as part of his bid, as is all coordination with the municipality and the local utility National Grid.

### 1.11 INTERPRETATION OF DRAWINGS

- A. Drawings are diagrammatic and indicate general arrangement of systems and work included in Contract. Drawings are not intended to specify or show every offset, fitting or component; however, Contract Documents require components and materials whether or not indicated or specified as necessary to make installation complete and operational.
- B. Contractor is responsible for all work shown on both Contract Drawings and these written specifications, including work detailed in the specifications and not shown on the drawings and including work shown on the Drawings and not described in the specifications. All ancillary equipment necessary for a complete installation shall be included, even if not shown, detailed or described. For conflicts between the Contract Drawings, written specifications and other contract information, the more stringent requirement shall apply, and the Engineer may direct the Contractor as to what is the preferred option to be provided.
- C. Any work installed contrary to, or without review by, the Engineer shall be subject to change as directed by the Engineer, and no extra compensation will be allowed for making these changes.
- D. Circuit layouts are not intended to show the number of fittings, or other installation details. Additional circuits shall be installed wherever needed to conform to the specific requirements of the equipment or local codes.
- E. As work progresses and for duration of Contract, maintain complete and separate set of prints of Contract Drawings at job site at all times. Record work completed and all changes from original Contract Drawings clearly and accurately, including work installed as a modification or addition to the original design.

### 1.12 ELECTRIC UTILITY

- A. The Electric Utility for this project is National Grid (Massachusetts Electric Company). All

coordination with the Electric Utility is the responsibility of the Contractor, All work and materials for the electric service shall be in accordance with the requirements of the Electric Utility, and are to be met under this Section and included in the bid price of the Contractor, (removal of existing service).

## **PART 2 – MATERIALS & PRODUCTS**

### **2.01 GENERAL**

- A. Materials and products furnished shall be designed for the intended use, shall meet all requirements of the latest edition of the National Electric Code (NEC), and all local codes.
- B. Materials shall be manufactured in accordance with the standards indicated in this Section, and typical industry standards and codes for the products specified. Materials and equipment shall be Underwriter's Laboratory (UL) listed.
- C. The materials used shall be new, unused, and of the best quality for the intended use. All equipment shall have the manufacturer's name, address, model or type designation, serial number and all applicable ratings clearly marked thereon in a location which can be readily observed after installation. The required information should be marked on durable nameplates that are permanently fastened to the equipment.
- D. Electrical equipment shall at all times during construction be adequately protected against mechanical injury or damage by water. Electrical equipment shall not be stored outside exposed to the elements. If any equipment or apparatus is damaged, such damage shall be repaired at no additional cost, or replaced at no additional cost as directed by the Engineer.

### **2.02 RACEWAYS**

- A. Rigid Metallic Conduit: Listed to Underwriters Laboratories Safety Standard UL6 and ANSI 080.1.
- B. Electrical Metallic Tubing (EMT) Listed to Underwriters Laboratories Safety Standard UL 797 Manufactured in accordance with ANSI C80.3
- C. Flexible Metallic Conduit: UL I. Liquidtight flexible metal conduit shall be used in wet locations.
- D. Polyvinyl Chloride (PVC) Conduit, electrical, gray, Schedule 40 or Schedule 80 as specified, meeting the requirements of UL 651 and NEMA TC-2. If concrete encasement is required, a minimum of 3,000 psi concrete shall be used. All conduits placed under roadways, and subject to vehicular traffic, shall be concrete-encased Schedule 40 (or Schedule 80 as approved).
- E. Minimum size of conduit shall be 3/4". Unless indicated on Drawings, conduit sizes can

be sized in accordance with National Electric Code (NEC). Conduit bends shall not have kinks or flats, and shall not be less than standard radii.

- F. Rigid Galvanized Steel (RGS) conduit shall be used for all power, control signal, and instrumentation wiring, except where noted. Conduit shall be fully threaded at both ends and each length shall be furnished with one threaded coupling. All 90 degree conduit sweeps shall be RGS.
- G. Conduits shall be made electrically continuous at coupling and connections to boxes and cabinets by means of joining fasteners or copper bond wires. Conduit shall be connected to grounded structural steel or the ground network. After assembly all conduit locknuts, all EMT coupling fittings, and all bond wire screws shall be set up tight before installation of wiring. Insulated metallic bushings shall be used on all conduits entering panel cabinets, pull-boxes, and wiring gutters, except on branch lighting circuits.
- H. Expansion fittings shall be provided on all conduits as required by the 2020 National Electrical Code, and as required by local and state codes. This includes, but is not limited to, vertical conduit risers coming from below-grade.

### **2.03 WIRE AND CABLE**

- A. Unless otherwise noted, conductors for power, lighting, and grounding above grade shall be No. 12 through No. 8 AWG, NEC type THWN/THHN, meeting the requirements of UL 83. Conductors for power and lighting shall be no smaller than No. 12 AWG.
- B. Conductors for power, lighting, grounding, and control below grade (and in wet locations) shall be No. 2 AWG and larger, NEC type XHHW (or XHHW-2), meeting the requirements of NEMA WC7 and ICEA S-66-524.
- C. All conductors shall be annealed copper, 98% conductivity, Class B stranded, except conductors used for power and lighting circuits No. 10 AWG and smaller which may be solid. All conductors should be rated for 600 volts or less, with a thermal rating of 90° C.

### **2.04 WIRE AND CABLE CONNECTORS AND DEVICES**

- A. Wire and cable connectors and devices shall meet the requirements of UL 486. Connectors, including miscellaneous nuts, bolts, and washers shall be silicon bronze. Ferrous materials shall not be used.

### **2.05 BOXES**

- A. Outlet and Switch Boxes: NEMA OS 1.
- B. Pull Boxes, Junction Boxes, and Equipment Enclosures: NEMA ICS 6. Pull boxes, junction boxes, and equipment enclosures shall be of NEMA Type I construction for indoor use, and NEMA Type 3R construction for outdoor or wet location use, unless otherwise noted.

- C. Box sizes shall not be less than that required by the Massachusetts Electrical Code.

## **2.06 WARNING TAPE**

- A. Warning tape shall be six (6) inches wide, polyethylene not less than 3.5 mil thick with a minimum strength of 1,500 psi. Install 8 inches below final grade. Tape shall be red for electric conduit, and red or yellow for communication conduit. Tape shall have black lettering on two lines as indicated below:

- B. For Electric conduit:

**CAUTION CAUTION CAUTION  
BURIED ELECTRIC LINE BELOW**

- C. For Telephone, Fire Alarm and Communication conduit:

**CAUTION.CAUTION.CAUTION  
BURIED COMMUNICATION LINE BELOW**

## **2.07 PANELBOARDS**

- A. Panelboards: NEMA PBI, and UL 67. Panelboards shall be door-in-door construction with copper bus. Circuit breakers shall be molded case, thermal magnetic, bolt-on type rated as noted, and rated to match panelboard voltage and interrupting rating. Provide circuit breaker sizes as shown on panel schedules. Provide spare breakers in sizes as directed by Owner or Engineer to fill each panel with spare breakers, above those indicated on panel schedules.

- B. The Contractor shall provide the following panelboards:

Panelboard P-1 120/240V, 1-phase, 3-wire, 250A main circuit breaker, 22kA A1C 30 circuit panelboard, (NEMA 1 enclosure with the number and size of circuit breakers as listed on the panel schedules provided in the Contract Drawings.

## **2.08 ELECTRICAL ENCLOSURE & CABINETS**

- A. The Contractor shall provide outdoor NEMA 3R stainless steel, to contain 120/240V panelboards, receptacles, etc. for power, with space for future equipment.
- B. Contractor shall size cabinet to coordinate with sizes of panelboard and equipment to be installed within cabinets. Dimensions shown are typical and are for reference only. Cabinet shall be similar to cabinets installed at the recently renovated Parks (list provided upon request). Cabinet shall include all equipment shown or implied and all equipment shall be installed inside of cabinet without physical conflicts and per NEC, Cabinet shall be sized for all necessary conduits, whether active, spare or future as listed on panelboard schedules.



- C. Cabinets shall be manufactured from 11 gauge minimum stainless steel with 12 gauge steel panel, mounted inside. Cabinets to have integral keyed locking mechanism, keyed alike, with provision for pad-lock. Cabinets shall be ventilated type and factory painted black powder-coat. Cabinets shall have door hold-open latches.

## **2.09 ELECTRIC HANDHOLES**

- A. Electric Handholes shall be strong, precast concrete and provided in the dimensions as shown on the Contract Drawings. Electric Handholes shall be unaffected by moisture, freezing temperatures, soil, and sub-soil chemicals.
- B. Handholes shall be provided with skid-resistant surface covers, with an Electric or Communications label for power, audio, etc. Handholes and Covers shall be designed for street-rated, heavy duty applications, meeting the requirements of the either: AASHTO HS-20 or ANSI/SCTE 77-2002 Tier 15 loading, with a minimum design load of 15,000 lbs. for both the handhole box and cover. Covers shall include recessed stainless steel captive bolts of a penta-head design. The nuts for the bolts shall be self-centering and corrosion resistant. Handholes shall meet the requirements of the latest edition of the National Electric Code (2020 or later) with regards to structural integrity, installation methods, grounding of the cover and metallic parts, etc. Handholes shall be UL listed for the intended use.
- C. Handholes shall be installed flush with final grade.

## **2.10 CAST-IN-PLACE CONCRETE FOUNDATIONS**

- A. The Contractor shall provide the materials, labor, and equipment necessary for the installation of cast-in-place concrete foundations, in accordance with these Specifications, Contract Drawings, City requirements, and all applicable codes & regulations.

## **2.11 SECURITY CAMERA SYSTEM**

- A. The Contractor shall provide a security camera system in accordance with City Requirements.

# **PART 3 - EXECUTION**

## **3.01 GENERAL**

- A. This Section covers the requirements for installation of materials, proper workmanship, testing, cleaning, grounding, and work methods to be followed by the Contractor. This Section also includes specific instructions and to be used in conjunction with the contract Drawings.
- B. Contractor is responsible for coordinating work with other trades, Owner, and Architect's schedule. Work will be coordinated such that systems can be properly

located, and conflicts and delays are avoided. Contractor shall consider commencement of work acceptance of existing conditions.

### **3.02 MATERIALS AND WORKMANSHIP**

- A. Work shall be executed in workmanlike manner and shall present neat, rectilinear and mechanical appearance when completed. Do not run raceway exposed unless shown exposed on Drawings. Material and equipment shall be new and installed according to manufacturer's recommended best practice so that complete installation shall operate safely and efficiently.

### **3.03 TESTING, INSPECTION AND CLEANING**

- A. Test wiring and connections for continuity and grounds before fixtures are connected; demonstrate insulation resistance by megger test as required at not less than 500 volts. Insulation resistance between conductors and grounds for secondary distribution systems shall meet National Electrical Code (NEC) and InterNational Electrical Testing Association (NETA) requirements.
- B. Verify and correct as necessary: voltages, tap settings, trip settings and phasing on equipment from secondary distribution system to point of use. Test secondary voltages at transformers, bus in panelboards, and at other locations on distribution systems as necessary. Test secondary voltages under no-load and full-load conditions.
- C. Test lighting fixtures with specified lamps in place for 100 hours. Replace lamps that fail within 90 days after acceptance by Owner at no extra cost to Owner (no exceptions).
- D. Provide necessary testing equipment and testing services.
- E. Failures or defects in workmanship or materials revealed by tests or inspection shall be corrected promptly and retested. Replace defective Material.
- F. Clean panels and other equipment, Panelboard interiors shall be cleaned and vacuumed. Equipment with damage to painted finish shall be repaired to Engineer's or Architect's satisfaction. After completion of project, clean exterior surfaces of electrical equipment.

### **3.04 WIRING METHODS**

- A. Install wire and cables in approved raceways as specified and as approved by authorities that have jurisdiction.
- B. Follow homerun circuit numbers and/or notes as shown on drawings to connect circuits to panelboards. Where homerun circuit numbers are not shown on Drawings, divide similar types of connected leads among phase buses so that currents are approximately equal in normal usage.
- C. Run concealed conduit in as direct lines as possible with a minimum number of bends,

longest possible radius. Run exposed conduit parallel to or at right angles to building/field lines. Bends shall be free from dents or flattening. The exact locations and routing shall be determined by the Contractor subject to the approval of the Owner and Engineer.

- D. Polarity of all electrical connections shall be observed in order to preserve phase relationship in all feeders and equipment.
- E. Splices shall be made in neat, workmanlike manner using approved mechanical connectors. After splicing, insulation equal to that on the spliced wires shall be applied at each splice. Splices are permitted only in junction boxes, outlet boxes, or other permanently accessible locations. Splices installed in electric handholes shall be weather and waterproof, pre-molded polymer splices. Hand taping of splices below-grade is not acceptable.

### **3.05 GROUNDING**

- A. Bond and ground equipment and systems connected under this Section in accordance with standards of the NEC and other applicable regulations and codes.
- B. Conduit system shall be electrically continuous throughout, grounded at service entrance. Equipment frames, enclosures, boxes, etc. shall be grounded by use of green-jacketed (or bare copper) ground sized as per Table 250-95 oldie NEC.
- C. Copper fittings for ground connections shall conform to the requirements of ASTM B 30. All bolts, u-bolts, cap screws, nuts, and lock washers for copper fitting shall be of approved corrosion-resisting material. Compression connectors required for all below-grade grounding connections.
- D. Ground Rods shall be 5/8" diameter and 8' in length, copperweld as required by applicable codes (NEC, NESC). Bonding connections to ground rods shall be permanent, welded or crimped, with copper connectors. All wire used for grounding shall be no smaller than #4 Awg copper, stranded conductor.

### **3.06 INSTALLATION OF ELECTRICAL EQUIPMENT**

- A. Contractor shall furnish and install the following major electrical components, and all necessary minor and expected accessories.
- B. Provide, furnish and install all products and work outlined in Part 1 of this Specification Section.
- C. Provide new conduit system for lighting and electrical work, in locations as shown on Contract Drawings. Utilize existing empty conduits (installed by others) where possible and install new conduits for a complete and functional system. Provide all new cabling for all electrical equipment listed.
- D. Install all equipment in locations as shown on Contract Drawings. All deviations must be

approved, in advance by Owner, Landscape Architect, and Engineer.

- E. Install all equipment per manufacturer's instructions.
- F. Balance the lighting, receptacle, and electrical load evenly on all circuits and on all phases of each circuit.
- G. Clean-up excavated areas, and restore with new loam & seed, as directed by Owner.
- H. Provide complete "As-Built" drawings to Engineer & Owner.

**3.07 INSTALLATION OF SECURITY CAMERA SYSTEM**

- A. The security camera system shall be installed in accordance with City Requirements, and with the Drawings and this Section.

**3.08 GUARANTEE AND ACCEPTANCE**

- A. Any defective elements shall be replaced in part or whole by the Contractor at no cost to the Owner.

**END OF SECTION**

## SECTION 26 56 68 – EXTERIOR ATHLETIC LIGHTING

### PART 1 – GENERAL

#### 1.1 SUMMARY

- A. Work covered by this section of the specifications shall conform to the contract documents, engineering plans as well as state and local codes.
- B. The purpose of these specifications is to define the lighting system performance and design standards for East Park using an LED Lighting source. The manufacturer / contractor shall supply lighting equipment to meet or exceed the standards set forth in these specifications.
- C. The sports lighting will be for the following venues:
  - 1. Baseball Field
- E. The primary goals of this sports lighting project are:
  - 1. Guaranteed Light Levels: Selection of appropriate light levels impact the safety of the players and the enjoyment of spectators. Therefore, light levels are guaranteed to not drop below specified target values for a period of 25 years.
  - 2. Environmental Light Control: It is the primary goal of this project to minimize spill light to adjoining properties and glare to the players, spectators, and neighbors. The LED design should provide better control than a good HID design.
  - 3. Life-cycle Cost: In order to reduce the operating budget, the preferred lighting system shall be energy efficient and cost effective to operate. All maintenance costs shall be eliminated for the duration of the warranty.
  - 4. Control and Monitoring: To allow for optimized use of labor resources and avoid unneeded operation of the facility, customer requires a remote on/off control system for the lighting system. Fields should be proactively monitored to detect luminaire outages over a 25-year life cycle. All communication and monitoring costs for 25-year period shall be included in the bid.

#### 1.2 LIGHTING PERFORMANCE

- A. Illumination Levels and Design Factors: Playing surfaces shall be lit to an average target illumination level and uniformity as specified in the chart below. Lighting calculations shall be developed, and field measurements taken on the grid spacing with the minimum number of grid points specified below. Appropriate light loss factors shall be applied and submitted for the basis of design. Average illumination level shall be measured in accordance with the IESNA LM-5-04 (IESNA Guide for Photometric Measurements of Area and Sports Lighting Installations). Illumination levels shall not to drop below desired target values in accordance to IES RP-6-15, Page 2, Maintained Average Illuminance and shall be guaranteed for the full warranty period.

Area of Lighting	Average Target Illumination Levels, (FC)	Maximum to Minimum Uniformity Ratio	Grid Points	Grid Spacing
Baseball	30 (infield) 20 (outfield)	2.5:1 (infield) 3:1 (outfield)	25 (infield) 164 (outfield)	20' x 20'

- B. Color: The lighting system shall have a minimum color temperature of 5700K and a CRI of 75.
- C. Mounting Heights: To ensure proper aiming angles for reduced glare and to provide better playability, minimum mounting heights shall be as described below. Higher mounting heights may be required based on photometric report and ability to ensure the top of the field angle is a minimum of 10 degrees below horizontal.

# of Poles	Pole Designation	Pole Height
3	A1, A2, B1	70'
1	B2	80'

### 1.3 ENVIRONMENTAL LIGHT CONTROL

- A. Light Control Luminaires: All luminaires shall utilize spill light and glare control devices including, but not limited to, internal shields, louvers, and external shields. No symmetrical beam patterns are accepted.
- B. Spill Light and Glare Control: To minimize impact on adjacent properties, spill light and candela values must not exceed the following.

Measured 150' From Field	Average
Vertical Footcandles	< ¼ FC
Horizontal Footcandles	< ¼ FC
Candela	< 10,000 CD

- C. Spill Scans: Spill scans must be submitted indicating the amount of horizontal and vertical footcandles along the specified lines. Light levels shall be taken at 30-foot intervals along the boundary line. Readings shall be taken with the meter orientation at both horizontal and aimed towards the most intense bank of lights. Illumination level shall be measured in accordance with the IESNA LM-5-04 after 1 hour warm up.
- D. The first page of a photometric report for all luminaire types proposed showing horizontal and vertical axial candle power shall be provided to demonstrate the capability of achieving the specified performance. Reports shall be certified by a qualified independent testing laboratory with a minimum of five years experience or by a manufacturer's laboratory with a current accreditation under the National Voluntary Laboratory Accreditation Program for Energy Efficient Lighting Products. A summary of the horizontal and vertical aiming angles for each luminaire shall be included with the photometric report.

#### 1.4 LIFE-CYCLE COSTS

- A. Manufacturer shall submit a 25-year life cycle cost calculation as outlined in the required submittal information.
- B. Preventative and Spot Maintenance: Manufacturer shall provide all preventative and spot maintenance, including parts and labor for 25 years from the date of equipment shipment. Individual outages shall be repaired when the usage of any field is materially impacted. Owner agrees to check fuses in the event of a luminaire outage.

### PART 2 – PRODUCT

#### 2.1 SPORTS LIGHTING SYSTEM CONSTRUCTION

- A. Manufacturing Requirements: All components shall be designed and manufactured as a system. All luminaires, wire harnesses, drivers and other enclosures shall be factory assembled, aimed, wired and tested.
- B. Durability: All exposed components shall be constructed of corrosion resistant material and/or coated to help prevent corrosion. All exposed carbon steel shall be hot dip galvanized per ASTM A123. All exposed aluminum shall be powder coated with high performance polyester or anodized. All exterior reflective inserts shall be anodized, coated, and protected from direct environmental exposure to prevent reflective degradation or corrosion. All exposed hardware and fasteners shall be stainless steel of 18-8 grade or better, passivated and coated with aluminum-based thermosetting epoxy resin for protection against corrosion and stress corrosion cracking. Structural fasteners may be carbon steel and galvanized meeting ASTM A153 and ISO/EN 1461 (for hot dipped galvanizing), or ASTM B695 (for mechanical galvanizing). All wiring shall be enclosed within the cross-arms, pole, or electrical components enclosure.
- C. System Description: Lighting system shall consist of the following:
  - 1. Galvanized steel poles and cross-arm assembly.
  - 2. Non-approved pole technology:
    - a. Square static cast concrete poles will not be accepted.

- b. Direct bury steel poles which utilize the extended portion of the steel shaft for their foundation will not be accepted due to potential for internal and external corrosive reaction to the soils and long term performance concerns.
- 3. Lighting systems shall use concrete foundations. See Section 2.3 for details.
  - a. For a foundation using a pre-stressed concrete base embedded in concrete backfill the concrete shall be air-entrained and have a minimum compressive design strength at 28 days of 3,000 PSI. 3,000 PSI concrete specified for early pole erection, actual required minimum allowable concrete strength is 1,000 PSI. All piers and concrete backfill must bear on and against firm undisturbed soil.
  - b. For anchor bolt foundations or foundations using a pre-stressed concrete base in a suspended pier or reinforced pier design pole erection may occur after 7 days. Or after a concrete sample from the same batch achieves a certain strength.
- 4. Manufacturer will supply all drivers and supporting electrical equipment
  - a. Remote drivers and supporting electrical equipment shall be mounted approximately 10 feet above grade in aluminum enclosures. The enclosures shall be touch-safe and include drivers and fusing with indicator lights on fuses to notify when a fuse is to be replaced for each luminaire. Disconnect per circuit for each pole structure will be located in the enclosure.
- 5. Manufacturer shall provide surge protection at the pole equal to or greater than 40 kA for each line to ground (Common Mode) as recommended by IEEE C62.41.2\_2002.
- 6. Wire harness complete with an abrasion protection sleeve, strain relief and plug-in connections for fast, trouble-free installation.
- 7. All luminaires, visors, and cross-arm assemblies shall withstand 150 mph winds and maintain luminaire aiming alignment.
- 8. Control cabinet to provide remote on-off control and monitoring of the lighting system. See Section 2.4 for further details.
- 9. Manufacturer shall provide lightning grounding as defined by NFPA 780 and be UL Listed per UL 96 and UL 96A.
  - a. Integrated grounding via concrete encased electrode grounding system.
  - b. If grounding is not integrated into the structure, the manufacturer shall supply grounding electrodes, copper down conductors, and exothermic weld kits. Electrodes and conductors shall be sized as required by NFPA 780. The grounding electrode shall be minimum size of 5/8 inch diameter and 8 feet long, with a minimum of 10 feet embedment. Grounding electrode shall be connected to the structure by a grounding electrode conductor with a minimum size of 2 AWG for poles with 75 feet mounting height or less, and 2/0 AWG for poles with more than 75 feet mounting height.
- D. Safety: All system components shall be UL listed for the appropriate application.

## 2.2 ELECTRICAL

- A. Electric Power Requirements for the Sports Lighting Equipment:
  - 1. Electric power: 480 Volt, 3 Phase



2. Maximum total voltage drop: Voltage drop to the disconnect switch located on the poles shall not exceed three (3) percent of the rated voltage.
- B. Energy Consumption: The kW consumption for the field lighting system shall be <30 kW.

## 2.3 STRUCTURAL PARAMETERS

- A. Wind Loads: Wind loads shall be based on the 2015 International Building Code. Wind loads to be calculated using ASCE 7-10, an ultimate design wind speed of 2015 and exposure category 130mph.
- B. Pole Structural Design: The stress analysis and safety factor of the poles shall conform to 2013 AASHTO Standard Specification for Structural Supports for Highway Signs, Luminaires, and Traffic Signals (LTS-6).
- C. Foundation Design: The foundation design shall be based on soil parameters as outlined in the geotechnical report. If no geotechnical report is available, the foundation design shall be based on soils that meet or exceed those of a Class 5 material as defined by 2009 IBC Table 1806.2.
- D. Foundation Drawings: Project specific foundation drawings stamped by a registered engineer in the state where the project is located are required. The foundation drawings must list the moment, shear (horizontal) force, and axial (vertical) force at ground level for each pole. These drawings must be submitted at time of bid to allow for accurate pricing

## 2.4 CONTROL

- A. Instant On/Off Capabilities: System shall provide for instant on/off of luminaires.
- B. Lighting contactor cabinet(s) constructed of NEMA Type 4 aluminum, designed for easy installation with contactors, labeled to match field diagrams and electrical design. Manual off-on-auto selector switches shall be provided.
- C. Dimming: System shall provide multi-watt dimming capability for all pole top luminaires
- D. Remote Lighting Control System: System shall allow owner and users with a security code to schedule on/off system operation via a web site, phone, fax or email up to ten years in advance. Manufacturer shall provide and maintain a two-way TCP/IP communication link. Trained staff shall be available 24/7 to provide scheduling support and assist with reporting needs.

The owner may assign various security levels to schedulers by function and/or fields. This function must be flexible to allow a range of privileges such as full scheduling capabilities for all fields to only having permission to execute "early off" commands by phone. Scheduling tool shall be capable of setting curfew limits.

Controller shall accept and store 7-day schedules, be protected against memory loss during power outages, and shall reboot once power is regained and execute any commands that would have occurred during outage.
- E. Remote Monitoring System: System shall monitor lighting performance and notify manufacturer if individual luminaire outage is detected so that appropriate maintenance can be scheduled. The controller shall determine switch position (manual or auto) and contactor status (open or closed).
- F. Management Tools: Manufacturer shall provide a web-based database and dashboard tool of actual field usage and provide reports by facility and user group. Dashboard shall also show current

status of luminaire outages, control operation and service. Mobile application will be provided suitable for IOS, Android and Blackberry devices.

Hours of Usage: Manufacturer shall provide a means of tracking actual hours of usage for the field lighting system that is readily accessible to the owner.

1. Cumulative hours: shall be tracked to show the total hours used by the facility
2. Report hours saved by using early off and push buttons by users.

- G. Communication Costs: Manufacturer shall include communication costs for operating the controls and monitoring system for a period of 25 years.

### PART 3 – EXECUTION

#### 3.1 SOIL QUALITY CONTROL

- A. It shall be the Contractor's responsibility to notify the Owner if soil conditions exist other than those on which the foundation design is based, or if the soil cannot be readily excavated. Contractor may issue a change order request / estimate for the Owner's approval / payment for additional costs associated with:
1. Providing engineered foundation embedment design by a registered engineer in the State of Massachusetts for soils other than specified soil conditions;
  2. Additional materials required to achieve alternate foundation;
  3. Excavation and removal of materials other than normal soils, such as rock, caliche, etc.

#### 3.2 DELIVERY TIMING

- A. Delivery Timing Equipment On-Site: The equipment must be on-site 6-8 weeks from receipt of approved submittals and receipt of complete order information.

#### 3.3 FIELD QUALITY CONTROL

- A. Illumination Measurements: Upon substantial completion of the project and in the presence of the Contractor, Project Engineer, Owner's Representative, and Manufacturer's Representative, illumination measurements shall be taken and verified. The illumination measurements shall be conducted in accordance with IESNA LM-5-04.
- B. Field Light Level Accountability
1. Light levels are guaranteed not to fall below the target maintained light levels for the entire warranty period of 25 Years.
  2. The contractor/manufacturer shall be responsible for an additional inspection one year from the date of commissioning of the lighting system and will utilize the owner's light meter in the presence of the owner.
  3. The contractor/manufacturer will be held responsible for any and all changes needed to bring these fields back to compliance for light levels and uniformities. Contractor/Manufacturer will be held responsible for any damage to the fields during these repairs.
- C. Correcting Non-Conformance: If, in the opinion of the Owner or his appointed Representative, the actual performance levels including footcandles and uniformity ratios are not in conformance with the requirements of the performance specifications and submitted information, the Manufacturer shall be required to make adjustments to meet specifications and satisfy Owner.

### 3.4 WARRANTY AND GUARANTEE

- A. 25-Year Warranty: Each manufacturer shall supply a signed warranty covering the entire system for 25 years from the date of shipment. Warranty shall guarantee specified light levels. Manufacturer shall maintain specifically-funded financial reserves to assure fulfillment of the warranty for the full term. Warranty does not cover weather conditions events such as lightning or hail damage, improper installation, vandalism or abuse, unauthorized repairs or alterations, or product made by other manufacturers.
- B. Maintenance: Manufacturer shall monitor the performance of the lighting system, including on/off status, hours of usage and luminaire outage for 25 years from the date of equipment shipment. Parts and labor shall be covered such that individual luminaire outages will be repaired when the usage of any field is materially impacted. Owner agrees to check fuses in the event of a luminaire outage.

## PART 4 – DESIGN APPROVAL

### 4.0 PRE-BID SUBMITTAL REQUIREMENTS (Non-Musco)

- A. Design Approval: The owner / engineer will review pre-bid submittals per section 4.0.B from all the manufacturers to ensure compliance to the specification 10 days prior to bid. If the design meets the design requirements of the specifications, a letter and/or addendum will be issued to the manufacturer indicating approval for the specific design submitted.
- B. Approved Product: Musco's Light-Structure System™ with TLC for LED™ is the approved product. All substitutions must provide a complete submittal package for approval as outlined in Submittal Information at the end of this section at least 10 days prior to bid. Special manufacturing to meet the standards of this specification may be required. An addendum will be issued prior to bid listing any other approved lighting manufacturers and designs.
- C. All listed manufacturers not pre-approved shall submit the information at the end of this section at least 10 days prior to bid. An addendum will be issued prior to bid; listing approved lighting manufacturers and the design method to be used.
- D. Bidders are required to bid only products that have been approved by this specification or addendum by the owner or owner's representative. Bids received that do not utilize an approved system/design, will be rejected.

REQUIRED SUBMITTAL INFORMATION FOR ALL MANUFACTURERS (NOT PRE-APPROVED) 10 DAYS PRIOR TO BID

*All items listed below are mandatory, shall comply with the specification and be submitted according to pre-bid submittal requirements. Complete the Yes/No column to indicate compliance (Y) or noncompliance (N) for each item. Submit checklist below with submittal.*

Yes / No	Tab	Item	Description
	A	Letter/ Checklist	Listing of all information being submitted must be included on the table of contents. List the name of the manufacturer's local representative and his/her phone number. Signed submittal checklist to be included.
	B	Equipment Layout	Drawing(s) showing field layouts with pole locations
	C	On Field Lighting Design	Lighting design drawing(s) showing: <ul style="list-style-type: none"> <li>a. Field Name, date, file number, prepared by</li> <li>b. Outline of field(s) being lighted, as well as pole locations referenced to the center of the field (x &amp; y), Illuminance levels at grid spacing specified</li> <li>c. Pole height, number of fixtures per pole, horizontal and vertical aiming angles, as well as luminaire information including wattage, lumens and optics</li> <li>d. Height of light test meter above field surface.</li> <li>e. Summary table showing the number and spacing of grid points; average, minimum and maximum illuminance levels in foot candles (fc); uniformity including maximum to minimum ratio, coefficient of variance (CV), coefficient of utilization (CU) uniformity gradient; number of luminaires, total kilowatts, average tilt factor; light loss factor.</li> </ul>
	D	Off Field Lighting Design	Lighting design drawing showing initial spill light levels along the boundary line (defined on bid drawings) in footcandles. Light levels shall be taken at 30-foot intervals along the boundary line. Readings shall be taken with the meter orientation at both horizontal and aimed towards the most intense bank of lights.
	E	Photometric Report	Provide first page of photometric report for all luminaire types being proposed showing candela tabulations as defined by IESNA Publication LM-35-02. Photometric data shall be certified by laboratory with current National Voluntary Laboratory Accreditation Program or an independent testing facility with over 5 years experience.
	F	Performance Guarantee	Provide performance guarantee including a written commitment to undertake all corrections required to meet the performance requirements noted in these specifications at no expense to the owner. Light levels must be guaranteed to not fall below target levels for warranty period.
	G	Structural Calculations	Pole structural calculations and foundation design showing foundation shape, depth backfill requirements, rebar and anchor bolts (if required). Pole base reaction forces shall be shown on the foundation drawing along with soil bearing pressures. Design must be stamped by a structural engineer in the state of Massachusetts, if required by owner. (May be supplied upon award).
	H	Control & Monitoring System	Manufacturer of the control and monitoring system shall provide written definition and schematics for automated control system to include monitoring. They will also provide ten (10) references of customers currently using proposed system in the state of Massachusetts.
	I	Electrical	Manufacturer bidding an alternate product must include a revised electrical distribution

		Distribution Plans	plan including changes to service entrance, panels and wire sizing, signed by a licensed Electrical Engineer in the state of Massachusetts.
	J	Warranty	Provide written warranty information including all terms and conditions. Provide ten (10) references of customers currently under specified warranty in the state of Massachusetts.
	K	Project References	Manufacturer to provide a list of ten (10) projects where the technology and specific fixture proposed for this project has been installed in the state of Massachusetts. Reference list will include project name, project city, installation date, and if requested, contact name and contact phone number.
	L	Product Information	Complete bill of material and current brochures/cut sheets for all product being provided.
	M	Delivery	Manufacturer shall supply an expected delivery timeframe from receipt of approved submittals and complete order information.
	N	Non-Compliance	Manufacturer shall list all items that do not comply with the specifications. If in full compliance, tab may be omitted.
	O	Life-cycle Cost Calculation	Document life-cycle cost calculations as defined in the specification. Identify energy costs for operating the luminaires. Maintenance cost for the system must be included in the warranty. All costs should be based on 25 Years. (complete table below)

25-Year Life Cycle Operating Cost			
a.	Luminaire energy consumption _____ luminaires x _____ kW demand per luminaire x kWh rate x annual usage hours x 25 years		
b.	Demand charges, if applicable	+	
c.	Cost for maintenance, not covered, for 25 years Assume 5 repairs at \$750 each if not included with the bid	+	
	TOTAL 25 -Year Life-cycle Operating Cost	=	

The information supplied herein shall be used for the purpose of complying with the specifications for Cornelia Warren Park Softball. By signing below I agree that all requirements of the specifications have been met and that the manufacturer will be responsible for any future costs incurred to bring their equipment into compliance for all items not meeting specifications and not listed in the Non-Compliance section.

Manufacturer: \_\_\_\_\_ Signature: \_\_\_\_\_

Contact Name: \_\_\_\_\_ Date: \_\_\_\_/\_\_\_\_/\_\_\_\_

Contractor: \_\_\_\_\_ Signature: \_\_\_\_\_

## SECTION 311000 - SITE CLEARING

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.
- B. Storm Water Pollution Prevention Plan and NPDES Construction General Permit.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Protecting existing vegetation to remain.
  - 2. Removing existing vegetation.
  - 3. Clearing and grubbing.
  - 4. Stripping and stockpiling topsoil.
  - 5. Stripping and stockpiling rock.
  - 6. Removing above- and below-grade site improvements.
  - 7. Disconnecting, capping or sealing, and abandoning site utilities in place.
  - 8. Temporary erosion and sedimentation control.
- B. Construction runoff or dewatering effluent shall not be discharged directly or tributary to stormwater management infiltration systems without the specific approval of the Owner or Engineer. Approval will require effluent water quality testing.

#### 1.3 DEFINITIONS

- A. Subsoil: Soil beneath the level of subgrade; soil beneath the topsoil layers of a naturally occurring soil profile, typified by less than 1 percent organic matter and few soil organisms.
- B. Surface Soil: Soil that is present at the top layer of the existing soil profile. In undisturbed areas, surface soil is typically called "topsoil," but in disturbed areas such as urban environments, the surface soil can be subsoil.
- C. Topsoil: Top layer of the soil profile consisting of existing native surface topsoil or existing in-place surface soil; the zone where plant roots grow.
- D. Topsoil: Top layer of the soil profile consisting of existing native surface topsoil or existing in-place surface soil; the zone where plant roots grow. Its appearance is generally friable,

pervious, and black or a darker shade of brown, gray, or red than underlying subsoil; reasonably free of subsoil, clay lumps, gravel, and other objects larger than 2 inches in diameter; and free of weeds, roots, toxic materials, or other nonsoil materials.

- E. Vegetation: Trees, shrubs, groundcovers, grass, and other plants.

#### 1.4 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.

#### 1.5 MATERIAL OWNERSHIP

- A. Except for materials indicated to be stockpiled or otherwise remain Owner's property, cleared materials shall become Contractor's property and shall be removed from Project site.

#### 1.6 INFORMATIONAL SUBMITTALS

- A. Existing Conditions: Documentation of existing trees and plantings, adjoining construction, and site improvements that establishes preconstruction conditions that might be misconstrued as damage caused by site clearing.
  - 1. Use sufficiently detailed photographs or video recordings.
  - 2. Include plans and notations to indicate specific wounds and damage conditions of each tree or other plant designated to remain.
- B. Record Drawings: Identifying and accurately showing locations of capped utilities and other subsurface structural, electrical, and mechanical conditions.

#### 1.7 FIELD CONDITIONS

- A. Traffic: Minimize interference with adjoining roads, streets, walks, and other adjacent occupied or used facilities during site-clearing operations.
  - 1. Do not close or obstruct streets, walks, or other adjacent occupied or used facilities without permission from Owner and authorities having jurisdiction.
  - 2. Provide alternate routes around closed or obstructed trafficways if required by Owner or authorities having jurisdiction.
- B. Salvageable Improvements: Carefully remove items indicated to be salvaged and store on Owner's premises where directed.
- C. Utility Locator Service: Notify Dig Safe for area where Project is located before site clearing.

#### SITE CLEARING

311000 - 2

- D. Do not commence site clearing operations until temporary erosion- and sedimentation-control measures are in place.
- E. Soil Stripping, Handling, and Stockpiling: Perform only when the soil is dry or slightly moist.

## PART 2 - PRODUCTS

### 2.1 COMPOST FILTER SOCK

- A. Biodegradable compost
- B. Hardwood Stakes: 1-inch by 1-inch by 2 feet kiln dried hardwood stakes.
  - 1. instructions.

### 2.2 SILT FENCE

- A. Amoco 2130® Silt Fence or approved equal.
- B. Wood support posts: Minimum 1-inch by 1-inch by 2 feet kiln dried hardwood posts.

### 2.3 FILTER FABRIC

- A. Nonwoven needle-punched geotextile, manufactured for subsurface drainage, made from polypropylene with minimum elongation of 50 percent; complying with the following properties determined according to AASHTO M 288:
  - 1. Survivability: Class 2.
  - 2. Apparent Opening Size: No. 70 sieve, maximum.
  - 3. Permittivity: 1.4 per second, minimum.

### 2.4 FILTER BAGS FOR CATCH BASINS

- A. Non-woven polypropylene filter bag manufactured specifically for controlling sediment flow into catch basins.
  - 1. Ultra-DrainGuard® Catch Basin Insert.
  - 2. Siltsack® Hi-Flow or equal.

## SITE CLEARING

311000 - 3



## 2.5 MATERIALS

- A. Satisfactory Soil Material: Requirements for satisfactory soil material are specified in Section 312000 "Earth Moving."
  - 1. Obtain approved borrow soil material off-site when satisfactory soil material is not available on-site.

## PART 3 - EXECUTION

### 3.1 PREPARATION

- A. Protect and maintain benchmarks and survey control points from disturbance during construction.
- B. Verify that trees, shrubs, and other vegetation to remain or to be relocated have been flagged.
- C. Protect existing site improvements to remain from damage during construction.
  - 1. Do not cut, remove, destroy or trim trees or other vegetation outside the designated areas without approval of the Owner.
  - 2. Restore damaged improvements to their original condition, as acceptable to Owner.

### 3.2 TEMPORARY EROSION AND SEDIMENTATION CONTROL

- A. Comply with the requirements of the Project's Storm Water Pollution Prevention Plan and the EPA's NPDES Construction General Permit.
- B. Provide temporary erosion- and sedimentation-control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways, according to erosion- and sedimentation-control Drawings and requirements of authorities having jurisdiction.
- C. As construction progresses and seasonal conditions dictate, more erosion control facilities may be required. Address new conditions that may be created and provide additional facilities over the above minimum requirements as may be required.
- D. As a minimum, the following shall apply:
  - 1. Trees may be cut whenever desired, but brush and stumps shall not be removed until 1 week prior the start of construction in that area. The existing ground surface shall be disturbed as little as possible prior to the start of construction.

## SITE CLEARING

311000 - 4

2. Provide erosion control barriers as shown on the Drawings or as otherwise required to reduce the sediment content of the water. Other methods which reduce the sediment content to an equal or greater degree may be used as approved by the Engineer.
3. Ensure that all runoff leaving the site flows to water courses in such a manner to prevent erosion.
4. Loam and seed or mulch disturbed areas as soon as practicable but not contrary to the requirements of other Sections.

E. Catch Basin Protection

1. Filter Bags
  - a. Install in accordance with manufacturer's recommendations.
  - b. Remove accumulated silt periodically as necessary to maintain effectiveness.
  - c. Dispose of accumulated silt off-site, or on-site as approved by the Owner.

F. Compost Sock/Silt Fence Barrier

1. Install as shown on Drawings to catch silt.
2. Install compost sock in conjunction with silt fence, unless otherwise indicated.
3. Stake in place as shown on Drawings.
4. Remove accumulated silt and replace compost sock and silt fence periodically as necessary to maintain effectiveness.
5. Dispose of accumulated silt off-site, or on-site as approved by the Owner.

G. Existing Drainage Facilities

1. Clean existing storm sewers, culverts, or other drainage facilities which become partially or totally blocked due to siltation from Contractor's operations. Make any necessary arrangements with the jurisdictional agency for the cleaning of the facility.

H. Temporary Drainage Diversion

1. Divert the surface runoff water around the site as may be required.
2. Restore drainage conditions to those existing prior to construction unless otherwise shown on the Drawings.

I. Inspect, maintain, and repair erosion- and sedimentation-control measures during construction until permanent vegetation has been established.

J. Remove erosion and sedimentation controls and restore and stabilize areas disturbed during removal.

### 3.3 EXISTING UTILITIES

- A. Owner will arrange for disconnecting and sealing indicated utilities that serve existing structures before site clearing, when requested by Contractor.
  - 1. Verify that utilities have been disconnected and capped before proceeding with site clearing.
- B. Locate, identify, disconnect, and seal or cap utilities indicated to be removed or abandoned in place.
  - 1. Arrange with utility companies to shut off indicated utilities.
  - 2. Owner will arrange to shut off indicated utilities when requested by Contractor.
- C. Locate, identify, and disconnect utilities indicated to be abandoned in place.
- D. Interrupting Existing Utilities: Do not interrupt utilities serving facilities occupied by Owner or others, unless permitted under the following conditions and then only after arranging to provide temporary utility services according to requirements indicated:
  - 1. Notify Owner not less than two days in advance of proposed utility interruptions.
  - 2. Do not proceed with utility interruptions without Owner's written permission.
- E. Excavate for and remove underground utilities indicated to be removed.
- F. Removal of underground utilities is included in earthwork sections; in applicable fire suppression, plumbing, HVAC, electrical, communications, electronic safety and security, and utilities sections; and in Section 024116 "Structure Demolition" and Section 024119 "Selective Demolition."

### 3.4 CLEARING AND GRUBBING

- A. Remove obstructions, trees, shrubs, and other vegetation to permit installation of new construction.
  - 1. Do not remove trees, shrubs, and other vegetation indicated to remain or to be relocated.
  - 2. Grind down stumps and remove roots larger than 2 inches in diameter, obstructions, and debris to a depth of 18 inches below exposed subgrade.
  - 3. Chip removed tree branches and dispose of off-site.
- B. Fill depressions caused by clearing and grubbing operations with satisfactory soil material unless further excavation or earthwork is indicated.
  - 1. Place fill material in horizontal layers not exceeding a loose depth of 8 inches and compact each layer to a density equal to adjacent original ground.

### SITE CLEARING

311000 - 6

### 3.5 TOPSOIL STRIPPING

- A. Remove sod and grass before stripping topsoil.
- B. Strip topsoil to depth of 6 inches in a manner to prevent intermingling with underlying subsoil or other waste materials.
  - 1. Remove subsoil and nonsoil materials from topsoil, including clay lumps, gravel, and other objects larger than 2 inches in diameter; trash, debris, weeds, roots, and other waste materials.
- C. Stockpile topsoil away from edge of excavations without intermixing with subsoil or other materials. Grade and shape stockpiles to drain surface water. Cover to prevent windblown dust and erosion by water.
  - 1. Limit height of topsoil stockpiles to 72 inches.
  - 2. Dispose of surplus topsoil. Surplus topsoil is that which exceeds quantity indicated to be stockpiled or reused.
  - 3. Stockpile surplus topsoil to allow for resspreading deeper topsoil.

### 3.6 SITE IMPROVEMENTS

- A. Remove existing above- and below-grade improvements as indicated and necessary to facilitate new construction.
- B. Remove slabs, paving, curbs, gutters, and aggregate base as indicated.
  - 1. Unless existing full-depth joints coincide with line of demolition, neatly saw-cut along line of existing pavement to remain before removing adjacent existing pavement. Saw-cut faces vertically.
  - 2. Paint cut ends of steel reinforcement in concrete to remain with two coats of antirust coating, following coating manufacturer's written instructions. Keep paint off surfaces that will remain exposed.

### 3.7 DISPOSAL OF SURPLUS AND WASTE MATERIALS

- A. Remove surplus soil material, unsuitable topsoil, obstructions, demolished materials, and waste materials including trash and debris, and legally dispose of them off Owner's property.
- B. Separate recyclable materials produced during site clearing from other nonrecyclable materials. Store or stockpile without intermixing with other materials, and transport them to recycling facilities. Do not interfere with other Project work.

END OF SECTION 311000

SITE CLEARING

311000 - 7

## SECTION 312000 - EARTH MOVING

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Excavating and filling for rough grading the Site.
  - 2. Preparing subgrades for slabs-on-grade, walks, pavements, turf and grasses, and plants.
  - 3. Subbase course for concrete walks and pavements.
  - 4. Subbase course and base course for asphalt paving.
  - 5. Subsurface drainage backfill for walls and trenches.
  - 6. Excavating and backfilling trenches for utilities and pits for buried utility structures.
- B. Related Requirements:
  - 1. Section 311000 "Site Clearing" for site stripping, grubbing, stripping and stockpiling topsoil, and removal of above- and below-grade improvements and utilities.
  - 2. Section 329200 "Turf and Grasses" for finish grading in turf and grass areas, including preparing and placing planting soil for turf areas.
  - 3. Section 329300 "Plants" for finish grading in planting areas and tree and shrub pit excavation and planting.
  - 4. Standard Specification: Massachusetts Department of Public Works Standard Specifications for Highways and Bridges, 1988 edition as amended.

#### 1.3 UNIT PRICES

- A. Work of this Section is affected by unit prices for earth moving specified in Section 012200 "Unit Prices."
- B. Quantity allowances for earth moving are included in Section 012100 "Allowances."

#### 1.4 DEFINITIONS

- A. Backfill: Soil material or controlled low-strength material used to fill an excavation.

1. Initial Backfill: Backfill placed beside and over pipe in a trench, including haunches to support sides of pipe.
  2. Final Backfill: Backfill placed over initial backfill to fill a trench.
- B. Base Course: Aggregate layer placed between the subbase course and hot-mix asphalt paving.
- C. Bedding Course: Aggregate layer placed over the excavated subgrade in a trench before laying pipe.
- D. Borrow Soil: Satisfactory soil imported from off-site for use as fill or backfill.
- E. Drainage Course: Aggregate layer supporting the slab-on-grade that also minimizes upward capillary flow of pore water.
- F. Excavation: Removal of material encountered above subgrade elevations and to lines and dimensions indicated.
1. Authorized Additional Excavation: Excavation below subgrade elevations or beyond indicated lines and dimensions as directed by Engineer. Authorized additional excavation and replacement material will be paid for according to Contract provisions for changes in the Work.
  2. Bulk Excavation: Excavation more than 10 feet in width and more than 30 feet in length.
  3. Unauthorized Excavation: Excavation below subgrade elevations or beyond indicated lines and dimensions without direction by Engineer. Unauthorized excavation, as well as remedial work directed by Engineer, will be without additional compensation.
- G. Fill: Soil materials used to raise existing grades.
- H. Rock:
1. Rock material in beds, ledges, unstratified masses, conglomerate deposits, and boulders of rock material that exceed 1 cu. yd. for bulk excavation or 3/4 cu. yd. for footing, trench, and pit excavation that cannot be removed by rock-excavating equipment equivalent to the following in size and performance ratings, without systematic drilling, ram hammering, ripping, or blasting, when permitted:
    - a. Equipment for Footing, Trench, and Pit Excavation: Late-model, track-mounted hydraulic excavator; equipped with a 42-inch- maximum-width, short-tip-radius rock bucket; rated at not less than 138-hp flywheel power with bucket-curling force of not less than 28,700 lbf and stick-crowd force of not less than 18,400 lbf with extra-long reach boom.
    - b. Equipment for Bulk Excavation: Late-model, track-mounted loader; rated at not less than 230-hp flywheel power and developing a minimum of 47,992-lbf breakout force with a general-purpose bare bucket.
  2. Rock material in beds, ledges, unstratified masses, conglomerate deposits, and boulders of rock material 3/4 cu. yd. or more in volume that exceed a standard penetration

resistance of 100 blows/2 inches when tested by a geotechnical testing agency, according to ASTM D1586.

- I. Structures: Buildings, footings, foundations, retaining walls, slabs, tanks, curbs, mechanical and electrical appurtenances, or other fabricated stationary features constructed above or below the ground surface.
- J. Subbase Course: Aggregate layer placed between the subgrade and base course for hot-mix asphalt pavement, or aggregate layer placed between the subgrade and a cement concrete pavement or a cement concrete or hot-mix asphalt walk.
- K. Subgrade: Uppermost surface of an excavation or the top surface of a fill or backfill immediately below subbase, drainage fill, drainage course, or topsoil materials.
- L. Utilities: On-site underground pipes, conduits, ducts, and cables as well as underground services within buildings.

## 1.5 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct preexcavation conference at Project site.
  - 1. Review methods and procedures related to earthmoving, including, but not limited to, the following:
    - a. Personnel and equipment needed to make progress and avoid delays.
    - b. Coordination of Work with utility locator service.
    - c. Coordination of Work and equipment movement with the locations of tree- and plant-protection zones.
    - d. Extent of trenching by hand or with air spade.
    - e. Field quality control.

## 1.6 ACTION SUBMITTALS

- A. Product Data: For each type of the following manufactured products required:
  - 1. Geotextiles.
  - 2. Controlled low-strength material, including design mixture.
  - 3. Warning tapes.
- B. Samples for Verification: For the following products, in sizes indicated below:
  - 1. Geotextile: 12 by 12 inches.
  - 2. Warning Tape: 12 inches long; of each color.

## 1.7 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For qualified testing agency.
- B. Material Test Reports: For each on-site and borrow soil material proposed for fill and backfill as follows:
  - 1. Classification according to ASTM D2487.
  - 2. Laboratory compaction curve according to ASTM D1557.
- C. Preexcavation Photographs or Videotape: Show existing conditions of adjoining construction and site improvements, including finish surfaces that might be misconstrued as damage caused by earth-moving operations. Submit before earth moving begins.

## 1.8 QUALITY ASSURANCE

- A. Geotechnical Testing Agency Qualifications: Qualified according to ASTM E329 and ASTM D3740 for testing indicated.

## 1.9 FIELD CONDITIONS

- A. Traffic: Minimize interference with adjoining roads, streets, walks, and other adjacent occupied or used facilities during earth-moving operations.
  - 1. Do not close or obstruct streets, walks, or other adjacent occupied or used facilities without permission from Owner and authorities having jurisdiction.
  - 2. Provide alternate routes around closed or obstructed traffic ways if required by Owner or authorities having jurisdiction.
- B. Utility Locator Service: Notify Dig Safe for area where Project is located before beginning earth-moving operations.
- C. Do not commence earth-moving operations until temporary site fencing and erosion- and sedimentation-control measures specified in Section 311000 "Site Clearing" are in place.
- D. Do not commence earth-moving operations until plant-protection measures specified in Section 015639 "Temporary Tree and Plant Protection" are in place.
- E. Existing Utilities: Do not interrupt utilities serving facilities occupied by Owner or others unless permitted in writing by Owner and then only after arranging to provide temporary utility services according to requirements indicated:
  - 1. Notify Owner not less than two days in advance of proposed utility interruptions.
  - 2. Do not proceed with utility interruptions without Owner's written permission.



- F. Demolish and completely remove from site existing underground utilities indicated to be removed. Coordinate with utility companies to shut off services if lines are active.
- G. Geotechnical Report: A geotechnical report has not been prepared for this Project. Conduct test borings and other exploratory operations as necessary to confirm existing subsurface conditions.

## PART 2 - PRODUCTS

### 2.1 SOIL MATERIALS

- A. General: Provide borrow soil materials when sufficient satisfactory soil materials are not available from excavations.
- B. Satisfactory Soils: Soil Classification Groups A-1, A-2-4, A-2-5, and A-3 according to AASHTO M 145, or a combination of these groups; free of rock or gravel larger than 3 inches in any dimension, debris, waste, frozen materials, vegetation, and other deleterious matter.
- C. Unsatisfactory Soils: Soil Classification Groups A-2-6, A-2-7, A-4, A-5, A-6, and A-7 according to AASHTO M 145, or a combination of these groups.
  - 1. Unsatisfactory soils also include satisfactory soils not maintained within 2 percent of optimum moisture content at time of compaction.
- D. Ordinary Fill: Well graded, natural inorganic soil approved by the Engineer, free of organic or other weak or compressible materials, or frozen materials, and of stones larger than one-half the lift thickness. It shall be of such nature and character that it can be compacted to the specified densities in a reasonable length of time. It shall be free of highly plastic clay, of all materials subject to decay, decomposition, or dissolution, and of cinders or other materials that will corrode piping or other metal. It shall have a minimum dry unit weight of not less than 115 pounds per cubic foot. Material from excavation on the site may be used as ordinary fill if it meets the above requirements.

- E. Processed Gravel: Sound, durable bank or crusher-run gravel and sand, practically free from loam, peat, clay, surface coatings and deleterious materials, well graded as follows:

<u>Sieve Size</u>	<u>Percent Passing By Weight</u>
3 in.	100
1 ½ in.	70-100
¾ in.	50-85
No. 4	30-60
No. 200	0-10

- F. Crushed Stone or Drainage Fill: Clean crushed stone approved by the Engineer and conforming to the following gradation:

<u>Sieve Size</u>	<u>Percent Passing By Weight</u>
1 in.	100
¾ in.	90-100
½ in.	10-50
3/8 in.	0-20
No. 4	0-5

- G. Screened Gravel: Hard, durable, particles of proper size and gradation, free from sand, loam, clay, excess fines, and deleterious materials. Screened gravel shall meet the requirements of ASTM C33, stone size No. 67 and shall conform to the following gradation:

<u>Sieve Size</u>	<u>Percent Passing By Weight</u>
1 in.	100
¾ in.	90-100
3/8 in.	20-55
No. 4	0-10
No. 8	0-5

- H. Structural Fill: Clean granular material free from ice, snow, roots, sod, rubbish, loam, peat, clay and other deleterious or organic matter conforming to the following gradation:

<u>Sieve Size</u>	<u>Percent Passing By Weight</u>
¾ in.	100
No. 4	30-85
No. 40	5-50
No. 200	0-8

- I. Sand Borrow: Clean inert, hard durable grains of quartz or other hard durable rock, free from loam or clay, surface coatings and deleterious materials. The allowable amount of material passing a No. 200 sieve as determined by AASHTO-T11 shall not exceed 10 percent by weight. Maximum particle size shall be 3/8 inch.
- J. Controlled Density Fill: Flowable, self-consolidating, rigid setting low-density material conforming to Massachusetts Department of Public Works Standard Specifications for Highways and Bridges, 1988 edition as amended, subsection M4.08.0.
- K. Sand: ASTM C 33/C 33M; fine aggregate.

## 2.2 ACCESSORIES

- A. Detectable Warning Tape: Acid- and alkali-resistant, polyethylene film warning tape manufactured for marking and identifying underground utilities, a minimum of 6 inches wide and 4 mils thick, continuously inscribed with a description of the utility, with metallic core encased in a protective jacket for corrosion protection, detectable by metal detector when tape is buried up to 30 inches deep; colored as follows:
1. Red: Electric.
  2. Yellow: Gas, oil, steam, and dangerous materials.
  3. Orange: Telephone and other communications.
  4. Blue: Water systems.
  5. Green: Sewer systems.
- B. Filter Fabric: Nonwoven needle-punched geotextile, manufactured for subsurface drainage, made from polypropylene with minimum elongation of 50 percent; complying with the following properties determined according to AASHTO M 288:
1. Survivability: Class 2.
  2. Apparent Opening Size: No. 70 sieve, maximum.
  3. Permittivity: 1.4 per second, minimum.

## PART 3 - EXECUTION

### 3.1 PREPARATION

- A. Protect structures, utilities, sidewalks, pavements, and other facilities from damage caused by settlement, lateral movement, undermining, washout, and other hazards created by earth-moving operations.
- B. Protect and maintain erosion and sedimentation controls during earth-moving operations.
- C. Protect subgrades and foundation soils from freezing temperatures and frost. Remove temporary protection before placing subsequent materials.

### 3.2 DEWATERING

- A. Provide dewatering system of sufficient scope, size, and capacity to control hydrostatic pressures and to lower, control, remove, and dispose of ground water and permit excavation and construction to proceed on dry, stable subgrades.
- B. Prevent surface water and ground water from entering excavations, from ponding on prepared subgrades, and from flooding Project site and surrounding area.
- C. Protect subgrades from softening, undermining, washout, and damage by rain or water accumulation.
  - 1. Reroute surface water runoff away from excavated areas. Do not allow water to accumulate in excavations. Do not use excavated trenches as temporary drainage ditches.
- D. Dispose of water removed by dewatering in a manner that avoids endangering public health, property, and portions of work under construction or completed. Dispose of water and sediment in a manner that avoids inconvenience to others.

### 3.3 EXPLOSIVES

- A. Explosives:
  - 1. Do not use explosives.
- B. Rock Removal: If rock is encountered during excavation, contact the Owner to establish a procedure for removal.
  - 1. Notify the Owner and other interested authorities at least 48 hours before any blasting is intended.

2. Exercise all possible care in drilling and blasting operations to ensure the stability of the remaining rock and to keep overbreak to a minimum. Produce excavated surfaces that are as smooth and sound as the nature of the rock permits. It is the Contractor's responsibility to produce the most satisfactory surface by use of techniques best suited to job conditions.
3. Presplitting: Form vertical and near vertical faces of excavation in rock by the blasting technique known as presplitting.
  - a. Use presplitting technique for rock cuts 10 feet or more in vertical height where design slope is 1 horizontal to 4 vertical or steeper.
  - b. Locate presplit holes so that the break will occur along the design lines shown on the Drawings.
  - c. Maintain alignment in the vertical plane of not more than 6 inches from the plane of specified slope.
  - d. Extend holes at least to the proposed bench levels and to the bottom of the proposed excavations.
  - e. Space presplit holes at intervals of not more than 24 in. center to center and no larger than 3 in. in diameter.
4. Clean exposed surfaces of rock so that they are free of loose fragments of rock and decomposed rock.

### 3.4 EXCAVATION, GENERAL

- A. Unclassified Excavation: Excavate to subgrade elevations regardless of the character of surface and subsurface conditions encountered. Unclassified excavated materials may include rock, soil materials, and obstructions. No changes in the Contract Sum or the Contract Time will be authorized for rock excavation or removal of obstructions.
  1. If excavated materials intended for fill and backfill include unsatisfactory soil materials and rock, replace with satisfactory soil materials.
  2. Remove rock to lines and grades indicated to permit installation of permanent construction without exceeding the following dimensions:
    - a. 24 inches outside of concrete forms other than at footings.
    - b. 12 inches outside of concrete forms at footings.
    - c. 6 inches outside of minimum required dimensions of concrete cast against grade.
    - d. Outside dimensions of concrete walls indicated to be cast against rock without forms or exterior waterproofing treatments.
    - e. 6 inches beneath bottom of concrete slabs-on-grade.
    - f. 86 inches beneath pipe in trenches and the greater of 24 inches wider than pipe or 42 inches wide.
- B. Classified Excavation: Excavate to subgrade elevations. Material to be excavated will be classified as earth and rock. Do not excavate rock until it has been classified and cross

sectioned by Engineer. The Contract Sum will be adjusted for rock excavation according to unit prices included in the Contract Documents. Changes in the Contract Time may be authorized for rock excavation.

1. Earth excavation includes excavating pavements and obstructions visible on surface; underground structures, utilities, and other items indicated to be removed; and soil, boulders, and other materials not classified as rock or unauthorized excavation.
  - a. Intermittent drilling; blasting, if permitted; ram hammering; or ripping of material not classified as rock excavation is earth excavation.
2. Rock excavation includes removal and disposal of rock. Remove rock to lines and subgrade elevations indicated to permit installation of permanent construction without exceeding the following dimensions:
  - a. 24 inches outside of concrete forms other than at footings.
  - b. 12 inches outside of concrete forms at footings.
  - c. 6 inches outside of minimum required dimensions of concrete cast against grade.
  - d. Outside dimensions of concrete walls indicated to be cast against rock without forms or exterior waterproofing treatments.
  - e. 6 inches beneath bottom of concrete slabs-on-grade.
  - f. 8 inches beneath pipe in trenches and the greater of 24 inches wider than pipe or 42 inches wide.

### 3.5 EXCAVATION FOR STRUCTURES

- A. Excavate to indicated elevations and dimensions within a tolerance of plus or minus 1 inch. If applicable, extend excavations a sufficient distance from structures for placing and removing concrete formwork, for installing services and other construction, and for inspections.
  1. Excavations for Footings and Foundations: Do not disturb bottom of excavation. Excavate by hand to final grade just before placing concrete reinforcement. Trim bottoms to required lines and grades to leave solid base to receive other work.
  2. Pile Foundations: Stop excavations 6 to 12 inches above bottom of pile cap before piles are placed. After piles have been driven, remove loose and displaced material. Excavate to final grade, leaving solid base to receive concrete pile caps.
  3. Excavation for Underground Tanks, Basins, and Mechanical or Electrical Utility Structures: Excavate to elevations and dimensions indicated within a tolerance of plus or minus 1 inch. Do not disturb bottom of excavations intended as bearing surfaces.

### 3.6 EXCAVATION FOR WALKS AND PAVEMENTS

- A. Excavate surfaces under walks and pavements to indicated lines, cross sections, elevations, and subgrades.

### 3.7 EXCAVATION FOR UTILITY TRENCHES

- A. Excavate trenches to indicated gradients, lines, depths, and elevations.
  - 1. Beyond building perimeter, excavate trenches to allow installation of top of pipe below frost line.
- B. Excavate trenches to uniform widths to provide the following clearance on each side of pipe or conduit. Excavate trench walls vertically from trench bottom to 12 inches (300 mm) higher than top of pipe. Remove all excavated materials not required or unsuitable for backfill and legally dispose of them off-site, or conduit unless provisions for on-site disposal have been approved by the Owner otherwise indicated.
  - 1. Clearance: As indicated.
- C. Trench Bottoms:
  - 1. Excavate and shape trench bottoms to provide uniform bearing and support of pipes and conduit. Shape subgrade to provide continuous support for bells, joints, and barrels of pipes and for joints, fittings, and bodies of conduits. Remove projecting stones and sharp objects along trench subgrade.
    - a. For pipes and conduit less than 6 inches in nominal diameter, hand-excavate trench bottoms and support pipe and conduit on an undisturbed subgrade.
    - b. For pipes and conduit 6 inches or larger in nominal diameter, shape bottom of trench to support bottom 90 degrees of pipe or conduit circumference. Fill depressions with tamped sand backfill.
    - c. For flat-bottomed, multiple-duct conduit units, hand-excavate trench bottoms and support conduit on an undisturbed subgrade.
    - d. Excavate trenches 6 inches deeper than elevation required in rock or other unyielding bearing material to allow for bedding course.
  - 2. Excavate trenches 4 inches deeper than bottom of pipe and conduit elevations to allow for bedding course. Hand-excavate deeper for bells of pipe.
    - a. Excavate trenches 6 inches deeper than elevation required in rock or other unyielding bearing material to allow for bedding course.

### 3.8 SUBGRADE INSPECTION

- A. Notify Engineer when excavations have reached required subgrade.
- B. If Engineer determines that unsatisfactory soil is present, continue excavation and replace with compacted backfill or fill material as directed.

- C. Proof-roll subgrade with a pneumatic-tired and loaded 10-wheel, tandem-axle dump truck weighing not less than 15 tons to identify soft pockets and areas of excess yielding. Do not proof-roll wet or saturated subgrades.
  - 1. Completely proof-roll subgrade in one direction, repeating proof-rolling in direction perpendicular to first direction. Limit vehicle speed to 3 mph
  - 2. Excavate soft spots, unsatisfactory soils, and areas of excessive pumping or rutting, as determined by Engineer, and replace with compacted backfill or fill as directed.
- D. Authorized additional excavation and replacement material will be paid for according to Contract provisions for changes in the Work.
- E. Reconstruct subgrades damaged by freezing temperatures, frost, rain, accumulated water, or construction activities, as directed by Engineer, without additional compensation.

### 3.9 UNAUTHORIZED EXCAVATION

- A. Fill unauthorized excavation under foundations or wall footings by extending bottom elevation of concrete foundation or footing to excavation bottom, without altering top elevation. Lean concrete fill, with 28-day compressive strength of 2500 psi may be used when approved by Engineer.
  - 1. Fill unauthorized excavations under other construction, pipe, or conduit as directed by Engineer.

### 3.10 STORAGE OF SOIL MATERIALS

- A. Stockpile borrow soil materials and excavated satisfactory soil materials without intermixing. Place, grade, and shape stockpiles to drain surface water. Cover to prevent windblown dust.
  - 1. Stockpile soil materials away from edge of excavations. Do not store within drip line of remaining trees.

### 3.11 BACKFILL

- A. Place and compact backfill in excavations promptly, but not before completing the following:
  - 1. Construction below finish grade including, where applicable, subdrainage, dampproofing, waterproofing, and perimeter insulation.
  - 2. Surveying locations of underground utilities for Record Documents.
  - 3. Testing and inspecting underground utilities.
  - 4. Removing concrete formwork.
  - 5. Removing trash and debris.



6. Removing temporary shoring, bracing, and sheeting.
7. Installing permanent or temporary horizontal bracing on horizontally supported walls.

- B. Place backfill on subgrades free of mud, frost, snow, or ice.

### 3.12 UTILITY TRENCH BACKFILL

- A. Place backfill on subgrades free of mud, frost, snow, or ice.
- B. Place and compact bedding course on trench bottoms and where indicated. Shape bedding course to provide continuous support for bells, joints, and barrels of pipes and for joints, fittings, and bodies of conduits.
1. Screened Gravel bedding is required below all pipes unless otherwise shown on Drawings or specified herein. Place bedding to the full width of the trench and to mid-diameter of the pipe as indicated on the Drawings.
  2. After a pipe is bedded, fill the trench to the centerline of the pipe with the specified bedding. Carefully and thoroughly tamp bedding around the pipe.
- C. Trenches under Footings: Backfill trenches excavated under footings and within 18 inches of bottom of footings with satisfactory soil; fill with concrete to elevation of bottom of footings. Concrete is specified in Section 033053 "Miscellaneous Cast-in-Place Concrete."
- D. Trenches under Roadways: Provide 4-inch thick, concrete-base slab support for piping or conduit less than 30 inches below surface of roadways. After installing and testing, completely encase piping or conduit in a minimum of 4 inches of concrete before backfilling or placing roadway subbase course. Concrete is specified in Section 033053 "Miscellaneous Cast-in-Place Concrete."
- E. Backfill voids with satisfactory soil while removing shoring and bracing.
- F. Initial Backfill:
1. Soil Backfill: Place and compact initial backfill of subbase material, free of particles larger than 1 inch in any dimension, to a height of 12 inches over the pipe or conduit.
  2. For non-plastic pipe or conduit, place and compact initial backfill of Ordinary Fill, free of particles larger than 1 inch to a height of 12 inches over the utility pipe or conduit.
    - a. Carefully compact initial backfill under pipe haunches and compact evenly up on both sides and along the full length of piping or conduit to avoid damage or displacement of piping or conduit. Coordinate backfilling with utilities testing.
  3. Fill voids with approved backfill materials as shoring and bracing, and sheeting is removed.

4. Controlled Low-Strength Material: Place initial backfill of controlled low-strength material to a height of 12 inches over the pipe or conduit. Coordinate backfilling with utilities testing.
- G. Final Backfill:
  1. Soil Backfill: Place and compact final backfill of satisfactory soil to final subgrade elevation.
  2. Controlled Low-Strength Material: Place final backfill of controlled low-strength material to final subgrade elevation.
- H. Warning Tape: Install warning tape directly above utilities, 12 inches below finished grade, except 6 inches below subgrade under pavements and slabs.

### 3.13 SOIL FILL

- A. Plow, scarify, bench, or break up sloped surfaces steeper than 1 vertical to 4 horizontal so fill material will bond with existing material.
- B. Place and compact fill material in layers to required elevations as follows:
  1. Under grass and planted areas, use satisfactory soil material.
  2. Under walks and pavements, use satisfactory soil material.
  3. Under steps and ramps, use engineered fill.
  4. Under building slabs, use engineered fill.
  5. Under footings and foundations, use engineered fill.
- C. Place soil fill on subgrades free of mud, frost, snow, or ice.

### 3.14 SOIL MOISTURE CONTROL

- A. Uniformly moisten or aerate subgrade and each subsequent fill or backfill soil layer before compaction to within 2 percent of optimum moisture content.
  1. Do not place backfill or fill soil material on surfaces that are muddy, frozen, or contain frost or ice.
  2. Remove and replace, or scarify and air dry, otherwise satisfactory soil material that exceeds optimum moisture content by 2 percent and is too wet to compact to specified dry unit weight.

### 3.15 COMPACTION OF SOIL BACKFILLS AND FILLS

- A. Place backfill and fill soil materials in layers not more than 8 inches in loose depth for material compacted by heavy compaction equipment and not more than 4 inches in loose depth for material compacted by hand-operated tampers.

- B. Place backfill and fill soil materials evenly on all sides of structures to required elevations and uniformly along the full length of each structure.
- C. Compact soil materials to not less than the following percentages of maximum dry unit weight according to ASTM D1557:
  - 1. Under structures, building slabs, steps, and pavements, scarify and recompact top 12 inches of existing subgrade and each layer of backfill or fill soil material at 95 percent.
  - 2. Under walkways, scarify and recompact top 6 inches below subgrade and compact each layer of backfill or fill soil material at 92 percent.
  - 3. Under turf or unpaved areas, scarify and recompact top 6 inches below subgrade and compact each layer of backfill or fill soil material at 85 percent.
  - 4. For utility trenches, compact each layer of initial and final backfill soil material at 95 percent.

### 3.16 GRADING

- A. General: Uniformly grade areas to a smooth surface, free of irregular surface changes. Comply with compaction requirements and grade to cross sections, lines, and elevations indicated.
  - 1. Provide a smooth transition between adjacent existing grades and new grades.
  - 2. Cut out soft spots, fill low spots, and trim high spots to comply with required surface tolerances.
- B. Site Rough Grading: Slope grades to direct water away from buildings and to prevent ponding. Finish subgrades to elevations required to achieve indicated finish elevations, within the following subgrade tolerances:
  - 1. Turf or Unpaved Areas: Plus or minus 1 inch
  - 2. Walks: Plus or minus 1 inch
  - 3. Pavements (except walks): Plus or minus 1/2 inch

### 3.17 SUBSURFACE DRAINAGE

- A. Subsurface Drain: Place subsurface drainage geotextile around perimeter of subdrainage trench. Place a 6-inch course of filter material on subsurface drainage geotextile to support subdrainage pipe. Encase subdrainage pipe in a minimum of 12 inches of filter material, placed in compacted layers 6 inches thick, and wrap in subsurface drainage geotextile, overlapping sides and ends at least 6 inches.
  - 1. Compact each filter material layer to 85 percent of maximum dry unit weight according to ASTM D 698.
- B. Drainage Backfill: Place and compact filter material over subsurface drain, in width indicated, to within 12 inches of final subgrade, in compacted layers 6 inches thick. Overlay drainage

backfill with one layer of subsurface drainage geotextile, overlapping sides and ends at least 6 inches.

1. Compact each filter material layer [to 85 percent of maximum dry unit weight according to ASTM D698.
2. Place and compact impervious fill over drainage backfill in 6-inch-thick compacted layers to final subgrade.

### 3.18 SUBBASE AND BASE COURSES UNDER PAVEMENTS AND WALKS

- A. Place subbase course and base course on subgrades free of mud, frost, snow, or ice.
- B. On prepared subgrade, place subbase course and base course under pavements and walks as follows:
  1. Install separation geotextile on prepared subgrade according to manufacturer's written instructions, overlapping sides and ends.
  2. Place base course material over subbase course under hot-mix asphalt pavement.
  3. Shape subbase course and base course to required crown elevations and cross-slope grades.
  4. Place subbase course and base course 6 inches or less in compacted thickness in a single layer.
  5. Place subbase course and base course that exceeds 6 inches in compacted thickness in layers of equal thickness, with no compacted layer more than 6 inches thick or less than 3 inches thick.
  6. Compact subbase course and base course at optimum moisture content to required grades, lines, cross sections, and thickness to not less than 95 percent of maximum dry unit weight according to ASTM D1557.
- C. Pavement Shoulders: Place shoulders along edges of subbase course and base course to prevent lateral movement. Construct shoulders, at least 12 inches wide, of satisfactory soil materials and compact simultaneously with each subbase and base layer to not less than 95 percent of maximum dry unit weight according to ASTM D1557.

### 3.19 FIELD QUALITY CONTROL

- A. Testing Agency: Owner will engage a qualified geotechnical engineering testing agency to perform tests and inspections.
- B. Allow testing agency to inspect and test subgrades and each fill or backfill layer. Proceed with subsequent earth moving only after test results for previously completed work comply with requirements.
- C. Footing Subgrade: At footing subgrades, at least one test of each soil stratum will be performed to verify design bearing capacities. Subsequent verification and approval of other

footing subgrades may be based on a visual comparison of subgrade with tested subgrade when approved by Engineer.

- D. Testing agency will test compaction of soils in place according to ASTM D1556, ASTM D2167, ASTM D2937, and ASTM D6938, as applicable. Tests will be performed at the following locations and frequencies:
  - 1. Paved and Building Slab Areas: At subgrade and at each compacted fill and backfill layer, at least one test for every 2000 sq. ft. or less of paved area or building slab but in no case fewer than three tests.
  - 2. Foundation Wall Backfill: At each compacted backfill layer, at least one test for every 100 feet or less of wall length but no fewer than two tests.
  - 3. Trench Backfill: At each compacted initial and final backfill layer, at least one test for every 150 feet or less of trench length but no fewer than two tests.
- E. When testing agency reports that subgrades, fills, or backfills have not achieved degree of compaction specified, scarify and moisten or aerate, or remove and replace soil materials to depth required; recompact and retest until specified compaction is obtained.

### 3.20 PROTECTION

- A. Protecting Graded Areas: Protect newly graded areas from traffic, freezing, and erosion. Keep free of trash and debris.
- B. Repair and reestablish grades to specified tolerances where completed or partially completed surfaces become eroded, rutted, settled, or where they lose compaction due to subsequent construction operations or weather conditions.
  - 1. Scarify or remove and replace soil material to depth as directed by Engineer; reshape and recompact.
- C. Where settling occurs before Project correction period elapses, remove finished surfacing, backfill with additional soil material, compact, and reconstruct surfacing.
  - 1. Restore appearance, quality, and condition of finished surfacing to match adjacent work, and eliminate evidence of restoration to greatest extent possible.

### 3.21 DISPOSAL OF SURPLUS AND WASTE MATERIALS

- A. Remove surplus satisfactory soil and waste materials, including unsatisfactory soil, trash, and debris, and legally dispose of them off Owner's property.
- B. Transport surplus satisfactory soil to designated storage areas on Owner's property. Stockpile or spread soil as directed by Engineer.

1. Remove waste materials, including unsatisfactory soil, trash, and debris, and legally dispose of them off Owner's property.

END OF SECTION 312000

## SECTION 312319 - DEWATERING

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.
- B. Storm Water Pollution Prevention Plan and NPDES Construction General Permit.

#### 1.2 SUMMARY

- A. Section includes:
  - 1. Construction Dewatering.
- B. Construction runoff or dewatering effluent shall not be discharged directly or tributary to stormwater management infiltration systems without the specific approval of the Owner or Engineer. Approval will require effluent water quality testing.
- C. Related Requirements:
  - 1. Section 312000 "Earth Moving" for excavating, backfilling, site grading, and controlling surface-water runoff and ponding.

#### 1.3 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.
  - 1. Verify availability of Installer's personnel, equipment, and facilities needed to make progress and avoid delays.
  - 2. Review condition of site to be dewatered including coordination with temporary erosion-control measures and temporary controls and protections.
  - 3. Review geotechnical report.
  - 4. Review proposed site clearing and excavations.
  - 5. Review existing utilities and subsurface conditions.
  - 6. Review observation and monitoring of dewatering system.

#### 1.4 ACTION SUBMITTALS

- A. Shop Drawings: For dewatering system, prepared by or under the supervision of a qualified professional engineer.

1. Include plans, elevations, sections, and details.
2. Show arrangement, locations, and details of wells and well points; locations of risers, headers, filters, pumps, power units, and discharge lines; and means of discharge, control of sediment, and disposal of water.
3. Include layouts of piezometers and flow-measuring devices for monitoring performance of dewatering system.
4. Include written plan for dewatering operations including sequence of well and well-point placement coordinated with excavation shoring and bracings and control procedures to be adopted if dewatering problems arise.

#### 1.5 INFORMATIONAL SUBMITTALS

- A. Field Quality-Control Submittals:
  1. Field quality-control reports.
- B. Qualification Statements: For Installer and professional engineer
- C. Existing Conditions: Using photographs or video recordings, show existing conditions of adjacent construction and site improvements that might be misconstrued as damage caused by dewatering operations. Submit before Work begins.
- D. Record Drawings: Identify locations and depths of capped wells and well points and other abandoned-in-place dewatering equipment.

#### 1.6 QUALITY ASSURANCE

- A. Qualifications:
  1. Installer: An experienced installer that has specialized in design of dewatering systems and dewatering work.

#### 1.7 FIELD CONDITIONS

- A. Project-Site Information: A geotechnical report has been prepared for this Project and is available for information only. The opinions expressed in this report are those of a geotechnical engineer and represent interpretations of subsoil conditions, tests, and results of analyses conducted by a geotechnical engineer. Owner is not responsible for interpretations or conclusions drawn from this data.
  1. Make additional test borings and conduct other exploratory operations necessary for dewatering in accordance with to performance requirements.



- B. Survey Work: Engage a qualified land surveyor or professional engineer to survey adjacent existing buildings, structures, and site improvements; establish exact elevations at fixed points to act as benchmarks. Clearly identify benchmarks and record existing elevations.

## PART 2 - PRODUCTS

### 2.1 PERFORMANCE REQUIREMENTS

- A. Dewatering Performance: Design, furnish, install, test, operate, monitor, and maintain dewatering system of sufficient scope, size, and capacity to control hydrostatic pressures and to lower, control, remove, and dispose of groundwater and permit excavation and construction to proceed on dry, stable subgrades.
  - 1. Design dewatering system, including comprehensive engineering analysis by a qualified professional engineer.
  - 2. Continuously monitor and maintain dewatering operations to ensure erosion control, stability of excavations and constructed slopes, prevention of flooding in excavation, and prevention of damage to subgrades and permanent structures.
  - 3. Prevent surface water from entering excavations by grading, dikes, or other means.
  - 4. Accomplish dewatering without damaging existing buildings, structures, and site improvements adjacent to excavation.
  - 5. Remove dewatering system when no longer required for construction.
- B. Regulatory Requirements: Comply with governing EPA notification regulations before beginning dewatering. Comply with water- and debris-disposal regulations of authorities having jurisdiction.

## PART 3 - EXECUTION

### 3.1 PREPARATION

- A. Protect structures, utilities, sidewalks, pavements, and other facilities from damage caused by settlement, lateral movement, undermining, washout, and other hazards created by dewatering operations.
  - 1. Prevent surface water and subsurface or groundwater from entering excavations, from ponding on prepared subgrades, and from flooding site or surrounding area.
  - 2. Protect subgrades and foundation soils from softening and damage by rain or water accumulation.
- B. Install dewatering system to ensure minimum interference with roads, streets, walks, and other adjacent occupied and used facilities.

## DEWATERING

312319 - 3

1. Do not close or obstruct streets, walks, or other adjacent occupied or used facilities without permission from Owner and authorities having jurisdiction. Provide alternate routes around closed or obstructed traffic ways if required by authorities having jurisdiction.
- C. Provide temporary grading to facilitate dewatering and control of surface water.
- D. Protect and maintain temporary erosion and sedimentation controls, which are specified in Section 311000 "Site Clearing," during dewatering operations.

### 3.2 INSTALLATION

- A. Install dewatering system utilizing wells, well points, or similar methods complete with pump equipment, standby power and pumps, filter material gradation, valves, appurtenances, water disposal, and surface-water controls.
  1. Space well points or wells at intervals required to provide sufficient dewatering.
  2. Use filters or other means to prevent pumping of fine sands or silts from the subsurface.
- B. Place dewatering system into operation to lower water to specified levels before excavating below groundwater level.
- C. Provide sumps, sedimentation tanks, and other flow-control devices as required by authorities having jurisdiction.
- D. Provide standby equipment on-site, installed and available for immediate operation, to maintain dewatering on continuous basis if any part of system becomes inadequate or fails.

### 3.3 OPERATION

- A. Operate system continuously until drains, sewers, and structures have been constructed and fill materials have been placed or until dewatering is no longer required.
- B. Operate system to lower and control groundwater to permit excavation, construction of structures, and placement of fill materials on dry subgrades. Drain water-bearing strata above and below bottom of foundations, drains, sewers, and other excavations.
  1. Do not permit open-sump pumping that leads to loss of fines, soil piping, subgrade softening, and slope instability.
  2. Reduce hydrostatic head in water-bearing strata below subgrade elevations of foundations, drains, sewers, and other excavations.
  3. Maintain piezometric water level a minimum of 24 inches below bottom of excavation.

- C. Dispose of water removed by dewatering in a manner that avoids endangering public health, property, and portions of work under construction or completed. Dispose of water and sediment in a manner that avoids inconvenience to others.
- D. Remove dewatering system from Project site on completion of dewatering. Plug or fill well holes with sand or cut off and cap wells a minimum of 36 inches below overlying construction.

### 3.4 FIELD QUALITY CONTROL

- A. Observation Wells: Provide observation wells or piezometers, take measurements, and maintain at least the minimum number indicated; additional observation wells may be required by authorities having jurisdiction.
  - 1. Observe and record daily elevation of groundwater and piezometric water levels in observation wells.
  - 2. Repair or replace, within 24 hours, observation wells that become inactive, damaged, or destroyed. In areas where observation wells are not functioning properly, suspend construction activities until reliable observations can be made. Add or remove water from observation-well risers to demonstrate that observation wells are functioning properly.
  - 3. Fill observation wells, remove piezometers, and fill holes when dewatering is completed.
- B. Survey-Work Benchmarks: Resurvey benchmarks regularly during dewatering and maintain an accurate log of surveyed elevations for comparison with original elevations. Promptly notify Engineer if changes in elevations occur or if cracks, sags, or other damage is evident in adjacent construction.
- C. Provide continual observation to ensure that subsurface soils are not being removed by the dewatering operation.
- D. Prepare reports of observations.

### 3.5 PROTECTION

- A. Protect and maintain dewatering system during dewatering operations.
- B. Promptly repair damages to adjacent facilities caused by dewatering.

END OF SECTION 312319

## SECTION 315000 - EXCAVATION SUPPORT AND PROTECTION

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section includes temporary excavation support and protection systems.
- B. Related Requirements:
  - 1. Section 013233 312000 "Earth Moving" for excavating and backfilling, for controlling surface-water runoff and ponding, and for dewatering excavations.

#### 1.3 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.
  - 1. Review geotechnical report.
  - 2. Review existing utilities and subsurface conditions.
  - 3. Review coordination for interruption, shutoff, capping, and continuation of utility services.
  - 4. Review proposed excavations.
  - 5. Review proposed equipment.
  - 6. Review monitoring of excavation support and protection system.
  - 7. Review coordination with waterproofing.
  - 8. Review abandonment or removal of excavation support and protection system.

#### 1.4 ACTION SUBMITTALS

- A. Product Data: For each type of product.
  - 1. Include construction details, material descriptions, performance properties, and dimensions of individual components and profiles, and calculations for excavation support and protection system.

- B. Shop Drawings: For excavation support and protection system, prepared by or under the supervision of a qualified professional engineer.
  - 1. Include plans, elevations, sections, and details.
  - 2. Show arrangement, locations, and details of soldier piles, piling, lagging, tiebacks, bracing, and other components of excavation support and protection system according to engineering design.
  - 3. Indicate type and location of waterproofing.
  - 4. Include a written plan for excavation support and protection, including sequence of construction of support and protection coordinated with progress of excavation.

#### 1.5 INFORMATIONAL SUBMITTALS

- A. Contractor Calculations: For excavation support and protection system. Include analysis data signed and sealed by the qualified professional engineer responsible for their preparation.
- B. Existing Conditions: Using photographs or video recordings, show existing conditions of adjacent construction and site improvements that might be misconstrued as damage caused by inadequate performance of excavation support and protection systems. Submit before Work begins.

#### 1.6 CLOSEOUT SUBMITTALS

- A. Record Drawings: Identify locations and depths of capped utilities, abandoned-in-place support and protection systems, and other subsurface structural, electrical, or mechanical conditions.

#### 1.7 FIELD CONDITIONS

- A. Interruption of Existing Utilities: Do not interrupt any utility-serving facilities occupied by Owner or others unless permitted under the following conditions and then only after arranging to provide temporary utility according to requirements indicated:
  - 1. Notify Owner no fewer than two days in advance of proposed interruption of utility.
  - 2. Do not proceed with interruption of utility without Owner's written permission.
- B. Survey Work: Engage a qualified land surveyor or professional engineer to survey adjacent existing buildings, structures, and site improvements; establish exact elevations at fixed points to act as benchmarks. Clearly identify benchmarks, and record existing elevations.
  - 1. Make additional test borings and conduct other exploratory operations necessary for excavation support and protection according to the performance requirements.

## PART 2 - PRODUCTS

### 2.1 PERFORMANCE REQUIREMENTS

- A. Delegated Design: Engage a qualified professional engineer, as defined in Section 014000 "Quality Requirements," to design excavation support and protection systems to resist all lateral loading and surcharge, including but not limited to, retained soil, groundwater pressure, adjacent building loads, adjacent traffic loads, construction traffic loads, material stockpile loads, and seismic loads, based on the following:
  - 1. Compliance with OSHA Standards and interpretations, 29 CFR 1926, Subpart P.
  - 2. Compliance with AASHTO Standard Specification for Highway Bridges or AASHTO LRFD Bridge Design Specification, Customary U.S. Units.
  - 3. Compliance with requirements of authorities having jurisdiction.
  - 4. Compliance with utility company requirements.
  - 5. Compliance with railroad requirements.

### 2.2 MATERIALS

- A. Provide materials that are either new or in serviceable condition.
- B. Structural Steel: ASTM A 36/A36M, ASTM A690/A690M, or ASTM A992/A992M.
- C. Steel Sheet Piling: ASTM A328/A328M, ASTM A572/A572M, or ASTM A690/A690M; with continuous interlocks.
- D. Wood Lagging: Lumber, mixed hardwood, nominal rough thickness of size and strength required for application.
- E. Cast-in-Place Concrete: ACI 301, of compressive strength required for application.
- F. Reinforcing Bars: ASTM A615/A615M, Grade 60, deformed.

## PART 3 - EXECUTION

### 3.1 PREPARATION

- A. Protect structures, utilities, sidewalks, pavements, and other facilities from damage caused by settlement, lateral movement, undermining, washout, and other hazards that could develop during excavation support and protection system operations.
  - 1. Shore, support, and protect utilities encountered.

### 3.2 INSTALLATION - GENERAL

- A. Locate excavation support and protection systems clear of permanent construction, so that construction and finishing of other work is not impeded.
- B. Install excavation support and protection systems to ensure minimum interference with roads, streets, walks, and other adjacent occupied and used facilities.
  - 1. Do not close or obstruct streets, walks, or other adjacent occupied or used facilities without permission from Owner and authorities having jurisdiction.
  - 2. Provide alternate routes around closed or obstructed traffic ways if required by authorities having jurisdiction.
- C. Install excavation support and protection systems without damaging existing buildings, structures, and site improvements adjacent to excavation.

### 3.3 SOLDIER PILES AND LAGGING

- A. Install steel soldier piles before starting excavation.
  - 1. Extend soldier piles below excavation grade level to depths adequate to prevent lateral movement.
  - 2. Space soldier piles at regular intervals not to exceed allowable flexural strength of wood lagging.
  - 3. Accurately align exposed faces of flanges to vary not more than 2 inches from a horizontal line and not more than 1:120 out of vertical alignment.
- B. Install wood lagging within flanges of soldier piles as excavation proceeds.
  - 1. Trim excavation as required to install lagging.
  - 2. Fill voids behind lagging with soil, and compact.
- C. Install wales horizontally at locations indicated on Drawings and secure to soldier piles.

### 3.4 SHEET PILING

- A. Before starting excavation, install one-piece sheet piling lengths and tightly interlock vertical edges to form a continuous barrier.
- B. Accurately place the piling using templates and guide frames unless otherwise recommended in writing by the sheet piling manufacturer.
  - 1. Limit vertical offset of adjacent sheet piling to 60 inches.
  - 2. Accurately align exposed faces of sheet piling to vary not more than 2 inches from a horizontal line and not more than 1:120 out of vertical alignment.

- C. Cut tops of sheet piling to uniform elevation at top of excavation.

### 3.5 BRACING

- A. Locate bracing to clear columns, floor framing construction, and other permanent work. If necessary to move brace, install new bracing before removing original brace.
  - 1. Do not place bracing where it will be cast into or included in permanent concrete work unless otherwise approved by Owner.
  - 2. Install internal bracing if required to prevent spreading or distortion of braced frames.
  - 3. Maintain bracing until structural elements are supported by other bracing or until permanent construction is able to withstand lateral earth and hydrostatic pressures.

### 3.6 TRENCH BOXES

- A. Use caution when using a steel trench box to install underground piping or conduit to ensure that items already installed are not pulled apart when the trench box is moved ahead to install the next pipe. It may be necessary to prevent the bottom of the trench box not from extending below mid-diameter of the pipe or to pick the end of the trench box up above mid-diameter before moving it ahead.

### 3.7 MAINTENANCE

- A. Monitor and maintain excavation support and protection system.
- B. Prevent surface water from entering excavations by grading, dikes, or other means.
- C. Continuously monitor vibrations, settlements, and movements to ensure stability of excavations and constructed slopes and to ensure that damage to permanent structures is prevented.

### 3.8 FIELD QUALITY CONTROL

- A. Survey-Work Benchmarks: Resurvey benchmarks daily during installation of excavation support and protection systems, excavation progress, and for as long as excavation remains open.
  - 1. Maintain an accurate log of surveyed elevations and positions for comparison with original elevations and positions.
  - 2. Promptly notify Engineer if changes in elevations or positions occur or if cracks, sags, or other damage is evident in adjacent construction.



- B. Promptly correct detected bulges, breakage, or other evidence of movement to ensure that excavation support and protection system remains stable.
- C. Promptly repair damages to adjacent facilities caused by installation or faulty performance of excavation support and protection systems.

### 3.9 REMOVAL AND REPAIRS

- A. Remove excavation support and protection systems when construction has progressed sufficiently to support excavation and earth and hydrostatic pressures.
  - 1. Remove in stages to avoid disturbing underlying soils and rock or damaging structures, pavements, facilities, and utilities.
  - 2. Remove excavation support and protection systems to a minimum depth of 48 inches below overlying construction, and abandon remainder.
  - 3. Fill voids immediately with approved backfill compacted to density specified in Section 312000 "Earth Moving."
  - 4. Repair or replace, as approved by Engineer, adjacent work damaged or displaced by removing excavation support and protection systems.
- B. Leave excavation support and protection systems permanently in place.

END OF SECTION 315000

## SECTION 321216 - ASPHALT PAVING

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:

- 1. Hot-mix asphalt paving.
- 2. Hot-mix asphalt patching.
- 3. Granite curbs.
- 4. Asphalt surface treatments.

- B. Related Requirements:

- 1. Section 024119 "Selective Demolition" for demolition and removal of existing asphalt pavement.
- 2. Section 312000 "Earth Moving" for subgrade preparation, fill material, separation geotextiles, unbound-aggregate subbase and base courses, and aggregate pavement shoulders.
- 3. Section 321313 "Concrete Paving" for concrete pavement and for separate concrete curbs.

#### 1.3 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.

- 1. Review methods and procedures related to hot-mix asphalt paving including, but not limited to, the following:
  - a. Review proposed sources of paving materials, including capabilities and location of plant that will manufacture hot-mix asphalt.
  - b. Review requirements for protecting paving work, including restriction of traffic during installation period and for remainder of construction period.

#### 1.4 ACTION SUBMITTALS

- A. Product Data: Include technical data and tested physical and performance properties.
  - 1. Herbicide.
  - 2. Paving geotextile.
  - 3. Joint sealant.

#### 1.5 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For paving-mix manufacturer.
- B. Material Certificates: For each paving material, from manufacturer.
  - 1. Aggregates.
  - 2. Asphalt binder.
  - 3. Asphalt cement.
  - 4. Cutback prime coat.
  - 5. Emulsified asphalt prime coat.
  - 6. Tack coat.
  - 7. Fog seal.
  - 8. Undersealing asphalt.
- C. Field quality-control reports.

#### 1.6 QUALITY ASSURANCE

- A. Manufacturer Qualifications: A paving-mix manufacturer registered with and approved by authorities having jurisdiction or the DOT of state in which Project is located.
- B. Testing Agency Qualifications: Qualified in accordance with ASTM D3666 for testing indicated.
- C. Regulatory Requirements: Comply with materials, workmanship, and other applicable requirements of the Commonwealth of Massachusetts Department of Transportation Standard Specifications for Highways and Bridges, 2021 edition as amended ("Standard Specification") for asphalt paving work.
  - 1. Measurement and payment provisions and safety program submittals included in standard specifications do not apply to this Section.

## 1.7 FIELD CONDITIONS

- A. Environmental Limitations: Do not apply asphalt materials if subgrade is wet or excessively damp, if rain is imminent or expected before time required for adequate cure, or if the following conditions are not met:
  - 1. Prime Coat: Minimum surface temperature of 60 deg F
  - 2. Tack Coat: Minimum surface temperature of 60 deg F
  - 3. Slurry Coat: Comply with weather limitations in ASTM D3910.
  - 4. Asphalt Base Course and Binder Course: Minimum surface temperature of 40 deg F and rising at time of placement.
  - 5. Asphalt Surface Course: Minimum surface temperature of 60 deg F at time of placement.

## PART 2 - PRODUCTS

### 2.1 AGGREGATES

- A. General: Use materials and gradations that have performed satisfactorily in previous installations.
- B. Coarse Aggregate: Comply with section M3.11.04A of the Standard Specification.
- C. Fine Aggregate: Comply with section M3.11.04B of the Standard Specification.
- D. Mineral Filler: Comply with section M3.11.05 of the Standard Specification.

### 2.2 ASPHALT MATERIALS

- A. Asphalt Binder: AASHTO MP 1, PG 64-28.
- B. Asphalt Cement: Comply with section M3.01.0 of the Standard Specification.
- C. Prime Coat: Asphalt emulsion prime coat complying with the Standard Specifications.
- D. Asphalt Cement: AASHTO M 140, emulsified asphalt or AASHTO M 208, cationic emulsified asphalt, slow setting, diluted in water, of suitable grade and consistency for application.
- E. Tack Coat: AASHTO M 140 emulsified asphalt, or AASHTO M 208 cationic emulsified asphalt, slow setting, diluted in water, of suitable grade and consistency for application.
- F. Water: Potable.
- G. Undersealing Asphalt: ASTM D3141/D3141M; pumping consistency.

## ASPHALT PAVING

321216 - 3

## 2.3 AUXILIARY MATERIALS

- A. Herbicide: Commercial chemical for weed control, registered by the EPA, and not classified as "restricted use" for locations and conditions of application. Provide in granular, liquid, or wettable powder form.
- B. Sand: ASTM D1073, Grade No. 2 or No. 3.
- C. Paving Geotextile: AASHTO M 288 paving fabric; nonwoven polypropylene; resistant to chemical attack, rot, and mildew; and specifically designed for paving applications.
- D. Joint Sealant: ASTM D6690, hot-applied, single-component, polymer-modified bituminous sealant.
- E. Wheel Stops: Precast, air-entrained concrete, 2500-psi minimum compressive strength, 4-1/2 inches high by 9 inches wide by 72 inches long. Provide chamfered corners, drainage slots on underside, and holes for anchoring to substrate.
  - 1. Dowels: Galvanized steel, 3/4-inch diameter, 20-inch minimum length.

## 2.4 MIXES

- A. Hot-Mix Asphalt: Type I-1 conforming to the Standard Specifications, Sections 420 and 460, and M3.11.03 for binder course, top course and dense mix job mix formulas.
  - 1. Binder course: Conform to the Standard Specifications M3.01.01 for binder course hot mix asphalt in accordance with the job mix formula installed in one layer.
  - 2. Top course: Conform to the Standard Specifications M3.11.4 for top course hot mix asphalt in accordance with the job mix formula installed in one layer.
- B. Emulsified-Asphalt Slurry: ASTM D3910, Type 1.

## 2.5 GRANITE CURBING AND EDGESTONE

- A. Curbing: Type VA4 in accordance with subsection M9.04.1 of the Standard Specification.
- B. Edgestone: Type SB in accordance with Sub-Section M9.04.2 of the Standard Specifications.
- C. Quality: Light gray in color, free from seams, and other imperfections that would impair structural integrity or appearance.

- D. Consistent source: Quarry all granite materials from a single source to produce consistent color and texture.

### PART 3 - EXECUTION

#### 3.1 EXAMINATION

- A. Verify that subgrade is dry and in suitable condition to begin paving.
- B. Proceed with paving only after unsatisfactory conditions have been corrected.

#### 3.2 PREPARATION

- A. Protection: Provide protective materials, procedures, and worker training to prevent asphalt materials from spilling, coating, or building up on curbs, driveway aprons, manholes, and other surfaces adjacent to the Work.
- B. Proof-roll subgrade below pavements with heavy pneumatic-tired equipment to identify soft pockets and areas of excess yielding. Do not proof-roll wet or saturated subgrades.
  - 1. Completely proof-roll subgrade in one direction, repeating proof-rolling in direction perpendicular to first direction. Limit vehicle speed to 3 mph
  - 2. Proof-roll with a loaded 10-wheel, tandem-axle dump truck weighing not less than 15 tons
  - 3. Excavate soft spots, unsatisfactory soils, and areas of excessive pumping or rutting, as determined by Engineer, and replace with compacted backfill or fill as directed.

#### 3.3 PATCHING

- A. Asphalt Pavement: Saw cut perimeter of patch and excavate existing pavement section to sound base. Excavate rectangular or trapezoidal patches, extending 12 inches into perimeter of adjacent sound pavement, unless otherwise indicated. Cut excavation faces vertically. Remove excavated material. Recompact existing unbound-aggregate base course to form new subgrade.
- B. Tack Coat: Before placing patch material, apply tack coat uniformly to vertical asphalt surfaces abutting the patch. Apply at a rate of 0.05 to 0.15 gal./sq. yd..
  - 1. Allow tack coat to cure undisturbed before applying hot-mix asphalt paving.
  - 2. Avoid smearing or staining adjoining surfaces, appurtenances, and surroundings. Remove spillages and clean affected surfaces.

- C. Placing Single-Course Patch Material: Fill excavated pavement areas with hot-mix asphalt base mix for full thickness of patch and, while still hot, compact flush with adjacent surface.
- D. Placing Two-Course Patch Material: Partially fill excavated pavements with hot-mix asphalt base course mix and, while still hot, compact. Cover asphalt base course with compacted layer of hot-mix asphalt surface course, finished flush with adjacent surfaces.

### 3.4 REPAIRS

- A. Leveling Course: Install and compact leveling course consisting of hot-mix asphalt surface course to level sags and fill depressions deeper than 1 inch in existing pavements.
  - 1. Install leveling wedges in compacted lifts not exceeding 3 inches thick.
- B. Crack and Joint Filling: Remove existing joint filler material from cracks or joints to a depth of 1/4 inch.
  - 1. Clean cracks and joints in existing hot-mix asphalt pavement.
  - 2. Use emulsified-asphalt slurry to seal cracks and joints less than 1/4 inch wide. Fill flush with surface of existing pavement and remove excess.
  - 3. Use hot-applied joint sealant to seal cracks and joints more than 1/4 inch wide. Fill flush with surface of existing pavement and remove excess.

### 3.5 SURFACE PREPARATION

- A. Ensure that prepared subgrade has been proof-rolled and is ready to receive paving. Immediately before placing asphalt materials, remove loose and deleterious material from substrate surfaces.
- B. Herbicide Treatment: Apply herbicide in accordance with manufacturer's recommended rates and written application instructions. Apply to dry, prepared subgrade or surface of compacted-aggregate base before applying paving materials.
  - 1. Mix herbicide with prime coat if formulated by manufacturer for that purpose.
- C. Tack Coat: Apply uniformly to surfaces of existing pavement at a rate of 0.05 to 0.15 gal./sq. yd..
  - 1. Allow tack coat to cure undisturbed before applying hot-mix asphalt paving.
  - 2. Avoid smearing or staining adjoining surfaces, appurtenances, and surroundings. Remove spillages and clean affected surfaces.

### 3.6 HOT-MIX ASPHALT PLACEMENT

- A. Machine place hot-mix asphalt on prepared surface, spread uniformly, and strike off. Place asphalt mix by hand in areas inaccessible to equipment in a manner that prevents segregation of mix. Place each course to required grade, cross section, and thickness when compacted.
  - 1. Place hot-mix asphalt base course in number of lifts and thicknesses indicated.
  - 2. Place hot-mix asphalt surface course in single lift.
  - 3. Spread mix at a minimum temperature of 250 deg F.
  - 4. Begin applying mix along centerline of crown for crowned sections and on high side of one-way slopes unless otherwise indicated.
  - 5. Regulate paver machine speed to obtain smooth, continuous surface free of pulls and tears in asphalt-paving mat.
- B. Place paving in consecutive strips not less than 10 feet wide unless infill edge strips of a lesser width are required.
  - 1. After first strip has been placed and rolled, place succeeding strips and extend rolling to overlap previous strips. Overlap mix placement about 1 to 1-1/2 inches from strip to strip to ensure proper compaction of mix along longitudinal joints.
  - 2. Complete a section of asphalt base course before placing asphalt surface course.
- C. Promptly correct surface irregularities in paving course behind paver. Use suitable hand tools to remove excess material forming high spots. Fill depressions with hot-mix asphalt to prevent segregation of mix; use suitable hand tools to smooth surface.

### 3.7 JOINTS

- A. Construct joints to ensure a continuous bond between adjoining paving sections. Construct joints free of depressions, with same texture and smoothness as other sections of hot-mix asphalt course.
  - 1. Clean contact surfaces and apply tack coat to joints.
  - 2. Offset longitudinal joints, in successive courses, a minimum of 6 inches.
  - 3. Offset transverse joints, in successive courses, a minimum of 24 inches.
  - 4. Construct transverse joints at each point where paver ends a day's work and resumes work at a subsequent time. Construct these joints using either "bulkhead" or "papered" method in accordance with AI MS-22, for both "Ending a Lane" and "Resumption of Paving Operations."
  - 5. Compact joints as soon as hot-mix asphalt will bear roller weight without excessive displacement.
  - 6. Compact asphalt at joints to a density within 2 percent of specified course density.



### 3.8 COMPACTION

- A. General: Begin compaction as soon as placed hot-mix paving will bear roller weight without excessive displacement. Compact hot-mix paving with hot hand tampers or with vibratory-plate compactors in areas inaccessible to rollers.
  - 1. Complete compaction before mix temperature cools to 185 deg F.
- B. Breakdown Rolling: Complete breakdown or initial rolling immediately after rolling joints and outside edge. Examine surface immediately after breakdown rolling for indicated crown, grade, and smoothness. Correct laydown and rolling operations to comply with requirements.
- C. Intermediate Rolling: Begin intermediate rolling immediately after breakdown rolling while hot-mix asphalt is still hot enough to achieve specified density. Continue rolling until hot-mix asphalt course has been uniformly compacted to the following density:
  - 1. Average Density, Marshall Test Method: 96 percent of reference laboratory density in accordance with AASHTO T 245, but not less than 94 percent or greater than 100 percent.
  - 2. Average Density, Rice Test Method: 92 percent of reference maximum theoretical density in accordance with ASTM D2041/D2041M, but not less than 90 percent or greater than 96 percent.
- D. Finish Rolling: Finish roll paved surfaces to remove roller marks while hot-mix asphalt is still warm.
- E. Edge Shaping: While surface is being compacted and finished, trim edges of pavement to proper alignment. Bevel edges while asphalt is still hot; compact thoroughly.
- F. Repairs: Remove paved areas that are defective or contaminated with foreign materials and replace with fresh, hot-mix asphalt. Compact by rolling to specified density and surface smoothness.
- G. Protection: After final rolling, do not permit vehicular traffic on pavement until it has cooled and hardened.
- H. Erect barricades to protect paving from traffic until mixture has cooled enough not to become marked.

### 3.9 GRANITE AND CONCRETE CURBS

- A. Inspect units for damage upon delivery to site. Unload and place units along excavated trench or other designated location with a minimum amount of handling.

1. Handle materials in such a manner so as to ensure delivery to trench in a sound and undamaged condition.
  2. Mark individual pieces of curved curbing to correspond to the radius and location where curbing is to be set.
- B. Make excavation in accordance with details on the drawings, extending below and behind finished curb sections as indicated.
1. Compact gravel base to a firm, even surface as specified for pavement base course.
- C. Complete installation of curb within the prepared trench so that each section is butted to the next continuously and conforming to the line, grade, and cross section shown on the drawings and in a manner which will prevent damage to the units.
1. Joint Width: minimum 1/8 inch maximum 1/4 inch.
- D. Fill joints between granite curbing and edging sections with cement mortar and neatly point on top and front face. Clean curbing of excess mortar after pointing.
- E. After the curb is set, backfill trench immediately with indicated material. Take care so as not to affect the line or grade of the curb during this procedure.

### 3.10 INSTALLATION TOLERANCES

- A. Grade: Maximum grades of pavement shall meet the following requirements unless otherwise indicated:
1. Handicap Parking Area: 2 percent.
  2. Sidewalk, Transverse: 2 percent.
  3. Sidewalk, Longitudinal: 5 percent.
  4. Ramp, Transverse: 2 percent.
  5. Ramp, Longitudinal: 1:12 rise to run ratio.
- B. Pavement Thickness: Compact each course to produce thickness indicated within the following tolerances:
1. Binder Course: Plus or minus 1/2 inch.
  2. Surface Course: Plus 1/4 inch, no minus.
- C. Pavement Surface Smoothness: Compact each course to produce surface smoothness within the following tolerances as determined by using a 10-foot straightedge applied transversely or longitudinally to paved areas:
1. Binder Course: 1/4 inch.
  2. Surface Course: 1/8 inch.

3. Crowned Surfaces: Test with crowned template centered and at right angle to crown. Maximum allowable variance from template is 1/4 inch.

### 3.11 SURFACE TREATMENTS

- A. Slurry Seals: Apply slurry coat in a uniform thickness in accordance with ASTM D3910 and allow to cure.

1. Roll slurry seal to remove ridges and provide a uniform, smooth surface.

### 3.12 FIELD QUALITY CONTROL

- A. Testing Agency: Engage a qualified testing agency to perform tests and inspections.
- B. Thickness: In-place compacted thickness of hot-mix asphalt courses will be determined in accordance with ASTM D3549/D3549M.
- C. Surface Smoothness: Finished surface of each hot-mix asphalt course will be tested for compliance with smoothness tolerances.
- D. In-Place Density: Testing agency will take samples of uncompacted paving mixtures and compacted pavement in accordance with AASHTO T 168.
  1. Reference maximum theoretical density will be determined by averaging results from four samples of hot-mix asphalt-paving mixture delivered daily to site, prepared in accordance with ASTM D2041/D2041M, and compacted in accordance with job-mix specifications.
  2. In-place density of compacted pavement will be determined by testing core samples in accordance with ASTM D1188 or ASTM D2726/D2726M.
    - a. One core sample will be taken for every 1000 sq. yd. or less of installed pavement, with no fewer than three cores taken.
    - b. Field density of in-place compacted pavement may also be determined by nuclear method in accordance with ASTM D2950/D2950M and coordinated with ASTM D1188 or ASTM D2726/D2726M.
- E. Replace and compact hot-mix asphalt where core tests were taken.
- F. Remove and replace or install additional hot-mix asphalt where test results or measurements indicate that it does not comply with specified requirements.

3.13 WASTE HANDLING

- A. General: Handle asphalt-paving waste in accordance with approved waste management plan required in Section 017419 "Construction Waste Management and Disposal."

END OF SECTION 321216

## SECTION 321313 - CONCRETE PAVING

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes Concrete Paving. Including the Following:
  - 1. Walks.
  - 2. Concrete Pads for Site Furnishings
- B. Related Requirements:
  - 1. Section 033053 "Miscellaneous Cast-in-Place Concrete" for general building applications of concrete.
  - 2. Section 321373 "Concrete Paving Joint Sealants" for joint sealants in expansion and contraction joints within concrete paving and in joints between concrete paving and asphalt paving or adjacent construction.

#### 1.3 DEFINITIONS

- A. Cementitious Materials: Portland cement alone or in combination with one or more of blended hydraulic cement, fly ash, slag cement, and other pozzolans.
- B. W/C Ratio: The ratio by weight of water to cementitious materials.

#### 1.4 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.
  - 1. Review methods and procedures related to concrete paving, including but not limited to, the following:
    - a. Concrete mixture design.
    - b. Quality control of concrete materials and concrete paving construction practices.
  - 2. Require representatives of each entity directly concerned with concrete paving to attend, including the following:

### CONCRETE PAVING

321313 - 1

- a. Contractor's superintendent.
- b. Concrete paving Subcontractor.

#### 1.5 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Samples for Initial Selection: For each type of product, ingredient, or admixture requiring color selection.
- C. Design Mixtures: For each concrete paving mixture. Include alternate design mixtures when characteristics of materials, Project conditions, weather, test results, or other circumstances warrant adjustments.

#### 1.6 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For qualified ready-mix concrete manufacturer and testing agency.
- B. Material Certificates: For the following, from manufacturer:
  - 1. Cementitious materials.
  - 2. Steel reinforcement and reinforcement accessories.
  - 3. Admixtures.
  - 4. Curing compounds.
  - 5. Applied finish materials.
  - 6. Bonding agent or epoxy adhesive.
  - 7. Joint fillers.
- C. Material Test Reports: For each of the following:
  - 1. Aggregates: Include service-record data indicating absence of deleterious expansion of concrete due to alkali-aggregate reactivity.
- D. Field quality-control reports.

#### 1.7 QUALITY ASSURANCE

- A. Ready-Mix-Concrete Manufacturer Qualifications: A firm experienced in manufacturing ready-mixed concrete products and that complies with ASTM C94/C94M requirements for production facilities and equipment.

### CONCRETE PAVING

321313 - 2

1. Manufacturer certified according to NRMCA's "Certification of Ready Mixed Concrete Production Facilities" (Quality Control Manual - Section 3, "Plant Certification Checklist").
- B. Testing Agency Qualifications: Qualified according to ASTM C1077 and ASTM E329 for testing indicated.
  1. Personnel conducting field tests must be qualified as ACI Concrete Field Testing Technician, Grade 1, according to ACI CP-1 or an equivalent certification program.

## 1.8 FIELD CONDITIONS

- A. Traffic Control: Maintain access for vehicular and pedestrian traffic as required for other construction activities.
- B. Cold-Weather Concrete Placement: Protect concrete work from physical damage or reduced strength that could be caused by frost, freezing, or low temperatures. Comply with ACI 306.1 and the following:
  1. When air temperature has fallen to or is expected to fall below 40 deg°F, uniformly heat water and aggregates before mixing to obtain a concrete mixture temperature of not less than 50 deg°F and not more than 80 deg°F at point of placement.
  2. Do not use frozen materials or materials containing ice or snow.
  3. Do not use calcium chloride, salt, or other materials containing antifreeze agents or chemical accelerators unless otherwise specified and approved in design mixtures.
- C. Hot-Weather Concrete Placement: Comply with ACI 301 and as follows when hot-weather conditions exist:
  1. Cool ingredients before mixing to maintain concrete temperature below 90 deg°F at time of placement. Chilled mixing water or chopped ice may be used to control temperature, provided water equivalent of ice is calculated in total amount of mixing water. Using liquid nitrogen to cool concrete is Contractor's option.
  2. Cover steel reinforcement with water-soaked burlap, so steel temperature will not exceed ambient air temperature immediately before embedding in concrete.
  3. Fog-spray forms[, **steel reinforcement**,] and subgrade just before placing concrete. Keep subgrade moisture uniform without standing water, soft spots, or dry areas.

## PART 2 - PRODUCTS

### 2.1 CONCRETE, GENERAL

- A. ACI Publications: Comply with ACI 301 unless otherwise indicated.

## CONCRETE PAVING

321313 - 3

## 2.2 FORMS

- A. Form Materials: Plywood, metal, metal-framed plywood, or other approved panel-type materials to provide full-depth, continuous, straight, and smooth exposed surfaces.
  - 1. Use flexible or uniformly curved forms for curves with a radius of 100 feet or less. Do not use notched and bent forms.
- B. Form-Release Agent: Commercially formulated form-release agent that will not bond with, stain, or adversely affect concrete surfaces and that will not impair subsequent treatments of concrete surfaces.

## 2.3 STEEL REINFORCEMENT

- A. Plain-Steel Welded-Wire Reinforcement: ASTM A1064/A1064M, fabricated from galvanized-steel wire into flat sheets.
- B. Deformed-Steel Welded-Wire Reinforcement: ASTM A1064/A1064M, flat sheet.
- C. Epoxy-Coated Welded-Wire Reinforcement: ASTM A884/A884M, Class A, plain steel.
- D. Reinforcing Bars: ASTM A615/A615M, Grade 60; deformed.
- E. Galvanized Reinforcing Bars: ASTM A767/A767M, Class II zinc coated, hot-dip galvanized after fabrication and bending; with ASTM A615/A615M, Grade 60 deformed bars.
- F. Epoxy-Coated Reinforcing Bars: ASTM A775/A775M or ASTM A934/A934M; with ASTM A615/A615M, Grade 60 deformed bars.
- G. Steel Bar Mats: ASTM A184/A184M; with ASTM A615/A615M, Grade 60 deformed bars; assembled with clips.
- H. Plain-Steel Wire: ASTM A1064/A1064M, galvanized.
- I. Deformed-Steel Wire: ASTM A1064/A1064M.
- J. Epoxy-Coated-Steel Wire: ASTM A884/A884M, Class A; coated, deformed.
- K. Joint Dowel Bars: ASTM A615/A615M, Grade 60 plain-steel bars; zinc coated (galvanized) after fabrication according to ASTM A767/A767M, Class I coating. Cut bars true to length with ends square and free of burrs.
- L. Epoxy-Coated, Joint Dowel Bars: ASTM A775/A775M; with ASTM A615/A615M, Grade 60 plain-steel bars.
- M. Tie Bars: ASTM A615/A615M, Grade 60; deformed.

## CONCRETE PAVING

321313 - 4



- N. Hook Bolts: ASTM A307, Grade A, internally and externally threaded. Design hook-bolt joint assembly to hold coupling against paving form and in position during concreting operations, and to permit removal without damage to concrete or hook bolt.
- O. Bar Supports: Bolsters, chairs, spacers, and other devices for spacing, supporting, and fastening reinforcing bars, welded-wire reinforcement, and dowels in place. Manufacture bar supports according to CRSI's "Manual of Standard Practice" from steel wire, plastic, or precast concrete of greater compressive strength than concrete specified, and as follows:
  - 1. Equip wire bar supports with sand plates or horizontal runners where base material will not support chair legs.
  - 2. For epoxy-coated reinforcement, use epoxy-coated or other dielectric-polymer-coated wire bar supports.
- P. Epoxy Repair Coating: Liquid, two-part, epoxy repair coating, compatible with epoxy coating on reinforcement.
- Q. Zinc Repair Material: ASTM A780/A780M.

## 2.4 CONCRETE MATERIALS

- A. Cementitious Materials: Use the following cementitious materials, of same type, brand, and source throughout Project:
  - 1. Portland Cement: ASTM C150/C150M, gray portland cement Type I.
  - 2. Fly Ash: ASTM C618, Class C or Class F.
  - 3. Slag Cement: ASTM C989/C989M, Grade 100 or 120.
- B. Normal-Weight Aggregates: ASTM C33/C33M, Class 4S, uniformly graded. Provide aggregates from a single source with documented service-record data of at least 10 years' satisfactory service in similar paving applications and service conditions using similar aggregates and cementitious materials.
  - 1. Maximum Coarse-Aggregate Size: 3/4 inch nominal.
  - 2. Fine Aggregate: Free of materials with deleterious reactivity to alkali in cement.
- C. Air-Entraining Admixture: ASTM C260/C260M.
- D. Chemical Admixtures: Admixtures certified by manufacturer to be compatible with other admixtures and to contain not more than 0.1 percent water-soluble chloride ions by mass of cementitious material.
  - 1. Water-Reducing Admixture: ASTM C494/C494M, Type A.
  - 2. Retarding Admixture: ASTM C494/C494M, Type B.
  - 3. Water-Reducing and Retarding Admixture: ASTM C494/C494M, Type D.
  - 4. High-Range, Water-Reducing Admixture: ASTM C494/C494M, Type F.

## CONCRETE PAVING

321313 - 5

- 5. High-Range, Water-Reducing and Retarding Admixture: ASTM C494/C494M, Type G.
  - 6. Plasticizing and Retarding Admixture: ASTM C1017/C1017M, Type II.
- E. Water: Potable and complying with ASTM C94/C94M.

## 2.5 CURING MATERIALS

- A. Absorptive Cover: AASHTO M 182, Class 3, burlap cloth made from jute or kenaf, weighing approximately 9 oz./sq. yd. dry.
- B. Moisture-Retaining Cover: ASTM C171, polyethylene film or white burlap-polyethylene sheet.
- C. Water: Potable.

## 2.6 RELATED MATERIALS

- A. Joint Fillers: ASTM D1752, cork or self-expanding cork in preformed strips.
- B. Bonding Agent: ASTM C1059/C1059M, Type II, non-redispersible, acrylic emulsion or styrene butadiene.
- C. Epoxy-Bonding Adhesive: ASTM C881/C881M, two-component epoxy resin capable of humid curing and bonding to damp surfaces; of class suitable for application temperature, of grade complying with requirements, and of the following types:
  - 1. [Types I and II, nonload bearing] [Types IV and V, load bearing], for bonding hardened or freshly mixed concrete to hardened concrete.
- D. Rock Salt: Sodium chloride crystals, kiln dried, coarse gradation with 100 percent passing 3/8-inch sieve and 85 percent retained on a No. 8 sieve.

## 2.7 CONCRETE MIXTURES

- A. Prepare design mixtures, proportioned according to ACI 301, for each type and strength of normal-weight concrete, and as determined by either laboratory trial mixtures or field experience.
  - 1. Use a qualified independent testing agency for preparing and reporting proposed concrete design mixtures for the trial batch method.
- B. Add air-entraining admixture at manufacturer's prescribed rate to result in normal-weight concrete at point of placement having an air content as follows:
  - 1. Air Content, 3/4-inch Nominal Maximum Aggregate Size: 6 percent plus or minus 1-1/2 percent.

## CONCRETE PAVING

321313 - 6

- C. Limit water-soluble, chloride-ion content in hardened concrete to 0.30 percent by weight of cement.
- D. Chemical Admixtures: Use admixtures according to manufacturer's written instructions.
  - 1. Use high-range, water-reducing and retarding admixture in concrete as required for placement and workability.
  - 2. Use water-reducing and retarding admixture when required by high temperatures, low humidity, or other adverse placement conditions.
- E. Color Pigment: Add color pigment to concrete mixture according to manufacturer's written instructions and to result in hardened concrete color consistent with approved mockup.
- F. Concrete Mixtures: Normal-weight concrete.
  - 1. Compressive Strength (28 Days): 4000 psi.
  - 2. Maximum W/C Ratio at Point of Placement: 0.45.
  - 3. Slump Limit: 5 inches, plus or minus 1 inch.

## 2.8 CONCRETE MIXING

- A. Ready-Mixed Concrete: Measure, batch, and mix concrete materials and concrete according to ASTM C94/C94M. Furnish batch certificates for each batch discharged and used in the Work.
  - 1. When air temperature is between 85 and 90 deg°F, reduce mixing and delivery time from 1-1/2 hours to 75 minutes; when air temperature is above 90 deg°F, reduce mixing and delivery time to 60 minutes.
- B. Project-Site Mixing: Measure, batch, and mix concrete materials and concrete according to ASTM C94/C94M. Mix concrete materials in appropriate drum-type batch machine mixer.
  - 1. For concrete batches of 1 cu. yd. or smaller, continue mixing at least 1-1/2 minutes, but not more than 5 minutes after ingredients are in mixer, before any part of batch is released.
  - 2. For concrete batches larger than 1 cu. yd., increase mixing time by 15 seconds for each additional 1 cu. yd..
  - 3. Provide batch ticket for each batch discharged and used in the Work, indicating Project identification name and number, date, mixture type, mixing time, quantity, and amount of water added.

## CONCRETE PAVING

321313 - 7

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- A. Examine exposed subgrades and subbase surfaces for compliance with requirements for dimensional, grading, and elevation tolerances.
- B. Proof-roll prepared subbase surface below concrete paving to identify soft pockets and areas of excess yielding.
  - 1. Completely proof-roll subbase in one direction. Limit vehicle speed to 3 mph.
  - 2. Proof-roll with a pneumatic-tired and loaded, 10-wheel, tandem-axle dump truck weighing not less than 15 tons.
  - 3. Correct subbase with soft spots and areas of pumping or rutting exceeding depth of 1/2 inch according to requirements in Section 312000 "Earth Moving."
- C. Proceed with installation only after unsatisfactory conditions have been corrected.

### 3.2 PREPARATION

- A. Remove loose material from compacted subbase surface immediately before placing concrete.

### 3.3 EDGE FORMS AND SCREED CONSTRUCTION

- A. Set, brace, and secure edge forms, bulkheads, and intermediate screed guides to required lines, grades, and elevations. Install forms to allow continuous progress of work and so forms can remain in place at least 24 hours after concrete placement.
- B. Clean forms after each use and coat with form-release agent to ensure separation from concrete without damage.

### 3.4 INSTALLATION OF STEEL REINFORCEMENT

- A. General: Comply with CRSI's "Manual of Standard Practice" for fabricating, placing, and supporting reinforcement.
- B. Clean reinforcement of loose rust and mill scale, earth, ice, or other bond-reducing materials.
- C. Arrange, space, and securely tie bars and bar supports to hold reinforcement in position during concrete placement. Maintain minimum cover to reinforcement.

## CONCRETE PAVING

321313 - 8

- D. Install welded-wire reinforcement in lengths as long as practicable. Lap adjoining pieces at least one full mesh, and lace splices with wire. Offset laps of adjoining widths to prevent continuous laps in either direction.
- E. Zinc-Coated Reinforcement: Use galvanized-steel wire ties to fasten zinc-coated reinforcement. Repair cut and damaged zinc coatings with zinc repair material.
- F. Epoxy-Coated Reinforcement: Use epoxy-coated steel wire ties to fasten epoxy-coated reinforcement. Repair cut and damaged epoxy coatings with epoxy repair coating according to ASTM D3963/D3963M.
- G. Install fabricated bar mats in lengths as long as practicable. Handle units to keep them flat and free of distortions. Straighten bends, kinks, and other irregularities, or replace units as required before placement. Set mats for a minimum 2-inch overlap of adjacent mats.

### 3.5 JOINTS

- A. General: Form construction, isolation, and contraction joints and tool edges true to line, with faces perpendicular to surface plane of concrete. Construct transverse joints at right angles to centerline unless otherwise indicated.
  - 1. When joining existing paving, place transverse joints to align with previously placed joints unless otherwise indicated.
- B. Construction Joints: Set construction joints at side and end terminations of paving and at locations where paving operations are stopped for more than one-half hour unless paving terminates at isolation joints.
  - 1. Continue steel reinforcement across construction joints unless otherwise indicated. Do not continue reinforcement through sides of paving strips unless otherwise indicated.
  - 2. Provide tie bars at sides of paving strips where indicated.
  - 3. Butt Joints: Use bonding agent at joint locations where fresh concrete is placed against hardened or partially hardened concrete surfaces.
  - 4. Doweled Joints: Install dowel bars and support assemblies at joints where indicated. Lubricate or coat with asphalt one-half of dowel length to prevent concrete bonding to one side of joint.
- C. Isolation Joints: Form isolation joints of preformed joint-filler strips abutting concrete curbs, catch basins, manholes, inlets, structures, other fixed objects, and where indicated.
  - 1. Locate expansion joints at intervals of 50 feet unless otherwise indicated.
  - 2. Extend joint fillers full width and depth of joint.
  - 3. Terminate joint filler not less than 1/2 inch or more than 1 inch below finished surface if joint sealant is indicated.

## CONCRETE PAVING

321313 - 9

4. Place top of joint filler flush with finished concrete surface if joint sealant is not indicated.
  5. Furnish joint fillers in one-piece lengths. Where more than one length is required, lace or clip joint-filler sections together.
  6. During concrete placement, protect top edge of joint filler with metal, plastic, or other temporary preformed cap. Remove protective cap after concrete has been placed on both sides of joint.
- D. Contraction Joints: Form weakened-plane contraction joints, sectioning concrete into areas as indicated. Construct contraction joints for a depth equal to at least one-fourth of the concrete thickness, as follows, to match jointing of existing adjacent concrete paving:
1. Sawed Joints: Form contraction joints with power saws equipped with shatterproof abrasive or diamond-rimmed blades. Cut 1/8-inch-wide joints into concrete when cutting action will not tear, abrade, or otherwise damage surface and before developing random contraction cracks.
    - a. Tolerance: Ensure that sawed joints are within 3 inches either way from centers of dowels.
  2. Doweled Contraction Joints: Install dowel bars and support assemblies at joints where indicated. Lubricate or coat with asphalt one-half of dowel length to prevent concrete bonding to one side of joint.
- E. Edging: After initial floating, tool edges of paving, gutters, curbs, and joints in concrete with an edging tool to a 1/4-inch radius. Repeat tooling of edges after applying surface finishes. Eliminate edging-tool marks on concrete surfaces.

### 3.6 CONCRETE PLACEMENT

- A. Before placing concrete, inspect and complete formwork installation, steel reinforcement, and items to be embedded or cast-in.
- B. Remove snow, ice, or frost from subbase surface and steel reinforcement before placing concrete. Do not place concrete on frozen surfaces.
- C. Moisten subbase to provide a uniform dampened condition at time concrete is placed. Do not place concrete around manholes or other structures until they are at required finish elevation and alignment.
- D. Comply with ACI 301 requirements for measuring, mixing, transporting, and placing concrete.
- E. Deposit and spread concrete in a continuous operation between transverse joints. Do not push or drag concrete into place or use vibrators to move concrete into place.

## CONCRETE PAVING

321313 - 10

- F. Consolidate concrete according to ACI 301 by mechanical vibrating equipment supplemented by hand spading, rodding, or tamping.
  - 1. Consolidate concrete along face of forms and adjacent to transverse joints with an internal vibrator. Keep vibrator away from joint assemblies, reinforcement, or side forms. Use only square-faced shovels for hand spreading and consolidation. Consolidate with care to prevent dislocating reinforcement dowels and joint devices.
- G. Screed paving surface with a straightedge and strike off.
- H. Commence initial floating using bull floats or darbies to impart an open-textured and uniform surface plane before excess moisture or bleedwater appears on the surface. Do not further disturb concrete surfaces before beginning finishing operations or spreading surface treatments.
- I. Curbs and Gutters: Use design mixture for automatic machine placement. Produce curbs and gutters to required cross section, lines, grades, finish, and jointing.

### 3.7 FLOAT FINISHING

- A. General: Do not add water to concrete surfaces during finishing operations.
- B. Float Finish: Begin the second floating operation when bleedwater sheen has disappeared and concrete surface has stiffened sufficiently to permit operations. Float surface with power-driven floats or by hand floating if area is small or inaccessible to power units. Finish surfaces to true planes. Cut down high spots and fill low spots. Refloat surface immediately to uniform granular texture.
  - 1. Medium-to-Fine-Textured Broom Finish: Draw a soft-bristle broom across float-finished concrete surface, perpendicular to line of traffic, to provide a uniform, fine-line texture.

### 3.8 INSTALLATION OF DETECTABLE WARNINGS

- A. Cast-in-Place Detectable Warning Tiles: Form blockouts in concrete for installation of tiles specified in Section 321726 "Tactile Warning Surfacing." Screed surface of concrete where tiles are to be installed to elevation, so that edges of installed tiles will be flush with surrounding concrete paving. Embed tiles in fresh concrete to comply with Section 321726 "Tactile Warning Surfacing" immediately after screeding concrete surface.

### 3.9 CONCRETE PROTECTION AND CURING

- A. General: Protect freshly placed concrete from premature drying and excessive cold or hot temperatures.
- B. Comply with ACI 306.1 for cold-weather protection.

## CONCRETE PAVING

321313 - 11

- C. Evaporation Retarder: Apply evaporation retarder to concrete surfaces if hot, dry, or windy conditions cause moisture loss approaching 0.2 lb/sq. ft. x h before and during finishing operations. Apply according to manufacturer's written instructions after placing, screeding, and bull floating or darbying concrete but before float finishing.
- D. Begin curing after finishing concrete but not before free water has disappeared from concrete surface.
- E. Curing Methods: Cure concrete by moisture curing, moisture-retaining-cover curing, curing compound, or a combination of these as follows:
  - 1. Moisture Curing: Keep surfaces continuously moist for not less than seven days with the following materials:
    - a. Water.
    - b. Continuous water-fog spray.
    - c. Absorptive cover, water saturated and kept continuously wet. Cover concrete surfaces and edges with 12-inch lap over adjacent absorptive covers.
  - 2. Moisture-Retaining-Cover Curing: Cover concrete surfaces with moisture-retaining cover, placed in widest practicable width, with sides and ends lapped at least 12 inches, and sealed by waterproof tape or adhesive. Immediately repair any holes or tears occurring during installation or curing period, using cover material and waterproof tape.
  - 3. Curing Compound: Apply uniformly in continuous operation by power spray or roller according to manufacturer's written instructions. Recoat areas subjected to heavy rainfall within three hours after initial application. Maintain continuity of coating, and repair damage during curing period.

### 3.10 PAVING TOLERANCES

- A. Grade: Maximum grades of pavement shall meet the following requirements unless otherwise indicated:
  - 1. Handicap Parking Area: 2 percent.
  - 2. Sidewalk, Transverse: 2 percent.
  - 3. Sidewalk, Longitudinal: 5 percent.
  - 4. Ramp, Transverse: 2 percent.
  - 5. Ramp, Longitudinal: 1:12 rise to run ratio.
- B. Comply with tolerances in ACI 117 and as follows:
  - 1. Elevation: 3/4 inch.
  - 2. Thickness: Plus 3/8 inch, minus 1/4 inch.
  - 3. Surface: Gap below 10-feet-long; unleveled straightedge not to exceed 1/2 inch.

## CONCRETE PAVING

321313 - 12



4. Alignment of Tie-Bar End Relative to Line Perpendicular to Paving Edge: 1/2 inch per 12 inches of tie bar.
5. Lateral Alignment and Spacing of Dowels: 1 inch.
6. Vertical Alignment of Dowels: 1/4 inch.
7. Alignment of Dowel-Bar End Relative to Line Perpendicular to Paving Edge: 1/4 inch per 12 inches of dowel.
8. Joint Spacing: 3 inches.
9. Contraction Joint Depth: Plus 1/4 inch, no minus.
10. Joint Width: Plus 1/8 inch, no minus.

### 3.11 FIELD QUALITY CONTROL

- A. Testing Agency: Engage a qualified testing agency to perform tests and inspections.
- B. Testing Services: Testing and inspecting of composite samples of fresh concrete obtained according to ASTM C172/C172M will be performed according to the following requirements:
  1. Testing Frequency: Obtain at least one composite sample for each 100 cu. yd. or fraction thereof of each concrete mixture placed each day.
    - a. When frequency of testing will provide fewer than five compressive-strength tests for each concrete mixture, testing to be conducted from at least five randomly selected batches or from each batch if fewer than five are used.
  2. Slump: ASTM C143/C143M; one test at point of placement for each composite sample, but not less than one test for each day's pour of each concrete mixture. Perform additional tests when concrete consistency appears to change.
  3. Air Content: ASTM C231/C231M, pressure method; one test for each composite sample, but not less than one test for each day's pour of each concrete mixture.
  4. Concrete Temperature: ASTM C1064/C1064M; one test hourly when air temperature is 40 deg°F and below and when it is 80 deg°F and above, and one test for each composite sample.
  5. Compression Test Specimens: ASTM C31/C31M; cast and laboratory cure one set of three standard cylinder specimens for each composite sample.
  6. Compressive-Strength Tests: ASTM C39/C39M; test one specimen at seven days and two specimens at 28 days.
    - a. A compressive-strength test to be the average compressive strength from two specimens obtained from same composite sample and tested at 28 days.
- C. Strength of each concrete mixture will be satisfactory if average of any three consecutive compressive-strength tests equals or exceeds specified compressive strength and no compressive-strength test value falls below specified compressive strength by more than 500 psi.

## CONCRETE PAVING

321313 - 13

- D. Test results to be reported in writing to Engineer, concrete manufacturer, and Contractor within 48 hours of testing. Reports of compressive-strength tests to contain Project identification name and number, date of concrete placement, name of concrete testing and inspecting agency, location of concrete batch in Work, design compressive strength at 28 days, concrete mixture proportions and materials, compressive breaking strength, and type of break for both 7- and 28-day tests.
- E. Nondestructive Testing: Impact hammer, sonoscope, or other nondestructive device may be permitted by Engineer but will not be used as sole basis for approval or rejection of concrete.
- F. Additional Tests: Testing and inspecting agency will make additional tests of concrete when test results indicate that slump, air entrainment, compressive strengths, or other requirements have not been met, as directed by Engineer.
- G. Concrete paving will be considered defective if it does not pass tests and inspections.
- H. Additional testing and inspecting, at Contractor's expense, will be performed to determine compliance of replaced or additional work with specified requirements.
- I. Prepare test and inspection reports.

### 3.12 REPAIR AND PROTECTION

- A. Remove and replace concrete paving that is broken, damaged, or defective or that does not comply with requirements in this Section. Remove work in complete sections from joint to joint unless otherwise approved by Engineer.
- B. Drill test cores, where directed by Engineer, when necessary to determine magnitude of cracks or defective areas. Fill drilled core holes in satisfactory paving areas with portland cement concrete bonded to paving with epoxy adhesive.
- C. Protect concrete paving from damage. Exclude traffic from paving for at least 14 days after placement. When construction traffic is permitted, maintain paving as clean as possible by removing surface stains and spillage of materials as they occur.
- D. Maintain concrete paving free of stains, discoloration, dirt, and other foreign material. Sweep paving not more than two days before date scheduled for Substantial Completion inspections.

END OF SECTION 321313

## CONCRETE PAVING

321313 - 14

## SECTION 321373 - CONCRETE PAVING JOINT SEALANTS

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Cold-applied joint sealants.
  - 2. Joint-sealant backer materials.
  - 3. Primers.

#### 1.3 ACTION SUBMITTALS

- A. Product Data:
  - 1. Concrete pavement joint sealants.
  - 2. Joint-sealant backer materials.
- B. Samples for Initial Selection: Manufacturer's standard color sheets, showing full range of available colors for each type of joint sealant.
- C. Samples for Verification: Actual sample of finished products for each kind and color of joint sealant required.
  - 1. Size: Joint sealants in 1/2-inch- (13-mm-) wide joints formed between two 6-inch- (150-mm-) long strips of material matching the appearance of exposed surfaces adjacent to joint sealants.
- D. Paving-Joint-Sealant Schedule: Include the following information:
  - 1. Joint-sealant application, joint location, and designation.
  - 2. Joint-sealant manufacturer and product name.
  - 3. Joint-sealant formulation.
  - 4. Joint-sealant color.

## CONCRETE PAVING JOINT SEALANTS

321373 - 1

#### 1.4 QUALITY ASSURANCE

##### A. Qualifications:

1. Installers: Entity that employs installers and supervisors who are trained and approved by manufacturer.

#### 1.5 PRECONSTRUCTION TESTING

- ##### A. Preconstruction Testing: Performed by a qualified testing agency.

#### 1.6 FIELD CONDITIONS

- ##### A. Do not proceed with installation of joint sealants under the following conditions:

1. When ambient and substrate temperature conditions are outside limits permitted by joint-sealant manufacturer or are below 40 deg F.
2. When joint substrates are wet.
3. Where joint widths are less than those allowed by joint-sealant manufacturer for applications indicated.
4. Where contaminants capable of interfering with adhesion have not yet been removed from joint substrates.

### PART 2 - PRODUCTS

#### 2.1 JOINT SEALANTS, GENERAL

- ##### A. Compatibility: Provide joint sealants, backer materials, and other related materials that are compatible with one another and with joint substrates under conditions of service and application, as demonstrated by joint-sealant manufacturer, based on testing and field experience.

#### 2.2 COLD-APPLIED JOINT SEALANTS

- ##### A. Single-Component, Self-Leveling, Silicone Joint Sealant: ASTM D5893/D5893M, Type SL.

#### 2.3 JOINT-SEALANT BACKER MATERIALS

- ##### A. Joint-Sealant Backer Materials: Nonstaining; compatible with joint substrates, sealants, primers, and other joint fillers; and approved for applications indicated by joint-sealant manufacturer, based on field experience and laboratory testing.

### CONCRETE PAVING JOINT SEALANTS

321373 - 2

- B. Round Backer Rods for Cold-Applied Joint Sealants: ASTM D 249, Type 3, of diameter and density required to control joint-sealant depth and prevent bottom-side adhesion of sealant.

## 2.4 PRIMERS

- A. Primers: Product recommended by joint-sealant manufacturer where required for adhesion of sealant to joint substrates indicated.

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- A. Examine joints to receive joint sealants, with Installer present, for compliance with requirements for joint configuration, installation tolerances, and other conditions affecting joint-sealant performance.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

### 3.2 PREPARATION

- A. Surface Cleaning of Joints: Before installing joint sealants, clean out joints immediately to comply with joint-sealant manufacturer's written instructions.
  - 1. Remove all foreign material from joint substrates that could interfere with adhesion of joint sealant, including dust, old joint sealants, oil, grease, waterproofing, water repellents, water, surface dirt, and frost.
- B. Joint Priming: Prime joint substrates where indicated or where recommended in writing by joint-sealant manufacturer, based on preconstruction joint-sealant-substrate tests or prior experience. Apply primer to comply with joint-sealant manufacturer's written instructions. Confine primers to areas of joint-sealant bond; do not allow spillage or migration onto adjoining surfaces.

### 3.3 INSTALLATION OF JOINT SEALANTS

- A. Comply with joint-sealant manufacturer's written installation instructions for products and applications indicated unless more stringent requirements apply.
- B. Joint-Sealant Installation Standard: Comply with recommendations in ASTM C1193 for use of joint sealants as applicable to materials, applications, and conditions.

## CONCRETE PAVING JOINT SEALANTS

321373 - 3

- C. Install joint-sealant backers to support joint sealants during application and at position required to produce cross-sectional shapes and depths of installed sealants relative to joint widths that allow optimum sealant movement capability.
  - 1. Do not leave gaps between ends of joint-sealant backer materials.
  - 2. Do not stretch, twist, puncture, or tear joint-sealant backer materials.
  - 3. Remove absorbent joint-sealant backer materials that have become wet before sealant application and replace them with dry materials.
- D. Install joint sealants immediately following backer materials installation, using proven techniques that comply with the following:
  - 1. Place joint sealants so they fully contact joint substrates.
  - 2. Completely fill recesses in each joint configuration.
  - 3. Produce uniform, cross-sectional shapes and depths relative to joint widths that allow optimum sealant movement capability.
- E. Tooling of Nonsag Joint Sealants: Immediately after joint-sealant application and before skinning or curing begins, tool sealants in accordance with the following requirements to form smooth, uniform beads of configuration indicated; to eliminate air pockets; and to ensure contact and adhesion of sealant with sides of joint:
  - 1. Remove excess joint sealant from surfaces adjacent to joints.
  - 2. Use tooling agents that are approved in writing by joint-sealant manufacturer and that do not discolor sealants or adjacent surfaces.
- F. Provide joint configuration to comply with joint-sealant manufacturer's written instructions unless otherwise indicated.

### 3.4 CLEANING AND PROTECTION

- A. Clean off excess joint sealant as the Work progresses, by methods and with cleaning materials approved in writing by joint-sealant manufacturers.
- B. Protect joint sealants, during and after curing period, from contact with contaminating substances and from damage resulting from construction operations or other causes so sealants are without deterioration or damage at time of Substantial Completion. If, despite such protection, damage or deterioration occurs, cut out and remove damaged or deteriorated joint sealants immediately and replace with joint sealant so installations in repaired areas are indistinguishable from the original work.

### 3.5 PAVING-JOINT-SEALANT SCHEDULE

- A. Joints within concrete paving.

## CONCRETE PAVING JOINT SEALANTS

321373 - 4

1. Joint Location:
    - a. Expansion and isolation joints in concrete paving.
    - b. Contraction joints in concrete paving.
    - c. Other joints as indicated.
  2. Joint Sealant: Single-component, self-leveling, silicone joint sealant.
  3. Joint-Sealant Color: Manufacturer's standard.
- B. Joints within concrete paving and between concrete and asphalt paving.
1. Joint Location:
    - a. Joints between concrete and asphalt paving.
    - b. Joints between concrete curbs and asphalt paving.
    - c. Other joints as indicated.

END OF SECTION 321373

## SECTION 321723 - PAVEMENT MARKINGS

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Painted markings applied to asphalt paving.

#### 1.3 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.
  - 1. Review methods and procedures related to marking asphalt paving or concrete surfaces including, but not limited to, the following:
    - a. Asphalt-paving or concrete-surface aging period before application of pavement markings.
    - b. Review requirements for protecting pavement markings, including restriction of traffic during installation period.

#### 1.4 ACTION SUBMITTALS

- A. Product Data: Include technical data and tested physical and performance properties.
  - 1. Pavement-marking paint, alkyd.
- B. Shop Drawings:
  - 1. Indicate pavement markings, colors, lane separations, defined parking spaces, and dimensions to adjacent work.
  - 2. Indicate, with international symbol of accessibility, spaces allocated for people with disabilities.
- C. Samples: For each exposed product and for each color and texture specified; on rigid backing, 8 inches square.



## 1.5 QUALITY ASSURANCE

- A. Regulatory Requirements: Comply with materials, workmanship, and other applicable requirements of Massachusetts Department of Transportation – Highway Division Standard Specification for Highways and Bridges for pavement-marking work.
  - 1. Measurement and payment provisions and safety program submittals included in standard specifications do not apply to this Section.

## 1.6 FIELD CONDITIONS

- A. Environmental Limitations: Proceed with pavement marking only on clean, dry surfaces and at a minimum ambient or surface temperature of 40 deg F for alkyd materials, and not exceeding 95 deg F

## PART 2 - PRODUCTS

### 2.1 MANUFACTURERS

- A. Source Limitations: Obtain pavement-marking paints from single source from single manufacturer.

### 2.2 PERFORMANCE REQUIREMENTS

- A. Accessibility Standard: Comply with applicable provisions of 521 CMR Architectural Access Board, the USDOJ's "2010 ADA Standards for Accessible Design", and the ArBA standards of the Federal agency having jurisdiction.

### 2.3 PAVEMENT-MARKING PAINT

- A. Pavement-Marking Paint, Alkyd: Alkyd-resin type, lead and chromate free, ready mixed, complying with AASHTO M 248, Type N; colors complying with FS TT-P-1952F.
  - 1. Color: White and Blue.

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- A. Verify that pavement-marking substrate is dry and in suitable condition to begin pavement marking in accordance with manufacturer's written instructions.

## PAVEMENT MARKINGS

321723 - 2

- B. Proceed with pavement marking only after unsatisfactory conditions have been corrected.

### 3.2 PAVEMENT MARKING

- A. Do not apply pavement-marking paint until layout, colors, and placement have been verified with Owner.
- B. Allow asphalt paving or concrete surfaces to age for a minimum of 30 days before starting pavement marking.
- C. Sweep and clean surface to eliminate loose material and dust.
- D. Apply paint with mechanical equipment to produce pavement markings, of dimensions indicated, with uniform, straight edges. Apply at manufacturer's recommended rates to provide a minimum wet film thickness of 15 mils.
  - 1. Apply graphic symbols and lettering with paint-resistant, die-cut stencils, firmly secured to asphalt paving or concrete surface. Mask an extended area beyond edges of each stencil to prevent paint application beyond stencil. Apply paint so that it cannot run beneath stencil.

### 3.3 PROTECTING AND CLEANING

- A. Protect pavement markings from damage and wear during remainder of construction period.
- B. Clean spillage and soiling from adjacent construction using cleaning agents and procedures recommended by manufacturer of affected construction.

END OF SECTION 321723

## SECTION 323113 - CHAIN LINK FENCES AND GATES

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Chain-link fences.
  - 2. Swing Gate.
- B. Related Requirements:
  - 1. Section 033053 "Miscellaneous Cast-in-Place Concrete" for cast-in-place concrete post footings.

#### 1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product.
  - 1. Include construction details, material descriptions, dimensions of individual components and profiles, and finishes for the following:
    - a. Fence and gate posts, rails, and fittings.
    - b. Chain-link fabric, reinforcements, and attachments.
    - c. Gates and hardware.

#### 1.4 INFORMATIONAL SUBMITTALS

- A. Product Certificates: For each type of chain-link fence and gate.
- B. Product Test Reports: For framework strength according to ASTM F 1043, for tests performed by manufacturer and witnessed by a qualified testing agency.

## 1.5 FIELD CONDITIONS

- A. Field Measurements: Verify layout information for chain-link fences and gates shown on Drawings in relation to property survey and existing structures. Verify dimensions by field measurements.

## PART 2 - PRODUCTS

### 2.1 VINYL COATED CHAIN-LINK FENCE FABRIC

- A. General: Provide fabric in one-piece heights measured between top and bottom of outer edge of selvage knuckle or twist according to "CLFMI Product Manual" and requirements indicated below:
  - 1. Fabric Height: As indicated on Drawings.
  - 2. Steel Wire for Fabric: Wire gauge shall be 9 gauge prior to PVC coating.
    - a. Polymer-Coated Fabric: Wire shall have polyvinyl chloride (PVC), plastic resin finish, factory applied over galvanizing prior to fabrication of fabric. Thickness of PVC coating shall be not less than 7 nor more than 20 mils thick. PVC coated wire shall be capable of being woven into fabric without the PVC coating cracking. Color shall be black.
    - b. Coat selvage ends of metallic-coated fabric before the weaving process with manufacturer's standard clear protective coating.
  - 3. Selvage: Knuckled at both selvages.

### 2.2 FENCE FRAMEWORK

- A. Posts and Rails: ASTM F 1043 for framework, including rails, braces, and line; terminal; and corner posts. Provide members with minimum dimensions and wall thickness according to ASTM F 1043 or ASTM F 1083 based on the following:
  - 1. Fence Height: As indicated on Drawings.
  - 2. Sizes for fence posts, gate frames and other framework members shall be as indicated on Drawings.
  - 3. Steel parts shall be hot-dipped galvanized inside and out prior to vinyl coating.
    - a. Heavy-Industrial-Strength Material: Group IA, round steel pipe, Schedule 40.
  - 4. Metallic Coating for Steel Framework:
    - a. Type A: Not less than minimum 2.0-oz./sq. ft. average zinc coating according to ASTM A 123/A 123M or 4.0-oz./sq. ft. zinc coating according to ASTM A 653/A 653M.

5. Galvanized steel parts shall be coated with polyvinyl chloride (PVC) plastic resin finish. PVC coating for framework shall match fabric color.

## 2.3 CHAIN LINK SWING GATES

- A. General: ASTM F 900 for gate posts and double swing gate types.
  1. Gate Leaf Width: As indicated.
  2. Framework Member Sizes and Strength: Based on gate fabric height as indicated.
- B. Pipe and Tubing:
  1. Zinc-Coated Steel: ASTM F 1043 and ASTM F 1083; protective coating and finish to match fence framework.
- C. Hardware:
  1. Hinges: 180-degree inward swing.
  2. Latch: Permitting operation from both sides of gate with provision for padlocking accessible from both sides of gate.

## 2.4 FITTINGS

- A. Provide fittings according to ASTM F 626.
- B. Post Caps: Provide for each post.
- C. Rail and Brace Ends: For each gate, corner, pull, and end post.
- D. Rail Fittings: Provide the following:
  1. Top Rail Sleeves: Pressed-steel or round-steel tubing not less than 6 inches long.
  2. Rail Clamps: Line and corner boulevard clamps for connecting intermediate and bottom rails to posts.
- E. Truss Rod Assemblies: Steel, hot-dip galvanized after threading rod and turnbuckle or other means of adjustment.
- F. Tie Wires, Clips, and Fasteners: According to ASTM F 626.
  1. Standard Round Wire Ties: For attaching chain-link fabric to posts, rails, and frames, according to the following:
    - a. Hot-Dip Galvanized Steel: **[0.106-inch]- [0.148-inch]-** diameter wire; galvanized coating thickness matching coating thickness of chain-link fence fabric.
- G. Finish:

1. Metallic Coating for Pressed Steel or Cast Iron: Not less than 1.2 oz./sq. ft. of zinc.
  - a. Polymer coating over metallic coating.

## 2.5 GROUT AND ANCHORING CEMENT

- A. Nonshrink, Nonmetallic Grout: Factory-packaged, nonstaining, noncorrosive, nongaseous grout complying with ASTM C 1107/C 1107M. Provide grout, recommended in writing by manufacturer, for exterior applications.
- B. Anchoring Cement: Factory-packaged, nonshrink, nonstaining, hydraulic-controlled expansion cement formulation for mixing with water at Project site to create pourable anchoring, patching, and grouting compound. Provide formulation that is resistant to erosion from water exposure without needing protection by a sealer or waterproof coating, and that is recommended in writing by manufacturer for exterior applications.

## PART 3 - EXECUTION

### 3.1 CHAIN-LINK FENCE INSTALLATION

- A. Install chain-link fencing according to ASTM F 567 and more stringent requirements specified.
  1. Install fencing on established boundary lines inside property line.
- B. Post Excavation: Drill or hand-excavate holes for posts to diameters and spacings indicated, in firm, undisturbed soil.
- C. Post Setting: Set posts in concrete with mechanical anchors at indicated spacing into firm, undisturbed soil.
  1. Verify that posts are set plumb, aligned, and at correct height and spacing, and hold in position during setting with concrete or mechanical devices.
  2. Concrete Fill: Place concrete around posts to dimensions indicated and vibrate or tamp for consolidation. Protect aboveground portion of posts from concrete splatter.
- D. Line Posts: Space line posts uniformly at 96 inches o.c. or as indicated on Drawings.
- E. Post Bracing and Intermediate Rails: Install according to ASTM F 567, maintaining plumb position and alignment of fence posts. Diagonally brace terminal posts to adjacent line posts with truss rods and turnbuckles. Install braces at end and gate posts and at both sides of corner and pull posts.
  1. Locate horizontal braces at mid-height of fabric 72 inches or higher. Install so posts are plumb when diagonal rod is under proper tension.

- F. Top Rail: Install according to ASTM F 567, maintaining plumb position and alignment of fence posts. Run rail continuously through line post caps, bending to radius for curved runs and terminating into rail end attached to posts or post caps fabricated to receive rail at terminal posts. Provide expansion couplings as recommended in writing by fencing manufacturer.
- G. Intermediate and Bottom Rails: Secure to posts with fittings.
- H. Tension or Stretcher Bars: Thread through fabric and secure to end, corner, pull, and gate posts, with tension bands spaced not more than 15 inches o.c.
- I. Tie Wires: Use wire of proper length to firmly secure fabric to line posts and rails. Attach wire at one end to chain-link fabric, wrap wire around post a minimum of 180 degrees, and attach other end to chain-link fabric according to ASTM F 626. Bend ends of wire to minimize hazard to individuals and clothing.
  - 1. Maximum Spacing: Tie fabric to line posts at 12 inches o.c. and to braces at 24 inches o.c.

### 3.2 GATE INSTALLATION

- A. Install gates according to manufacturer's written instructions, level, plumb, and secure for full opening without interference. Attach fabric as for fencing. Attach hardware using tamper-resistant or concealed means. Install ground-set items in concrete for anchorage. Adjust hardware for smooth operation.

### 3.3 ADJUSTING

- A. Lubricate hardware and other moving parts.

END OF SECTION 323113

## SECTION 323223 - SEGMENTAL RETAINING WALLS

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Segmental retaining walls.
- B. Related Requirements:
  - 1. Section 312000 "Earth Moving" for excavation for segmental retaining walls, base material, soil fill, fill placement and compaction, and field in-place density testing.

#### 1.3 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.

#### 1.4 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Samples for Initial Selection: Manufacturer's standard color sheets, showing full range of available colors and textures for segmental retaining wall units.
- C. Samples for Verification: Actual sample of finished products for each type of exposed finish of segmental retaining wall units.
  - 1. Size: Full-size units.
- D. Delegated Design Submittals: For segmental retaining walls, including analysis data signed and sealed by the qualified professional engineer responsible for their preparation.

## SEGMENTAL RETAINING WALLS

323223 - 1



## 1.5 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For testing agency.
- B. Product Certificates: For each type of segmental retaining wall unit from manufacturer.
  - 1. Include test data for shear strength between segmental retaining wall units in accordance with ASTM D6916.
  - 2. Include test data for connection strength between segmental retaining wall units and soil reinforcement in accordance with ASTM D6638.
- C. Test and Evaluation Reports:
  - 1. Product Test Reports: For each type of segmental retaining wall unit for tests performed by qualified testing agency.
    - a. Include test data for shear strength between segmental retaining wall units in accordance with ASTM D6916.
    - b. Include test data for connection strength between segmental retaining wall units and soil reinforcement in accordance with ASTM D6638.
  - 2. Preconstruction Test Reports: For segmental retaining wall units.
- D. Source Quality-Control Submittals:
  - 1. Source quality-control reports.
- E. Field Quality-Control Submittals:
  - 1. Field quality-control reports.

## 1.6 QUALITY ASSURANCE

- A. Qualifications: Qualified in accordance with ASTM E329 for testing indicated.

## 1.7 MOCKUPS

- A. Build mockups to verify selections made under Sample submittals and to demonstrate aesthetic effects.
  - 1. Build mockup of segmental retaining wall approximately 72 inches long by not less than 36 inches high above finished grade at front of wall.
    - a. Include typical base and cap or finished top construction.
    - b. Include backfill to typical finished grades at both sides of wall.
    - c. Include typical end construction at one end of mockup.

2. Subject to compliance with requirements, approved mockups may become part of the completed Work if undisturbed at time of Substantial Completion.

## 1.8 DELIVERY, STORAGE, AND HANDLING

- A. Store and handle concrete units and accessories to prevent deterioration or damage due to contaminants, breaking, chipping, or other causes.
- B. Store geosynthetics in manufacturer's original packaging with labels intact. Store and handle geosynthetics to prevent deterioration or damage due to sunlight, chemicals, flames, temperatures above 160 deg F or below 32 deg F, and other conditions that might damage them. Verify identification of geosynthetics before use and examine them for defects as material is placed.

## PART 2 - PRODUCTS

### 2.1 SEGMENTAL RETAINING WALL UNITS

- A. Concrete Units: ASTM C1372, Normal Weight, except that maximum water absorption shall not exceed 7 percent by weight and units shall not differ in height more than plus or minus 1/16 inch from specified dimension.
  1. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, licensees of one of the following:
    - a. Redi-Rock International – Ledgestone Series
  2. Provide units that comply with requirements in ASTM C1372 for freeze-thaw durability.
  3. Provide units that interlock with courses above and below by means of integral lugs, lips, or tongues and grooves.
- B. Color: As selected by Owner or Landscape Architect from manufacturer's full range.
- C. Shape and Texture: Naturalistic split face finish. Not to show tooling. Not to have uniform face from block to block. - Provide units matching basic shape, dimensions, and face texture indicated by referencing manufacturer's pattern designation.
- D. Special Units: Provide corner units, end units, and other shapes as needed to produce segmental retaining walls of dimensions and profiles indicated and to provide texture on exposed surfaces.

## SEGMENTAL RETAINING WALLS

323223 - 3

## 2.2 INSTALLATION MATERIALS

- A. Cap Adhesive: Product supplied or recommended by segmental retaining wall unit manufacturer for adhering cap units to units below.
- B. Leveling Base: Comply with requirements in Section 312000 "Earth Moving" for base course.
  - 1. Leveling Course: Crushed stone.
- C. Drainage Fill: Shall be minimum 1" washed stone.
- D. Nonreinforced-Soil Fill: Comply with requirements in Section 312000 "Earth Moving" for satisfactory soils.
- E. Drainage Geotextile: Nonwoven needle-punched geotextile, manufactured for subsurface drainage applications, made from polyolefins or polyesters; with elongation of greater than 50 percent.
  - 1. Apparent Opening Size: No. 70 to 100 sieve, maximum; ASTM D4751.
  - 2. Minimum Grab Tensile Strength: 110 lb; ASTM D4632/D4632M.
  - 3. Minimum Weight: 4 oz./sq. yd..

## 2.3 SOURCE QUALITY CONTROL

- A. Factory test and inspect each roll of soil reinforcement for minimum average roll values for geosynthetic index property tests, including the following:
  - 1. Weight.
  - 2. Grab or single-rib strength.
  - 3. Aperture opening.
  - 4. Rib or yarn size.

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- A. Examine areas and conditions, with Installer present, for compliance with requirements for excavation tolerances, condition of subgrades, and other conditions affecting performance of the Work.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

## SEGMENTAL RETAINING WALLS

323223 - 4

### 3.2 INSTALLATION OF RETAINING WALLS

- A. General: Place units in accordance with NCMA's "Segmental Retaining Wall Installation Guide" and segmental retaining wall unit manufacturer's written instructions.
- B. Do not use units with chips, cracks, or other defects that are visible at a distance of 20 feet where such defects are exposed in the completed Work.
- C. Leveling Base: Place and compact base material to thickness indicated and with not less than 95 percent maximum dry unit weight in accordance with ASTM D698.
  - 1. Leveling Course: Crushed stone. Compact to a smooth, level surface.
- D. First Course: Place first course of segmental retaining wall units for full length of wall. Place units in firm contact with each other, properly aligned and level.
  - 1. Tamp units into leveling base as necessary to bring tops of units into a level plane.
- E. Subsequent Courses: Remove excess fill and debris from tops of units in course below. Place units in firm contact, properly aligned, and directly on course below.
  - 1. For units with lugs designed to fit into holes in adjacent units, lay units so lugs are accurately aligned with holes, and bedding surfaces are firmly seated on beds of units below.
- F. Cap Units: Place cap units and secure with cap adhesive.

### 3.3 FILL PLACEMENT

- A. General: Comply with requirements in Section 312000 "Earth Moving," with NCMA's "Segmental Retaining Wall Installation Guide" and segmental retaining wall unit manufacturer's written instructions.
- B. Fill voids between and within units with drainage fill. Place fill as each course of units is laid.
- C. Place, spread, and compact drainage fill and soil fill in uniform lifts for full width and length of embankment as wall is laid. Place and compact fills without disturbing alignment of units. Where both sides of wall are indicated to be filled, place fills on both sides at same time. Begin at wall, and place and spread fills toward embankment.
  - 1. Use only hand-operated compaction equipment within 48 inches of wall or one-half of height above bottom of wall, whichever is greater.
  - 2. Compact reinforced-soil fill to not less than 95 percent maximum dry unit weight in accordance with ASTM D698.

- a. In areas where only hand-operated compaction equipment is allowed, compact fills to not less than 90 percent maximum dry unit weight in accordance with ASTM D698.
- 3. Compact nonreinforced-soil fill to comply with Section 312000 "Earth Moving."
- D. Place a layer of drainage fill at least 12 inches wide behind wall to within 12 inches of finished grade. Place a layer of drainage geotextile between drainage fill and soil fill.
- E. Place impervious fill over top edge of drainage fill layer.
- F. Slope grade at top of wall away from wall unless otherwise indicated. Slope grade at wall base away from wall. Provide uniform slopes that prevent ponding.

### 3.4 CONSTRUCTION TOLERANCES

- A. Variation from Level: For bed-joint lines along walls, do not exceed 1-1/4 inches in 10 feet, 3 inches maximum.
- B. Variation from Indicated Batter: For slope of wall face, do not vary from indicated slope by more than 1-1/4 inches in 10 feet.

### 3.5 FIELD QUALITY CONTROL

- A. Testing Agency: Engage a qualified testing agency to perform tests and inspections.
- B. Comply with requirements in Section 312000 "Earth Moving" for field quality control.
- C. Tests and Inspections:
  - 1. In each compacted backfill layer, perform at least one field in-place compaction test for each 50 feet or less of segmental retaining wall length.
  - 2. In each compacted backfill layer, perform at least one field in-place compaction test for each 50 feet or less of segmental retaining wall length.
  - 3. Segmental retaining wall system will be considered defective if it does not pass tests and inspections.
- D. Prepare test and inspection reports.

### 3.6 ADJUSTING

- A. Remove and replace segmental retaining wall construction of the following descriptions:

## SEGMENTAL RETAINING WALLS

323223 - 6

1. Broken, chipped, stained, or otherwise damaged units. Units may be repaired if Landscape Architect approves methods and results.
  2. Segmental retaining walls that do not match approved Samples and mockups.
  3. Segmental retaining walls that do not comply with other requirements indicated.
- B. Replace units so segmental retaining wall matches approved Samples and mockups, complies with other requirements, and shows no evidence of replacement.

END OF SECTION 323223

## SECTION 328400 - IRRIGATION

### PART 1 – GENERAL

#### 1.1 SUMMARY

- A. Provide all materials, labor, installation equipment, and technical service to complete automatic athletic field irrigation system, plumbing equipment, work within the irrigation vault, as well as the testing and warranty of the system as defined in this Specification and Construction Drawings.
- B. Items of work specifically included are:
  - 1. Procurement of all applicable licenses, permits, and fees.
  - 2. Coordination of all utilities.
  - 3. Verification of site conditions.
  - 4. Maintenance during guarantee period.
  - 5. Connection of electrical power supply to irrigation control system and irrigation control system to vault ground.
  - 6. Providing new plumbing within vault for overall new and existing irrigation systems.
  - 7. Restarting and validating existing irrigation systems with new plumbing supply.
- C. Athletic Field Irrigation System shall be a new irrigation system, expanded off existing irrigation mainline with a new controller (controller existing and new irrigation systems) and refurbished plumbing water supply. Sprinkler head placement and throw radius shall be better than head-to-head coverage.
- D. Provide new pressure reducing valve within irrigation vault to reduce incoming pressure of 140 psi to 75 psi.
- E. Provide new water meter and backflow preventer within irrigation vault.
  - 1. Provide drain and blow-out port in irrigation vault.
- F. Provide and train Owner on remote irrigation management through Internet based platform through cellular internet service as part of irrigation system controls.

#### 1.2 QUALIFICATIONS.

- A. Qualified irrigation system installers must have a minimum experience of five (5) years with work and products specified herein, including:
  - 1. Internet-Based Smart Controllers
  - 2. Athletic Field Irrigation Systems
  - 3. Domestic Water Plumbing Systems

4. Two-Wire Controller and Valve Installation

B. Submit three (3) references for similar work performed in the last five (5) calendar years, including:

1. Contact name
2. Company Name
3. Contact Phone Number
4. Project Name and Location
5. Brief Project Description

1.3 UTILITIES

A. Water Service Point of Connection

1. Existing domestic water service for irrigation originates from within Cristoforo Colombo Park vault and is to be installed by licensed project trade professionals.

a. Plumbing Equipment requirements:

- 1) New 2-Inch Water Meter within Vault
- 2) New 2-Inch Backflow Preventer within Vault
- 3) Refurbished 2-Inch Water Service within Vault

b. Flow and pressure requirements at Athletic Field:

- 1) Flow: Maximum 65 gallons per minute
- 2) Pressure: 75 pounds per square inch (downstream of pressure reducing valve)

2. Furnish and provide one (1) backflow preventer, water meter, and winterization port within irrigation vault.

- a. Furnish specified irrigation flow control equipment for installation within irrigation vault.
- b. Approximate exterior irrigation points of connection for irrigation are noted on Drawings.

B. Electrical Power Source to New Irrigation Controller

1. Reuse existing irrigation controller circuit for new irrigation controller.
2. Reuse existing conduits for valve wire within vault.

a. New Conduits (Where Necessary)

- 1) Provide minimum Schedule 80 PVC conduits with long elbow sweeps and under all hardscape through sleeves.

C. Internet for Irrigation Controller



1. Provide cellular card for internet-based access through any web-enabled device.

D. Pipe Sleeves

1. Pipe sleeves to be beneath all hardscape, as indicated on Construction Drawings.
  - a. Pipe sleeve requirements
    - 1) One 6-inch PVC SDR 35 Solvent Weld
    - 2) Extend 18 inches beyond edge of hardscape
    - 3) Minimum cover: 24 inches

1.4 RELATED REQUIREMENTS

- A. Coordinate with other project trades and refer to overall project Construction Document Specifications and Drawings, including, but not limited to:
  1. Division 01 – General Requirements
  2. Division 02 – Existing Conditions
  3. Division 03 – Concrete
  4. Division 22 – Plumbing
  5. Division 26 – Electrical
  6. Division 31 – Earthwork
  7. Division 32 – Exterior Improvements
  8. Division 33 – Utilities
  9. Construction Drawings:
    - a. IR-1.00 through IR-2.01
    - b. Review all other Project Construction Documents for coordination.

1.5 APPLICABLE STANDARDS AND CODES

- A. At a minimum, comply with the following standards and codes:
  1. American Society for Testing and Materials (ASTM)
  2. National Standard Plumbing Code (NSPC)
  3. National Electric Code (NEC)
  4. National Sanitary Foundation (NSF)
  5. Underwriters Laboratories, Inc. (UL)
  6. Occupational Safety and Health Administration (OSHA)
- B. Comply with applicable laws, standards, and regulations of the local governing authority. All local laws more stringent than those referenced above shall take precedent.

1.6 SUBMITTALS

- A. Submit the following under provisions of Division 1:

1. Literature: Manufacturer's product data sheets, specifications and installation instructions for materials listed in this Specification (Part 2 – Products).
  - a. Product submittals shall be concise (no extraneous pages or sections) and clearly marked to show submitted product model, type, size, etc.
  - b. Substitute Product Submittal:
    - 1) Provide specified product submittals for “an approved equal” to Owner’s Representative for approval.
    - 2) Alternate products are acceptable when products of equal or better quality and performance are submitted and approved by the Owner’s Representative.
    - 3) Substitute Product Submittals constitute representation that:
      - a) Substitute products have been thoroughly investigated and have been determined to be equal or superior in all respects to that specified.
      - b) Substitute products shall provide the same warranties as specified products.
      - c) Substitute products are compatible with interfacing items.
      - d) Assume responsibility of and guarantee system performance as a result of product substitution, including making all subsequent changes to meet design specifications.
  - c. Work shall not commence until all products specified are submitted and approved in a written notification by Owner’s Representative.
  - d. All product installed shall be new, without defects, and of quality and performance as specified.
2. Schedule: Submit Schedule of all products to be furnished hereunder, indicating manufacturer, size, and model.
  - a. Ensure that all of the types/styles of products and installation equipment specified herein can be furnished by the manufacturer submitted.
  - b. Provide all spare irrigation parts as noted (see Spare Irrigation Parts)
  - c. Prior to submitting schedule, confirm current site conditions are as provided in the Construction Drawings.

#### 1.7 DELIVERY, STORAGE AND HANDLING

- A. Do not deliver materials to the site, until all specified submittals have been submitted to, and approved by, the Owner’s Representative.
- B. Coordinate with Owner’s Representative for temporary storage and staging areas.
- C. Protect materials from damage from construction traffic, weather, corrosion, and other causes while stored on-site. Minimize on-site storage as possible.
- D. Store and handle all products and materials in compliance with manufacturer instructions and recommendations.

## 1.8 GUARANTEE AND REPLACEMENT

- A. Guarantee entire irrigation system, parts and labor, for one (1) year from official written date of acceptance by Owner's Representative. Provide written warranty showing date of completion and period of warranty prior to request for final payment.
- B. System malfunctions occurring during the guarantee period due to defective materials, poor workmanship, or improper adjustment shall be corrected to satisfaction of Owner's Representative at no additional cost to the Owner.
  - 1. Repair all defects within 10 days of notification from Owner or Owner's Representative.
  - 2. Repair defects with approved products.
- C. First-year spring system start-up and winterization shall be included in system guarantee.
- D. Manufacturer warranties shall be provided for all products and materials where such warranties are offered in published product data. Copies of manufacturer warranties are to be included in the Operations and Maintenance Manual (See Operation and Maintenance).

## PART 2 – PRODUCTS

### 2.1 AUTOMATIC IRRIGATION CONTROLLER

- A. Controller
  - 1. Size: 16-Station Maximum
  - 2. Construction: Electronic with 120-Volt Input and 24-28 Volt Output; Outdoor Stainless-Steel Wall-Mounted Enclosure.
  - 3. Standards: UL-Listed
  - 4. Features: Manual and Automatic Control, Water Budgeting, Cycle-Soak, Sensor Input Terminals, Internal Transformer, Flow Monitoring Capability, Lightning Protection, Remote Control via Internet, Conventional Wire.
  - 5. Manufacturer/Model: Rain Bird ESP-LXME2 PRO (per Owner)
- B. External Devices (Matching Manufacturer and Compatible with Controller)
  - 1. Wired Rain Sensor (free of Overhead Obstruction, attached to pedestal in perforated canister)
  - 2. 2-Inch Brass Flow Sensor
    - a. Provide Isolation Valves and Unions on Each Side for Winterization
    - b. Flow Range = 2 – 105 gpm
  - 3. Surge Suppression and Grounding (at Controller)
- C. Outdoor Controller Grounding
  - 1. Size

- a. Wire: 6AWG
  - b. Rod: 5/8-Inch Diameter x 12-Foot Long
  - c. Plate: 4-Inch x 96-Inch x 1/16-Inch Thick
2. Construction
  - a. Wire: Bare Copper
  - b. Rod: Copper
  - c. Plate: Copper with Loresco PowerSet Ground Enhancement Material Above and Below
3. Ratings: UL-Listed
  - a. Features: Cadweld Connectors from Wire to Rod, Plate Manufacturer provided Plate Connections, PVC or ADS Drain Pipe and Grate Cover over Rod Plate with Metal Detection

## 2.2 WIRE

### A. Conventional Wire

1. Size: 14AWG Minimum
2. Construction: Single Strand Solid Copper Conductor with PVC Insulation
3. Ratings: UL-Listed, NEC (Class II Circuit), Direct Burial UF/TWU, up to 600-Volt Potential
4. Standards: ASTM B-3, ASTM B-8
5. Markings: Manufacturer, Rating, Size, and Type
6. Manufacturer/Model: Paige Electric Model P7001D; Service Wire Company UF14, UF12; Regency Wire & Cable 14AWG, 12AWG; or Approved Equal.

### B. Wire Splices

1. Type: Direct Burial Wire Splice Kit (All Components Intact)
2. Construction: Lockable Plastic Tube, Pre-Filled with Insulation Gel
3. Ratings: UL-Listed, NEC, Direct Burial and Submersion, up to 600-Volt Potential
4. Manufacturer/Model: 3M DBY-6; Rain Bird DB Series; or Approved Equal.

### C. Wire Conduit

1. Size: 1-Inch Minimum
2. Construction: PVC, Solvent Weld
3. Ratings: Schedule 80
4. Fittings: Long Sweep Elbows
5. Manufacturer: Cresline; Certainteed, JM Eagle; or Approved Equal.

## 2.3 PIPE AND FITTINGS

### A. Irrigation Mainline and Lateral

1. Size: 2.5-Inch
2. Construction: Polyvinyl Chloride (PVC), Solvent Weld
3. Ratings: Class 200 SDR 21
4. Markings: Manufacturer, Nominal Size, Class or Schedule, Pressure, Extrusion Date, Pipe Insertion Mark.
5. Manufacturer: Cresline; Certainteed; JM Eagle; or Approved Equal.
6. Fittings
  - a. For Valves Toe Nipples: Schedule 80 PVC
  - b. Other Fittings: Schedule 40 PVC
7. Markings: NSF Designation, Size, Class or Schedule
8. Manufacturer: Lasco; Spears; Dura; or Approved Equal

B. Solvent

1. Type: NSF Type I or Type II PVC
2. Standards: ASTM D-2564
3. Manufacturer: IPS Weld-On 711; Oatey HD Cement; Rectorseal Gold; or Approved Equal

C. Primer

1. Type: NSF for PVC
2. Standards: ASTM F-656
3. Manufacturer: IPS Weld-On P-68; Oatey Clear Primer; Rectorseal Jim PR-2; or Approved Equal

## 2.4 ELECTRIC ZONE VALVES

A. Sprinkler Zone Valve

1. Size: 2-Inch
2. Construction: Plastic Globe Valve with Reinforced Nylon or Fiberglass Body
3. Ratings: 200 psi
4. Features: Manual Bleed Screw, Flow Control, Pressure Regulation, and Filter/Scrubber
5. Manufacturer/Model: Hunter ICV-FS; Rain Bird PESB; or Approved Equal

B. Master Valve

1. Size: 2-Inch
2. Construction: Brass Globe Valve
3. Ratings: 220 psi
4. Features: Manual Bleed Screw, Flow Control, Pressure Regulation, and Filter
5. Manufacturer/Model: Hunter IBV-FS; or Approved Equal

## 2.5 ISOLATION VALVES

A. Mainline Isolation Valve

1. Size: 2.5-Inch and Smaller
2. Construction: Bronze, Gate Valve
3. Ratings: 200 psi
4. Features: Steel Cross Handle, Non-Rising Stem
5. Manufacturer/Model: Nibco T-113K; Apollo 102T-K; or Approved Equal

B. Winterization Isolation Ball Valves

1. Size: 2-Inch, normally closed
2. Construction: Brass, Steel Tee Handle, Standard Port
3. Ratings: 600 psi
4. Features: Blow-Out-Proof Stem, Plated Brass Ball.
5. Manufacturer/Model: Apollo 70-105-01; or Approved Equal

2.6 QUICK COUPLING VALVES

A. Mainline Quick Coupling Valve

1. Size: 1-Inch, Normally Closed
2. Construction: Brass, Spring-Loaded Valve Seat, Key Engaged
3. Ratings: 125 psi
4. Features: 1-Inch NPT Inlet, ACME Key, Locking Vinyl Cover, Anti-Rotation Stabilization Wings
5. Manufacturer/Model: Hunter HQ-44RC-AW; or Approved Equal.

B. Swing Joint Assembly

1. Size: 1-Inch
2. Construction: PVC, with O-Ring Seals and Brass Threaded Outlet
3. Manufacturer: Hunter HSJ-1 with SnapLok; or Approved Equal

2.7 ROTARY SPRINKLERS

A. Body

1. Size: 6-Inch Pop-Up
2. Construction: Plastic, Ratcheting Riser, Removable Nozzle, Internal Check Valve
3. Ratings: Pressure Regulated to 40 psi
4. Manufacturer/Model: Hunter PROS-06-PRS40-CV; Rain Bird 1806-SAM-PRS-P45, or Approved Equal

B. Nozzles

1. 12' – 30' Radius (see Contract Drawings)
2. Features: Full and Part-Circle Fixed-Arc and Strip Patterns
3. Manufacturer/Model: Hunter MP Rotator, Toro Precision Rotating, or Approved Equal

## 2.8 GEAR-DRIVEN ROTOR SPRINKLERS

### A. General

1. Size: 6-Inch Stainless Steel Pop-Up Riser with ¾-Inch or 1-Inch NPT Bottom Inlet
2. Construction: Gear-Driven, Removable Nozzle, Internal Check Valve, Stainless Steel Retraction Spring, Rubber Cover, Stainless Steel Riser
3. Features: Adjustable, Part, and Full Circle
4. Manufacturer/Model:
  - a. Turfgrass: Hunter I-20-06-SS; Rain Bird 5006-SAM-PRS-SS
5. Spacing: As shown on Drawings, generally 80% - 100% of manufacturer rating

### B. Swing Joint Assembly

1. Size: ¾-Inch or 1-Inch with 12-Inch Lay Arm
2. Construction: PVC, with O-Ring Seals and Threaded Outlet
3. Manufacturer: Hunter HSJ-1-12; Rain Bird TSJ-12; Lasco G132-100 or Approved Equal
4. Provide Combination PVC Insert Tee Fitting with FPT Outlet at Lateral for Swing Joint

## 2.9 VALVE BOXES

### A. Plastic Valve Boxes in Planter Beds only. Coordinate final field placement with Landscape Architect.

### B. General

1. Size:
  - a. 12-Inch Standard Valve Box
    - 1) Single 2-Inch Electric Zone Valve
    - 2) Double 1-Inch or 1½-Inch Electric Zone Valves
  - b. 6-Inch Round
    - 1) Wire Splice
  - c. 10-Inch Round
    - 1) Single 1-Inch or 1½-Inch Electric Zone Valve
    - 2) Isolation Valve
    - 3) Quick Coupling Valve
2. Construction: Resin
3. Ratings: Tensile Strength 3,000-5,000 psi
4. Color: Green or Black (per Owner's Representative)
5. Features: Lockable, Bolt-Down Covers, Brick Supported

6. Manufacturer/Model: Carson, Model Specification Grade NDS Pro; Rain Bird VB; or Approved Equal

## 2.10 PRESSURE REDUCING VALVE

### A. General

1. Size: 2-Inch
2. Construction: Bronze, Stainless Steel Springs,
3. Features: Adjustable Screw for Pressure Reducing from 50 – 100 psi, Manufactured in USA, Integral Stainless Steel Strainer, Double Union NPT with Pressure Gauge Option
4. Manufacturer/Model: Apollo, or Approved Equal.

## 2.11 METER

### A. Size: 2-Inch

### B. Construction: Bronze

### C. Features: Magnetic Drive with Automatic Meter Register (AMR), Oval Flanges

### D. Manufacturer: Badger, Model Recordall 2-inch, or Approved Equal.

1. Approval required by local water department before ordering equipment.

## 2.12 EARTH MATERIALS

### A. Stone (in Valve Boxes)

1. Type: ¾-Inch (minimum) Crushed Stone

### B. Clean Sand

1. Gradation: (passing by weight)
  - a. No. 4 Sieve= 80% Minimum
  - b. No. 200 Sieve = 5% Maximum

## 2.13 COPPER PIPE (INSIDE VAULT)

### A. Size: 2-inch

### B. Construction: Type K Copper

### C. Standards: ASTM B-88



- D. Fittings: Wrought Copper, Silver Solder Joint (per ASTM B-828), Non-Corrosive Flux

#### 2.14 SPARE PARTS

- A. Wrenches, Keys, and Tools for Servicing and Adjusting Sprinkler Heads (2)
- B. Quick Coupler Valve Keys (1)
- C. Gate Valve (1 of each size on Drawings)
- D. Electric Zone Valve (1 of each size on Drawings)
- E. Sprinkler Heads and Nozzles (3 of Each)
- F. Assorted Valves and Fittings

### PART 3 – EXECUTION

#### 3.1 GENERAL

- A. Competent superintendents and assistants shall be on-site at all times during product delivery, installation, testing, and system adjustments.
  - 1. Field communication by Owner or Owner's Representative to superintendent shall be binding.
- B. System features shall be laid out as indicated on Drawings, making minor adjustments for variations in planting arrangements or field conditions. Major changes shall be reviewed with Owner's Representative before acceptance.
  - 1. Irrigation lines shown on Construction Drawings are diagrammatic only. Location of irrigation equipment is contingent upon and subject to integration with all other underground utilities, tree roots, and hardscape design elements.

#### 3.2 EXAMINATION

- A. Review and verify project conditions are as indicated on Construction Drawings prior to starting work, including but not limited to:
  - 1. Utilities provided by Others
  - 2. Site grades and dimensions
  - 3. Athletic Field, landscaping and features
  - 4. Structures
  - 5. Pipe sleeves
- B. Report any irregularities of site conditions to the Owner's Representative prior to beginning

work.

- C. Beginning of installation connotes acceptance of existing project conditions.

### 3.3 PROJECT COORDINATION

- A. Coordinate with Owner's Representative to expeditiously install system.
- B. Provide written notifications (electronic is acceptable) to Owner's Representative prior to work commencement, weekly for progress report, for any proposed changes to system design, and upon installation completion.
- C. All questions of design intent, proposed design changes, field notifications, and product substitution after installation commences shall be in writing to Owner's Representative as a Request for Information (RFI).
- D. Utility Coordination:
  - 1. Maintain 6-inch minimum clearance between irrigation lines and any utility line. Do not install sprinkler lines directly above another utility of any kind.
  - 2. Exercise care when excavating, trenching, and working near existing utilities.

### 3.4 SITE PROTECTION

- A. Protect landscaping, paving, structures, walls, footings, etc. from damage caused during work. Damage to work of another trade shall be reported at once.
- B. Replace or repair any damage with same product or material, to the satisfaction of Owner's Representative at no additional cost to the Owner per Guarantee.
- C. Route pipe as necessary to prevent damage to tree roots. Where trenching must occur near trees, provide proper root pruning and sealing methods to all roots 1-inch and larger.

### 3.5 EXCAVATION, TRENCHING, AND BACKFILLING

- A. Notify and request approval from Owner's Representative if pipe pulling is the intended installation method. Pipe pulling is an accepted installation practice only under the following conditions:
  - 1. Maximum pipe size 2 inches, and
  - 2. Suitable soils (i.e. naturally rounded loamy soils without sharp rocks), and
  - 3. Specified pipe burial depth can be maintained.
- B. Pipe Trench:
  - 1. Excavate trenches straight and true, minimizing site disturbance as possible.
  - 2. Final trench bottom shall be undisturbed soil and shall be free of rocks and debris larger

than 1 inch or with sharp edges. If trench base is unsuitable for laying pipe, over excavate 2 inches below pipe invert, and place Clean Sand or Stone.

C. Clean Backfill:

1. Material: Clean Sand (See Earth Materials)
  - a. Clean backfill must be free of foreign material, debris, frozen material and rocks larger than 1-inch.
2. Carefully place clean backfill a minimum depth of 10-inches over pipe and wire, tamp in place.
3. Carefully place material around pipe and wire, tamp in place.

D. Trench Backfill:

1. Material: Re-use excavated material
  - a. Clean backfill must be free of foreign material, debris, frozen material, and rocks larger than 1-inch.
2. Place and compact in maximum 6-inch lifts to dry density equal to undisturbed soil. Compaction by truck or equipment tires is prohibited.
3. Avoid backfilling in hot weather.
4. Match adjacent subsurface grades without hills or depressions. Repair settling (as required by Guarantee).
5. If final planting soils, mulch, or sod were removed or disturbed during trenching, replace to match Project Specifications and regrade as necessary.
  - a. Use sod cutter where applicable, or reseed disturbed areas to acceptance of Owner.

### 3.6 PIPE INSTALLATION

A. Copper Pipe Installation

1. All copper work within irrigation vault shall be installed by licensed plumber.

B. PVC Pipe Installation

1. Cut plastic pipe with handsaw or pipe cutter, removing all burrs at cut ends. All pipe cuts shall be square and true. Bevel cut end as required to conform to manufacturer instructions.
2. Make all solvent-weld joints as per manufacturer's instructions and avoid applying excess primer or solvent. Do not wipe off excess solvent from each connection.
  - a. Allow welded joints minimum 5 minutes set-up/curing time before moving or handling.
    - 1) Above 80°F: Allow connections to set 24 hours

- 2) Below 80°F: Follow manufacturer instructions
  - 3) Below 40°F: Prohibited
3. Maximum deflection per joint shall not exceed manufacturer limits.
4. Maintain 1-inch minimum between lines which cross at angles of 45 to 90 degrees
- C. Pipe and wire shall run in same trench as mainline, at the elevation of the pipe invert (See Wire Installation).
- D. Pipe Cover (unpaved surfaces):
  1. PVC Mainline = 15 inches
  2. PVC Lateral = 12 inches
- E. Pipe Protection:
  1. Prevent foreign material from entering pipe during installation.
  2. Open ends of pipe shall be closed by watertight plug or seal when not in use.
  3. Securely store pipe when not scheduled for installation.
  4. Pipe shall not be installed when water is in trench, during rainstorms, or when temperature is below 40 °F.
    - a. No additional pipe may be installed or backfilled if water enters trench during pipe installation. Remove all water from trench before resuming installation.
    - b. Pipe installed at temperatures below 40 °F shall be removed and replaced at no cost to owner.
  5. Trenched PVC pipe shall be snaked to accommodate for expansion and contraction due to changes in temperature.

### 3.7 PIPE SLEEVE INSTALLATION

- A. Coordinate with Owner's Representative.
- B. New Pipe Sleeves:
  1. Pipe Sleeve Cover: Minimum 24 inches
  2. Install pipe sleeves where irrigation pipe runs under hardscape (see Construction Drawings).
  3. Extend pipe sleeves minimum 18 inches beyond edges of hardscapes.
  4. Prior to installation of pipe, pipe sleeve ends shall be field marked with vertical wood stakes extending above grade to allow field location during irrigation system installation.
- C. Cutting through or jacking under new pavement shall be strictly prohibited. Failure to provide sleeves shall require notification to Owner's Representative for resolution.

### 3.8 ELECTRICAL CONDUIT INSTALLATION

- A. Outdoor Electrical conduit shall be installed:
  - 1. Under and through all hardscape areas
  - 2. For all above ground wiring
- B. Electrical conduit shall extend 18 inches beyond edges of hardscape.

### 3.9 ELECTRIC ZONE VALVE INSTALLATION

- A. Install electric zone valves on level crushed stone base generally where shown on Construction Drawings. Do not pour stone around valves that are already installed.
- B. Install all Schedule 80 PVC threaded nipples with Teflon tape, isolation valves, and/or union couplings in and out of electric zone valves as shown on details on Construction Drawings.
- C. Set valves plumb with adjusting handle and all bolts, screws, and wiring accessible through valve box opening.
- D. Install at sufficient depth to provide between 4-6 inches of cover from top of valve to finish grade.
- E. Install specified valve box over all electric zone valves. Ensure lid is flush with final proposed grade.
- F. Adjust zone valve operation after installation using flow control device on valve.

### 3.10 ISOLATION VALVE INSTALLATION

- A. Install isolation valves per detail where indicated on Construction Drawings.
- B. Install all isolation valves on level crushed stone base for operation ease with appropriate valve wrench. Do not pour stone around valves that are already installed.
- C. Install specified valve box over all isolation valves. Ensure lid is flush with final proposed grade.
- D. Check and tighten valve bonnet packing before valve box and backfill installation.

### 3.11 QUICK COUPLING VALVE INSTALLATION

- A. Install quick coupling valves where indicated on Construction Drawings; generally, at ends of mainline branches and immediately downstream of well.
- B. Mount mainline quick coupling valves on 1-inch diameter, 12-inch long brass swing joint assemblies and stabilizers.

### 3.12 WIRE INSTALLATION

- A. Install wiring per local codes for less than 30-Volt service.
- B. Install valve wire in trench alongside mainline at invert elevation. Backfill carefully to avoid any damage to wire insulation on conductors.
  - 1. In areas of unsuitable material, use clean sand in bottom of trench before placing wire (see Excavation, Trenching, and Backfilling)
  - 2. Minimum cover: 12-inches
- C. Maintain sufficient slack for expansion, contraction and servicing. Do not install wiring tightly.
  - 1. Provide 30 inches slack between for valve wire in valve boxes.
  - 2. Provide sufficient length of wire in valve boxes to allow valve solenoid, splice, wire, and all connections to be brought above grade for servicing.
  - 3. Coil slack for neatness in valve box.
- D. Provide waterproof splices at all in-ground wire connections using approved splice kits. All splices shall be made in valve boxes and recorded on Record Drawings.
- E. Provide complete wiring diagram showing wire routing for connections between controller and valves as specified in Record Documents.
- F. Securely store wire when not scheduled for installation.

### 3.13 GROUND INSTALLATION

- A. Controller Grounding
  - 1. Wire 6AWG Bare Copper Wire to Grounding Rod and Plate as shown on drawings.
  - 2. Grounding Rod
    - a. Contractor to ensure no obstructions below grade at grounding rod site (Call 811 / DIG-SAFE if necessary)
    - b. Prepare valve box for grounding rod installation 8 feet from all valve boxes and electrical equipment. Drive 8-foot grounding rod into earth with 6 inches minimum below valve box lid.
    - c. Make Cadweld connection between bare copper wire from lightning arrestor splice to grounding rod lug.

### 3.14 SPRINKLER INSTALLATION

- A. Sprinklers shall not exceed maximum spacing as indicated on Construction Drawings.
- B. Install sprinklers flush with grade on PVC swing joints as specified.
- C. Flush system before installing internals, flush caps, and nozzles (see Testing and Adjustments)

- D. Adjust all sprinklers after installation using flow control device on valve. Do not exceed radius reduction recommendations from manufacturer.

### 3.15 VALVE BOX INSTALLATION

- A. Furnish and install valve boxes as per valve schedule above for each valve, splice, or sensor.
- B. Install valve boxes on minimum 4-inches crushed stone base. Pouring stone into valve box after installation is not acceptable.
- C. Finish elevation of all boxes shall be at grade, unless otherwise noted in Drawings.
- D. Provide level brick supports beneath valve boxes.
  - 1. For square/rectangular boxes, provide four (4) supports - one at each corner.
  - 2. For round boxes, provide three (3) supports equally spaced.

### 3.16 AUTOMATIC IRRIGATION CONTROLLER INSTALLATION

- A. Controller
  - 1. Controller located inside Stainless Steel Enclosure.
  - 2. Wire valves and external sensors into controller through conduits and set proper programming.
    - a. Program "Cycle-Soak" feature for all zones with sloped or poorly draining soils.
  - 3. Use Irrigation Plans provided for Recommended Quantity and Assignment
  - 4. Using licensed electrical, wire controller to 120-Volt, 20-Amp electrical supply provided by Electrical Contractor.
  - 5. Provide keys to Owner after final walkthrough.
- B. Rain Sensors
  - 1. Install wireless Rain Sensor on eave of stage roof, minimizing distance to receiver in vault.
  - 2. Rain Sensor shall have direct overhead exposure to atmospheric conditions and not in contact with overhead irrigation.
- C. Grounding
  - 1. Provide outdoor grounding for irrigation controller with grounding rod and grounding plate. Refer to Ground Installation and Construction Drawings details for installation steps.

### 3.17 TESTING AND ADJUSTMENTS

- A. Include all testing and adjustments in submitted bid price.

B. System Flushing:

1. Open electric zone valves and flush out irrigation system under full head of water before installing sprinkler internals, flush caps, and nozzles.
2. Flush entire irrigation system after complete installation.
3. Clogged nozzles shall be remedied after completion of irrigation system.

C. Testing:

1. Test all pipe and valves for leaks at operating pressure. Repair all leaks and retest until leaks are remedied.
2. Perform coverage test with Owner's Representative present. Operate electric zone valves for five (5) minutes minimum during coverage test. Readjust sprinkler nozzles and head locations (as necessary) to attain proper coverage. Replace any equipment that does not meet specified standards.
3. After testing, clean all equipment of debris during installation.

D. Adjust sprinkler heads and valve boxes as necessary for mowing and landscaping.

E. Throughout guarantee period, adjust sprinklers and ensure coverage due to settlement and landscaping operations.

### 3.18 RECORD DOCUMENTS

A. Record (As-Built) Drawings

1. Maintain and update Record Drawings with red-line markings as project progresses, including locations of:
  - a. Sprinklers and descriptions (nozzle, pop-up height, and type)
  - b. Valve Boxes and descriptions (valve type, zone numbers, splice, etc.)
  - c. All equipment installed with distinct symbols
  - d. Pipe routing and tees
  - e. Wire routing and splices
2. Locations of installed equipment (valve, controller, sensors) shall be referenced by two permanent locations (swing ties) or GPS.
3. Make all notes legible as work progresses, any new equipment added shall use distinct symbols denoting location.
4. Document any changes from original Construction Drawings.
5. Prints of original Construction Drawings may be obtained from the Owner's Representative at cost (0% markup).
6. Record Drawings shall be used as basis of payment for work completed. Provide copies of red-lined set to Owner's Representative along with payment request.

B. Record Documents

1. Record Documents shall be on-site at all times. Maintain record of the following as the



project progresses:

- a. Materials Approved and approval date
  - b. Pressure Test results, testing personnel and testing date.
  - c. Materials delivered, Accepted, and Installed by whom and date.
  - d. Field Communications and Requests for Information (RFI)
- C. Prior to final punchlist, provide complete electronic and hard copy files of Record Drawings and Documents to Owner's Representative as part of project completion. All information must be complete and shall be added to submitted documents prior to acceptance.

### 3.19 OPERATION AND MAINTENANCE

#### A. General

1. Bid price shall include up to four (4) hours of irrigation system overview and instruction with Owner and/or Owner's Representative.

#### B. Operation and Maintenance Manual

1. Provide three (3) hard cover binders titled "Operation and Maintenance for East Park Irrigation System" prior to application for acceptance and final payment.
2. Operation and Maintenance Manual shall include, but not be limited to:
  - a. Title Page and Table of Contents
  - b. One-Paragraph Written Description of Irrigation System
  - c. Manufacturers' Data and Cut Sheets of Equipment, including:
    - 1) Copies of all approved submittals
    - 2) Wire resistance readings to each electric valve at completion (for future troubleshooting)
    - 3) Recommended operating settings
    - 4) Recommended maintenance schedule
    - 5) Name, address, and telephone number of installer (for repairs, spring startup, and winterization during 1-year guarantee period)
    - 6) Irrigation program for periods without rain and recommended settings including, zone run time, days per week, cycle-soak, and rain sensor suspension.
    - 7) Rain Bird IQ (Weather Network) settings, login, and troubleshooting
  - d. Winterization and Spring Startup Instructions (after 1-year guarantee period)
  - e. Guarantee Data
  - f. Pockets with Folded Plans of:
    - 1) Original Design Drawing
    - 2) Final Record Drawing
    - 3) Controller Valve and Wiring System Diagram Drawing

3.20 SITE CLEANUP

- A. Remove all unused materials and equipment from project site safely and efficiently. Dispose of all unused materials legally - including construction debris and trash.
- B. Adjust ground, compact, and re-plant around irrigation sprinkler heads and trenches as necessary for proper angle and elevation.
- C. Fill all depressions, erosion rills, tire tracks, etc. with proper planting soil mix to ensure site drainage.

3.21 FINAL ACCEPTANCE

- A. Final Acceptance of Irrigation System is predicated on:
  - 1. Complete system installation, adjustment, testing, and instructional overview.
  - 2. Submission of Operation and Maintenance Manuals to Owner's Representative.
  - 3. Proper Programming and Internet Connection of Automatic Irrigation Controller
  - 4. Completed and approved all punchlist items.
- B. Owner's Representative shall provide written notice (hard copy and/or electronic) for Final Acceptance. Date of Final Acceptance notice shall serve as start of 1-year Guarantee period as described above.

END OF SECTION 328400

## SECTION 329200 - TURF AND GRASSES

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Seeding.
  - 2. Hydroseeding.
  - 3. Sodding.
- B. Related Requirements:
  - 1. Section 329300 "Plants" for trees, shrubs, ground covers, and other plants as well as border edgings and mow strips.

#### 1.3 DEFINITIONS

- A. Finish Grade: Elevation of finished surface of planting soil.
- B. Pesticide: A substance or mixture intended for preventing, destroying, repelling, or mitigating a pest. Pesticides include insecticides, miticides, herbicides, fungicides, rodenticides, and molluscicides. They also include substances or mixtures intended for use as a plant regulator, defoliant, or desiccant.
- C. Pests: Living organisms that occur where they are not desired or that cause damage to plants, animals, or people. Pests include insects, mites, grubs, mollusks (snails and slugs), rodents (gophers, moles, and mice), unwanted plants (weeds), fungi, bacteria, and viruses.
- D. Planting Soil: Existing, on-site soil; imported soil; or manufactured soil that has been modified with soil amendments and perhaps fertilizers to produce a soil mixture best for plant growth.
- E. Subgrade: The surface or elevation of subsoil remaining after excavation is complete, or the top surface of a fill or backfill before planting soil is placed.

#### 1.4 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.

#### 1.5 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For landscape Installer.
- B. Certification of Grass Seed: From seed vendor for each grass-seed monostand or mixture, stating the botanical and common name, percentage by weight of each species and variety, and percentage of purity, germination, and weed seed. Include the year of production and date of packaging.
- C. Product Certificates: For fertilizers, from manufacturer.
- D. Pesticides and Herbicides: Product label and manufacturer's application instructions specific to Project.

#### 1.6 QUALITY ASSURANCE

- A. Installer Qualifications: A qualified landscape installer whose work has resulted in successful turf establishment.
  - 1. Professional Membership: Installer shall be a member in good standing of either the National Association of Landscape Professionals or AmericanHort.
  - 2. Experience: Three years' experience in turf installation in addition to requirements in Section 014000 "Quality Requirements."
  - 3. Installer's Field Supervision: Require Installer to maintain an experienced full-time supervisor on Project site when work is in progress.
  - 4. Pesticide Applicator: State licensed, commercial.

#### 1.7 DELIVERY, STORAGE, AND HANDLING

- A. Seed and Other Packaged Materials: Deliver packaged materials in original, unopened containers showing weight, certified analysis, name and address of manufacturer, and indication of compliance with state and Federal laws, as applicable.
- B. Bulk Materials:
  - 1. Do not dump or store bulk materials near structures, utilities, walkways and pavements, or on existing turf areas or plants.

2. Provide erosion-control measures to prevent erosion or displacement of bulk materials; discharge of soil-bearing water runoff; and airborne dust reaching adjacent properties, water conveyance systems, or walkways.
3. Accompany each delivery of bulk materials with appropriate certificates.

## 1.8 FIELD CONDITIONS

- A. Planting Restrictions: Plant during one of the following periods. Coordinate planting periods with initial maintenance periods to provide required maintenance from date of planting completion.
  1. Spring Planting: April 15 to June 15.
  2. Fall Planting: September 15 to November 15.
- B. Weather Limitations: Proceed with planting only when existing and forecasted weather conditions permit planting to be performed when beneficial and optimum results may be obtained. Apply products during favorable weather conditions according to manufacturer's written instructions.

## PART 2 - PRODUCTS

### 2.1 SEED

- A. Grass Seed: Fresh, clean, dry, new-crop seed complying with AOSA's "Rules for Testing Seeds" for purity and germination tolerances.
- B. Seed Species: State-certified seed of grass species as follows:
- C. Seed Species: Seed of grass species as follows, with not less than 95 percent germination, not less than 85 percent pure seed, and not more than 0.5 percent weed seed:
  1. General Lawn Mixture: Proportioned by weight as follows:
    - a. 40 percent perennial ryegrass (*Lolium perenne*)
    - b. 25 percent Kentucky bluegrass (*Poa pratensis*)
    - c. 25 percent chewings red fescue (*Festuca rubra* variety)
    - d. 10 percent creeping red fescue

### 2.2 TURFGRASS SOD

- A. Turfgrass Sod: **Certified Number 1 Quality/Premium, including limitations on thatch, weeds, diseases, nematodes, and insects**, complying with "Specifications for Turfgrass Sod Materials" in TPI's "Guideline Specifications to Turfgrass Sodding." Furnish viable sod of uniform density,

color, and texture that is strongly rooted and capable of vigorous growth and development when planted.

- B. Turfgrass Species, Cool-Season Grass: Sod of grass species as follows, with not less than 85 percent germination, not less than 95 percent pure seed, and not more than 0.5 percent weed seed:
  - 1. Full Sun: Kentucky bluegrass (*Poa pratensis*), a minimum of three cultivars.
  - 2. Sun and Partial Shade: Proportioned by weight as follows:
    - a. 50 percent Kentucky bluegrass (*Poa pratensis*).
    - b. 30 percent chewings red fescue (*Festuca rubra* variety).
    - c. 10 percent perennial ryegrass (*Lolium perenne*).
    - d. 10 percent redtop (*Agrostis alba*).

## 2.3 FERTILIZERS

- A. Commercial Fertilizer: Commercial-grade complete fertilizer of neutral character, consisting of fast- and slow-release nitrogen, 50 percent derived from natural organic sources of urea formaldehyde, phosphorous, and potassium in the following composition:
  - 1. Composition:
    - a. 1 lb/1000 sq. ft. of actual nitrogen, 4 percent phosphorous, and 2 percent potassium, by weight.
    - b. Nitrogen, phosphorous, and potassium in amounts recommended in soil reports from a qualified soil-testing laboratory.
- B. Slow-Release Fertilizer: Granular or pelleted fertilizer consisting of 50 percent water-insoluble nitrogen, phosphorus, and potassium in the following composition:
  - 1. Composition:
    - a. 20 percent nitrogen, 10 percent phosphorous, and 10 percent potassium, by weight.
    - b. Nitrogen, phosphorous, and potassium in amounts recommended in soil reports from a qualified soil-testing laboratory.

## 2.4 MULCHES

- A. Straw Mulch: Provide air-dry, clean, mildew- and seed-free, salt hay or threshed straw of wheat, rye, oats, or barley.

## 2.5 PESTICIDES

- A. General: Pesticide, registered and approved by the EPA, acceptable to authorities having jurisdiction, and of type recommended by manufacturer for each specific problem and as required for Project conditions and application. Do not use restricted pesticides unless authorized in writing by authorities having jurisdiction.
- B. Pre-Emergent Herbicide (Selective and Nonselective): Effective for controlling the germination or growth of weeds within planted areas at the soil level directly below the mulch layer.
- C. Post-Emergent Herbicide (Selective and Nonselective): Effective for controlling weed growth that has already germinated.

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- A. Examine areas to be planted for compliance with requirements and other conditions affecting installation and performance of the Work.
  - 1. Verify that no foreign or deleterious material or liquid such as paint, paint washout, concrete slurry, concrete layers or chunks, cement, plaster, oils, gasoline, diesel fuel, paint thinner, turpentine, tar, roofing compound, or acid has been deposited in soil within a planting area.
  - 2. Suspend planting operations during periods of excessive soil moisture until the moisture content reaches acceptable levels to attain the required results.
  - 3. Uniformly moisten excessively dry soil that is not workable or which is dusty.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.
- C. If contamination by foreign or deleterious material or liquid is present in soil within a planting area, remove the soil and contamination as directed by Landscape Architect and replace with new planting soil.

### 3.2 PREPARATION

- A. Protect structures; utilities; sidewalks; pavements; and other facilities, trees, shrubs, and plantings from damage caused by planting operations.
  - 1. Protect adjacent and adjoining areas from hydroseeding and hydromulching overspray.
  - 2. Protect grade stakes set by others until directed to remove them.

- B. Install erosion-control measures to prevent erosion or displacement of soils and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways.

### 3.3 TURF AREA PREPARATION

- A. Limit turf subgrade preparation to areas to be planted.
- B. Newly Graded Subgrades: Loosen subgrade to a minimum depth of 4 inches. Remove stones larger than 1 inch in any dimension and sticks, roots, rubbish, and other extraneous matter and legally dispose of them off Owner's property.
  - 1. Apply superphosphate fertilizer directly to subgrade before loosening.
  - 2. Spread topsoil, apply soil amendments and fertilizer on surface, and thoroughly blend Planting Soil.
    - a. Delay mixing fertilizer with Planting Soil if planting will not proceed within a few days.
    - b. Mix lime with dry soil before mixing fertilizer.
  - 3. Spread Planting Soil to a depth of 6 inches but not less than required to meet finish grades after light rolling and natural settlement. Do not spread if Planting Soil or subgrade is frozen, muddy, or excessively wet.
    - a. Spread approximately 1/2 the thickness of Planting Soil over loosened subgrade. Mix thoroughly into top 2 inches of subgrade. Spread remainder of Planting Soil.
    - b. Reduce elevation of Planting Soil to allow for soil thickness of sod.
- C. Unchanged Subgrades: If turf is to be planted in areas unaltered or undisturbed by excavating, grading, or surface-soil stripping operations, prepare surface soil as follows:
  - 1. Remove existing grass, vegetation, and turf. Do not mix into surface soil.
  - 2. Loosen surface soil to a depth of at least 6 inches. Apply soil amendments and fertilizers according to Planting Soil mix proportions and mix thoroughly into top 4 inches of soil. Till soil to a homogeneous mixture of fine texture.
    - a. Apply superphosphate fertilizer directly to surface soil before loosening.
  - 3. Remove stones larger than 1 inch in any dimension and sticks, roots, trash, and other extraneous matter.
  - 4. Legally dispose of waste material, including grass, vegetation, and turf, off Owner's property.
- D. Finish Grading: Grade planting areas to a smooth, uniform surface plane with loose, uniformly fine texture. Grade to within plus or minus 1/2 inch of finish elevation. Roll and rake, remove ridges, and fill depressions to meet finish grades. Limit finish grading to areas that can be planted in the immediate future.



- E. Moisten prepared area before planting if soil is dry. Water thoroughly and allow surface to dry before planting. Do not create muddy soil.
- F. Before planting, obtain Landscape Architect's acceptance of finish grading; restore planting areas if eroded or otherwise disturbed after finish grading.

### 3.4 SEEDING

- A. Sow seed with spreader or seeding machine. Do not broadcast or drop seed when wind velocity exceeds 5 mph.
  - 1. Evenly distribute seed by sowing equal quantities in two directions at right angles to each other.
  - 2. Do not use wet seed or seed that is moldy or otherwise damaged.
  - 3. Do not seed against existing trees. Limit extent of seed to outside edge of planting saucer.
- B. Sow seed at a total rate of 3 to 4 lb/1000 sq. ft.
- C. Rake seed lightly into top 1/8 inch of soil, roll lightly, and water with fine spray.

### 3.5 HYDROSEEDING

- A. Hydroseeding: Mix specified seed, fertilizer, and fiber mulch in water, using equipment specifically designed for hydroseed application. Continue mixing until uniformly blended into homogeneous slurry suitable for hydraulic application.
  - 1. Mix slurry with fiber-mulch manufacturer's recommended tackifier.
  - 2. Spray-apply slurry uniformly to all areas to be seeded in a one-step process. Apply slurry at a rate so that mulch component is deposited at not less than 1500-lb/acre dry weight, and seed component is deposited at not less than the specified seed-sowing rate.
  - 3. Spray-apply slurry uniformly to all areas to be seeded in a two-step process. Apply first slurry coat at a rate so that mulch component is deposited at not less than 500-lb/acre dry weight, and seed component is deposited at not less than the specified seed-sowing rate. Apply slurry cover coat of fiber mulch (hydromulching) at a rate of 1000 lb/acre.

### 3.6 SODDING

- A. Lay sod within 24 hours of harvesting unless a suitable preservation method is accepted by Landscape Architect prior to delivery time. Do not lay sod if dormant or if ground is frozen or muddy.
- B. Lay sod to form a solid mass with tightly fitted joints. Butt ends and sides of sod; do not stretch or overlap. Stagger sod strips or pads to offset joints in adjacent courses. Avoid damage to soil

or sod during installation. Tamp and roll lightly to ensure contact with soil, eliminate air pockets, and form a smooth surface. Work sifted soil or fine sand into minor cracks between pieces of sod; remove excess to avoid smothering sod and adjacent grass.

1. Lay sod across slopes exceeding 1:3.
  2. Anchor sod on slopes exceeding 1:6 with wood pegs spaced as recommended by sod manufacturer but not less than two anchors per sod strip to prevent slippage.
- C. Saturate sod with fine water spray within two hours of planting. During first week after planting, water daily or more frequently as necessary to maintain moist soil to a minimum depth of 1-1/2 inches below sod.

### 3.7 TURF MAINTENANCE

- A. General: Maintain and establish turf by watering, fertilizing, weeding, mowing, trimming, replanting, and performing other operations as required to establish healthy, viable turf. Roll, regrade, and replant bare or eroded areas and remulch to produce a uniformly smooth turf. Provide materials and installation the same as those used in the original installation.
1. Fill in as necessary soil subsidence that may occur because of settling or other processes. Replace materials and turf damaged or lost in areas of subsidence.
  2. In areas where mulch has been disturbed by wind or maintenance operations, add new mulch and anchor as required to prevent displacement.
  3. Apply treatments as required to keep turf and soil free of pests and pathogens or disease. Use integrated pest management practices whenever possible to minimize the use of pesticides and reduce hazards.
- B. Watering: Install and maintain temporary piping, hoses, and turf-watering equipment to convey water from sources and to keep turf uniformly moist to a depth of 4 inches.
1. Schedule watering to prevent wilting, puddling, erosion, and displacement of seed or mulch. Lay out temporary watering system to avoid walking over muddy or newly planted areas.
  2. Water turf with fine spray at a minimum rate of 1 inch per week unless rainfall precipitation is adequate.
- C. Mow turf as soon as top growth is tall enough to cut. Repeat mowing to maintain specified height without cutting more than one-third of grass height. Remove no more than one-third of grass-leaf growth in initial or subsequent mowings. Do not delay mowing until grass blades bend over and become matted. Do not mow when grass is wet. Schedule initial and subsequent mowings to maintain the following grass height:
1. Mow Kentucky bluegrass to a height of 1-1/2 to 2 inches.
- D. Turf Postfertilization: Apply fertilizer after initial mowing and when grass is dry.
1. Use fertilizer that provides actual nitrogen of at least 1 lb/1000 sq. ft. to turf area.

### 3.8 SATISFACTORY TURF

- A. Turf installations shall meet the following criteria as determined by Landscape Architect:
  - 1. Satisfactory Seeded Turf: At end of maintenance period, a healthy, uniform, close stand of grass has been established, free of weeds and surface irregularities, with coverage exceeding 90 percent over any 10 sq. ft. and bare spots not exceeding 5 by 5 inches.
- B. Use specified materials to reestablish turf that does not comply with requirements, and continue maintenance until turf is satisfactory.

### 3.9 PESTICIDE APPLICATION

- A. Apply pesticides and other chemical products and biological control agents according to requirements of authorities having jurisdiction and manufacturer's written recommendations. Coordinate applications with Owner's operations and others in proximity to the Work. Notify Owner before each application is performed.
- B. Post-Emergent Herbicides (Selective and Nonselective): Apply only as necessary to treat already-germinated weeds and according to manufacturer's written recommendations.

### 3.10 CLEANUP AND PROTECTION

- A. Promptly remove soil and debris created by turf work from paved areas. Clean wheels of vehicles before leaving site to avoid tracking soil onto roads, walks, or other paved areas.
- B. Remove surplus soil and waste material, including excess subsoil, unsuitable soil, trash, and debris, and legally dispose of them off Owner's property.
- C. Erect temporary fencing or barricades and warning signs as required to protect newly planted areas from traffic. Maintain fencing and barricades throughout initial maintenance period and remove after plantings are established.
- D. Remove nondegradable erosion-control measures after grass establishment period.

END OF SECTION 329200

## SECTION 329300 - PLANTS

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Plants.
  - 2. Tree stabilization.
- B. Related Requirements:
  - 1. Section 329200 "Turf and Grasses" for turf (lawn) and meadow planting, hydroseeding, and erosion-control materials.

#### 1.3 DEFINITIONS

- A. Backfill: The earth used to replace or the act of replacing earth in an excavation.
- B. Balled and Burlapped Stock: Plants dug with firm, natural balls of earth in which they were grown, with a ball size not less than diameter and depth recommended by ANSI Z60.1 for type and size of plant required; wrapped with burlap, tied, rigidly supported, and drum laced with twine with the root flare visible at the surface of the ball as recommended by ANSI Z60.1.
- C. Finish Grade: Elevation of finished surface of planting soil.
- D. Pesticide: A substance or mixture intended for preventing, destroying, repelling, or mitigating a pest. Pesticides include insecticides, miticides, herbicides, fungicides, rodenticides, and molluscicides. They also include substances or mixtures intended for use as a plant regulator, defoliant, or desiccant. Some sources classify herbicides separately from pesticides.
- E. Pests: Living organisms that occur where they are not desired or that cause damage to plants, animals, or people. Pests include insects, mites, grubs, mollusks (snails and slugs), rodents (gophers, moles, and mice), unwanted plants (weeds), fungi, bacteria, and viruses.
- F. Planting Area: Areas to be planted.

- G. Planting Soil: Existing, on-site soil; imported soil; or manufactured soil that has been modified with soil amendments and perhaps fertilizers to produce a soil mixture best for plant growth.
- H. Plant; Plants; Plant Material: These terms refer to vegetation in general, including trees, shrubs, vines, ground covers, ornamental grasses, bulbs, corms, tubers, or herbaceous vegetation.
- I. Root Flare: Also called "trunk flare." The area at the base of the plant's stem or trunk where the stem or trunk broadens to form roots; the area of transition between the root system and the stem or trunk.
- J. Stem Girdling Roots: Roots that encircle the stems (trunks) of trees below the soil surface.
- K. Subgrade: The surface or elevation of subsoil remaining after excavation is complete, or the top surface of a fill or backfill before planting soil is placed.

#### 1.4 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.

#### 1.5 ACTION SUBMITTALS

- A. Product Data: For each type of product.
  - 1. Plant Materials: Include quantities, sizes, quality, and sources for plant materials.
  - 2. Plant Photographs: Include color photographs in digital format of each required species and size of plant material as it will be furnished to Project. Take photographs from an angle depicting true size and condition of the typical plant to be furnished. Include a scale rod or other measuring device in each photograph. For species where more than 20 plants are required, include a minimum of three photographs showing the average plant, the best quality plant, and the worst quality plant to be furnished. Identify each photograph with the full scientific name of the plant, plant size, and name of the growing nursery.

#### 1.6 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For landscape Installer. Include list of similar projects completed by Installer demonstrating Installer's capabilities and experience. Include project names, addresses, and year completed, and include names and addresses of owners' contact persons.
- B. Product Certificates: For each type of manufactured product, from manufacturer, and complying with the following:
  - 1. Manufacturer's certified analysis of standard products.

#### PLANTS

329300 - 2

2. Analysis of other materials by a recognized laboratory made according to methods established by the Association of Official Analytical Chemists, where applicable.
- C. Pesticides and Herbicides: Product label and manufacturer's application instructions specific to Project.
- D. Sample Warranty: For special warranty.

#### 1.7 CLOSEOUT SUBMITTALS

- A. Maintenance Data: Recommended procedures to be established by Owner for maintenance of plants during a calendar year. Submit before expiration of required maintenance periods.

#### 1.8 QUALITY ASSURANCE

- A. Installer Qualifications: A qualified landscape installer whose work has resulted in successful establishment of plants.
  1. Professional Membership: Installer shall be a member in good standing of either the National Association of Landscape Professionals or AmericanHort
  2. Experience: Five years' experience in landscape installation in addition to requirements in Section 014000 "Quality Requirements."
  3. Installer's Field Supervision: Require Installer to maintain an experienced full-time supervisor on Project site when work is in progress.
    - a. Landscape Industry Certified Technician - Exterior.
  4. Pesticide Applicator: State licensed, commercial.
- B. Provide quality, size, genus, species, and variety of plants indicated, complying with applicable requirements in ANSI Z60.1.
  1. Selection of plants purchased under allowances is made by Landscape Architect, who tags plants at their place of growth before they are prepared for transplanting.
- C. Measurements: Measure according to ANSI Z60.1. Do not prune to obtain required sizes.
  1. Trees and Shrubs: Measure with branches and trunks or canes in their normal position. Take height measurements from or near the top of the root flare for field-grown stock and container-grown stock. Measure main body of tree or shrub for height and spread; do not measure branches or roots tip to tip. Take caliper measurements 6 inches above the root flare for trees up to 4-inch caliper size, and 12 inches above the root flare for larger sizes.
  2. Other Plants: Measure with stems, petioles, and foliage in their normal position.

- D. Plant Material Observation: Landscape Architect may observe plant material either at place of growth or at site before planting for compliance with requirements for genus, species, variety, cultivar, size, and quality. Landscape Architect may also observe trees and shrubs further for size and condition of balls and root systems, pests, disease symptoms, injuries, and latent defects and may reject unsatisfactory or defective material at any time during progress of work. Remove rejected trees or shrubs immediately from Project site.
  - 1. Notify Landscape Architect of sources of planting materials seven days in advance of delivery to site.

#### 1.9 DELIVERY, STORAGE, AND HANDLING

- A. Packaged Materials: Deliver packaged materials in original, unopened containers showing weight, certified analysis, name and address of manufacturer, and indication of compliance with state and Federal laws if applicable.
- B. Bulk Materials:
  - 1. Do not dump or store bulk materials near structures, utilities, walkways and pavements, or on existing turf areas or plants.
  - 2. Provide erosion-control measures to prevent erosion or displacement of bulk materials; discharge of soil-bearing water runoff; and airborne dust reaching adjacent properties, water conveyance systems, or walkways.
  - 3. Accompany each delivery of bulk materials with appropriate certificates.
- C. Do not prune trees and shrubs before delivery. Protect bark, branches, and root systems from sun scald, drying, wind burn, sweating, whipping, and other handling and tying damage. Do not bend or bind-tie trees or shrubs in such a manner as to destroy their natural shape. Provide protective covering of plants during shipping and delivery. Do not drop plants during delivery and handling.
- D. Handle planting stock by root ball.
- E. Apply antidesiccant to trees and shrubs using power spray to provide an adequate film over trunks (before wrapping), branches, stems, twigs, and foliage to protect during digging, handling, and transportation.
  - 1. If deciduous trees or shrubs are moved in full leaf, spray with antidesiccant at nursery before moving and again two weeks after planting.
- F. Wrap trees and shrubs with burlap fabric over trunks, branches, stems, twigs, and foliage to protect from wind and other damage during digging, handling, and transportation.
- G. Deliver plants after preparations for planting have been completed, and install immediately. If planting is delayed more than six hours after delivery, set plants and trees in their appropriate

aspect (sun, filtered sun, or shade), protect from weather and mechanical damage, and keep roots moist.

1. Set balled stock on ground and cover ball with soil, peat moss, sawdust, or other acceptable material.
2. Do not remove container-grown stock from containers before time of planting.
3. Water root systems of plants stored on-site deeply and thoroughly with a fine-mist spray. Water as often as necessary to maintain root systems in a moist, but not overly wet condition.

#### 1.10 FIELD CONDITIONS

- A. Field Measurements: Verify actual grade elevations, service and utility locations, irrigation system components, and dimensions of plantings and construction contiguous with new plantings by field measurements before proceeding with planting work.
- B. Planting Restrictions: Plant during one of the following periods. Coordinate planting periods with maintenance periods to provide required maintenance from date of Substantial Completion.
  1. Spring Planting: April 1<sup>st</sup> - May 30<sup>th</sup>
  2. Fall Planting: September 15<sup>th</sup> – October 31<sup>st</sup>
- C. Weather Limitations: Proceed with planting only when existing and forecasted weather conditions permit planting to be performed when beneficial and optimum results may be obtained. Apply products during favorable weather conditions according to manufacturer's written instructions and warranty requirements.

#### 1.11 WARRANTY

- A. Special Warranty: Installer agrees to repair or replace plantings and accessories that fail in materials, workmanship, or growth within specified warranty period.
  1. Failures include, but are not limited to, the following:
    - a. Death and unsatisfactory growth, except for defects resulting from abuse, lack of adequate maintenance, or neglect by Owner.
    - b. Structural failures including plantings falling or blowing over.
    - c. Faulty performance of tree stabilization.
    - d. Deterioration of metals, metal finishes, and other materials beyond normal weathering.
  2. Warranty Periods: From date of planting completion.
    - a. Trees, Shrubs, Vines, and Ornamental Grasses: 12 months.



3. Include the following remedial actions as a minimum:
  - a. Immediately remove dead plants and replace unless required to plant in the succeeding planting season.
  - b. Replace plants that are more than 25 percent dead or in an unhealthy condition at end of warranty period.
  - c. A limit of one replacement of each plant is required except for losses or replacements due to failure to comply with requirements.
  - d. Provide extended warranty for period equal to original warranty period, for replaced plant material.

## PART 2 - PRODUCTS

### 2.1 PLANT MATERIAL

- A. General: Furnish nursery-grown plants true to genus, species, variety, cultivar, stem form, shearing, and other features indicated in Plant List, Plant Schedule, or Plant Legend indicated on Drawings and complying with ANSI Z60.1; and with healthy root systems developed by transplanting or root pruning. Provide well-shaped, fully branched, healthy, vigorous stock, densely foliated when in leaf and free of disease, pests, eggs, larvae, and defects such as knots, sun scald, injuries, abrasions, and disfigurement.
  1. Trees with damaged, crooked, or multiple leaders; tight vertical branches where bark is squeezed between two branches or between branch and trunk ("included bark"); crossing trunks; cut-off limbs more than 3/4 inch in diameter; or with stem girdling roots are unacceptable.
  2. Collected Stock: Do not use plants harvested from the wild, from native stands, from an established landscape planting, or not grown in a nursery unless otherwise indicated.
- B. Provide plants of sizes, grades, and ball or container sizes complying with ANSI Z60.1 for types and form of plants required. Plants of a larger size may be used if acceptable to Landscape Architect, with a proportionate increase in size of roots or balls.
- C. Root-Ball Depth: Furnish trees and shrubs with root balls measured from top of root ball, which begins at root flare according to ANSI Z60.1. Root flare shall be visible before planting.
- D. Labeling: Label at least one plant of each variety, size, and caliper with a securely attached, waterproof tag bearing legible designation of common name and full scientific name, including genus and species. Include nomenclature for hybrid, variety, or cultivar, if applicable for the plant.
- E. If formal arrangements or consecutive order of plants is indicated on Drawings, select stock for uniform height and spread, and number the labels to assure symmetry in planting.

## 2.2 MULCHES

- A. Organic Mulch: Free from deleterious materials and suitable as a top dressing of trees and shrubs, consisting of one of the following:
  - 1. Type: Ground or shredded bark.
  - 2. Size Range: 3 inch maximum, 1/2 inch minimum.
  - 3. Color: Natural.

## 2.3 PESTICIDES

- A. General: Pesticide registered and approved by the EPA, acceptable to authorities having jurisdiction, and of type recommended by manufacturer for each specific problem and as required for Project conditions and application. Do not use restricted pesticides unless authorized in writing by authorities having jurisdiction.
- B. Pre-Emergent Herbicide (Selective and Nonselective): Effective for controlling the germination or growth of weeds within planted areas at the soil level directly below the mulch layer.
- C. Post-Emergent Herbicide (Selective and Nonselective): Effective for controlling weed growth that has already germinated.

## 2.4 TREE-STABILIZATION MATERIALS

- A. Trunk-Stabilization Materials:
  - 1. Upright and Guy Stakes: Rough-sawn, sound, new hardwood, free of knots, holes, cross grain, and other defects, 2-by-2-inch nominal by length indicated, pointed at one end.
  - 2. Tree-Tie Webbing: UV-resistant polypropylene or nylon webbing with brass grommets.
  - 3. Flags: Standard surveyor's plastic flagging tape, white, 6 inches long.

## 2.5 MISCELLANEOUS PRODUCTS

- A. Antidesiccant: Water-insoluble emulsion, permeable moisture retarder, film forming, for trees and shrubs. Deliver in original, sealed, and fully labeled containers and mix according to manufacturer's written instructions.
- B. Burlap: Non-synthetic, biodegradable.
- C. Mycorrhizal Fungi: Dry, granular inoculant containing at least 5300 spores per lb of vesicular-arbuscular mycorrhizal fungi and 95 million spores per lb of ectomycorrhizal fungi, 33 percent hydrogel, and a maximum of 5.5 percent inert material.

## PLANTS

329300 - 7

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- A. Examine areas to receive plants, with Installer present, for compliance with requirements and conditions affecting installation and performance of the Work.
  - 1. Verify that no foreign or deleterious material or liquid such as paint, paint washout, concrete slurry, concrete layers or chunks, cement, plaster, oils, gasoline, diesel fuel, paint thinner, turpentine, tar, roofing compound, or acid has been deposited in soil within a planting area.
  - 2. Verify that plants and vehicles loaded with plants can travel to planting locations with adequate overhead clearance.
  - 3. Suspend planting operations during periods of excessive soil moisture until the moisture content reaches acceptable levels to attain the required results.
  - 4. Uniformly moisten excessively dry soil that is not workable or which is dusty.
- B. If contamination by foreign or deleterious material or liquid is present in soil within a planting area, remove the soil and contamination as directed by Landscape Architect and replace with new planting soil.
- C. Proceed with installation only after unsatisfactory conditions have been corrected.

### 3.2 PREPARATION

- A. Protect structures, utilities, sidewalks, pavements, and other facilities and turf areas and existing plants from damage caused by planting operations.
- B. Install erosion-control measures to prevent erosion or displacement of soils and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways.
- C. Lay out individual tree and shrub locations and areas for multiple plantings. Stake locations, outline areas, adjust locations when requested, and obtain Landscape Architect's acceptance of layout before excavating or planting. Make minor adjustments as required.
- D. Lay out plants at locations directed by Landscape Architect. Stake locations of individual trees and shrubs and outline areas for multiple plantings.

### 3.3 EXCAVATION FOR TREES AND SHRUBS

- A. Planting Pits and Trenches: Excavate circular planting pits.
  - 1. Excavate planting pits with sides sloping inward at a 45-degree angle. Excavations with vertical sides are unacceptable. Trim perimeter of bottom leaving center area of bottom

- raised slightly to support root ball and assist in drainage away from center. Do not further disturb base. Ensure that root ball will sit on undisturbed base soil to prevent settling. Scarify sides of planting pit smeared or smoothed during excavation.
  2. Excavate approximately three times as wide as ball diameter for balled and burlapped stock.
  3. Do not excavate deeper than depth of the root ball, measured from the root flare to the bottom of the root ball.
  4. If area under the plant was initially dug too deep, add soil to raise it to the correct level and thoroughly tamp the added soil to prevent settling.
  5. Maintain angles of repose of adjacent materials to ensure stability. Do not excavate subgrades of adjacent paving, structures, hardscapes, or other new or existing improvements.
  6. Maintain supervision of excavations during working hours.
  7. Keep excavations covered or otherwise protected when unattended by Installer's personnel.
- B. Backfill Soil: Subsoil and topsoil removed from excavations may be used as backfill soil unless otherwise indicated.
- C. Obstructions: Notify Landscape Architect if unexpected rock or obstructions detrimental to trees or shrubs are encountered in excavations.
1. Hardpan Layer: Drill 6-inch-diameter holes, 24 inches apart, into free-draining strata or to a depth of 10 feet, whichever is less, and backfill with free-draining material.
- D. Drainage: Notify Landscape Architect if subsoil conditions evidence unexpected water seepage or retention in tree or shrub planting pits.
- E. Fill excavations with water and allow to percolate away before positioning trees and shrubs.

### 3.4 TREE PLANTING

- A. Inspection: At time of planting, verify that root flare is visible at top of root ball according to ANSI Z60.1. If root flare is not visible, remove soil in a level manner from the root ball to where the top-most root emerges from the trunk. After soil removal to expose the root flare, verify that root ball still meets size requirements.
- B. Roots: Remove stem girdling roots and kinked roots. Remove injured roots by cutting cleanly; do not break.
- C. Balled and Burlapped Stock: Set each plant plumb and in center of planting pit or trench with root flare 2 inches above adjacent finish grades.
1. Backfill: For trees, use excavated soil for backfill.

2. After placing some backfill around root ball to stabilize plant, carefully cut and remove burlap, rope, and wire baskets from tops of root balls and from sides, but do not remove from under root balls. Remove pallets, if any, before setting. Do not use planting stock if root ball is cracked or broken before or during planting operation.
3. Backfill around root ball in layers, tamping to settle soil and eliminate voids and air pockets. When planting pit is approximately one-half filled, water thoroughly before placing remainder of backfill. Repeat watering until no more water is absorbed.
4. Continue backfilling process. Water again after placing and tamping final layer of soil.

### 3.5 TREE, SHRUB, AND VINE PRUNING

- A. Remove only dead, dying, or broken branches. Do not prune for shape.
- B. Prune trees as directed by Landscape Architect or Certified Arborist.
- C. Prune trees according to standard professional horticultural and arboricultural practices. Unless otherwise indicated by Landscape Architect, do not cut tree leaders; remove only injured, dying, or dead branches from trees and shrubs; and prune to retain natural character.
- D. Do not apply pruning paint to wounds.

### 3.6 TREE STABILIZATION

- A. Trunk Stabilization by Upright Staking and Tying: Install trunk stabilization as follows unless otherwise indicated:
  1. Upright Staking and Tying:
    - a. Stake trees of 2- through 5-inch caliper. Stake trees of less than 2-inch caliper only as required to prevent wind tip out. Use a minimum of two stakes of length required to penetrate at least 18 inches below bottom of backfilled excavation and to extend to the dimension indicated on Drawings above grade. Set vertical stakes and space to avoid penetrating root balls or root masses.
    - b. Stake trees with two stakes for trees up to 12 feet high and 2-1/2 inches or less in caliper; three stakes for trees less than 14 feet high and up to 4 inches in caliper. Space stakes equally around trees.
  2. Support trees with bands of flexible ties at contact points with tree trunk. Allow enough slack to avoid rigid restraint of tree.

### 3.7 PLANTING AREA MULCHING

- A. Mulch backfilled surfaces of planting areas and other areas indicated.

1. Organic Mulch in Planting Areas: Apply 3-inch average thickness of organic mulch extending 12 inches beyond edge of individual planting pit or trench and over whole surface of planting area, and finish level with adjacent finish grades. Do not place mulch within 3 inches of trunks or stems.

### 3.8 PLANT MAINTENANCE

- A. Maintain plantings by pruning, cultivating, watering, weeding, fertilizing, mulching, restoring planting saucers, adjusting and repairing tree-stabilization devices, resetting to proper grades or vertical position, and performing other operations as required to establish healthy, viable plantings.
- B. Fill in, as necessary, soil subsidence that may occur because of settling or other processes. Replace mulch materials damaged or lost in areas of subsidence.
- C. Apply treatments as required to keep plant materials, planted areas, and soils free of pests and pathogens or disease. Use integrated pest management practices when possible to minimize use of pesticides and reduce hazards. Treatments include physical controls such as hosing off foliage, mechanical controls such as traps, and biological control agents.

### 3.9 PESTICIDE APPLICATION

- A. Apply pesticides and other chemical products and biological control agents according to authorities having jurisdiction and manufacturer's written recommendations. Coordinate applications with Owner's operations and others in proximity to the Work. Notify Owner before each application is performed.
- B. Pre-Emergent Herbicides (Selective and Nonselective): Apply to tree, shrub, and ground-cover areas according to manufacturer's written recommendations. Do not apply to seeded areas.
- C. Post-Emergent Herbicides (Selective and Nonselective): Apply only as necessary to treat already-germinated weeds and according to manufacturer's written recommendations.

### 3.10 REPAIR AND REPLACEMENT

- A. General: Repair or replace existing or new trees and other plants that are damaged by construction operations, in a manner approved by Landscape Architect.
  1. Submit details of proposed pruning and repairs.
  2. Perform repairs of damaged trunks, branches, and roots within 24 hours, if approved.
  3. Replace trees and other plants that cannot be repaired and restored to full-growth status, as determined by Landscape Architect.

- B. Remove and replace trees that are more than 25 percent dead or in an unhealthy condition before the end of the corrections period or are damaged during construction operations that Landscape Architect determines are incapable of restoring to normal growth pattern.
  - 1. Provide new trees of same size as those being replaced.
  - 2. Species of Replacement Trees: Same species being replaced.

### 3.11 CLEANING AND PROTECTION

- A. During planting, keep adjacent paving and construction clean and work area in an orderly condition. Clean wheels of vehicles before leaving site to avoid tracking soil onto roads, walks, or other paved areas.
- B. Remove surplus soil and waste material including excess subsoil, unsuitable soil, trash, and debris and legally dispose of them off Owner's property.
- C. Protect plants from damage due to landscape operations and operations of other contractors and trades. Maintain protection during installation and maintenance periods. Treat, repair, or replace damaged plantings.
- D. After installation and before Substantial Completion, remove nursery tags, nursery stakes, tie tape, labels, wire, burlap, and other debris from plant material, planting areas, and Project site.
- E. At time of Substantial Completion, verify that tree-watering devices are in good working order and leave them in place. Replace improperly functioning devices.

### 3.12 MAINTENANCE SERVICE

- A. Maintenance Service for Trees and Shrubs: Provide maintenance by skilled employees of landscape Installer. Maintain as required in "Plant Maintenance" Article. Begin maintenance immediately after plants are installed and continue until plantings are acceptably healthy and well established, but for not less than maintenance period below:
  - 1. Maintenance Period: 12 months from date of planting completion.

END OF SECTION 329300

## SECTION 330500 - COMMON WORK RESULTS FOR UTILITIES

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. This Section includes the following:
  - 1. Piping joining materials.
  - 2. Transition fittings.
  - 3. Sleeves.
  - 4. Grout.
  - 5. Equipment installation common requirements.
  - 6. Concrete bases.

#### 1.3 DEFINITIONS

- A. Exposed Installations: Exposed to view outdoors or subject to outdoor ambient temperatures and weather conditions.
- B. Concealed Installations: Concealed from view and protected from weather conditions and physical contact by building occupants but subject to outdoor ambient temperatures. Examples include installations within unheated shelters.
- C. PVC: Polyvinyl chloride plastic.
- D. DI: Ductile Iron
- E. HDPE: High Density Polyethylene plastic.

#### 1.4 ACTION SUBMITTALS

- A. Product Data: For the following:
  - 1. Identification devices



## 1.5 QUALITY ASSURANCE

- A. Steel Support Welding: Qualify procedures and personnel according to AWS D1.1/D1.1M, "Structural Welding Code - Steel."
- B. Steel Piping Welding: Qualify processes and operators according to ASME Boiler and Pressure Vessel Code: Section IX, "Welding and Brazing Qualifications."
  - 1. Comply with provisions in ASME B31 Series, "Code for Pressure Piping."
  - 2. Certify that each welder has passed AWS qualification tests for welding processes involved and that certification is current.
- C. Comply with ASME A13.1 for lettering size, length of color field, colors, and viewing angles of identification devices.

## 1.6 DELIVERY, STORAGE, AND HANDLING

- A. Deliver pipes and tubes with factory-applied end caps. Maintain end caps through shipping, storage, and handling to prevent pipe end damage and to prevent entrance of dirt, debris, and moisture.
- B. Store plastic pipes protected from direct sunlight. Support to prevent sagging and bending.

## 1.7 COORDINATION

- A. Coordinate installation of required supporting devices and set sleeves in poured-in-place concrete and other structural components as they are constructed.
- B. Coordinate installation of identifying devices after completing covering and painting if devices are applied to surfaces.
- C. Coordinate size and location of concrete bases. Formwork, reinforcement, and concrete requirements are specified in Section 033000 "Cast-in-Place Concrete."

## PART 2 - PRODUCTS

### 2.1 PIPING JOINING MATERIALS

- A. Pipe-Flange Gasket Materials: Suitable for chemical and thermal conditions of piping system contents.
  - 1. ASME B16.21, nonmetallic, flat, asbestos free, 1/8-inch maximum thickness, unless otherwise indicated.

## COMMON WORK RESULTS FOR UTILITIES

330500 - 2

- a. Full-Face Type: For flat-face, Class 125, cast-iron and cast-bronze flanges.
    - b. Narrow-Face Type: For raised-face, Class 250, cast-iron and steel flanges.
  2. AWWA C110, rubber, flat face, 1/8 inch thick, unless otherwise indicated; and full-face or ring type, unless otherwise indicated.
  - B. Flange Bolts and Nuts: ASME B18.2.1, carbon steel, unless otherwise indicated.
  - C. Plastic, Pipe-Flange Gasket, Bolts, and Nuts: Type and material recommended by piping system manufacturer, unless otherwise indicated.
  - D. Solder Filler Metals: ASTM B32, lead-free alloys. Include water-flushable flux according to ASTM B813.
  - E. Brazing Filler Metals: AWS A5.8, BCuP Series, copper-phosphorus alloys for general-duty brazing, unless otherwise indicated; and AWS A5.8, BAg1, silver alloy for refrigerant piping, unless otherwise indicated.
  - F. Welding Filler Metals: Comply with AWS D10.12/D10.12M for welding materials appropriate for wall thickness and chemical analysis of steel pipe being welded.
  - G. Solvent Cements for Joining Plastic Piping:
    1. ABS Piping: ASTM D2235.
    2. CPVC Piping: ASTM F493.
    3. PVC Piping: ASTM D2564. Include primer according to ASTM F656.
    4. PVC to ABS Piping Transition: ASTM D3138.
  - H. Fiberglass Pipe Adhesive: As furnished or recommended by pipe manufacturer.
- 2.2 TRANSITION FITTINGS
- A. Transition Fittings, General: Same size as, and with pressure rating at least equal to and with ends compatible with, piping to be joined.
  - B. Transition Couplings NPS 1-1/2 and Smaller:
    1. Underground Piping: Manufactured piping coupling or specified piping system fitting.
    2. Aboveground Piping: Specified piping system fitting.
  - C. AWWA Transition Couplings NPS 2 and Larger:
    1. Description: AWWA C219, metal sleeve-type coupling for underground pressure piping.
  - D. Plastic-to-Metal Transition Fittings:

1. Description: PVC one-piece fitting with manufacturer's Schedule 80 equivalent dimensions; one end with threaded brass insert, and one solvent-cement-joint or threaded end.
- E. Plastic-to-Metal Transition Unions:
  1. Description: MSS SP-107, PVC four-part union. Include brass or stainless-steel threaded end, solvent-cement-joint or threaded plastic end, rubber O-ring, and union nut.
- F. Flexible Transition Couplings for Underground Nonpressure Drainage Piping:
  1. Description: ASTM C1173 with elastomeric sleeve ends same size as piping to be joined, and corrosion-resistant metal band on each end.

## 2.3 SLEEVES

- A. Galvanized-Steel Sheet Sleeves: 0.0239-inch minimum thickness; round tube closed with welded longitudinal joint.
- B. Steel Pipe Sleeves: ASTM A53/A53M, Type E, Grade B, Schedule 40, galvanized, plain ends.
- C. Cast-Iron Sleeves: Cast or fabricated "wall pipe" equivalent to ductile-iron pressure pipe, with plain ends and integral waterstop, unless otherwise indicated.
- D. Molded PVC Sleeves: Permanent, with nailing flange for attaching to wooden forms.
- E. PVC Pipe Sleeves: ASTM D1785, Schedule 40.
- F. Molded PE Sleeves: Reusable, PE, tapered-cup shaped, and smooth outer surface with nailing flange for attaching to wooden forms.

## 2.4 GROUT

- A. Description: ASTM C1107, Grade B, nonshrink and nonmetallic, dry hydraulic-cement grout.
  1. Characteristics: Post hardening, volume adjusting, nonstaining, noncorrosive, nongaseous, and recommended for interior and exterior applications.
  2. Design Mix: 5000-psi, 28-day compressive strength.
  3. Packaging: Premixed and factory packaged.

## PART 3 - EXECUTION

### 3.1 PIPED UTILITY DEMOLITION

- A. Refer to Section 024119 "Selective Demolition" for general demolition requirements and procedures.
- B. Disconnect, demolish, and remove piped utility systems, equipment, and components indicated to be removed.
  - 1. Piping to Be Removed: Remove portion of piping indicated to be removed and cap or plug remaining piping with same or compatible piping material.
  - 2. Piping to Be Abandoned in Place: Drain piping. Fill abandoned piping with flowable fill, and cap or plug piping with same or compatible piping material.
  - 3. Equipment to Be Removed: Disconnect and cap services and remove equipment.
  - 4. Equipment to Be Removed and Reinstalled: Disconnect and cap services and remove, clean, and store equipment; when appropriate, reinstall, reconnect, and make operational.
  - 5. Equipment to Be Removed and Salvaged: Disconnect and cap services and remove equipment and deliver to Owner.
- C. If pipe, insulation, or equipment to remain is damaged in appearance or is unserviceable, remove damaged or unserviceable portions and replace with new products of equal capacity and quality.

### 3.2 PIPING INSTALLATION

- A. Install piping according to the following requirements and utilities Sections specifying piping systems.
- B. Drawing plans, schematics, and diagrams indicate general location and arrangement of piping systems. Indicated locations and arrangements were used to size pipe and calculate friction loss, expansion, pump sizing, and other design considerations. Install piping as indicated unless deviations to layout are approved on the Coordination Drawings.
- C. Install piping indicated to be exposed and piping in equipment rooms and service areas at right angles or parallel to building walls. Diagonal runs are prohibited unless specifically indicated otherwise.
- D. Install piping to permit valve servicing.
- E. Install piping at indicated slopes.
- F. Install piping free of sags and bends.

## COMMON WORK RESULTS FOR UTILITIES

330500 - 5

- G. Install fittings for changes in direction and branch connections.
- H. Select system components with pressure rating equal to or greater than system operating pressure.
- I. Sleeves are not required for core-drilled holes.
- J. Permanent sleeves are not required for holes formed by removable PE sleeves.
- K. Install sleeves for pipes passing through concrete and masonry walls and concrete floor and roof slabs.
  - 1. Cut sleeves to length for mounting flush with both surfaces.
    - a. Exception: Extend sleeves installed in floors of equipment areas or other wet areas 2 inches above finished floor level.
  - 2. Install sleeves in new walls and slabs as new walls and slabs are constructed.
    - a. PVC or Steel Pipe Sleeves: For pipes smaller than NPS 6.
    - b. Steel Sheet Sleeves: For pipes NPS 6 and larger, penetrating gypsum-board partitions.
- L. Verify final equipment locations for roughing-in.
- M. Refer to equipment specifications in other Sections for roughing-in requirements.

### 3.3 PIPING JOINT CONSTRUCTION

- A. Join pipe and fittings according to the following requirements and utilities Sections specifying piping systems.
- B. Ream ends of pipes and tubes and remove burrs. Bevel plain ends of steel pipe.
- C. Remove scale, slag, dirt, and debris from inside and outside of pipe and fittings before assembly.
- D. Threaded Joints: Thread pipe with tapered pipe threads according to ASME B1.20.1. Cut threads full and clean using sharp dies. Ream threaded pipe ends to remove burrs and restore full ID. Join pipe fittings and valves as follows:
  - 1. Apply appropriate tape or thread compound to external pipe threads unless dry seal threading is specified.
  - 2. Damaged Threads: Do not use pipe or pipe fittings with threads that are corroded or damaged. Do not use pipe sections that have cracked or open welds.

- E. Welded Joints: Construct joints according to AWS D10.12/D10.12M, using qualified processes and welding operators according to Part 1 "Quality Assurance" Article.
- F. Flanged Joints: Select appropriate gasket material, size, type, and thickness for service application. Install gasket concentrically positioned. Use suitable lubricants on bolt threads.
- G. Grooved Joints: Assemble joints with grooved-end pipe coupling with coupling housing, gasket, lubricant, and bolts according to coupling and fitting manufacturer's written instructions.
- H. Soldered Joints: Apply ASTM B813 water-flushable flux, unless otherwise indicated, to tube end. Construct joints according to ASTM B828 or CDA's "Copper Tube Handbook," using lead-free solder alloy (0.20 percent maximum lead content) complying with ASTM B32.
- I. Brazed Joints: Construct joints according to AWS's "Brazing Handbook," "Pipe and Tube" Chapter, using copper-phosphorus brazing filler metal complying with AWS A5.8.
- J. Pressure-Sealed Joints: Assemble joints for plain-end copper tube and mechanical pressure seal fitting with proprietary crimping tool to according to fitting manufacturer's written instructions.
- K. Plastic Piping Solvent-Cemented Joints: Clean and dry joining surfaces. Join pipe and fittings according to the following:
  - 1. Comply with ASTM F402 for safe-handling practice of cleaners, primers, and solvent cements.
  - 2. ABS Piping: Join according to ASTM D2235 and ASTM D2661 appendixes.
  - 3. CPVC Piping: Join according to ASTM D2846/D2846M Appendix.
  - 4. PVC Pressure Piping: Join schedule number ASTM D1785, PVC pipe and PVC socket fittings according to ASTM D2672. Join other-than-schedule-number PVC pipe and socket fittings according to ASTM D2855.
  - 5. PVC Nonpressure Piping: Join according to ASTM D2855.
  - 6. PVC to ABS Nonpressure Transition Fittings: Join according to ASTM D3138 Appendix.
- L. Plastic Pressure Piping Gasketed Joints: Join according to ASTM D3139.
- M. Plastic Nonpressure Piping Gasketed Joints: Join according to ASTM D3212.
- N. Plastic Piping Heat-Fusion Joints: Clean and dry joining surfaces by wiping with clean cloth or paper towels. Join according to ASTM D2657.
  - 1. Plain-End PE Pipe and Fittings: Use butt fusion.
  - 2. Plain-End PE Pipe and Socket Fittings: Use socket fusion.
- O. Bonded Joints: Prepare pipe ends and fittings, apply adhesive, and join according to pipe manufacturer's written instructions.

### 3.4 PIPING CONNECTIONS

- A. Make connections according to the following, unless otherwise indicated:
  - 1. Install unions, in piping NPS 2 and smaller, adjacent to each valve and at final connection to each piece of equipment.
  - 2. Install flanges, in piping NPS 2-1/2 and larger, adjacent to flanged valves and at final connection to each piece of equipment.
  - 3. Install dielectric fittings at connections of dissimilar metal pipes.

### 3.5 CONCRETE BASES

- A. Concrete Bases: Anchor equipment to concrete base according to equipment manufacturer's written instructions and according to seismic codes at Project.
  - 1. Construct concrete bases of dimensions indicated, but not less than 4 inches larger in both directions than supported unit.
  - 2. Install dowel rods to connect concrete base to concrete floor. Unless otherwise indicated, install dowel rods on 18-inch centers around the full perimeter of base.
  - 3. Install epoxy-coated anchor bolts for supported equipment that extend through concrete base, and anchor into structural concrete floor.
  - 4. Place and secure anchorage devices. Use supported equipment manufacturer's setting drawings, templates, diagrams, instructions, and directions furnished with items to be embedded.
  - 5. Install anchor bolts to elevations required for proper attachment to supported equipment.
  - 6. Install anchor bolts according to anchor-bolt manufacturer's written instructions.
  - 7. Use 3000-psi, 28-day compressive-strength concrete and reinforcement as specified in Section 033000 "Cast-in-Place Concrete."

### 3.6 GROUTING

- A. Mix and install grout for equipment base bearing surfaces, pump and other equipment base plates, and anchors.
- B. Clean surfaces that will come into contact with grout.
- C. Provide forms as required for placement of grout.
- D. Avoid air entrapment during placement of grout.
- E. Place grout, completely filling equipment bases.
- F. Place grout on concrete bases and provide smooth bearing surface for equipment.

- G. Place grout around anchors.
- H. Cure placed grout.

END OF SECTION 330500



## SECTION 334200 - STORMWATER CONVEYANCE

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.
- B. Storm Water Pollution Prevention Plan and NPDES Construction General Permit.
- C. Order of Conditions for this project issued by the City of Worcester Conservation Commission.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. PE pipe and fittings.
  - 2. Non-pressure transition couplings.
  - 3. Cleanouts.
  - 4. Manholes.
  - 5. Plastic, channel drainage systems.
  - 6. Catch basins.
  - 7. Stormwater inlets.
  - 8. Pipe outlets.
  - 9. Stormwater disposal systems.
  - 10. Water Quality Inlets
- B. Construction and permanent runoff or dewatering effluent shall not be discharged directly or tributary to stormwater management infiltration systems without the specific approval of the Owner or Engineer. Approval will require effluent water quality testing.

#### 1.3 DEFINITIONS

- A. FRP: Fiberglass-reinforced plastic.

#### 1.4 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Shop Drawings:

## STORMWATER CONVEYANCE

334200 - 1

1. Manholes: Include plans, elevations, sections, details, frames, and covers.
2. Catch basins and stormwater inlets. Include plans, elevations, sections, details, frames, covers, and grates.
3. Water Quality Inlets: Include plans, elevations, sections, details, frames, covers, and grates.

#### 1.5 INFORMATIONAL SUBMITTALS

- A. Product Certificates: For each type of cast-iron soil pipe and fitting, from manufacturer.

#### 1.6 DELIVERY, STORAGE, AND HANDLING

- A. Do not store plastic manholes, pipe, and fittings in direct sunlight.
- B. Protect pipe, pipe fittings, and seals from dirt and damage.
- C. Handle manholes in accordance with manufacturer's written rigging instructions.
- D. Handle catch basins and stormwater inlets in accordance with manufacturer's written rigging instructions.

#### 1.7 FIELD CONDITIONS

- A. Interruption of Existing Storm Drainage Service: Do not interrupt service to facilities occupied by Owner or others unless permitted under the following conditions and then only after arranging to provide temporary service in accordance with requirements indicated:
  1. Notify Owner no fewer than two days in advance of proposed interruption of service.
  2. Do not proceed with interruption of service without Owner's written permission.

### PART 2 - PRODUCTS

#### 2.1 CORRUGATED-PE PIPE AND FITTINGS

- A. Source Limitations: Obtain corrugated-PE pipe and fittings from single manufacturer.
- B. Corrugated-PE Drainage Pipe and Fittings NPS 3 to NPS 10: AASHTO M 252, Type S, with smooth waterway for coupling joints.
- C. Corrugated-PE Pipe and Fittings NPS 12 to NPS 60: AASHTO M 294, Type S, with smooth waterway for coupling joints.

### STORMWATER CONVEYANCE

334200 - 2

- D. Corrugated-PE Silttight Couplings: PE sleeve with ASTM D1056, Type 2, Class A, Grade 2 gasket material that mates with pipe and fittings.
- E. Corrugated-PE Soiltight Couplings: AASHTO M 294, corrugated, matching pipe and fittings.

## 2.2 NONPRESSURE TRANSITION COUPLINGS

- A. Comply with ASTM C1173, elastomeric, sleeve-type, reducing or transition coupling, for joining underground nonpressure piping. Include ends of same sizes as piping to be joined, and corrosion-resistant-metal tension band and tightening mechanism on each end.
- B. Sleeve Materials:
  - 1. For Plastic Pipes: ASTM F477, elastomeric seal or ASTM D5926, PVC.
- C. Unshielded, Flexible Couplings:
  - 1. Source Limitations: Obtain unshielded, flexible couplings from single manufacturer.
  - 2. Description: Elastomeric sleeve with stainless-steel shear ring and corrosion-resistant-metal tension band and tightening mechanism on each end.

## 2.3 CLEANOUTS

- A. PVC Cleanouts:
  - 1. Source Limitations: Obtain PVC cleanouts from single manufacturer.
  - 2. Description: PVC body with PVC threaded plug. Include PVC sewer pipe fitting and riser to cleanout of same material as sewer piping.

## 2.4 MANHOLES

- A. Standard Precast Concrete Manholes:
  - 1. Description: ASTM C478, precast, reinforced concrete, of depth indicated, with provision for sealant joints.
  - 2. Diameter: 48 inches minimum unless otherwise indicated.
  - 3. Ballast: Increase thickness of precast concrete sections or add concrete to base section as required to prevent flotation.
  - 4. Base Section: 6-inch minimum thickness for floor slab and 4-inch minimum thickness for walls and base riser section, and separate base slab or base section with integral floor.
  - 5. Riser Sections: 4-inch minimum thickness, and lengths to provide depth indicated.
  - 6. Top Section: Eccentric-cone type unless concentric-cone or flat-slab-top type is indicated, and top of cone of size that matches grade rings.
  - 7. Joint Sealant: ASTM C990, bitumen or butyl rubber.

8. Resilient Pipe Connectors: ASTM C923, cast or fitted into manhole walls, for each pipe connection.
9. Steps: [Individual FRP steps or FRP ladder] [Individual FRP steps; FRP ladder; or ASTM A615/A615M, deformed, 1/2-inch steel reinforcing rods encased in ASTM D4101, PP wide enough to allow worker to place both feet on one step and designed to prevent lateral slippage off step. Cast or anchor steps into sidewalls at 12- to 16-inch intervals. Omit steps if total depth from floor of manhole to finished grade is less than 60 inches.
10. Adjusting Rings: Interlocking HDPE rings with level or sloped edge in thickness and diameter matching manhole frame and cover, and of height required to adjust manhole frame and cover to indicated elevation and slope. Include sealant recommended by ring manufacturer.
11. Grade Rings: Reinforced-concrete rings, 6- to 9-inch total thickness, to match diameter of manhole frame and cover, and height as required to adjust manhole frame and cover to indicated elevation and slope.

B. Manhole Frames and Covers:

1. Description: Ferrous; 24-inch ID by 7- to 9-inch riser with 4-inch-minimum width flange and 26-inch-diameter cover. Include indented top design with lettering cast into cover, using wording equivalent to "STORM SEWER."
2. Material: ASTM A536, Grade 60-40-18 ductile iron unless otherwise indicated.

## 2.5 CONCRETE

A. General: Cast-in-place concrete in accordance with ACI 318, ACI 350, and the following:

1. Cement: ASTM C150/C150M, Type II.
2. Fine Aggregate: ASTM C33/C33M, sand.
3. Coarse Aggregate: ASTM C33/C33M, crushed gravel.
4. Water: Potable.

B. Portland Cement Design Mix: 4000 psi minimum, with 0.45 maximum water/cementitious materials ratio.

1. Reinforcing Fabric: ASTM A1064/A1064M, steel, welded wire fabric, plain.
2. Reinforcing Bars: ASTM A615/A615M, Grade 60 (420 MPa) deformed steel.

## 2.6 POLYMER-CONCRETE, CHANNEL DRAINAGE SYSTEMS

A. Narrow, Sloped-Invert, Polymer-Concrete Channel Drainage Systems:

1. Source Limitations: Obtain narrow, sloped-invert channel drainage systems from single manufacturer.
2. Description: Modular system of channel sections, grates, and appurtenances; designed so grates fit into channel recesses without rocking or rattling.

## STORMWATER CONVEYANCE

334200 - 4

3. Channel Sections: Narrow, interlocking-joint, sloped-invert, polymer-concrete modular units with end caps.
    - a. Include rounded bottom, with built-in invert slope of 0.6 percent and with outlets in number, sizes, and locations indicated.
    - b. Include extension sections necessary for required depth.
    - c. Dimensions: 4-inch inside width. Include number of units required to form total lengths indicated.
    - d. Frame: Included ductile iron frame for grate
  4. Grates: Manufacturer's designation heavy duty," with slots or perforations, and of width and thickness that fit recesses in channel sections.
    - a. Material: Ductile iron
      - 1) Locking Mechanism: Manufacturer's standard device for securing grates to channel sections.
  5. Covers: Solid ductile iron of width and thickness that fit recesses in channel sections, and of lengths indicated.
  6. Supports, Anchors, and Setting Devices: Manufacturer's standard unless otherwise indicated.
  7. Channel-Section Joining and Fastening Materials: As recommended by system manufacturer.
- B. Drainage Specialties: Precast, polymer-concrete units.
1. Large Catch Basins:
    - a. 24-by-12-inch polymer-concrete body, with outlets in quantities and sizes indicated.
    - b. Gray-iron slotted grate.
    - c. Frame: Include gray-iron or steel frame for grate.

## 2.7 CATCH BASINS

- A. Standard Precast Concrete Catch Basins:
1. Description: ASTM C478, precast, reinforced concrete, of depth indicated, with provision for sealant joints.
  2. Base Section: 6-inch minimum thickness for floor slab and 4-inch minimum thickness for walls and base riser section, and separate base slab or base section with integral floor.
  3. Riser Sections: 4-inch minimum thickness, 48-inch diameter, and lengths to provide depth indicated.

4. Top Section: Eccentric-cone type unless concentric-cone or flat-slab-top type is indicated. Top of cone of size that matches grade rings.
  5. Joint Sealant: ASTM C990, bitumen or butyl rubber.
  6. Adjusting Rings: Interlocking rings with level or sloped edge in thickness and shape matching catch basin frame and grate. Include sealant recommended by ring manufacturer.
  7. Grade Rings: Include two or three reinforced-concrete rings, of 6- to 9-inch total thickness, that match 24-inch-diameter frame and grate.
  8. Pipe Connectors: ASTM C923, resilient, of size required, for each pipe connecting to base section.
- B. Frames and Grates: ASTM A536, Grade 60-40-18, ductile iron designed for A-16 (AASHTO HS20-44), structural loading. Include flat grate with small square or short-slotted drainage openings.
1. Size: 24 by 24 inches minimum unless otherwise indicated.
  2. Grate Free Area: Approximately 50 percent unless otherwise indicated.

## 2.8 STORMWATER DISPOSAL SYSTEMS

- A. Chamber Systems:
1. Manufacturers: Subject to compliance with requirements, provide products by one of the following, or approved equal:
    - a. Cultec, Inc.
  2. Storage and Leaching Chambers: Molded PE with perforated sides and open bottom. Include number of chambers, distribution piping, end plates, and other standard components as required for system total capacity.
  3. Filtering Material: ASTM D 448, Size No. 24, 1-1/2- to 2-inch washed, crushed stone.
  4. Filter Mat: Geotextile woven or spun filter fabric, in one or more layers, for minimum total unit weight of 4 oz./sq. yd.

## 4.2 WATER QUALITY INLETS

- A. The water quality inlet shall be as indicated on the Contract Drawings and is a Contech CDS1515-3-C.

## PART 5 - EXECUTION

### 5.1 EARTHWORK

- A. Excavation, trenching, and backfilling are specified in Section 312000 "Earth Moving."

### 5.2 PIPING INSTALLATION

- A. General Locations and Arrangements: Drawing plans and details indicate general location and arrangement of underground storm drainage piping. Location and arrangement of piping layout take into account design considerations. Install piping as indicated, to extent practical. Where specific installation is not indicated, follow piping manufacturer's written instructions.
- B. Install piping beginning at low point, true to grades and alignment indicated with unbroken continuity of invert. Place bell ends of piping facing upstream. Install gaskets, seals, sleeves, and couplings in accordance with manufacturer's written instructions for use of lubricants, cements, and other installation requirements.
- C. Install manholes for changes in direction unless fittings are indicated. Use fittings for branch connections unless direct tap into existing sewer is indicated.
- D. Install proper size increasers, reducers, and couplings where different sizes or materials of pipes and fittings are connected. Reducing size of piping in direction of flow is prohibited.
- E. When installing pipe under streets or other obstructions that cannot be disturbed, use pipe-jacking process of microtunneling.
- F. Install gravity-flow, nonpressure drainage piping in accordance with the following:
  - 1. Install piping pitched down in direction of flow.
  - 2. Install piping NPS 6 and larger with restrained joints at tee fittings and at changes in direction. Use corrosion-resistant rods, pipe or fitting manufacturer's proprietary restraint system, or cast-in-place concrete supports or anchors.
  - 3. Install PE corrugated sewer piping in accordance with ASTM D2321.

### 5.3 PIPE JOINT CONSTRUCTION

- A. Join gravity-flow, nonpressure drainage piping in accordance with the following:
  - 1. Join corrugated-PE piping in accordance with ASTM D3212 for push-on joints.
  - 2. Join dissimilar pipe materials with nonpressure-type flexible couplings.

#### 5.4 DRAIN INSTALLATION

- A. Install type of drains in locations indicated.
  - 1. Use Light-Duty, top-loading classification drains as noted on the plans.
- B. Fasten grates to drains if indicated.
- C. Set drain frames and covers with tops flush with ground surface.

#### 5.5 MANHOLE INSTALLATION

- A. General: Install manholes, complete with appurtenances and accessories indicated.
- B. Install precast concrete manhole sections with sealants in accordance with ASTM C891.
- C. Where specific manhole construction is not indicated, follow manhole manufacturer's written instructions.
- D. Set tops of frames and covers flush with finished surface of manholes that occur in pavements.

#### 5.6 CATCH BASIN INSTALLATION

- A. Construct catch basins to sizes and shapes indicated.
- B. Set frames and grates to elevations indicated.

#### 5.7 STORMWATER OUTLET INSTALLATION

- A. Construct riprap of broken stone, as indicated.
- B. Install outlets that spill onto grade, with flared end sections that match pipe, where indicated.

#### 5.8 WATER QUALITY INLET INSTALLATION

- A. General: Install water quality inlets according to water quality inlet manufacturer's written instructions.
- B. Install water quality inlets, complete with appurtenances and accessories indicated.
- C. Install precast concrete sections with sealants according to ASTM C 891.

### STORMWATER CONVEYANCE

334200 - 8



- D. Set tops of frames and covers flush with finished surface of manholes that occur in pavements. Set tops 3 inches above finished surface elsewhere unless otherwise indicated.

#### 5.9 CONCRETE PLACEMENT

- A. Place cast-in-place concrete in accordance with ACI 318.

#### 5.10 CHANNEL DRAINAGE SYSTEM INSTALLATION

- A. Install with top surfaces of components, except piping, flush with finished surface.
- B. Assemble channel sections to form slope down toward drain outlets. Use sealants, adhesives, fasteners, and other materials recommended by system manufacturer.
- C. Embed channel sections and drainage specialties in 6-inch-minimum concrete around bottom and sides.
- D. Fasten grates to channel sections if indicated.
- E. Assemble channel sections with flanged or interlocking joints.
- F. Embed channel sections in 6-inch-minimum concrete around bottom and sides.

#### 5.11 STORMWATER DISPOSAL SYSTEM INSTALLATION

- A. Chamber Systems: Excavate trenches of width and depth, and install system and backfill in accordance with chamber manufacturer's written instructions. Include storage and leaching chambers, filtering material, and filter mat.

#### 5.12 CONNECTIONS

- A. Connect nonpressure, gravity-flow drainage piping in building's storm building drains.
- B. Connect force-main piping to building's storm drainage force mains specified in Section 221413 "Facility Storm Drainage Piping." Terminate piping where indicated.
- C. Make connections to existing piping and underground manholes.
  - 1. Make branch connections from side into existing piping, NPS 21 or larger, or to underground manholes and structures by cutting into existing unit and creating an opening large enough to allow 3 inches of concrete to be packed around entering connection. Cut end of connection pipe passing through pipe or structure wall to conform to shape of and be flush with inside wall unless otherwise indicated. On outside of pipe, manhole, or structure wall, encase entering connection in 6 inches of concrete

#### STORMWATER CONVEYANCE

334200 - 9

for minimum length of 12 inches to provide additional support of collar from connection to undisturbed ground.

- a. Use concrete that will attain a minimum 28-day compressive strength of 3000 psi unless otherwise indicated.
    - b. Use epoxy-bonding compound as interface between new and existing concrete and piping materials.
  2. Protect existing piping, manholes, and structures to prevent concrete or debris from entering while making tap connections. Remove debris or other extraneous material that may accumulate.
- D. Pipe couplings, expansion joints, and deflection fittings with pressure ratings at least equal to piping rating may be used in applications below unless otherwise indicated.
1. Use nonpressure-type flexible couplings where required to join gravity-flow, nonpressure sewer piping unless otherwise indicated.
    - a. Unshielded flexible couplings for same or minor difference OD pipes.
    - b. Unshielded, increaser/reducer-pattern, flexible couplings for pipes with different OD.
    - c. Ring-type flexible couplings for piping of different sizes where annular space between smaller piping's OD and larger piping's ID permits installation.

#### 5.13 IDENTIFICATION

- A. Materials and their installation are specified in Section 312000 "Earth Moving." Arrange for installation of green warning tape directly over piping and at outside edge of underground structures.
1. Use warning tape or detectable warning tape over ferrous piping.
  2. Use detectable warning tape over nonferrous piping and over edges of underground structures.

#### 5.14 FIELD QUALITY CONTROL

- A. Inspect interior of piping to determine whether line displacement or other damage has occurred. Inspect after approximately 24 inches of backfill is in place, and again at completion of Project.
1. Submit separate reports for each system inspection.
  2. Defects requiring correction include the following:
    - a. Alignment: Less than full diameter of inside of pipe is visible between structures.

#### STORMWATER CONVEYANCE

334200 - 10

- b. Deflection: Flexible piping with deflection that prevents passage of ball or cylinder of size not less than 92.5 percent of piping diameter.
  - c. Damage: Crushed, broken, cracked, or otherwise damaged piping.
  - d. Infiltration: Water leakage into piping.
  - e. Exfiltration: Water leakage from or around piping.
- 3. Replace defective piping using new materials, and repeat inspections until defects are within allowances specified.
- 4. Reinspect and repeat procedure until results are satisfactory.
- B. Test new piping systems, and parts of existing systems that have been altered, extended, or repaired, for leaks and defects.
  - 1. Do not enclose, cover, or put into service before inspection and approval.
  - 2. Test completed piping systems in accordance with requirements of authorities having jurisdiction.
  - 3. Schedule tests and inspections by authorities having jurisdiction with at least 24 hours' advance notice.
  - 4. Submit separate report for each test.
  - 5. Gravity-Flow Storm Drainage Piping: Test in accordance with requirements of authorities having jurisdiction, UNI-B-6, and the following:
    - a. Exception: Piping with soil tight joints unless required by authorities having jurisdiction.
    - b. Option: Test plastic piping in accordance with ASTM F1417.
- C. Leaks and loss in test pressure constitute defects that must be repaired.
- D. Replace leaking piping using new materials, and repeat testing until leakage is within allowances specified.

#### 5.15 CLEANING

- A. Clean interior of piping of dirt and superfluous materials. Flush with potable water.

END OF SECTION 334200